

Numerics

- 12-Mbps to 60-Mbps data rates, 197
- 1-Mbps to 11-Mbps data rates, 197
- 2.4 GHz frequency band, 191
- 3.5 GHz frequency band, 192
- 5 GHz frequency band, 192
- 60 GHz frequency band, 193
- 802.1x wireless standards, 289
- 802.11 wireless standards, 289-290
 - advancements, 283
- 802.11a wireless standards, 289
- 802.11b wireless standards, 289
 - access points
 - hardware provider organizations, 294
 - locating, 123
 - cellular service integration, 283
- 802.15.1 wireless standards, 290
- 802.16 wireless standards, 290
- 802.16 Working Group on Broadband Wireless Access, 284
- 900 MHz frequency band, 190

A

- access, equipment, sites, 128
- access control lists (ACLs), 278
- access point hardware, provider organizations, 294
- access points, 258
 - 802.11b access points, locating, 123
 - cellular architecture, connectivity, 85
 - noise vulnerability, RF site surveys, 120
- ACLs (access control lists), 278
- addresses (MAC)
 - ACLs (access control lists), 205
 - table size, 204
- Advanced Encryption Standard (AES), 207
- advertising literature, reading, 266
- AES (Advanced Encryption Standard), 207
- amateur radio operators, interference, dealing with, 280
- amplitude modulation, 7, 20
 - attenuation, 23-24
- antenna systems, 225
 - antenna coverings, 173
 - beamwidth, 41-43
 - bidirectional antennas, combining, 156
 - circularly polarized antennas, 148, 199
 - combining, 155
 - bidirectional antenna systems, 156
 - diversity antenna systems, 157-159
 - power dividers, 156
 - corner reflector antennas, 152
 - current, 21
 - directing, physical site surveys, 99
 - directional antennas, 259
 - directivity, 38-39
 - directors, 138-139
 - distant obstacles, avoiding, 101
 - diversity, 199
 - driven elements, 134
 - bidirectional-driven element radiation patterns, 135
 - lights, 134-137
 - multiple-driven element radiation patterns, 136
 - electromagnetic waves, 20
 - equipment distance, minimizing, 97-98
 - feed systems, 170-172
 - cable types, 171
 - coaxial cable loss, 170
 - impedance, 170
 - power-handling capabilities, 171
 - size issues, 171
 - upper frequency limits, 171
 - isolating, 159-165, 173
 - cross-polarization isolation, 164
 - horizontal separation isolation, 162-164
 - noise reduction, 159-160
 - obstruction isolation, 164-165
 - vertical separation isolation, 161-162
 - Fresnel zone clearances, calculating, 94
 - gains, 40
 - grounding, physical site surveys, 102-105
 - height, physical site surveys, 101
 - helix antennas, 154-155
 - horizontally polarized sector antennas, 147
 - interference, reducing, 133-148, 250, 256, 260
 - lenses, 138-139
 - lightning protection, 14, 103
 - lights, 134-137
 - manufacturers, 296
 - mesh architecture, installation, 77
 - mounting, physical site surveys, 102
 - mounting hardware, 173
 - obstacles, avoiding, 101
 - omnidirectional antennas, 149-150
 - point-to-point architecture, 60
 - panel antennas, 153-154
 - parabolic reflector antennas, 153
 - parasitic arrays, 134
 - placement, physical site surveys, 99-101
 - point-to-multipoint architecture, selection, 69
 - point-to-point architecture
 - selection, 60
 - system expansion, 63
 - polarization, 140-145
 - circular polarization, 143-144
 - cost-effective deployment, 145-146
 - cross polarization, 144-145
 - horizontal polarization, 142-143
 - multipath resistance, 147-148
 - noise reduction, 146-147
 - vertical polarization, 140-141

- power, focusing, 133-148, 250, 256, 260
- power lines, avoiding, 101
- radiation patterns, 39-40
- receiving antennas
 - gains, 51
 - sensitivity threshold, 52
 - transmission line loss, 51
- reflectors, 137-138
- rooftop-mounted antennas, installing, 232-243
- safety issues, 13-16
- sector antenna systems, 163-166
 - downtilt, 168
 - F/B ratios, 168
 - horizontal beamwidth, 168
 - low-noise access point locations, 167
 - polarization, 167
 - sector orientations, 167
 - sector radius, 167
 - selecting, 167-169
 - vertical beamwidth, 168
- selectable polarization, 200
- selecting, 133
- site management, contacting, 95
- smart antennas, 200
- spillover, 41
- tower-mounted antennas, installing, 228-232
- triangulation, 260
- vertically polarized omnidirectional antennas, 145
- waves
 - free-space waves, 25
 - reflected waves, 25-28
- Yagi-Uda antennas, 151
- AP equipment, choosing, 215-216
- application layer
 - functions, 184
 - network design, 210
 - NMS (network management system), 210-211
 - protocols, 184
 - security, 211
- architecture
 - cellular architecture, 71-75
 - advantages, 72-73
 - disadvantages, 74-75
 - evaluating, 84-86
 - choosing, 59-66
 - end users
 - availability confirmations, 90
 - location mapping, 79-80
 - hub site availability, confirming, 90
 - mesh architecture, 75-76
 - advantages, 76-77
 - disadvantages, 78
 - evaluating, 86-88
 - usage, 78
 - OSI reference model, 180-186
 - point-to-multipoint architecture, 66-68
 - advantages, 68
 - disadvantages, 69-71
 - evaluating, 82-83

- point-to-point architecture, 21-52, 59-66, 100, 104, 111-117, 125, 135-166, 173, 181-183, 231-235, 250, 256, 260
 - advantages, 59-62
 - appropriate usage, 65-66
 - disadvantages, 62-65
 - evaluating, 81
- preliminary architecture, drafting, 88-89
- selecting, 21-52, 59, 67, 72, 76, 79-90, 100, 104, 111-117, 125, 135-166, 173, 181-183, 231-235, 250, 256, 260
 - site availability, confirming, 90
 - TCP/IP reference model, 180-186
 - users, grouping by proximity, 82
- ATM (Asynchronous Transfer Mode) interfaces, 188
- atmospheric effects, signals, 28-31
- attenuation, amplitude, 23-24
- attenuation losses, 190
- attenuators, 260
- authentication, 206
- available bandwidth, wireless networks, maximizing, 13-16

B

- backbones
 - bandwidth, point-to-point architecture, 63
 - capacity, considerations, 213
 - dedicated bandwidth, 214
 - licensed backbones, 214
 - license-free backbones, 214
 - shared bandwidth, 214
 - wired backbones, 214
 - wireless backbones, 214
- backhauls, licensed backhauls, using, 273
- band of frequencies, inspecting, 110-112
- bandpass filters, 258
- bandwidth, 195-198
 - backbone bandwidth, point-to-point architecture, 63
 - managing, network layer, 208
 - mesh architecture, managing, 78
 - point-to-multipoint architecture, managing, 69
 - throughput, differentiating between, 268
 - wireless networks, maximizing available bandwidth, 13-16
- beaconing, disabling, 278
- beamwidth, antennas, 41-43
- BGP (Border Gateway Protocol), 184
- bidirectional antenna systems, combining, 156
- bidirectional-driven element radiation patterns, antennas, 135
- black holes, avoiding, 285-287
- books, suggested reading, 300-301
- Border Gateway Protocol (BGP), 184
- bridged WANs, routed WANs, compared, 212-213
- bridging, data link layer, 203-204
- broadband
 - hot spots, 284
 - wireless networks, 4
- broadband optical equipment, 284
- building management, contacting, physical site surveys, 95

C

- cable, 225
 - coaxial cable
 - manufacturers, 296
 - runs, 172
 - interfaces, 187
 - jumpers, 172
 - pigtails, 172
 - power-handling capabilities, 171
 - routing, physical site surveys, 98-99
 - running, rooftop-mounted antennas, 239
 - types, 171
 - upper frequency limits, 171
- calculations
 - dBm power reference level, 36
 - EIRP (Equivalent Isotropic Radiated Power), 228
 - fade margin calculations, 52-53
 - Fresnel zone clearances, antennas, 94
 - wireless link budget calculations, 49-53
- cellular architecture, 71-75
 - access points, connectivity, 85
 - advantages, 72-73
 - disadvantages, 74-75
 - evaluating, 84-86
 - geographical coverage, 73
 - limited spectrum, re-using, 74
 - low interference, verification, 74
 - network capacity, 73
 - redundant end user coverage, 73
 - roaming, 73
 - testing, 75
 - usage, 75
- certification, FCC equipment certification, 281-282
- circularly polarized antennas, 143-144, 148, 199
- coaxial arrestors, 241
- coaxial cable
 - loss, feed systems, 170
 - manufacturers, 296
 - runs, 172
- collaboration, installation, 226
- commercial tower companies, cost considerations, 286
- Communications Act of 1934, 7
- community networks, 284
 - resources, 302
- compasses
 - headings, measuring, 88
 - using, 260
- configurable power control, transmitters, 201
- connections, waterproofing, 235-236
- connectivity, access points, cellular architecture, 85
- controlled equipment environments, locating, controlled equipment environments, 97
- converters, Ethernet, 204
- corner reflector antennas, 152
- cost
 - hardware
 - point-to-multipoint architecture, 70
 - point-to-point architecture, 61
 - license-free wireless networks, advantages of, 9

- point-to-multipoint architecture
 - facilities, 70
 - installation, 71
- point-to-point architecture
 - costs, 62
 - facilities, 61
- coverage, testing, 127
- coverings, antennas, 173
- CPE (customer premises equipment), 66, 225, 274
 - cost reductions, 283
- criteria evaluations, RF site surveys, 124-126
- cross polarization, antennas, 144-145
 - isolation, 164
- current (electron flow), 20-21
- customer premises equipment (CPE). *See* CPE (customer premises equipment)
- cycles per second, 20

D

- Data Encryption Standard (DES), 207
- data link layer
 - bridging features, 203-204
 - functions, 185
 - MAC sublayer features, 205
 - protocols, 185
 - security features, 205-207
- data rates
 - 12-Mbps to 60-Mbps, 197
 - 1-Mbps to 11-Mbps data rates, 197
 - distances, compared, 196
 - sub-1 Mbps data rates, 197
 - throughput, compared, 195-196
- dBm power reference level, 35-36
- dBs (decibels), 272-273
- dedicated bandwidth, shared bandwidth, compared, 214
- deployment speed, license-free wireless networks, advantages of, 10
- DES (Data Encryption Standard), 207
- desense, 258
- DHCP (Dynamic Host Configuration Protocol) servers, 208, 265
- dialup telco interfaces, 187
- diffraction, signals, 28
- Direct Sequence Spread Spectrum (DSSS). *See* DSSS
- directing antennas, physical site surveys, 38-39, 99
- directional antennas, 259
- direction-finding techniques, noise, 259-261
- directors, antennas, 138-139
- dish antennas. *See* parabolic reflector antennas
- distance
 - data rate, compared, 196
 - hub sites, measuring, 88
 - links, doubling, 53
- distributers, peripheral devices, 298

- diversity antenna systems, 157-159, 199
- documentation, 226
 - outdoor wireless systems, verifying, 227
- documenting
 - noise-reduction results, 262
 - RF site surveys, 124
 - test results, 245
- downtilt, sector antennas, 168
- drafting, preliminary network architecture, 88-89
- drip loops, connections, waterproofing, 235
- driven elements, antennas, 134
 - bidirectional-driven element radiation patterns, 135
 - lights, 134-137
 - multiple-driven element radiation patterns, 136
- DSL interfaces, 187
- DSSS (Direct Sequence Spread Spectrum), 8, 115
 - modulation, 193-195
 - noise, minimizing, 254-257
- duplex throughput, simplex throughput, compared, 195-196
- Dynamic Host Configuration Protocol (DHCP) servers.
See DHCP
- dynamic IP routing, 208

E

- educational seminars, attending, 267
- EIRP (Equivalent Isotropic Radiated Power), 228
- electromagnetic waves, 20
- electron flow, 20
- e-mail lists
 - joining, 267
 - resources, 302
- emergencies, planning for, 272
- encryption, AES (Advanced Encryption Standard), 207
- end users, location mapping, network architecture, 79-80
- equipment (wireless), 177
 - 802.11b compatibility, 212
 - AP equipment, choosing, 215-216
 - broadband optical equipment, 284
 - CPE (customer premises equipment), 274
 - deployment sites, 179
 - environmental decisions, 218-221
 - Ethernet ports, 187
 - evolution of, 177
 - FCC certifications, 281-282
 - features, researching, 178
 - high-speed data ports, 187-188
 - interference reduction, 198-200
 - low-speed data ports, 187
 - market/cost considerations, 211
 - needless mixing, avoiding, 274
 - needs, reviewing, 178
 - NLOS (non line-of-sight) capabilities, 189, 285-286
 - noise reduction, 198-200
 - OSI reference model, 180-186
 - physical layer
 - security, 200-201
 - wired-interface feature options, 186-203

- point-to-point architecture, upgrades, 65
- sites, accessing, 128
- TCP/IP reference model, 180-186
- testing
 - labs, 179
 - outdoors, 179-180
 - safety, 179
- Equivalent Isotropic Radiated Power (EIRP)
 - calculations, 228
- Ethernet
 - converters, 204
 - ports, 187
- e-zines, 301

F

- F/B ratios, sector antennas, 168
- facilities
 - point-to-multipoint architecture, cost, 70
 - point-to-point architecture, cost, 61
- fade margin calculations, 52-53, 244, 275
- FCC (Federal Communications Commission), 6
 - equipment certification, 281-282
 - establishment of, 7
 - inquiries, responding to, 282
 - licensing regulations, changes to, 287
 - lobbying, 282
 - power limits, 280
 - rules and regulations, documentation, 302
 - wireless licensing, history of, 5-8
- feed systems
 - antennas, 170-172
 - cable types, 171
 - coax cable loss, 170
 - impedance, 170
 - power-handling capability, 171
 - size issues, 171
 - upper-frequency limits, 171
- FHSS (Frequency Hopping Spread Spectrum)
 - modulation, 8, 194
 - noise, minimizing, 257
- File Transfer Protocol (FTP), 184
- filtering protocols, 206
- firewalls, 210
- fixed business markets, serving, 268
- fixed residential markets, serving, 268
- flashlight power ratios, 33-34
- frames, 183-184
- free space optical hardware, provider organizations, 295
- free-space path loss, link budget, 50-51
- free-space path loss (FSPL), 161
- free-space waves, 25
- frequencies
 - license-free frequency bands, 9, 190
 - 2.4 GHz, 191
 - 3.5 GHz, 192
 - 5 GHz, 192

- 60 GHz, 193
- 900 MHz, 190
- wireless waves, 20
- frequency hopping, 7
- Frequency Hopping Spread Spectrum (FHSS) modulation. *See* FHSS
- frequency modulation, 7
- frequency plans, 255
 - creating, 89
- Fresnel zone clearance, 46-49
 - antennas, calculating, 94
- FSPL (free-space path loss), 161
- FTP (File Transfer Protocol), 184
- functions
 - application layer, 184
 - data link layer, 185
 - network layer, 184
 - transport layer, 184

G

- gains
 - antennas, 40
 - receiving antennas, 51
- geographical coverage, cellular architecture, 73
- governmental licensing regulations, changes to, 287
- grounding
 - antennas, physical site surveys, 102-105
 - equipment, manufacturers, 297
 - mast-mounted antenna systems, 242
 - residence-mounted antenna systems, 242
 - rooftop-mounted antennas, 240-242
 - tower-mounted antenna systems, 241
- grouping users, proximity, 82
- guy wires, rooftop-mounted antennas, attaching, 237

H

- hardware
 - access point hardware, provider organizations, 294
 - free space optical hardware, provider organizations, 295
 - mounting hardware, provider organizations, 296
 - point-to-point architecture, cost, 61, 70
 - security hardware, provider organizations, 295
 - wireless hardware, provider organizations, 293-294
 - wireless hotspot hardware, provider organizations, 294
- headings, compass headings, measuring, 88
- height, antennas, physical site surveys, 101
- heights, working with, safety issues, 13
- helix antennas, 154-155
- Hertz (Hz), 6, 20
- high noise level, point-to-point architecture, 66
- high radio-frequency (RF) environments, working in, 229
- high-power transmitters, receiver performance, 286
- high-reliability services, committing to, 269

- high-speed data ports, 187-188
- horizontal beamwidth, 42
 - sector antennas, 168
- horizontal polarization, antennas, 142-143, 147
- horizontal separation isolation, antenna systems, 162-164
- hot spots, broadband, 284
- hotspot hardware, provider organizations, 294
- HTTP (Hypertext Transfer Protocol), 182
- hub sites
 - availability, confirming, 90
 - distances, measuring, 88
 - low-noise hub sites, point-to-point architecture, 64
- Hypertext Transfer Protocol (HTTP), 182

I

- IEEE (Institute of Electrical and Electronics Engineers), 284
- impedance, feed systems, 170
- in-band noise sources, locating, 122-123
- inputs (wireless), 172
- inquiries, FCC, responding to, 282
- inside wireless systems, mounting, 231
- installation
 - antennas, mesh architecture, 77
 - collaboration, 226
 - installation personnel, safety training, 226
 - outdoor wireless systems
 - documentation verification, 227
 - preparing for, 225-227
 - point-to-multipoint architecture, cost, 71
 - point-to-point architecture, cost, 62
 - preplanning, 270
 - rooftop-mounted antennas, 232-243
 - tools, 227
 - tower-mounted antennas, 228-232
- Institute of Electrical and Electronics Engineers (IEEE), 284
- insurance, sites, requirements, 128
- intelligence, wireless networking, 7
- interference
 - amateur radio operators, dealing with, 280
 - cellular architecture, verification, 74
 - dealing with, 279
 - levels, minimizing, 251-263
 - minimizing, wireless systems, 263
 - out-of-band signals, 251
 - reducing, 133-148, 198-200, 250, 256, 260
 - sites, avoiding, 128
- intermittent noise, 259
- invisible wireless signals, making visible, 11
- IP (Internet Protocol), 181
- isolating antenna systems, 159-165, 173
 - cross-polarization isolation, 164
 - horizontal separation isolation, 162-164
 - noise reduction, 159-160
 - obstruction isolation, 164-165
 - vertical separation isolation, 161-162

J-L

jumpers (connecting cables), 172
 laboratories, equipment, testing, 179
 Lamar, Hedy, 7
 LANs (local-area networks), 5
 large and complex model, WISPs, 266
 leases, sites
 negotiating, 127-129
 rates, 128
 lenses, antennas, 138-139
 licence-free spread spectrum signaling, 8-9
 licence-free wireless networking, 5-12
 See also wireless networks
 licensed backbones, license-free backbones, compared, 214
 licensed backhauls, using, 273
 licensed wireless systems, interference, minimizing, 263
 license-free backbones, licensed backbones, compared, 214
 license-free frequency bands, 190
 2.4 GHz, 191
 3.5 GHz, 192
 5 GHz, 192
 60 GHz, 193
 900 MHz, 190
 license-free wireless networks
 advantages, 9-10
 challenges of, 11-16
 frequencies, 9
 licensing, regulations, changes to, 287
 lightning protection, 240-242
 antennas, providing, 103
 wireless antennas, 14
 lightning-protection equipment, manufacturers, 297
 lights, antennas, 134-137
 limited spectrum, cellular architecture, re-using, 74
 line-of-sight (LOS) paths. *See* LOS
 link budget
 free-space path loss, 50-51
 transmitter antenna system transmission line loss, 50
 transmitter output power, 50
 transmitting antenna gain, 50
 links
 budget, 50-51
 distance, doubling, 53
 longer-than-normal links, point-to-point
 architecture, 65
 planning, 53-55
 point-to-multipoint wireless links, testing, 245
 point-to-point wireless links, testing, 243
 lobbying, FCC, 282
 local-area networks (LANs), 5
 location mapping, end users, network architecture, 79-80
 longer-than-normal links
 planning, 53-55
 point-to-point architecture, 65
 LOS (line-of-sight) paths, 93
 inspecting, 89
 mesh architecture, 76
 point-to-multipoint architecture, determination, 70

 point-to-point architecture, 60, 63
 obtaining, 43-49
 visual LOS paths, 43
 low interference, cellular architecture, verification, 74
 low-noise access point locations, sector antennas, 167
 low-noise AP locations, selecting, 270-271
 low-noise hub sites, point-to-point architecture, 64
 low-speed data ports, 187

M

MAC addresses
 ACLs (access control lists), 205
 table size, 204
 MAC sublayer features, data link layer, 205
 manmade noise, 251
 MANs (metropolitan area networks), 5
 manufacturers
 antenna systems, 296
 coaxial cable, 296
 grounding equipment, 297
 lightning-protection equipment, 297
 mounting hardware, 296
 test equipment, 297
 towers, 296
 mapping
 end user locations, network architecture, 79-80
 topographic maps, purchasing, 80
 using, 260
 mast-mounted antenna systems
 grounding, 242
 raising, 237-239
 IEEE 802.11 Handbook, 301
 measuring
 compass headings, 88
 distances, hub sites, 88
 fade margins, 275
 throughput, 243, 276-277
 mesh architecture, 75-76
 advantages, 76-77
 antennas, installation, 77
 bandwidth, managing, 78
 disadvantages, 78
 evaluating, 86-88
 LOS paths, 76
 network design process, 77
 routing redundancy, 77
 usage, 78
 wireless nodes, 78
 metropolitan area networks (MANs), 5
 microwave energy, working with, safety issues, 14
 microwave radiation, dangers of, 229
 microwave reflections, 26-28
 mirrors, antennas, 137-138
 mixing equipment, avoiding, 274
 mobile markets, serving, 268
 modulation, 193
 amplitude modulation, 7

- DSSS (Direct Sequence Spread Spectrum), 193-195
- FHSS (Frequency Hopping Spread Spectrum)
 - modulation, 194
 - frequency modulation, 7
- OFDM (Orthogonal Frequency Division Multiplexing) modulation, 194
- spread spectrum modulation, 7
- wireless signals, 7
- modulation types, 189, 193-195
- mounting
 - antennas, physical site surveys, 102
 - inside wireless equipment, 231
- mounting hardware, 173
- manufacturers, 296
- multipath fading, 199
- multipath resistance, antennas, 147-148
- multiple-driven element radiation patterns, antennas, 136

N

- narrowband FHSS signals, 194
- NAT (Network Address Translation), 208
- natural disasters, planning for, 272
- natural noise, 251
- nearby out-of-band noise sources, locating, 121
- near-line-of-sight (NLOS), 70, 189
- negotiating leases, sites, 127-129
- NEMA (National Electrical Manufacturer's Association), 234
- Network Address Translation (NAT), 208
- network architecture
 - cellular architecture, 71-75
 - advantages, 72-73
 - disadvantages, 74-75
 - evaluating, 84-86
 - choosing, 59-66
 - end users
 - availability confirmations, 90
 - location mapping, 79-80
 - hub sites, confirming, 90
 - mesh architecture, 75-76
 - advantages, 76-77
 - disadvantages, 78
 - evaluating, 86-88
 - usage, 78
 - point-to-multipoint architecture, 66-68
 - advantages, 68
 - disadvantages, 69-71
 - evaluating, 82-83
 - point-to-point architecture, 21-48, 52, 59-66, 100, 104, 111-117, 125, 135-166, 173, 181-183, 231-235, 250, 256, 260
 - appropriate usage, 65-66
 - disadvantages, 62-65
 - evaluating, 81
 - preliminary network architecture, drafting, 88-89

- selecting, 21-52, 59, 67, 72, 76, 79-90, 100, 104, 111-117, 125, 135-166, 173, 181-183, 231-235, 250, 256, 260
- site availability, confirming, 90
- users, grouping by proximity, 82
- network architecture flexibility, license-free wireless networks, advantages of, 10
- network capacity, cellular architecture, 73
- network design, application layer, 210
- network design processes, mesh architecture, 77
- network independence, license-free wireless networks, advantages of, 10
- network layer
 - bandwidth, managing, 208
 - functions, 184
 - protocols, 184
 - QoS (Quality of Service), 209
 - roaming, 209
 - routing features, 207-208
 - security features, 209-210
- network management system (NMS), 210-211
- networks
 - community networks, 284
 - security, enhancing, 277-278
 - stable wireless networks, deploying, 273-275
 - throughput
 - managing, 275-277
 - measuring, 276-277
 - niche markets, serving, 267-268
- NLOS (near-line-of-sight) equipment, 70, 189
- NLOS (non-line-of-sight) equipment, 189, 285-286
- NMS (network management system), application layer, 210-211
- nodes, mesh architecture, 78
- noise
 - intermittent noise, 259
 - levels, minimizing, 251-263
 - locating, direction-finding techniques, 259-261
 - low-noise AP locations, selecting, 270-271
 - manmade noise, 251
 - minimizing
 - DSSS networks, 254-257
 - FHSS networks, 257
 - other networks, 257
 - out-of-band transmitters, 258
 - natural noise, 251
 - network performance, monitoring, 262
 - noise-reduction results, documenting, 262
 - receiver noise, 251
 - reducing, 146-147, 198-200
 - isolation, 159-160
 - SNR, variations, 258-259
 - steady noise, 259
- noise figure, receivers, 202

O

- obstruction isolation, antenna systems, 164-165
- OC-3 (Optical Carrier 3) interfaces, 188
- OC-12 (Optical Carrier 12) interfaces, 188
- OFDM (Orthogonal Frequency Division Multiplexing) modulation, 194
- omnidirectional antennas, 149-150
 - point-to-point architecture, 60
- online magazines, 301
- Open Shortest Path First (OSPF), 208
- optical hardware, provider organizations, 295
- orientation, sectors, sector antennas, 167
- Orthogonal Frequency Division Multiplexing (OFDM) modulation, 194
- OSI reference model, 180-186
 - application layer, 184
 - data link layer, 185-186
 - frames, 183-184
 - network layer, 184
 - packets, 183-184
 - peer protocols, 182
 - services, 182-183
 - transport layer, 184
- OSPF (Open Shortest Path First) routing protocol, 208
- other networks, noise, minimizing, 257
- outdoor wireless systems
 - installing
 - documentation verification, 227
 - preparations, 225-227
 - rooftop-mounted antenna systems, installing, 232-243
 - testing, 243-245
 - tower-mounted antenna systems, installing, 228-232
- outdoors, equipment, testing, 179-180
- out-of-band signals, interference, 251
- out-of-band transmitters, noise, minimizing, 258
- output power, 172
 - transmitters, 201

P

-
- packets, 183-184
 - panel antennas, 153-154
 - parabolic reflector antennas, 153
 - parasitic arrays, antennas, 134
 - paths, testing, 127
 - pattern isolation loss, 162
 - peak-hold feature, spectrum analyzers, 114
 - peer protocols, 182
 - penny ratios, wireless power, 32-33
 - peripheral devices
 - antenna systems, 172
 - distributors, 298
 - personnel, safety training, 226
 - physical layer
 - security features, 200-201
 - wired-interface features, 186-203

- physical site surveys
 - grounding, 102-105
 - height, 101
 - mounting, 102
 - placement, 99-101
 - pointing, 99
 - cables, routing, 98-99
 - controlled equipment environments, locating, 97
 - equipment-to-antenna distances, minimizing, 97-98
 - performing, 21-48, 52, 93-106, 135-166, 173, 250, 256, 260
 - preliminary network design
 - reviewing, 94
 - revising, 105-106
 - preparing for, 96
 - roofs, surveying, 99
 - site management, contacting, 95
- pigtails (connecting cables), 172
 - ping latency, monitoring, 262
 - placing antennas, physical site surveys, 99-101
 - PoE (Power-over-Ethernet), 203
 - point-to-multipoint architecture, 66-68
 - advantages, 68
 - antennas, selection, 69
 - bandwidth, managing, 69
 - cost, installation, 71
 - disadvantages, 69-71
 - evaluating, 82-83
 - facilities, cost, 70
 - hardware, initial cost, 70
 - LOS paths, determination, 70
 - low cost, 68
 - multiple point-to-multipoint architectures,
 - evaluating, 84
 - new technology testing, 68
 - scalability, 68
 - sectors, 68
 - site surveys, 70
 - support, 71
 - testing, 71
 - usage, 71
 - point-to-multipoint wireless links
 - testing, 245
 - point-to-point architecture, 21-66, 100, 104, 111-117, 125, 135-166, 173, 181-183, 231-235, 250, 256, 260
 - advantages, 59-62
 - antenna selection, 60
 - antennas
 - omnidirectional antennas, 60
 - system expansion, 63
 - appropriate usage, 65-66
 - backbone bandwidth, availability, 63
 - disadvantages, 62-65
 - equipment upgrades, 65
 - evaluating, 81
 - facility costs, 61
 - hardware costs, 61
 - high noise level, 66

- installation, costs, 62
- longer-than-normal links, 65
- LOS paths, 60
 - availability, 63
- low-noise hub sites, 64
- site surveys, 61-64
- support, 62
- testing, 62
- two locations, 65
- point-to-point wireless links, testing, 243
- polarization, antennas, 140-145
 - circular polarization, 143-144
 - cost-effective deployment, 145-146
 - cross polarization, 144-145
 - horizontal polarization, 142-143
 - multipath resistance, 147-148
 - noise reduction, 146-147
 - sector antennas, 167
 - vertical polarization, 140-141
- portable markets, serving, 268
- power (wireless), 32-36
 - focusing, antennas, 133-148, 250, 256, 260
 - penny ratios, 32-33
 - power ratios, 33-34
- power dividers, combined antenna systems, 156
- power limits (FCC), 280
- power lines, avoiding, antennas, 101
- power ratios, wireless power, 33-34
- Power-over-Ethernet (PoE), 203
- precipitation, signal interference, 29-30
- preliminary network design, physical site surveys
 - reviewing, 94
 - revising, 105-106
- pricing, services, 269
- propagation (wireless), 19-21
- protocols
 - application layer, 184
 - data link layer, 185
 - filtering, 206
 - network layer, 184
 - peer protocols, 182
 - transport layer, 184
- provider organizations
 - access point hardware, 294
 - antenna systems, 296
 - free space optical hardware, 295
 - security hardware, 295
 - wireless hardware, 293-294
 - wireless hotspot hardware, 294
 - wireless software, 298-299
- proximity, users, grouping by, 82

Q-R

- QoS (Quality of Service) network layer, 209
- radiation patterns, antennas, 39-40
- radio amateurs, becoming, 267

- radio frequency (RF) site surveys. *See* RF
- radios, smart radios, 200
- radius, sector antennas, 167
- rates, leases, sites, 128
- ratios, 32
- real-world obstacles, wireless networks, 11-12
- real-world signal inspections, spectrum analyzers, 115-118, 125
- receivers
 - high-power transmitters, performance issues, 286
 - noise, 251
 - noise figure, 202
 - selectivity, 198
 - thresholds, 202
- receiving antennas
 - gains, 51
 - sensitivity threshold, 52
 - transmission line loss, 51
- redundant end user coverage, cellular architecture, 73
- reflected waves, 25-28
 - microwave reflections, 26-28
 - sky waves, 25-26
- reflectors, antennas, 137-138
- refraction, signal interference, 30-31
- reserving throughput, 277
- residence-mounted antenna systems, grounding, 242
- resources
 - community networks, 302
 - e-mail lists, 302
 - online magazines, 301
 - suggested reading, 300-301
 - user groups, 302
- retransmission percentage, monitoring, 262
- RF (radio frequency) site surveys, 107
 - 802.11b access points, locating, 123
 - access point vulnerability to noise, 120
 - coverage, testing, 127
 - criteria evaluation and conclusion, 124-126
 - documenting, 124
 - in-band noise sources, locating, 122-123
 - nearby out-of-band noise sources, locating, 121
 - paths, testing, 127
 - point-to-point architecture, 64
 - SNR (signal-to-noise ratio), observing, 120
 - spectrum analyzers, 109-115
 - real-world signal inspection, 115-118, 125
 - substitutions, 124
 - test equipment, 108
- RIP (Router Information Protocol), 184, 208
- roaming
 - cellular architecture, 73
 - network layer, 209
- roof-mounted antenna bases, building, 232-234
- roofs, physical site surveys, 99
- rooftop-mounted antenna systems
 - cabling, running, 239
 - grounding, 240-242
 - guy wires, attaching, 237

- installing, 232-243
 - lightning protection, 240-242
 - masts, raising, 237-239
- route redundancy, mesh architecture, 77
- routed WANs, bridged WANs, compared, 212-213
- routing
 - cables, physical site surveys, 98-99
 - dynamic IP routing, 208
 - network layer, 207-208
 - static IP routing, 208
- Routing Information Protocol (RIP), 184, 208
- running cabling, rooftop-mounted antennas, 239
- runs, coaxial cable, 172

S

- safety
 - equipment, testing, 179
 - training, installation personnel, 226
 - wireless networks, 13-16
- SAs (spectrum analyzers), 259
- scalability, point-to-multipoint architecture, 68
- SEC (super Ethernet converter), 204
- sector antenna systems, 163, 165-166
 - downtilt, 168
 - F/B ratios, 168
 - horizontal beamwidth, 168
 - low-noise access point location, 167
 - polarization, 167
 - sector orientations, 167
 - sector radius, 167
 - selecting, 167-169
 - vertical beamwidth, 168
- sectors, point-to-multipoint architecture, 68
- security
 - application layer, 211
 - authentication, 206
 - data link layer, 205-207
 - encryption, 207
 - enhancing, 277-278
 - firewalls, 210
 - network layer, 209-210
 - physical layer, 200-201
 - software, providers, 295
- security hardware, provider organizations, 295
- selectable polarization, antennas, 200
- selectivity, signals, receivers, 198
- sensitivity threshold, receiver antennas, 52
- service organizations, 300
- shared bandwidth, dedicated bandwidth, compared, 214
- signals
 - atmospheric effects, 28-31
 - decibels (dBs), 272-273
 - diffraction, 28
 - Fresnel zone clearance, 46-49
- interference
 - amateur radio operators, 280
 - levels, minimizing, 251-263
 - out-of-bound signals, 251
- noise
 - direction-finding techniques, 259-261
 - documenting reduction results, 262
 - levels, minimizing, 251-263
 - manmade noise, 251
 - natural noise, 251
 - network performance, 262
- selectivity, receivers, 198
- SNR (Signal-to-Noise Ratio), 249-250, 256, 260
 - variations, 258-259
- weather problems, 28-31
- signal-to-noise ratio (SNR). *See* SNR
- Simple Mail Transfer Protocol (SMTP), 184
- simplex throughput, duplex throughput, compared, 195-196
- site management, contacting, physical site surveys, 95
- site surveys
 - conducting, 273
 - performing, 93
 - physical site surveys
 - antenna direction, 99
 - antenna grounding, 102-105
 - antenna height, 101
 - antenna mounting, 102
 - antenna placement, 99-101
 - cable routing, 98-99
 - controlled equipment environments, 97
 - equipment-to-antenna distance, 97-98
 - performing, 21-52, 93-106, 135-166, 173, 250, 256, 260
 - preliminary network design, 94, 105-106
 - preparing for, 96
 - roofs, 99
 - site management contacts, 95
- point-to-multipoint architecture, 70
- point-to-point architecture, 61-63
 - RF (radio frequency) site surveys, 64
- RF (radio frequency) site surveys, 107
 - 802.11b access points, 123
 - access point vulnerability to noise, 120
 - coverage testing, 127
 - criteria evaluation and conclusion, 124-126
 - documenting, 124
 - in-band noise sources, 122-123
 - nearby out-of-band noise sources, 121
 - path testing, 127
 - SNR (signal-to-noise ratio), 120
 - spectrum analyzers, 109-118, 124-125
 - test equipment, 108
- sites
 - availability, confirming, 90
 - equipment, accessing, 128
 - insurance, requirements, 128
 - interference, avoiding, 128
 - leases

- negotiating, 127-129
 - rates, 128
 - towers, requirements, 129
 - work requirements, 129
- sky waves, 25-26
- small and simple model, WISPs, 265
- small-office/home-office (SOHO) markets
 - servicing, 268
- smart antennas, 200
- smart radios, 200
- SMTP (Simple Mail Transfer Protocol), 184
- SNR (signal-to-noise ratio), 249-250, 256, 260
 - monitoring directly, 262
 - observing, 120
 - variations, 258-259
- software
 - security software, providers, 295
 - wireless software, 298-299
- SOM (system-operating margin), 52
- Spanning Tree Protocol, 204
- spectrum analyzers
 - band of frequencies, inspecting, 110-112
 - input, 109
 - output, 109
 - peak-hold feature, 114
 - RF site surveys, 109-115
 - real-world signal inspection, 115-118, 125
 - signals, detecting, 116
 - substitutions, 124
 - three-signal spectrum analyzer coverage, display, 112
 - wireless protocol analyzers, compared, 108
- spectrum analyzers (SAs), 259
- spillover, antennas, 41
- spread spectrum modulation, 7
- spread spectrum signaling, licence-free spread spectrum signaling, 8-9
- stable wireless networks, deploying, 273-275
- static IP routing, 208
- steady noise, 259
- sub-1 Mbps data rates, 197
- suggested reading, 300-301
- super Ethernet converter (SEC), 204
- support
 - point-to-multipoint architecture, 71
 - point-to-point architecture, 62
- switching, 204
 - turnaround time, 205
- system-operating margin (SOM), 52

T

- T1/E1 interfaces, 188
- T3/E3 interfaces, 188
- table sizes, MAC addresses, 204

- tagging, VLANs (virtual LANs), 205
- talkback/order wire interfaces, 188
- TCP (Transmission Control Protocol), 181
- TCP/IP reference model, 180-186
 - application layer, 184
 - data link layer, 185-186
 - frames, 183-184
 - network layer, 184
 - packets, 183-184
 - peer protocols, 182
 - services, 182-183
 - transport layer, 184
- Telnet, 184
- test equipment
 - manufacturers, 297
 - RF (radio frequency) site surveys, 108
- test techniques, 226
- testing
 - cellular architecture, 75
 - coverage, 127
 - documenting, 245
 - equipment
 - labs, 179
 - outdoors, 179-180
 - safety, 179
 - paths, 127
 - point-to-multipoint architecture, 71
 - point-to-point architecture, 62
 - wireless systems, 243-245
- three-signal spectrum analyzer coverage display, 112
- thresholds, receivers, 202
- throughput, 195-198
 - bandwidth, differentiating between, 268
 - data rate, compared, 195-196
 - managing, 275-277
 - measuring, 243, 276-277
 - reserving, 277
- tools, installations, 227
- topographic maps, purchasing, 80
- tower companies, cost considerations, 286
- tower-mounted antenna systems
 - grounding, 241
 - installing, 228-232
- towers
 - managing, 95
 - manufacturers, 296
 - requirements, 129
- Transmission Control Protocol (TCP), 181
- transmission line loss, receiver antennas, 51
- transmitter antenna system transmission line loss
 - link budget, 50
- transmitter output power, link budget, 50
- transmitters
 - configurable power control, 201
 - high-power transmitters, receiver performance, 286
 - out-of-band transmitters, noise reduction, 258
 - output power, 201
- transmitting antenna gain, link budget, 50

- transport layer
 - functions, 184
 - protocols, 184
- trends, anticipating, 282
- triangulation, antennas, 260
- Triple DES (3DES), 207
- turnaround time, switching, 205

U-V

- UDP (User Datagram Protocol), 184
- upper frequency limits, feed systems, 171
- user groups, resources, 302
- users, grouping, proximity, 82
- vertical beamwidth, 43
 - sector antennas, 168
- vertical polarization, antennas, 140-141
- vertical separation isolation, antenna systems, 161-162
- vertically polarized omnidirectional antennas, 145
- virtual private networks (VPNs), 210
- visual LOS paths, 43
 - wireless LOS paths, compared, 44
- VLANs (virtual LANs), tagging, 205
- VoIP (Voices over Internet Protocol), 188
- VPNs (virtual private networks), 210

W-X-Y-Z

- WANs (wide-area networks), 5-9
 - bridged WANs, 212-213
 - LOS (line-of-sight) paths, obtaining, 43-49
 - routed WANs, 212-213
 - wireless frequencies, 20
 - wireless power, 32-36
 - wireless propagation, 19-21
 - wireless WANs, 5-9
 - wireless wavelength, 21-22
- waterproofing, connections, 235-236
- wavelength, 21-22
- waves
 - electromagnetic waves, 20
 - free-space waves, 25
 - frequencies, 20
 - reflected waves, 25-28
 - microwave reflections, 26-28
 - sky waves, 25-26
 - wireless wavelength, 21-22
- WCAI (Wireless Communications Association International), 301
- weather problems, signals, 28-31
- WEP (Wired Equivalent Privacy), 278
- wide-area networks (WANs). *See* WANs
- wideband FHSS signals, 194

- wind, signal interference, 30
- wired backbones, wireless backbones, compared, 214
- Wired Equivalent Privacy (WEP), 278
- wired networks, wireless networks, compared, 3-4
- wired-interface feature options, physical layer, 186-203
- wireless 802.11b cards, 217
- wireless antennas
 - lightning protection, 14
 - safety issues, 13-16
- wireless backbones, wired backbones, compared, 214
- Wireless Communications Association International (WCAI), 301
- wireless equipment, environmental decisions, 218-221
- wireless hardware, provider organizations, 293-294
- wireless hotspot hardware, provider organizations, 294
- wireless Internet service providers (WISPs). *See* WISPs
- wireless licensing, 5-8
- wireless link budget calculations, 49-53
- wireless LOS (line-of-sight) paths,
 - obtaining, 43-49
 - compared, 44
- wireless networks, 11-12
 - See also* license-free wireless networks
 - available bandwidth, maximizing, 13-16
 - broadband, 4
 - intelligence, 7
 - license-free wireless networks, 5-9
 - real-world obstacles, 11-12
 - WANs (wide-area networks), 5-9
 - wired networks, compared, 3-4
 - working with, safety issues, 13-16
- wireless nodes, mesh architecture, 78
- wireless power
 - penny ratios, 32-33
 - power ratios, 33-34
- wireless propagation, 19-21
- wireless protocol analyzers, spectrum analyzers, compared, 108
- wireless signals, modulation, 7
- wireless software, 298-299
- wireless standards, 289-290
- wireless systems, testing, 243-245
- WISPA (Wireless Internet Service Providers Association), 301
- WISPs (wireless Internet service providers), 265, 294
 - industry organizations, 301
 - interference, dealing with, 279
 - large and complex model, 266
 - locating, 302
 - niche markets, serving, 267-268
 - small and simple model, 265
 - success, planning for, 265-270
 - visiting, 267
- work requirements, sites, 129
- Yagi-Uda antennas, 151