

## Numerics

- 2B1Q, 166
- 802.11b standard
  - key operations, 107–108
  - performance, 108–109
- 802.11g standard, 109
- 802.16 standard, 113
  - adaptive modulation schemes, 116
  - line-of-sight radio propagation, 131
  - MAC CPS, 124
    - MAC addressing, 124–126
  - modulation schemes, 121–122
  - network design, 131–132
  - overlapping network solutions, 131–132
  - privacy sublayer
    - key management protocol, 123
    - packet data encryption, 123
    - SAs, 123–124
  - reference model, 114
    - IEs, 119
    - MAC CPS, 115
    - MAC layer, 115
    - physical layer, 115–119
    - privacy sublayer, 115, 122–123
    - service-specific CS, 115
  - scheduling services, 126–127
    - GPC mode, 127–128
    - GPSS mode, 127–128
    - requests, 127
  - typical network architecture, 114
  - wireless MAN-SC air interface, 113

## A

- AAL (ATM adaptation layer), 225
- absorption loss, 153
- access networks, 7, 10
  - bottlenecks, causes of, 27
  - CCM approach
    - market analysis, 262–263
    - planning phase, 252, 257–258
  - comparing, 22–23
  - MANs, 10
  - wired, 10
    - cable networks, 17–19
    - DSL, 11–12
    - fiber, 12–17
    - PSTN, 19–20

- wireless, 20
  - fixed wireless, 21
  - free space optics, 22
  - infrared waves, 22
  - WiFi, 22
- acquisition techniques, 152
- active scanning, WLANs, 108
- ad hoc networks, 101–103, 243
- adaptive modulation schemes (802.16 standard), 116
- addition of holes, 140
- ADSL (asymmetrical DSL), 11, 170–171
  - interoperability with EPONs, 270–271
  - RADSL, 172–173
  - splitterless, 171–172
- ADSL lite, 172
- aerosol absorption coefficient, 153
- air as wireless medium, 87–88
- amplitude modulation, 9
- antennae
  - EIRP, 96–97
  - half-power beamwidth, 96
  - smart antennas, 97
    - major lobe, 98
    - multipath phase problem, 99
    - transmission strategies, 98
- antenna theory, 95–96
- APD (Avalanche photodetector), 145
- APONs, 36
- APs (access points)
  - ad hoc mode, 103
  - infrastructure mode, 102
- architectures
  - implementing, 222
  - of CWDM networks, 72
- ARPANET, 3
- ARQ (automatic repeat request), 187
- association (WLANs), 108
- asymmetrical DSL services. *See* ADSL
- asynchronous impulsive noise, 186
- ATM (Asynchronous Transfer Mode), 223
  - implementation costs, 227–228
  - in core networks, 224–225
  - PONs, 16
    - versus MPLS in core networks, 223, 226–227
- ATM forum, 224
- attenuation, 14, 87
  - of PLC channels, 185–186
- attenuation coefficient, 153
- attributes of CBR, 219
- ATU-C (ADSL terminal unit-central office), 170
- ATU-R (ADSL terminal unit-remote), 170

auto-tracking, 152  
 Avalanche breakdown, 146  
 Avalanche multiplication, 145  
 Avalanche photodiodes, 145–146

## B

backoff, 128  
 bandgap energy, 140  
 bandwidth management  
   attenuation, 14  
   impact on first mile access, 5–6  
     resource provisioning, 6–7  
   intelligent city networks, 213–214  
   last inch requirements, 240  
   maximizing with WDM, 59  
   on access networks, 7, 10  
     cable networks, 17–19  
     DSL, 11–12  
     fiber, 12–17  
     MANs, 10  
     PSTNs, 19–20  
     wired networks, 10  
     wireless, 20–22  
   protection bandwidth, 68  
 bandwidth on demand, 4  
 BE (Best-Effort) service, 127  
 beacon frames, 108  
 beam spreading, 154  
 BER (bit error rate), 62, 148–150  
 best-effort service, 216  
 BFSK (Binary Frequency Shift Keying), 93  
 billing, 274  
 BLSR (bidirectional line-switched ring), 69  
 BoD (bandwidth on demand), 204  
 bottlenecks  
   causes of in access networks, 27  
   commercial solutions to, 27–28  
 BPONs (broadband PONs), 16  
   advantages of, 37  
   cells, 36  
   CTS, 36  
   data rates, 36  
   interoperability with DSL and PLC, 271  
 BPSK (Binary Phase Shift Keying), 103  
 BRI (bit-rate interface), 166  
 broadband services, 7  
   DSL, 161–162  
     ADSL, 170–172  
     asymmetrical services, 164–165

CAP, 176  
 DMT, 175–176  
 DSLAMs, 163  
 HDSL, 166–167  
 HDSL2, 169–170  
 IDSL, 165–166  
 incremental services, 179  
 limitations of, 162  
 poor customer service, 177  
 RADSL, 172–173  
 service provisioning, 178  
 SDSL, 168  
 symmetrical services, 164  
 typical xDSL network, 176  
 USP, 162  
 VDSL, 173–174  
 BS (base station), backoff, 128  
 BSS (basic service set), 102  
 business case for first mile networks, 247. *See also*  
   technology case  
     CCM business model, 249–250  
       first mile planning process, 250–252,  
       257–258  
       pricing versus CDM model, 259–262  
     CDM business model, 248–249  
       Classical Terminal Assignment  
       problem, 249  
       incremental services, 249  
   data services, 238  
   intelligent cities, 203–207  
     backbone, 207–208  
     bandwidth management, 213–214  
     BoD, 204  
     economic implications, 209  
     managing, 210, 212–214  
     optical layer, 208  
   video services, 238  
     telemedicine, 240  
     video distribution, 239  
     videoconferencing, 239  
     visualization, 240  
   voice services, 236–237

## C

cable networks, 17–19  
 calculating  
   BER, 148–150  
   EIRP, 97  
   Mie scattering, 153

- optical power of optical splitter output, 32
- power budget, 152–153
- SNR, 150–151
- total loss, 152–153
- CAP (Carrierless Amplitude/Phase) modulation, 176
- CAPEX (capital expenditure), 248
- case studies
  - CCM business model, 249–250
    - first mile planning process, 250–252, 257–258
    - pricing versus CDM model, 259–262
  - CDM business model, 248–249
    - Classical Terminal Assignment problem, 249
    - incremental services, 249
  - of PLC
    - direct access point, 191–192
    - interface point, 191
    - management issues, 189
    - repeaters, 191
    - SNMP-based management, 189
- categories of last mile network end users, 241
- CATV (Community Antenna Television), 17
  - HFC, 18
  - HFC plant, 198–199
- CBR (constraint-based routing), 219
- CCK (Complementary Code Keying), 104–105
- CCM (cumulative comprehensive model) business model, 249–250
  - first mile planning process, 250–252, 257–258
  - market analysis of access area, 262–263
  - pricing versus CDM model, 259–262
- CDM (conventional distributed model) business model, 248–249
  - Classical Terminal Assignment problem, 249
  - incremental services, 249
  - pricing versus CCM model, 259–262
- CDMA, 90–91
  - DSSS, 92–93
  - FHSS, 91–94
  - handoff, 91
- cellular networks, WCDMA, 20
- channel characteristics of PLC, 185
  - attenuation, 185–186
  - impedance, 185
- channel spacing in WDM systems, 63
- characteristics of transponders, 74
- characterizing OADMs in CWDM networks, 72–74
- churns, 214
- circuit-based voice systems, 236
- Classical Terminal Assignment problem, 249
- classifying PONs, 36
  - APONs, 36
  - BPONs
    - advantages of, 37
    - cells, 36
    - data rates, 36
  - EPONs, 39–40, 42
  - GPONs, 38
    - design characteristics, 39
    - GFP, 38
    - GSR, 38
- CMIP (common management information protocol), 211
- collision avoidance, 100
- collisions
  - in 802.16 networks, contention resolution, 128
  - upstream communication in PON networks, 32–33
    - STDM, 34–35
    - TDM, 33
- colored background noise, 186
- commercial enterprise solutions to access network bottlenecks, 27–28
- common part sublayer (IEEE 802.16 MAC layer), 124
  - MAC addressing, 124–126
- communication infrastructure, prohibitive development costs, 183
- community networks, 233. *See also* intelligent city networks
  - data services, 238
  - data-centric applications, 236
  - economic viability, 235
  - Ethernet solution, 244
  - healthcare applications, 235
  - security needs, 234–235
  - TDM solution, 244
  - telemedicine, 240
  - video services, 238–239
  - visualization, 240
  - voice services, 236–237
- comparing
  - first mile access technologies, 22–23
  - performance of PON schemes, 53–54
  - PLC and alternative first-mile solutions, 195
  - pricing methods, CCM versus CDM business models, 259–262
- concave lenses, 151
- conduction state, 140
- congestion, 217
- contention resolution, IEEE 802.16, 128
- contention transmission, SSs, 128
- convex lenses, 151

core networks

- ATM, 224–225
  - implementation costs, 227–228
  - versus MPLS, 223, 226–227
- bandwidth management, 5
  - light-trials, 6
- first mile access problems, 4
- MPLS, 225–226
- CQ (custom queuing), 218
- creating business case for first mile networks, 247
- CSMA (carrier sense multiple access), 100, 187–188
- CTS (Common Technical Specification), 36
- CuPLUS, 189
- CWDM (coarse wavelength division multiplexing), 14, 60
  - benefits of, 67
  - channel spacing, 60
  - deployment standards, 66–67
  - Ethernet protection
    - with EtherChannel and UDLD, 71
    - with STP and UDLD, 71
  - interoperability with PONs, 268–269
  - lightpath protection, 68
    - line-switched protection, 69–70
    - path-switched 1+1 protection, 69
  - metro access solutions, 61
  - network architecture, 72
  - network design rules, 74
    - examples, 76–82
    - power-budget calculations, 75–76
  - network elements, 63
    - thin film filters, 65–66
    - VCESLs, 64–65
  - OADM, characterization, 72–74
  - protection bandwidth, 68
  - relaxed component manufacturing tolerance, 63
  - ring topology, 62
  - services, 67–68
  - versus DWDM, 63

## D

data- oriented communication, QoS architecture, 222–223

data rates

- of BPONs, 36
- of STP, 9

data services in first mile business case, 238

data-centric applications in community network, 236

dB (decibel), 277

DBR (distributed Bragg reflector) lasers, 142

delay spread, 100

deploying

- CWDM, standards, 66–67
- DSL, low cost of, 179
- FSO networks, 156
- PLC, telco requirements, 192–193

designing

- 802.16 networks, 131–132
- CWDM networks, 74
  - examples, 76–82
  - power-budget calculations, 75–76

devices

- CWDM, 63
  - thin film filters, 65–66
  - VCESLs, 64–65
- DSLAMs, 163
- lenses, 151
- modems, 9
- NF, 148
- optical receivers, 146–148
  - shot noise, 147
  - thermal noise, 147
- PCMICA cards, 107
- transponders, 62
  - characteristics of, 74

DFB (distributed fiber Bragg) lasers, 141

DiffServ, 219–220

digital divide, 7

direct access point in PLC first-mile networks, 191–192

disruptive technologies

- EPONs, 40, 42
  - locating market niches for, 41

distance limitations of SDSL, 168

distributed feedback, 141–142

Distributed IFS, 106

DL-MAP message format, 118

DMT (Discrete Multi-Tone), 175–176

DOCSIS specification, 122

Dostert, Klaus, 185

downlink subframes (IEEE 802.16), 119–121

downstream communication in PONs, 30

DSL (Digital Subscriber Line), 11–12, 162

- ADSL, 170–171
  - RADSL, 172–173
  - splitterless, 171–172
- asymmetrical services, 164–165
- cost of deployment, 179
- DSLAMs, 163
- HDSL, 166–167
- HDSL2, 169–170



FDD (frequency-division duplexing), 117–119  
     downlink subframe structure, 120  
 FDM (frequency-division multiplexing), 89–90  
 features of PONs, 28  
 FHSS (frequency hopping spread spectrum), 91–94  
 fiber cut, protecting against, 68–69  
 fiber networks, 12–13  
     attenuation, 14  
     bandwidth, WDM, 59  
     narrow-aperture lasers, 13  
     PONs, 15–17  
         ATM PONs, 16  
         BPONs, 16  
         EPONs, 17  
         features, 15–16  
         GPONs, 16  
     WDM, 3, 13–14  
         CWDM, 14  
         Light trails, 6  
 fiber to the curb, PLC-EPON networks, 194–195  
 fiber to the home, prohibitive cost of, 194  
 FIFO queueing, 218  
 first mile access problem, 4, 9  
 fixed wireless networks, 21  
 flow control, 217  
 Fraunhofer theory of diffraction, 95  
 free space optics, 22  
 frequency modulation, 9  
 FSK (frequency shift keying), 186–187  
 FSO systems, 138  
     deploying, 156  
     factors affecting  
         beam spreading, 154  
         Mie scattering, 153–154  
         Rayleigh scattering, 154  
         weather conditions, 154–155  
 lasers, 139–141  
     DBR, 142  
     DFB, 141–142  
     safety, 155  
 lenses, 151  
 receivers  
     photodetectors, 142–145  
     optical receivers, 146–148  
     tracking and acquisition techniques, 152  
 FTTU (fiber to the end user) through PON, 242  
 full duplex transmission, 12  
 future applications, 274–275

## G-H

G.Lite, 172  
 gain  
     antenna theory, 95–96  
     dBs, 277  
     processing gain of SS systems, 95  
 geometric path loss, 138  
 GFP (Generic Framing Protocol), 16, 38  
 GMPLS (Generalized Multiprotocol Label Switching), 211  
 GPC (Grant per Connection) mode, 127–128  
 GPONs (Gigabit PONs), 16, 38  
     design characteristics, 39  
     GFP, 38  
     GSR, 38  
 GPSS (Grant per Subscriber Station) mode, 127–128  
 GSR (gigabit service requirement), 38  
  
 half-power beamwidth, 96  
 handoff, 91  
 HDSL (high-data-rate DSL), 11, 166–167  
 HDSL2 (next-generation HDSL), 168–170  
 healthcare, broadband network applications, 235  
 HFC (hybrid fiber coax)  
     networks, 18  
     plants, 198–199  
 home networking, PLC solutions, 198  
 HomePlug 1.0 standard, 195–197  
  
**I**  
  
 IDSL (ISDN-DSL), 165–166  
 IEEE 802.11b, 103  
     dynamic rate shifting, 105  
     evolution of, 100  
         Mobile IP, 101–102  
     infrastructure mode, 102  
     key operations, 107–108  
     physical layer, 105  
         CCK, 104–105  
         MAC sublayer, 106  
         management frames, 106  
         QPSK, 103–104  
 IEEE 802.16  
     adaptive modulation schemes, 116  
     contention resolution, 128  
     line-of-sight radio propagation, 131

- MAC CPS, 124
  - MAC addressing, 124–126
- modulation schemes, 121–122
- network design, 131–132
- overlapping network solutions, 131–132
- privacy sublayer
  - key management protocol, 123
  - packet data encryption, 123
  - SAs, 123–124
- reference model, 114
  - IEs, 119
  - MAC CPS, 115
  - MAC layer, 115
  - physical layer, 115–119
  - privacy sublayer, 115, 122–123
  - service-specific CS, 115
- scheduling services, 126–127
  - GPC mode, 127–128
  - GPSS mode, 127–128
  - requests, 127
- typical network architecture, 114
- wireless MAN-SC air interface, 113
- IEEE 802.1Q VLANs, 221–222
- IEs (information elements), fields, 119
- IFS (Interframe space), 106
- impedance of PLC channels, 185
- implementing
  - MPLS and ATM, cost of, 227–228
  - network architectures, 222
- incremental services, 249
- indoor power-line networks, 184–185
- infrared waves, 22
- initialization of SSs, 128–130
- intelligent city networks, 203–207
  - backbone, 207–208
  - bandwidth management, 213–214
  - BoD, 204
  - economic implications, 209
  - managing, 210, 212
    - bandwidth management, 213–214
    - mobility management, 212–213
  - optical layer, 208
- interface point of PLC first-mile networks, 191
- interoperability
  - of BPONs and DSL, 271
  - of CWDM and PON, 268–269
  - of EPONs and ADSL, 270–271
  - of EPONs and WiFi, 270
  - PLC and LRE, 269–270
- interwavelength distance, 60
- IntServ (Integrated Services), 220–221

- IPACT (Interleaved Polling with Adaptive Cycle Time), 48
  - comparing performance with other PON schemes, 53–54
- ISM (Industrial, Scientific, and Medical) band, 102
- ITU G.694.2 recommendation, 66

## J-K

---

- jitter, 216

- key management protocol (IEEE 802.16 privacy sublayer), 123

## L

---

- label stacking, 225–226

- labels, 225

- lasers, 139–141

- DBR, 142

- DFB, 141–142

- FSO, safety, 155

- narrow-aperture, 13

- VCSELs, 64

- line width, 65

- lasing threshold, 141

- last inch

- bandwidth requirements, 240

- wireless solution, 243

- Legacy TDM networks, 216

- legislation, Telecommunications Act of 1996, 7

- lenses, 151

- Light trails, 6

- lightpath protection of CWDM networks, 68

- line-switched protection, 69–70

- path-switched 1+1 protection, 69

- limitations of DSL, 162

- line encoding standards

- CAP, 176

- DMT, 175–176

- line width, 65

- line-of-sight radio propagation, 802.16, 131

- line-switched protection, 69–70

- link-margin analysis, 152–153

- load balancing, 217

- LRE (long-reach Ethernet), 42–43

- interoperability with PLC, 269–270

- multiple-dwelling deployments, 174

- self-synchronizing scrambler mechanism, 174

# M

- MAC (media access control)
  - addressing, IEEE 802.16, 124–126
  - HomePlug 1.0, 196–197
  - in PLC, CSMA, 187–188
- MAC CPS (IEEE 802.16 standard), 115
- MAC layer (IEEE 802.16 standard), 115
- MAC sublayer (802.11b physical layer), 106
- management frames (802.11b), 106
- management systems, impact on billing, 274
- managing
  - intelligent city networks, 210, 212
    - bandwidth management, 213–214
    - mobility management, 212–213
  - multiple technologies in networks, 272–274
  - PLC networks, 189
- MANs (metropolitan-area networks), 10,
  - See also* WirelessMAN standard
  - intelligent city networks, 207
- market analysis
  - of CCM access area, 262–263
  - of PLC, 197–198
- market niches for new technologies, 41
- maximizing optical fiber bandwidth, 60
- mean center wavelength, 73
- measuring
  - fairness of TUR in PONs, 52
  - receiver performance
    - BER, 148–150
    - SNR, 150–151
- Mie scattering, 153–154
- minislots, 119
- mismatch of electronic technology and optical
  - bandwidth, 59
- MMF (multimode fiber), 272
- Mobile IP, 101–102
- modems, 9
- modes, 272
- modulation schemes, 9
  - CAP, 176
  - for IEEE 802.16 standard, 121–122
    - physical layer, 116
  - FSK, 186–187
  - OFDM, 187–188
  - PLC requirements, 186
  - QAM, 170
    - in LRE implementations, 174
  - QPSK, 103–104
  - SS, 187
- MPCP (Multipoint Control Protocol), 44
- MPLS (Multiprotocol Label Switching), 4, 211
  - implementation costs, 227–228
  - in core networks, 225–226
  - traffic queueing, 218
  - versus ATM in core networks, 223, 226–227
- multiple technologies
  - billing, 274
  - managing, 272–274
- multiple-dwelling deployments, LRE, 174
- multiple-tier networks, 5
- multiplexing
  - CDMA, 90–91
    - DSSS, 92–93
    - FHSS, 91–94
  - CWDM, 60
    - benefits of, 67
    - channel spacing, 60
    - deployment standards, 66–67
    - lightpath protection, 68–70
    - metro access solutions, 61
    - network architecture, 72
    - network elements, 63
    - OADM, characterization, 72–74
    - protection bandwidth, 68
    - ring topology, 62
    - services, 67–68
    - thin film filters, 65–66
    - VCEs, 64–65
  - FDM, 89–90
  - multiple frequencies on power lines, 186
  - OFDM, 188
  - TDM, 88–89
  - WDM, 63
- multiplicative factor, 146
- municipality-owned networks. *See* intelligent city networks

# N

- narrow-aperture lasers, 13
- narrowband noise, 186
- network management, 272–274
- NF (noise figure), 148
- nodal failure, protecting against in CWDM networks, 68
- noise in PLC channels, 186
- NP (nondeterministic polynomial time) complete, 6
- nrtPS (non-real-time polling service), 127
- NtPLUS, 190



## O

- OADM (optical add/drop multiplexers), 62
- OFDM (orthogonal FDM), 187–188
- OLTUs (optical line terminal units), 17, 29–30
- ONU (optical network unit), 17, 29–30
- optical communications, units of power measurements, 277
- optical fiber networks, 12–13
- optical layer (intelligent city networks), 208
- optical loss, 153
- optical networks
  - attenuation, 14
  - CWDM, 60
    - benefits of, 67
    - channel spacing, 60
    - deployment standards, 66–67
    - design rules, 74–76
    - Ethernet protection, 71
    - lightpath protection, 68–70
    - metro access solutions, 61
    - network architecture, 72
    - network design examples, 76–82
    - network elements, 63
    - OADM, characterization, 72–74
    - protection bandwidth, 68
    - ring topology, 62
    - services, 67–68
    - thin film filters, 65–66
    - VCSELs, 64–65
  - lasers, 139–141
    - DBR, 142
    - DFB, 141–142
  - modes, 272
  - narrow-aperture lasers, 13
  - PONs, 15–17
    - APONs, 16, 36
    - BPONs, 16, 36–37
    - calculating optical power of optical splitter output, 32
    - EPONs, 17, 39–40, 42–52
    - features, 15–16, 28
    - GPONs, 16, 38–39
    - topology, 29–31
    - upstream communication, 32–35
  - third generation, 208
  - WDM, 13–14
    - interwavelength distance, 60
- optical receivers, 146–148
  - shot noise, 147
  - thermal noise, 147
- overlapping 802.16 network solutions, 131–132

## P

- P2MP topology, EPONs, 43–44
- packet-based networks versus TDM networks, 211
- PAgP (Port Aggregation Protocol), 71
- paradigm shift in telecommunications business model, causes of, 233
  - data services, 238
  - data-centric applications, 236
  - economic viability, 235
  - health care applications, 235
  - security needs, 234–235
  - telemedicine, 240
  - video services, 238–239
  - visualization, 240
  - voice services, 236–237
- pass-band, 73
- path-switched 1+1 protection, 69
- PCM (pulse code modulation), 237
- PCMCIA cards for WLANs, 107
- peak wavelength, 73
- performance
  - BER, 62, 148–150
  - comparative evaluation of PON schemes, 53–54
  - of 802.11b networks, 108–109
  - SNR, 150–151
- performance oversupply, 40
- per-hop behavior, 220
- periodic impulse noise, 186
- phase modulation, 9
- phase shift keying, QPSK, 103–104
- photocurrent, 143
- photodetectors, 142–143
  - PIN, 143–145
- photodiodes, 143
  - Avalanche, 145–146
  - PIN, 143–145
- photonic winter, 205
- physical layer
  - of IEEE 802.11b standard, 105
    - CCK, 104–105
    - MAC sublayer, 106
    - management frames, 106
    - QPSK, 103–104
  - of IEEE 802.16 standard, 115–116
    - FDD, 117–119
    - FDD downlink subframe structure, 120
    - TDD downlink subframe structure, 120
    - modulation schemes, 116
  - of HomePlug 1.0, 197
- PIN photodetectors, 143–145
- PIN photodiodes, 143–145

- planning first mile, CCM approach, 250–252, 257–258
- PLC (power-line communication), 4, 183
  - adapting to telco requirements, 192–193
  - and alternative first-mile solutions, 195
  - case study
    - direct access point, 191–192
    - interface point, 191
    - management issues, 189
    - repeaters, 191
    - SNMP-based management, 189
  - channel characteristics, 185
    - attenuation, 185–186
    - impedance, 185
  - EPON solutions, fiber to the curb, 194–195
  - HomePlug 1.0 standard, 195–196
  - indoor power-line networks, 184–185
  - interoperability
    - with BPONs, 271
    - with LRE, 269–270
  - market analysis, 197–198
  - modulation
    - FSK, 186–187
    - OFDM, 187
    - SS, 187
  - modulation requirements, 186
  - multiplexing, 186
    - OFDM, 188
  - noise, 186
  - signal processing, 196
  - standardization, HomePlug 1.0, 196–197
  - standards and frequency regulations, 189
  - versus DSL, 198
- PLCP (Physical Layer Convergence Protocol), 105
- PLUSmms, 190
- PMD (physical medium dependent), 105
- point-coordination IFS, 106
- PONs, 15–17
  - APONs, 16, 36
  - BPONs, 16
    - advantages of, 37
    - cells, 36
    - data rates, 36
  - calculating optical power of optical splitter output, 32
  - comparing performance of PON schemes, 53–54
  - EPONs, 17, 39–40, 42
    - IPACT, 48
    - P2MP topology, 43–44
    - standardization, 42–43
    - TUR, 44–52
  - features of, 15–16, 28
  - FTTU, 242
  - GPONs, 16
    - design characteristics, 39
    - GFP, 38
    - GSR, 38
  - interoperability with CWDM, 268–269
  - topologies, 29
    - OLT, 29–30
    - ONU, 29–30
    - star topology, 31
  - upstream communication, 32
    - prohibitive cost of, 33
    - STDN, 34–35
    - TDM, 33
- population inversion, 140
- POTS splitters in ADSL implementations, 171
- power measurements, 277
- power-budget calculations, 75–76, 152–153
  - maximum distance in point-to-point systems, 75–76
  - maximum distance in ring systems, 76
- PQ (priority queuing), 218
- preamplifiers, 146
- pricing methods, CCM versus CDM business model, 259–262
- privacy sublayer (IEEE 802.16 standard), 115, 122–123
  - key management protocol, 123
  - packet data encryption, 123
  - processing gain, 95
  - SAs, 123–124
- prohibitive cost of BPON deployment, 37
- protecting CWDM networks from failure
  - dedicated protection, 70
  - equipment failure, 68
  - fiber failure, 68–69
  - line-switched protection, 69–70
  - N protection, 70
  - path-switched 1+1 protection, 69
  - shared protection, 70
  - with EtherChannel and UDLD, 71
  - with STP and UDLD, 71
- protection bandwidth, 68
- PSTNs (Public Switched Telephone Networks), 19–20
  - STP-based, 9
  - universal connectivity, 241

## Q

- Q factor, 63
- QAM (Quadrature Amplitude Modulation), 170
  - in LRE implementations, 174
- QoS (quality of service), 216–217
  - architectures
    - for data-oriented communication, 222–223
    - for voice-oriented communication, 222
  - DiffServ, 219–220
  - in small-scale networks, 216
  - IntServ, 220–221
  - service classes, 217–218
- QPSK (Quadrature Phase Shift Keying), 11, 103–104
- queuing traffic with MPLS, 218

## R

- RADSL (rate-adaptive DSL), 172
- rain-fade factor, 131
- Raleigh fading, 100
- ranging, 36
- Rayleigh scattering, 154
- RBOCs (regional Bell operating companies), telco
  - deployment requirements, 192–193
- receivers
  - DSSS, 93
  - measuring performance
    - BER, 148–150
    - SNR, 150–151
  - optical, 146–148
  - photodetectors, 142–143
    - PIN, 143–145
  - shot noise, 147
  - thermal noise, 147
- Reciprocity theorem, 95
- reference protocol model for IEEE 802.16
  - standard, 114
    - IEs, 119
    - MAC CPS, 115
    - MAC layer, 115
      - CPS, 124–126
      - privacy sublayer, 122–124
    - physical layer, 115–116
      - duplexing schemes, 116–119
      - modulation schemes, 116
    - privacy sublayer, 115
    - service-specific CS, 115

- reflective stack (thin film filters), 66
- relaxed manufacturing tolerance of CWDM
  - components, 63
- repeaters in PLC first-mile networks, 191
- requests, 127
- residential access of HDSL, 167
- resource allocation, 217
- resource provisioning, 6–7
- revenue matrix for service-based pricing, 259–260
- ring topology, CWDM networks, 62
- roaming, 108
- RpPLUS, 189
- RSpec, 220
- RSTP, CWDM Ethernet protection, 71
- RSVP, (Resource Reservation Protocol), 221
- rtPS (Real-time Polling Service), 127

## S

- S/W (share to work) ratio, 70
- safety for FSO networks, 155
- SAR (segmentation and reassembly) sublayer (ATM), 225
- SAs (IEEE 802.16 privacy sublayer), 123–124
- scattering
  - Mie scattering, 153–154
  - Rayleigh scattering, 154
- scheduling services, IEEE 802.16, 126–127
  - GPC mode, 127–128
  - GPSS mode, 127–128
  - requests, 127
- SDSL (symmetrical DSL), 168
- security, broadband network requirements, 234–235
- self-synchronizing scrambler mechanism
  - in LRE, 174
- semiconductor-based photodetectors, 143
- service categories (ATM), 224
- service classes, 217–218
- service provisioning of DSL, 178
- service-specific CS (IEEE 802.16), 115
- Shannon's theory, 94
- shared protection, 70
- Short IFS, 106
- shot noise, 147
- signal processing of PLC, 196
- signaling, 214
- single-pair DSL, 168
- single-to-multipoint splitters, 30
- SLAs (service-level agreements), 217
- slow-hopping, 91

- small-scale networks, QoS, 216
- smart antennas, 97
  - major lobe, 98
  - multipath phase problem, 99
  - transmission strategies, 98
- SNMP (Simple Network Management Protocol), PLC management, 189
- SNR (signal-to-noise ratio), 150–151
  - of PLC channels, 185
- soft switches, 237
- spacers (thin film filters), 66
- spacing, 60
  - in WDM systems, 63
- splitterless ADSL, 171–172
  - RADSL, 172–173
- splitters, single-to-multipoint, 30
- spontaneous emission, 140
- SS (spread spectrum) systems, 187
  - FHSS, 93–94
  - processing gain, 95
- SSL (Secure Sockets Layer), 238
- SSs (subscriber stations)
  - contention transmission, 128
  - initialization, 128–130
- standards
  - EFM, 42–43
  - IPACT, 48
  - P2MP topology, 43–44
  - TUR, 44–52
- for CWDM deployment, 66–67
- IEEE 802.16, 113
  - contention resolution, 128
  - line-of-sight radio propagation, 131
  - MAC CPS, 124–126
  - modulation schemes, 121–122
  - network design considerations, 131–132
  - overlapping network solutions, 131–132
  - privacy sublayer, 122–124
  - reference model, 114–119
  - scheduling services, 126–128
  - SS initialization, 128–130
  - typical network architecture, 114
  - wirelessMAN-SC air interface, 113
- PLC, 189
  - HomePlug 1.0, 195–197
- star topology of PONs, 31–32
- start point indicators, 45
- STDM, 34
  - implementing in PONs, 34–35
  - synchronization, 35
- stimulated emission, 140

- STP (shielded twisted-pair), 9
  - data transfer rates, 9
  - Ethernet protection in CWDM networks, 71
- subcarriers, 196
- subframes (IEEE 802.16), 119–121
- subheaders of IEEE 802.16 MAC layer, 126
- symmetrical DSL services, 164
  - SDSL, 168
  - symmetrical VDSL, 173–174
- synchronization, STDM, 35

---

## T

---

- TDD, downlink subframe structure, 120
- TDM (time-division multiplexing), 12, 88–89, 244
  - implementing in PONs, 33
- TE (traffic engineering), 217
- technology case
  - categories of last mile network end users, 241
  - Ethernet solutions, 244
  - FTTU, 242
  - last inch solutions, 243
  - TDM solutions, 244
- telcos, PLC deployment requirements, 192–193
- telecommunications, causes for business model paradigm shift, 233
  - data services, 238
  - data-centric applications, 236
  - economic viability, 235
  - healthcare applications, 235
  - security needs, 234–235
  - telemedicine, 240
  - video services, 238–239
  - distribution, 239
  - visualization, 240
  - voice services, 236–237
- Telecommunications Act of 1996, 7
- teleconferencing, 274
- telemedicine, role in telecommunications business model, 240
- thermal noise, 147
- thin film filters, 65–66
- third generation of optical networks, 208
- topologies
  - of PONs, 29
    - EPONs, P2MP, 44
    - OLT, 29–30
    - ONU, 29–30
    - star topology, 31
  - ring, CWDM networks, 62

total loss, calculating, 152–153  
 tracking, 152  
 transition layer (thin film filters), 66  
 transponders, 62  
   characteristics of, 74  
 TSpec, 220  
 TUR (Transmission Upon Reception), 44–46  
   comparing performance with other PON schemes, 53–54  
   measuring fairness, 52  
   numeric evaluation of, 49–51  
   system operation, 47–48  
 typical xDSL network, 176

## U

UDLD (unidirectional link detection), Ethernet  
   protection in CWDM networks, 71  
 UGS (Unsolicited Grant Service), 127  
 UL-MAP message format, 118–119  
 underbilling, 274  
 unified management of intelligent city  
   networks, 214  
 units of power measurement, 277  
 universal connectivity of PSTN, 241  
 uplink subframes (IEEE 802.16), 119–121  
 upstream communication in PONs, 30, 32  
   prohibitive cost of, 33  
   STDN, 34–35  
   TDM, 33  
 USP (user selling point) of DSL, 162  
 UPSR (unidirectional path-switched ring), 69

## V

VCESLs (vertical cavity surface emitting lasers, 64–65  
 VDSL (very-high-data-rate DSL), 173  
   LRE, 174  
   multiple-dwelling deployments, 174  
   self-synchronizing scrambler  
     mechanism, 174  
   symmetrical DSL, 173–174  
 video distribution, 239  
 video services in first mile business case, 238–239  
 videoconferencing, 239

visualization, role in telecommunications business  
   model, 240  
 VLANs, IEEE 802.1Q, 221–222  
 voice oriented communication, QoS  
   architecture, 222  
 voice services in first mile business case, 236–237  
 VoIP, 237

## W-Z

WCDMA (wideband code-division multiple  
   access), 20  
 WDM (wavelength division multiplexing) systems, 3,  
   13, 59, 63  
   CWDM, 14, 60  
     benefits of, 67  
     channel spacing, 60  
     deployment standards, 66–67  
     lightpath protection, 68–70  
     metro access solutions, 61  
     network architecture, 72  
     network design examples, 76–82  
     network design rules, 74–76  
     network elements, 63  
     OADMs, characterization, 72–74  
     protection bandwidth, 68  
     relaxed component manufacturing tolerance,  
       63  
     ring topology, 62  
     services, 67–68  
     thin film filters, 65–66  
     VCESLs, 64–65  
     versus DWDM, 63  
   interwavelength distance, 60  
   light trails, 6  
 weather conditions, effect on FSO, 154–155  
 WFQ (weighted fair queuing), 218  
 WiFi, 22  
   interoperability with EPONs, 270  
 wired networks, 4  
   as access networks, 10  
     cable networks, 17–19  
     DSL, 11–12  
     fiber, 12–17  
     PSTN, 19–20  
 wireless networks, 4, 20, 212  
   air as medium, 87–88  
   delay spread, 100

- fading, 100
- FHSS, 93–94
- fixed wireless, 21
- free space optics, 22
- infrared waves, 22
- mobility management, 213
- multiplexing
  - CDMA, 90–93
  - FDM, 89–90
  - TDM, 88–89
- WiFi, 22
- wireless solution for last inch users, 243
- WirelessMAN standard, 113
  - contention resolution, 128
  - line-of-sight radio propagation, 131
  - MAC layer
    - CPS, 124–126
    - privacy sublayer, 122–124
  - modulation schemes, 121–122
  - network design considerations, 131–132
  - reference model, 114
    - IEs, 119
    - MAC CPS, 115
    - MAC layer, 115
    - physical layer, 115–119
    - privacy sublayer, 115
    - service-specific CS, 115
  - scheduling services, 126–127
    - GPC mode, 127–128
    - GPSS mode, 127–128
  - requests, 127
  - SSs, initialization, 128–130
  - typical network architecture, 114
  - wirelessMAN-SC air interface, 113
- WirelessMAN-SC air interface, 113
- WLANs (wireless LANs), 22, 100
  - active scanning, 108
  - ad hoc, 101
  - association, 108
  - roaming, 108