

## Symbols

---

### A

---

- AAA (authentication, authorization, and accounting) 43–44, 421
  - commands 53–68
    - aaa accounting system command 51
    - aaa authentication enable command 58
    - aaa authentication login command 55
    - aaa authentication ppp command 59
    - aaa authorization command 61
    - aaa new-model command 62
  - configuring 45–52
  - defining 44–45
  - protocols 45–46
- access
  - broadband 11–12, 365
    - ADSL 384–392
    - cable 366
    - DSL 366, 380–383
    - satellite 367–368
    - wireless 368–369
  - central site connections 19
  - Cisco Access Control 46, 49
    - administrator GUI client 50
    - components 49–50
    - options 48
    - routers 46–47
  - LAPM 83
  - remote node connections 112–113
  - routers 51
  - servers 48
  - WAN 16
    - remote access 26–37
    - remote/branch offices 22
- access lists
  - configuring 179
  - DDR 172
  - dialer lists 178–179
  - IPSec 455
- access-list command 172
- accounting. *See also* AAA
- ACL (access control list) 466
  - configuring 467
  - symmetrical peer 468
- ACS (Cisco Secure Access Control Server) 46, 49
  - administrator GUI client 50
  - components 49–50
  - options 48
  - routers 46–47
- activation of dial backups 275–276
- active states, Frame Relay 236
- adaptation rates 186
- adding routes 286
- addresses
  - async interface commands 119–120
  - DLCI 234
  - IP
    - configuring 343–354
    - global addresses 342–343
    - NAT 331–338
    - source addresses 339–342
    - troubleshooting 354–359
  - mapping 238–240
  - overlapping 353
  - PAT 333
    - configuring 395, 400
    - DSL 396
- administration of networks 47
- administrator GUI client, ACS 50
- ADSL (asymmetric digital subscriber line) 381, 384–392
- Advanced Voice Video and Integrated Data (AVVID) 379
- AH (Authentication Header) 421, 437, 464
- algorithms
  - Diffie-Helman 434
  - hashing 435
  - LZ 136
- amplifiers 74
- antenna sites 373
- applications
  - dialer profiles 215
  - traffic (WAN) 16
- applying DLCIs 240
- architecture, PPP 113–115
- asymmetric digital subscriber line (ADSL) 381, 384–392
- asymmetric encryption 433. *See also* encryption
- async interface 117

async interface commands 117–120  
*asynchronous analog dialup connections, 73. See also modems*  
 asynchronous callback 130  
**Asynchronous Callback Line/Interface Commands**  
 132  
 asynchronous connections  
   chat scripts 104–105  
   configuring 93–95  
   interface async command 87  
 asynchronous interfaces, rotary groups 207  
 asynchronous lines, connecting NAS 91  
**ATM (Asynchronous Transfer Mode)** 13  
   configuring 399  
   troubleshooting 402  
**authentication** 420. *See also AAA*  
   Layer 2 B channel 58  
   login 55  
   PPP 59, 121–128  
   remote/branch offices 23  
**Authentication Header (AH)** 421, 437, 464  
 authentication, authorization, and accounting (AAA)  
 43–44, 421  
   commands 53–68  
   configuring 45–52  
   defining 44–45  
   protocols 45–46  
**authorization** 420. *See also AAA*  
   with character mode 65  
   commands 64  
   configuring 60  
**autoconfiguration.** *See also configuration*  
   chat scripts 104–105  
   modems 96–103  
     debugging 103  
     troubleshooting 104  
**autoconfigure type command** 99  
**autodiscovery**  
   configuring 98  
   modems 97  
**autoselection**  
   command, 118  
   PPP encapsulation 116  
**AUX ports, connecting** 90  
**availability**  
   remote/branch offices 23  
   WAN 16  
**AVVID (Advanced Voice Video and Integrated Data)** 379

**B**

**B channels, ISDN dialer profiles** 214  
**backups**  
   central site connections 20  
   commands  
     backup delay command 276  
     backup interface command 275–276  
     backup interface dialer number command 282  
     backup load command 278  
   dial  
     configuring 273–280  
     dialer interfaces as 280–282  
     dialer watch 289–290  
     floating static routes 287  
     verifying 286  
   load 282–290  
**backward explicit congestion notification (BECN)**  
 252  
**balancing loads**, 284  
**bandwidth**  
   command 183  
   compression 320–325  
   MLP 182–184  
   queuing 297. *See also queuing*  
   speed comparisons 16–18  
   WAN 16  
**basic rate interface.** *See BRI*  
**BECN (backward explicit congestion notification)**  
 252  
**binding outbound calls, troubleshooting** 223  
**branch offices**  
   installing 33  
   WAN 21–23  
**BRI (basic rate interface)**  
   configuring 153–160  
   monitoring 187, 190–191  
**bridge-group virtual interface (BVI)** 387  
**bridging ADSL**, 387. *See also ADSL*  
**broadband.** *See also bandwidth; connections*  
   access 11–12  
   cable  
     components 376–378  
     HFC 373–374  
     infrastructure 370–373  
     provisioning 379  
     RF channels 374–376  
     router configuration 379–380

- 
- connections
    - ADSL 384–392
    - cable 366
    - DSL 366, 380–383
    - satellite access 367–368
    - wireless access 368–369
  - DSL
    - configuring 393
    - troubleshooting 400–405
  - buffered mode 84
  - BVI (bridge-group virtual interface) 387
  
  - C**
  - C/N (carrier-to-noise) 377
  - CA (Certificate of Authority) 420
  - cable. *See also* bandwidth; connections
    - connections 30
    - infrastructure 370–373
      - components 376–378
      - HFC 373–374
      - provisioning 379
      - RF channels 374–376
      - router configuration 379–380
    - modems 366
  - cable modem termination system (CMTS) 373
  - CAB-OCTAL-ASYNC 80
  - CAB-OCTAL-KIT 80
  - callback
    - asynchronous 130
    - clients 133
    - disconnecting 135
    - PPP 121, 128, 131–133
    - servers 134
  - called party number verification 185–186
  - calling line identification (CLID) 184–185
  - calls, configuring simple ISDN 175
  - CAP modulation 385
  - carrier signals 377
  - carrier-to-noise (C/N) 377
  - CBWFQ (Class-Based Weighted Fair Queuing) 297
    - class defaults 312
    - configuring 305–314
  - CCITT (Consultative Committee of International Telegraph and Telephone) 74
  - central office (CO) broadband connections 365
  - central sites
    - protocols 48
    - routers 21
    - WAN 18, 19–21
  - Certificate of Authority (CA) 420
  - CET (Cisco Encryption Technology) 436
  - Challenge Handshake Authentication Protocol (CHAP) 121–128
  - channel service units/data service units (CSUs/DSUs) 6
  - channel service units (CSUs) 74
  - channels, ADSL 385. *See also* ADSL
  - CHAP (Challenge Handshake Authentication Protocol) 121–128
  - character mode, authorization commands 65
  - chat scripts 104–105
  - CIR (committed information rate) 252
  - circuits, Frame Relay 233. *See also* Frame Relay
  - circuit-switched connections
    - dial backups 273–280
    - dialer interfaces as 280–282
  - Cisco Access Control 46, 49
    - administrator GUI client 50
    - components 49–50
    - options 48
    - routers 46–47
  - Cisco Encryption Technology (CET) 436
  - Cisco product selection tools 36
  - Cisco Secure Access Control Server. *See* ACS
  - class class-default command 312
  - Class-Based Weighted Fair Queuing (CBWFQ) 297, 305–314
  - classes
    - class-map command 310
    - defaults 312
    - defining 212
    - dialer maps 211
  - clearing
    - commands 477
    - NAT entries 357
  - CLID (calling line identification) 184–185
  - clients
    - ACS 50
    - configuring 394
    - CPE as 392–397
    - PPP callback 133
    - PPPoE 394
    - RADIUS 54
    - security 48
    - TACACS+ 53

clock source command 165  
clock speed 252  
clouds, Frame Relay 232  
CMTS (cable modem termination system) 373  
CO (central office) broadband connections 365  
coaxial cable 376. *See also* cable  
codecs (coders/decoders) 73  
coexistence, ADSL/POTS 384  
commands 117  
AAA 53–68  
    aaa accounting system 51  
    aaa authentication enable 58  
    aaa authentication login 55  
    aaa authentication ppp 59  
    aaa authorization 61  
    aaa new-model 62  
access-list 172  
accounting 66–68  
async interface 119–120  
Asynchronous Callback Line/Interface 132  
autoconfigure type 99  
autoselect 118  
backups  
    backup delay 276  
    backup interface 275–276  
    backup interface dialer number 282  
    backup load 278  
bandwidth 183  
class class-default 312  
class-map 310  
clear 477  
clock source 165  
crypto  
    crypto ipsec security-association lifetime 466  
    crypto ipsec transform-set 464  
    crypto isakmp enable 457  
    crypto isakmp identity 461  
    crypto isakmp key 461  
    crypto isakmp policy 457  
    crypto maps 472  
debug 189  
    debug confmodem 103  
    debug crypto ipsec 478  
    debug dialer 192  
    debug dialer packet 226  
    debug isdn events 192  
    debug ppp authentication 144, 192  
    debug ppp multilink 142  
    debug ppp negotiation 144, 192, 404  
delay 0 40 277  
dial backups 275  
dialer  
    dialer callback-secure 135  
    dialer callback-server username 135  
    dialer enable-timeout 129  
    dialer hold-queue timeout 129  
    dialer idle-timeout 168  
    dialer isdn speed 56 218  
    dialer load-threshold 170, 182  
    dialer load-threshold load 143  
    dialer map 135, 157, 173  
    dialer pool-member 219, 220, 223  
    dialer pool-member number 281  
    dialer profiles 214  
    dialer rotary-group 206  
    dialer string 212  
    dialer watch 289–290  
    dialer-group 172  
    dialer-list 171  
    dialer-map 125  
dsl operating-mode 398  
encapsulation hdlc 159  
EXEC 92  
fair-queue 304  
frame-relay  
    frame-relay map 239  
    frame-relay traffic-rate 260  
group-range 207  
import all DHCP pool configuration 397  
interface  
    interface async 87  
    interface atm number 394  
    interface dialer 205  
    interface dialer global 217  
    interface serial 87  
    interface serial interface-number 159  
ip  
    ip address 119  
    ip dhcp pool name global configuration 397  
    ip route 288  
    ip tcp header-compression 138  
    ip tcp header-compression passive 138  
    ip unnumbered 119  
isdn  
    isdn answer1 186  
    isdn answer2 186  
    isdn call interface 192  
    isdn caller 185

---

- isdn configuration 157
- isdn disconnect interface 192
- isdn switch-type 158, 162
- line 85–88
- linecode 164
- load-interval 278
- load-interval interface 278
- login authentication list-name 55
- map-class
  - map-class 135
  - map-class dialer class-name 218
- match 310
- modems 94
  - modem autoconfiguration 96
  - modem autoconfigure discovery 98
  - modem autoconfigure name 99
  - modemcap edit usr\_new 102
  - modemcap entry modem-name 101
- physical layer-sync 91
- ping 454
- policy-map 311
- ppp 118
  - ppp authentication 59
  - ppp authentication CHAP 127
  - ppp callback accept 135
  - ppp callback request 133
  - ppp multilink interface configuration 182
  - ppp pap sent-username 124
- pri-group 165
- priority 315
- pulse-time 129
- pvc interface configuration 399
- queue-limit 315
- radius-server
  - radius-server host 54
  - radius-server key 54
- random-detect 315
- show 454
  - show command 316
  - show compress 139
  - show crypto ipsec transform-set 476
  - show crypto map 477
  - show dialer 143, 144
  - show dialer interface bri number 221
  - show frame-relay pvc 264
  - show interface 242
  - show interface atm 403
  - show interface dialer 221
  - show interface type number 286
- show interfaces bri 190
- show ip nat translation 354
- show isdn status 187
- show line 85
- show modemcap 98
- show ppp multilink 191
- show privilege 64
- show process cpu 137
- show queuing custom 318
- show traffic-shape 264
- show traffic-shape statistics 265
- tacacs-server host 54
- traffic-share
  - traffic-share balanced 286
  - traffic-share min 286
- transform 464
- transport input control 89
- username 135
- variance
  - variance 2 285–286
  - variance multiplier 285
- vpdn
  - vpdn enable 393
  - vpdn-group name 393
- committed burst (B) 252
- comparisons
  - queuing 319
  - transport mode/tunneling 438
- compatibility of IPSec 455
- components
  - ACS 49–50
  - cable 376–378
  - DLCI 234–235
  - Frame Relay 232–234
  - ISDN BRI 154
  - PPP 113
  - WAN 3
- compression 320–325
  - configuring 138
  - enabling 325
  - MPPC 323
  - PPP 121
  - speed 84
  - STAC 321, 324
  - standards 83
  - TCP headers 136
  - V.42bis 83
  - verifying 138

configuration  
  AAA 43–44, 52  
    commands 53–68  
    defining 44–45  
    protocols 45–46  
  authentication 59  
  authorization 60  
  autodiscovery 98  
  cable 379–380  
  CBWFQ 305–314  
  command authorization 64  
  compression 138, 324  
  CPE as PPPoE clients 392–397  
  crypto ACLs 467  
  crypto maps 471  
  DDR 167–181  
    testing 192  
    verifying 186–192  
  default static routes 397  
  DHCP 397  
  dial backups 273–280  
    dialer interfaces as 280–282  
    dialer watch 289–290  
    floating static routes 287  
    verifying 286  
  dialer interfaces 217, 394  
  dialer lists 179  
  dialer map classes 211  
  dialer profile commands 214  
  DSL 393  
    dialer interfaces 399  
    PAT 400  
    PPPoA 398–400  
  Frame Relay 236–238  
    applying DLCIs 240  
    hub-spoke topologies 241–242  
    mapping addresses 238–240  
    subinterfaces 244–250  
    traffic shaping 255–266  
    troubleshooting 242–244  
  global IPSec SAs 466  
  IKE 456–462  
  interface protocols 158  
  IOS command privilege levels 63  
  IPSec 445–454, 463–475  
    IKE Phase 1 policy 446–449  
    IKE Phase 2 policy 449–452  
    peers 452–453  
    troubleshooting 454–456, 475–481

ISDN  
  BRI interfaces 153–160  
  called party number 185–186  
  CLID 184–185  
  commands 157  
  MPP 182–184  
  PPP 181–182  
  PRI interfaces 160–167  
  rate adaptation 186  
  simple calls 175  
  legacy DDR 201–203  
  dialer profiles 208–220  
  troubleshooting dialer profiles 221–227  
  login authentication 55  
  LQQ 314–316  
  modems 93–95  
    autoconfiguration 96–103  
    debugging autoconfiguration 103  
    troubleshooting autoconfiguration 104  
  Multilink PPP 140–143  
  named lists 57  
  NAT 343–354  
  PAT 395  
  physical interfaces 219  
  PPP 115–120  
    authentication 121–128  
    callback clients 133  
    LCP options 128–140  
    servers 134  
  PPPoE clients 394  
  preshared keys 461  
  queuing 316–319  
  RADIUS 54  
  rotary groups 203–206  
    interfaces 207  
    ISDN 206  
    limitations 207  
  SPIDs 159  
  symmetrical crypto ACLs 468  
  TACACS+ 53  
  transform sets 463  
  WAN 16  
  WFQ 301–304  
  WRED 311  
congestion 296–297. *See also* troubleshooting  
  options 299–301  
  policies 298  
  prioritization 297

connections, 91  
 asynchronous analog dialup 73. *See also*  
 modems  
 asynchronous modems 8  
 AUX ports 90  
 broadband 365  
     ADSL 384–392  
     cable 366  
     DSL 366, 380–383  
     satellite access 367–368  
     wireless access 368–369  
 cable  
     components 376–378  
     HFC 373–374  
     infrastructure 370–373  
     provisioning 379  
     RF channels 374–376  
     router configuration 379–380  
 compression 321  
 console ports 90  
 DDR  
     configuring 167–181  
     verifying 186–192  
 dial backups 273–280  
 DSL  
     configuring 393  
     troubleshooting 400–405  
 Frame Relay  
     applying DLCIs 240  
     components 232–234  
     configuring 236–238  
     configuring traffic shaping 255–266  
     DLCI 234–235  
     hub-spoke topologies 241–242  
     mapping addresses 238–240  
     signaling 235–236  
     subinterfaces 244–250  
     traffic shaping 251–255  
     troubleshooting 242–244  
 interfaces 207  
 ISDN, 153  
     CLID 184–185  
     configuring rotary groups 206  
     dialer profiles with B channels 214  
 limitations of rotary groups 207  
 modems 73–74, 88–90  
     autoconfiguration 96–103  
     autodiscovery 97  
     chat scripts 104–105  
     commands 94  
     compression 84  
     configuring 93–95  
     debugging autoconfiguration 103  
     DTE-DCE interface 74–75  
     DTE-to-DTE wiring 78  
     error control 83  
     EXEC command 92  
     initialization strings 95  
     line commands 85–88  
     modulation 81–83  
     NAS 91  
     operations 77–78  
     RJ-45 wiring 79  
     routers 90–91  
     signaling data 75–77  
     troubleshooting autoconfiguration 104  
     working connections 80–81  
 MPPC 323  
 PPP  
     configuring 115  
     debugging 143–145  
 PVC 274  
 queuing 296–297  
     options 299–301  
     policies 298  
     prioritization 297  
 remote node 111–113  
 resetting 168  
 serial 91  
 VPNs  
     selecting 427–430  
     types of 417–427  
 WAN 4–6  
     broadband access 11–12  
     cabling 30  
     central sites 19–21  
     dedicated circuit-switched 6–7  
     encapsulation protocols 12–15  
     on-demand circuit-switched 7–10  
     packet-switched virtual 10–11  
     remote access 26–37  
     remote/branch offices 21–23  
     routers (central sites) 21  
     site requirements 18  
     SOHO 24–25  
     speed comparisons 16–18  
     types 16  
 console ports, connecting 90

- Consultative Committed of International Telegraph and Telephone (CCITT) 74
- controllers, parameters of 164
- conversion
  - hashing 435
  - speed 84
- costs
  - central site connections 19
  - WAN 16, 22
- CPE (customer premises equipment) 232, 365, 392–397
- CPU usage, compression 137
- crypto ACLs 466
  - creating 467
  - symmetrical peer 468
- crypto commands
  - crypto ipsec security-association lifetime command 466
  - crypto ipsec transform-set command 464
  - crypto isakmp enable command 457
  - crypto isakmp identity command 461
  - crypto isakmp key command 461
  - crypto isakmp policy command 457
- crypto maps 469
  - commands 472
  - configuring 471
  - interfaces 473
- cryptosystems 420, 430–436
- CSU/DSU (channel service unit/data service unit) 6
- CSUs (channel service units) 74
- customer premises equipment. *See CPE*
- customization
  - AAA 43–44, 52
    - commands 53–68
    - defining 44–45
    - protocols 45–46
  - ACS 48
    - authentication 59
    - authorization 60
    - autodiscovery 98
    - cable 379–380
    - CBWFQ 305–314
    - command authorization 64
    - compression 138, 324
    - CPE as PPPoE clients 392–397
    - crypto ACLs 467
    - crypto maps 471
    - DDR 167–181
      - testing 192
      - verifying 186–192
    - default static routes 397
    - DHCP 397
    - dial backups 273–280
      - dialer interfaces as 280–282
      - dialer watch 289–290
      - floating static routes 287
      - verifying 286
    - dialer interfaces 217, 394
    - dialer lists 179
    - dialer map classes 211
    - dialer profile commands 214
    - DSL 393
      - dialer interfaces 399
      - PAT 400
      - PPPoA 398–400
    - Frame Relay 236–238
      - applying DLCIs 240
      - hub-spoke topologies 241–242
      - mapping addresses 238–240
      - subinterfaces 244–250
      - traffic shaping 255–266
      - troubleshooting 242–244
    - global IPsec SAs 466
    - IKE 456–462
    - interface protocols 158
    - IOS command privilege levels 63
    - IPSec 445–454, 463–475
      - IKE Phase 1 policy 446–449
      - IKE Phase 2 policy 449–452
      - peers 452–453
      - troubleshooting 454–456, 475–481
    - ISDN
      - BRI interfaces 153–160
      - called party number 185–186
      - CLID 184–185
      - commands 157
      - MPP 182–184
      - PPP 181–182
      - PRI interfaces 160–167
      - rate adaptation 186
      - simple calls 175
      - legacy DDR 201–203
        - dialer profiles 208–220
        - troubleshooting dialer profiles 221–227
      - login authentication 55
      - LQQ 314–316
      - modems 93–95
        - autoconfiguration 96–103
        - debugging autoconfiguration 103
        - troubleshooting autoconfiguration 104

Multilink PPP 140–143  
 named lists 57  
 NAT 343–354  
 PAT 395  
 physical interfaces 219  
 PPP 115–120  
   authentication 121–128  
   callback clients 133  
   LCP options 128–140  
   servers 134  
 PPPoE clients 394  
 preshared keys 461  
 queuing 316–319  
 RADIUS 54  
 rotary groups 203–206  
   interfaces 207  
   ISDN 206  
   limitations 207  
 SPIDs 159  
 symmetrical crypto ACLs 468  
 TACACS+ 53  
 transform sets 463  
 WAN 16  
 WFQ 301–304  
 WRED 311

## D

data communications equipment (DCE) 6, 232  
 data compression. *See* compression  
 Data Over Cable Service Interface Specification (DOCSIS) 375  
 data service units (DSUs) 74  
 data terminal equipment (DTE) 232  
 databases, creating entries 101  
 DBS (direct broadcast satellite) 365  
 DCE (data communications equipment) 6, 232  
 DDR (dial-on-demand routing). *See also* routing  
   access lists 172  
   configuring 167–181  
   destination parameters 173  
   dial backups 274. *See also* backups  
   legacy DDR 201–203  
     dialer profiles 208–220  
     troubleshooting dialer profiles 221–227  
   testing 192  
   troubleshooting 187  
   verifying 186–192

DE (discard eligibility) 252  
 debug commands 189  
   debug confmodem command 103  
   debug crypto ipsec command 478  
   debug dialer command 192  
   debug dialer packet command 226  
   debug isdn events command 192  
   debug ppp authentication command 144, 192  
   debug ppp multilink command 142  
   debug ppp negotiation command 144, 192, 404  
 debugging. *See also* troubleshooting  
   autoconfiguration 103  
   IPSec 475–481  
   NAT 356  
   PPP 143–145  
 decryption 420  
 dedicated circuit-switched connections 6–7  
 default classes, configuring 312  
 default static routes, configuring 397  
 defining  
   AAA 44–45  
   interesting traffic 171  
   map classes 212  
 delay 0 40 command 277  
 deleted states, Frame Relay 236  
 demilitarized zone (DMZ) 424  
 design  
   AAA 43–44, 52  
   commands 53–68  
   defining 44–45  
   protocols 45–46  
 ACS 48  
 authentication 59  
 authorization 60  
 autodiscovery 98  
 cable 379–380  
 CBWFQ 305–314  
 command authorization 64  
 compression 138, 324  
 CPE as PPPoE clients 392–397  
 crypto ACLs 467  
 crypto maps 471  
 DDR 167–181  
   testing 192  
   verifying 186–192  
 default static routes 397  
 DHCP 397  
 dial backups 273–280  
   dialer interfaces as 280–282  
   dialer watch 289–290

- floating static routes 287
- verifying 286
- dialer interfaces 217, 394
- dialer lists 179
- dialer map classes 211
- dialer profile commands 214
- DSL 393
  - dialer interfaces 399
  - PAT 400
  - PPPoA 398–400
- Frame Relay 236–238
  - applying DLCIs 240
  - hub-spoke topologies 241–242
  - mapping addresses 238–240
  - subinterfaces 244–250
  - traffic shaping 255–266
  - troubleshooting 242–244
- global IPSec SAs 466
- IKE 456–462
- interface protocols 158
- IOS command privilege levels 63
- IPSec 445–454, 463–475
  - IKE Phase 1 policy 446–449
  - IKE Phase 2 policy 449–452
  - peers 452–453
  - troubleshooting 454–456, 475–481
- ISDN
  - BRI interfaces 153–160
  - called party number 185–186
  - CLID 184–185
  - commands 157
  - MPP 182–184
  - PPP 181–182
  - PRI interfaces 160–167
  - rate adaptation 186
  - simple calls 175
  - legacy DDR 201–203
  - dialer profiles 208–220
  - troubleshooting dialer profiles 221–227
- login authentication 55
- LQQ 314–316
- modems 93–95
  - autoconfiguration 96–103
  - debugging autoconfiguration 103
  - troubleshooting autoconfiguration 104
- Multilink PPP 140–143
- named lists 57
- NAT 343–354
- PAT 395
- physical interfaces 219
- PPP 115–120
  - authentication 121–128
  - callback clients 133
  - LCP options 128–140
  - servers 134
- PPPoE clients 394
- preshared keys 461
- queuing 316–319
- RADIUS 54
- rotary groups 203–206
  - interfaces 207
  - ISDN 206
  - limitations 207
- SPIDs 159
- symmetrical crypto ACLs 468
- TACACS+ 53
- transform sets 463
- WAN 16
- WFQ 301–304
- WRED 311
- destination parameters, DDR 173
- devices
  - ACS 46–48
  - DCE 6
  - ISDN 155
  - VPNs 422
  - WAN 111–112
- DHCP (Dynamic Host Configuration Protocol) 119, 396–397
- dial backups
  - activating 276
  - configuring 273–280
  - dialer interfaces as 280–282
  - dialer watch 289–290
  - floating static routes 287
  - verifying 286
- dial map command options 173
- dialer commands
  - dialer callback-secure command 135
  - dialer callback-server username command 135
  - dialer enable-timeout command 129
  - dialer hold-queue timeout command 129
  - dialer idle-timeout command 168
  - dialer isdn speed 56 command 218
  - dialer load-threshold command 170 182
  - dialer load-threshold load command 143
  - dialer map command 135, 157

- dialer pool-member command 219, 220, 223
- dialer pool-member number command 281
- dialer rotary-group command 206
- dialer string command 212
- dialer watch commands 289–290
- dialer-group command 172
- dialer-list command 171
- dialer-map command 125
- dialer interfaces. *See also* interfaces
  - configuring 217, 394
  - as dial backups 280
  - DSL 399
- dialer lists
  - access lists 178
  - configuring 179
- dialer maps
  - classes 211
  - statements 202
- dialer profiles
  - applications 215
  - commands 214
  - legacy DDR 203, 208–227
- dialer rotary groups
  - configuring 203–206
  - interfaces 207
  - ISDN 206
  - limitations 207
- dial-on-demand routing (DDR). *See also* routing
  - access lists 172
  - configuring 167–181
  - destination parameters 173
  - dial backups 274. *See also* backups
  - legacy DDR 201–203
    - dialer profiles 208–220
    - troubleshooting dialer profiles 221–227
  - testing 192
  - troubleshooting 187
  - verifying 186–192
- dialup connections 73. *See also* connections; modems
- Differentiated Services Code Point (DSCP) 308
- Diffie-Hellman algorithm 434
- digital amplifiers 74
- digital subscriber line. *See* DSL
- direct broadcast satellite (DBS) 365
- disabling split horizons 246
- discard eligibility (DE) 252
- disconnections. *See also* connections
  - callback 135
  - troubleshooting 225
- discovery
  - configuring 98
  - modem autodiscovery 97
- discrete multitone (DMT) 385
- distribution network 373
- DLCI (data-link connection identifier)
  - applying 240
  - Frame Relay 233–235
- DMT (discrete multitone) 385
- DMZ (demilitarized zone) 424
- DOCSIS (Data Over Cable Service Interface Specification) 375
- downstream (DS) 376
- DS (downstream) 376
- DSCP (Differentiated Services Code Point) 308
- DSL (digital subscriber line) 366, 380–381. *See also* connections
  - ATM interfaces 399
  - configuring 393
  - dialer interfaces 399
  - limitations 383
  - modulation 398
  - PAT 396, 400
  - PPPoA 398–400
  - PPPoE 394
  - scaling 396
  - troubleshooting 400–405
  - types of 382–392
- dsl operating-mode command 398
- DSLAM (DSL access multiplexer) 381
- DSUs (data service units) 74
- DTE (data terminal equipment) 232
- DTE-DCE interface 74–75
- DTE-to-DTE wiring 78
- dynamic address mapping 238–239
- Dynamic Host Configuration Protocol (DHCP) 119
- dynamic mapping 332
- dynamic NAT, configuring 350. *See also* NAT

## E

- 
- E1 controller parameters 164
  - ease of management, WAN 16
  - editing
    - modemcap databases 101
    - transform sets 465
  - EIA (Electronics Industries Association) 74
  - EIGRP (Enhanced IGRP), load sharing 284
  - EIR (excess information rate) 254

electromagnetic frequencies 374  
Electronic Industries Association (EIA) 74  
elements, dialer profiles 210. *See also* dialer profiles  
enabling  
    AAA 52  
    CLID 184–185  
    IKE 457  
    passwords 58  
    PPP 116, 117  
    rate adaptation 186  
    STAC compression 324  
    TCP/IP header compression 325  
Encapsulating Security Payload (ESP) 421, 438, 464  
encapsulation  
    configuring 115  
    Frame Relay 15  
    GRE 429  
    hdlc command 159  
    ISDN 155  
    Layer 2 B channel protocols 158  
    PPP 13  
    protocols 158  
    WAN 12–15  
encoding ADSL 385. *See also* ADSL  
encryption 420. *See also* security  
    asymmetric 433  
    cryptosystems 430–436  
    symmetric 432  
    tunneling 421  
    VPNs 427–430  
end-to-end keepalives 286  
entries, modemcap databases 101  
errors. *See also* troubleshooting  
    ISAKMP 481  
    modems 83  
ESP (Encapsulating Security Payload) 421, 438, 464  
excess burst (B) 252  
excess information rate (EIR) 254  
excessive traffic loads, configuring dial backups 277  
EXEC  
    commands 92  
    sessions 91, 117  
extended ACLs, creating crypto ACLs 467

## F

---

fair-queue command 304  
FDM (frequency-division multiplexing) 377  
FEC (forward error correction) 378

FECN (forward explicit congestion notification) 252  
FIFO (first-in, first-out) 296  
filters, microfilters 385  
Firewalls, PIX 46. *See also* security  
fixed wireless broadband markets 368  
floating static routes 287  
flowcharts  
    asynchronous callback 130  
    autoselect 118  
    IKE/IPSec 443  
    queuing options 299  
formatting. *See also* configuration  
    crypto ACLs 467  
    frames 115  
    modemcap database entries 101  
forward error correction (FEC) 378  
forwarding L2F 429  
Frame Relay 12  
    commands  
        frame-relay map command 239  
        frame-relay traffic-rate command 260  
    components 232–234  
    configuring 236–238  
        applying DLCIs 240  
        hub-spoke topologies 241–242  
        mapping addresses 238–240  
        subinterfaces 244  
        traffic shaping 255–266  
        troubleshooting 242–244  
    DLCI 234–235  
    encapsulation 15  
    signaling 235–236  
    traffic shaping 251–255  
frames  
    controllers 164  
    PPP 115  
frequencies, DSL 381. *See also* DSL  
frequency-division multiplexing (FDM) 377

## G

---

global addresses 342–343  
global IPSec SAs, configuring 466  
granularity of CBWFQ 307  
GRE (Generic Routing Encapsulation) 419, 429  
group-range command 207  
groups, configuring PPPoE 393

GSOs (geostationary orbit satellites) 368  
 GUI (graphical user interface) 50. *See also* interfaces

## H

hashing 420, 435  
 HDLC (high-level data link control) 12, 115  
 headends 373. *See also* cable  
 headers  
   TCP compression 136  
   TCP/IP compression 322  
 HFC (hybrid fiber-coaxial) 373–374  
 high primary lines, dial backups 275  
 how modemcap command 98  
 hub-spoke topologies 241–242  
 hunt groups 204. *See also* rotary groups  
 hybrid fiber-coaxial cable 373–374

## I

IARP (Inverse Address Resolution Protocol) 235  
 identities, ISAKMP 460  
 IKE (Internet Key Exchange) 421  
   configuring 456–462  
   enabling 457  
   flowcharts 443  
   IPSec 441  
   Phase 1 policy 446–449  
   Phase 2 policy 449–452  
   policies  
     creating 457  
     negotiation 459  
 implementation. *See also* configuration  
   PPP callback 129  
   VPNs 427–430  
 import all DHCP pool configuration command 397  
 inactive states, Frame Relay 236  
 in-band PPP sessions 117  
 incoming calls  
   rotary groups 204  
   troubleshooting 225  
 increasing bandwidth 182–184  
 infrastructure (cable) 370–373  
   components 376–378

HFC 373–374  
 provisioning 379  
 RF channels 374–376  
 router configuration 379–380  
 ingress noise 377  
 initialization strings 95  
 inside global address overloading, configuring 352  
 inside global addresses 336  
 installation  
   branch offices 33  
   SOHO 34  
   WAN 31  
 integrated routing and bridging (IRB) 387  
 Integrated Services Digital Network. *See* ISDN  
 integrity of hashing 435  
 interfaces  
   ACS 50  
   async commands 117–120  
   Backup 274  
   BRI  
     configuring ISDN 153–160  
     monitoring 187, 190–191  
   BVI 387  
   commands  
     interface async command 87  
     interface atm number command 394  
     interface dialer command 205  
     interface dialer global command 217  
     interface serial command 87  
     interface serial interface-number  
       command 159  
   crypto maps 473  
   dial backup 276  
   dialer 211  
     configuring 217, 394  
     as dial backups 280  
   DSL 399  
   DSL 399, 402  
   DTE-DCE 74–75  
   Frame Relay signaling 235–236  
   LMI 286  
   Multilink PPP 142–143  
   NNI 232, 286  
   physical  
     configuring 219  
     limitations as dial backups 280  
   PRI 160–167  
   protocols 158  
   R 155

rotary groups 207  
S/T 155  
serial 91  
show interface command 242  
subinterfaces  
    Frame Relay 244–250  
U 155  
UNI 232  
WAN 28–29

International Organization for Standardization  
    Connectionless Network Service (ISO CLNS) 201

International Organization for Standardization’s  
    high-level data link control (ISO-HDLC) 111

International Telecommunication Union–  
    Telecommunications Standards Sector (ITU-T) 74

Internet Key Exchange (IKE) 421  
    configuring 456–462  
    enabling 457  
    flowcharts 443  
    IPSec 441  
    Phase 1 policy 446–449  
    Phase 2 policy 449–452  
    policies  
        creating 457  
        negotiation 459

Internet Security Association and Key Management  
Protocol. *See* ISAKMP

interpretability (PPP) 111–112  
    architecture 113–115  
    configuring 115  
    frames 115

interesting traffic (ISDN DDR) 171

Inverse Address Resolution Protocol (IARP) 235

IOS command privilege levels 63

IOS cryptosystem 430–436

IP (Internet Protocol)  
    crypto ACLs 466  
    commands  
        ip address command 119  
        ip dhcp pool name global configuration  
            command 397  
        ip route command 288  
        ip tcp header-compression command 138  
        ip tcp header-compression passive  
            command 138  
        ip unnumbered command 119

NAT 331–338  
    configuring 343–354  
    global addresses 342–343

source addresses 339–342  
troubleshooting 354–359

PAT 333

IPSec (IP Security Protocol) 429, 436–445  
    configuring 445–446, 453–454, 463–475

IKE  
    configuring 456–462  
    Phase 1 policy 446–449  
    Phase 2 policy 449–452  
    peers 452–453  
    transforms 449  
    troubleshooting 454–456, 475–481

IRB (integrated routing and bridging) 387

ISAKMP (Internet Security Association and Key  
Management Protocol) 421  
    error messages 481  
    identities 460  
    policies 476

ISDN (Integrated Services Digital Network). *See*  
*also* connections  
    B channel dialer profiles 214  
    BRI  
        configuring 153–160  
        monitoring 187, 190–191  
    commands 157  
        isdn answer1 command 186  
        isdn answer2 command 186  
        isdn call interface command 192  
        isdn caller command 185  
        isdn disconnect interface command 192  
        isdn switch-type command 158, 162

DDR  
    configuring 167–181  
    verifying 186–192

Layer 2 debug commands 189

Layer 3 debug commands 189

layers 155

PPP 181–182  
    called party number 185–186  
    CLID 184–185  
    MLP 182–184  
        rate adaptation 186

PRI 160–167

protocols 154

rotary groups 129, 206

services 160

simple calls 175

SPIDs 159

troubleshooting 187

ISO (International Organization for Standardization's high-level data link control (ISO-HDLC) 111  
 ISO CLNS (International Organization for Standardization Connectionless Network Service) 201  
 ITU-T (International Telecommunication Union-Telecommunications Standards Sector) 74

## K

---

keepalives  
 dial backups 276  
 end-to-end 286  
 key exchanges, cryptosystems 430–436  
 keys  
 management 420  
 preshared 461

## L

---

L2F (Layer 2 Forwarding) 429  
 L2TP (Layer 2 Tunneling Protocol) 419, 429  
 LAPB (Link Access Procedure Balanced) protocol 201, 321  
 LAPM (Link Access Procedure for Modems) 83  
 Layer 1  
 DSL 402  
 status messages 188  
 Layer 2  
 channel encapsulation protocols 158  
 DSL 403  
 ISDN debug commands 189  
 layers  
 DSL 401  
 ISDN protocols 155  
 VPNs 427–430  
 LCP (Link Control Protocol)  
 configuring 128–140  
 PPP 121  
 legacy DDR 201–203. *See also* DDR  
 dialer profiles 208–220  
 troubleshooting 221–227  
 Lempel-Ziv (LZ) algorithm 136  
 LEOS (low-earth-orbit satellites) 368  
 lifetimes, IPSec SAs 466  
 limitations  
 of DSL 383  
 physical interfaces as backup interfaces 280  
 rotary groups 207  
 line commands 85–88  
 linecode command 164  
 lines  
 numbering 87  
 types 87  
 Link Access Procedure Balanced (LAPB) protocol 201, 321  
 Link Access Procedure for Modems (LAPM) 83  
 links  
 compression 321  
 WAN 297  
 lists  
*ACL. See ACL*  
 DDR 172  
 LLQ (Low Latency Queuing) 297  
 LMDS (Local Multipoint Distribution Service) 368  
 LMI (Local Management Interface) 235–236, 286.  
*See also* interfaces  
 load backups, primary line failures 282–290  
 load distribution, TCP 345  
 load sharing  
 EIGRP 284  
 OSPF 283  
 load-interval command 278  
 load-interval interface configuration command 278  
 local access rates 252  
 local best metrics 286  
 local loops, PSTN 73  
 Local Multipoint Distribution Service (LMDS) 368  
 login, configuring authentication 55  
 login authentication list-name command 55  
 loops, PSTN 73  
 Low Latency Queuing (LLQ) 297, 314–316  
 low-earth-orbit satellites (LEOS) 368  
 LZ (Lempel-Ziv) algorithm 136

## M

---

management  
 compression 320–325  
 keys 420

networks 47  
queuing 296–297  
    options 299–301  
    policies 298  
    prioritization 297  
WAN 16

map classes  
    commands  
        map-class command 135  
        map-class dialer class-name command 218  
    defining 212  
    dialers 211

maps  
    addresses 238–240  
    class 310  
    crypto 469  
        configuring 471  
        interfaces 473  
    DLCI 234

masks, DHCP 397

match command 310

Maximum Received Reconstructed Unit (MRRU)  
    141

memory, compression 137

messages  
    errors. *See* errors; troubleshooting  
    hashing 435  
    ISAKMP 481  
    status 188

metrics, local best 286

Microcom's Networking Protocol (MNP) 83

microfilters 385

Microsoft Point-to-Point Compression (MPPC) 136,  
    323

mismatch, speed 84

MLP (Multilink PPP)  
    configuring 182–184  
    troubleshooting 192  
    verifying 191

MNP (Microcom's Networking Protocol) 83

modemcap databases 101  
    modemcap edit usr\_new command 102  
    modemcap entry modem-name command 101

modems. *See also* connections  
    asynchronous analog dialup connections 73  
    asynchronous connections 8  
    autoconfiguration 96–103  
        debugging 103  
        troubleshooting 104

autodiscovery 97–98  
cable 366, 379  
chat scripts 104–105  
commands 94  
    modem autoconfigure command 96  
    modem autoconfigure discovery command 98  
    modem autoconfigure name command 99  
configuring 93–95  
connections 73–74, 88–90  
    compression 84  
    DTE-DCE interface 74–75  
    DTE-to-DTE wiring 78  
    error control 83  
    EXEC commands 92  
    line commands 85–88  
    modulation 81–83  
    NAS 91  
    operations 77–78  
    RJ-45 wiring 79  
    routers 90–91  
    signaling data 75–77  
    working connections 80–81

DSL 366, 380–381, 393  
initialization strings 95

modes  
    access 51  
    buffered 84  
    character authorization 65  
    packets 66

modification of transform sets 465

modular interfaces, WAN 29. *See also* interfaces

modulation 81–83  
    CAP 385  
    DSL 398

monitoring  
    ISDN BRI 187–191  
    PPP 191  
    traffic 277

MPPC (Microsoft Point-to-Point Compression)  
    136, 323

MRRU (Maximum Received Reconstructed Unit)  
    141

Multilink PPP 140–143 *See* MLP

multiple access connections  
    central site connections 19  
    remote/branch offices 22

multiple async interfaces, sharing IP addresses 119

multiple destinations, legacy DDR with 202

multiple WANs 111–112  
multiplexing  
  Frame Relay 233. *See also* Frame Relay  
  troubleshooting 164  
multipoint subinterfaces 248. *See also* subinterfaces

## N

---

named lists, configuring 57  
NAS (Network Access Server) modems 91  
NAT (Network Address Translation) 331–338  
  configuring 343–354  
  global addresses 342–343  
  source addresses 339–342  
  troubleshooting 354–359  
National Television Systems Committee (NTSC)  
  375, 377  
NBMA (nonbroadcast multiaccess) networks 233  
negotiation  
  IKE policies 459  
  PAP 123  
  PPP 404  
  transform sets 465  
networks. *See also* connections  
  cable 373  
  management 47  
  NAT 331–338  
    configuring 343–354  
    global addresses 342–343  
    source addresses 339–342  
    troubleshooting 354–359  
  NBMA 233  
  overlapping 343  
  STDM 254  
  WAN  
    broadband access 11–12  
    central sites 19–21  
    components 3  
    connections 4–6  
    dedicated circuit-connections 6–7  
    encapsulation protocols 12–15  
    on-demand circuit-connections 7–10  
    packet-switched virtual 10–11  
    remote access 26–37  
    remote/branch office 21–23  
    routers (central sites) 21  
    site requirements 18

SOHO 24–25  
speed comparisons 16–18  
types 16  
NGSOs (nongeostationary orbit satellites) 368  
NNI (Network-to-Network Interface) 232, 286  
nodes, remote connections 111–113  
noise, troubleshooting 377  
nonbroadcast multiaccess (NBMA) networks 233  
nonoccurrence of dialing, troubleshooting 222  
NT1/NT2 functions 155  
NTSC (National Television Systems Committee)  
  375, 377  
null modems 78. *See also* modems  
numbering lines 87

## O

---

ODN (public data network) 232  
on-demand circuit-switched connections 7–10  
Open Shortest Path First (OSPF) 283  
Open System Interconnection (OSI) 111  
operations, modems 77–78  
optimization  
  AAA 43–44, 52  
    commands 53–68  
    defining 44–45  
    protocols 45–46  
  ACS 48  
  authentication 59  
  authorization 60  
  autodiscovery 98  
  cable 379–380  
  CBWFQ 305–314  
  command authorization 64  
  compression 138, 324  
  CPE as PPPoE clients 392–397  
  crypto ACLs 467  
  crypto maps 471  
  DDR 167–181  
    testing 192  
    verifying 186–192  
  default static routes 397  
  DHCP 397  
  dial backups 273–280  
    dialer interfaces as 280–282  
    dialer watch 289–290  
    floating static routes 287  
    verifying 286

- dialer interfaces 217, 394
- dialer lists 179
- dialer map classes 211
- dialer profile commands 214
- DSL 393
  - dialer interfaces 399
  - PAT 400
  - PPPoA 398–400
- Frame Relay 236–238
  - applying DLCIs 240
  - hub-spoke topologies 241–242
  - mapping addresses 238–240
  - subinterfaces 244–250
  - traffic shaping 255–266
  - troubleshooting 242–244
- global IPSec SAs 466
- IKE 456–462
- interface protocols 158
- IOS command privilege levels 63
- IPSec 445–454, 463–475
  - IKE Phase 1 policy 446–449
  - IKE Phase 2 policy 449–452
  - peers 452–453
  - troubleshooting 454–456, 475–481
- ISDN
  - BRI interfaces 153–160
  - called party number 185–186
  - CLID 184–185
  - commands 157
  - MPP 182–184
  - PPP 181–182
  - PRI interfaces 160–167
  - rate adaptation 186
  - simple calls 175
- legacy DDR 201–203
  - dialer profiles 208–220
  - troubleshooting dialer profiles 221–227
- login authentication 55
- LQQ 314–316
- modems 93–95
  - autoconfiguration 96–103
  - debugging autoconfiguration 103
  - troubleshooting autoconfiguration 104
- Multilink PPP 140–143
- named lists 57
- NAT 343–354
- PAT 395
- physical interfaces 219
- PPP 115–120
  - authentication 121–128
  - callback clients 133
  - LCP options 128–140
  - servers 134
- PPPoE clients 394
- preshared keys 461
- queuing 316–319
- RADIUS 54
- rotary groups 203–206
  - interfaces 207
  - ISDN 206
  - limitations 207
- SPIDs 159
- symmetrical crypto ACLs 468
- TACACS+ 53
- transform sets 463
- WAN 16
- WFQ 301–304
- WRED 311
- options. *See also* customization
  - ACS 48
  - dialer map command 173
  - LCP
    - configuring PPP 128–140
    - PPP 121
  - PPP configuration 182
  - queuing 299–301
- OSI (Open System Interconnection) 111
- OSPF (Open Shortest Path First) 283
- outbound calls, troubleshooting 223
- out-of-band EXEC sessions 117
- overlapping
  - addresses 353
  - networks 343
- overloading addresses 342
- oversubscription 252

## P

---

- packets
  - DLCI 234
  - modes 66
  - PADT 391
- packet-switched virtual connections 10–11
- PADT (PPP Active Discovery Terminate) 391
- PAL (Phase Alternating Line) 375–377

- PAP (Password Authentication Protocol) 121–128
- parameters
- controllers 164
  - crypto maps 470
  - destination 173
  - IKE 448
  - ISAKMP policies 476
- passing data over Frame Relay 234
- Password Authentication Protocol. *See PAP*
- passwords. *See also* security
- enabling 58
  - PAP 121–128
- PAT (Port Address Translation) 333, 395
- configuring 400
  - DSL 396
- payload compression 321. *See also* compression
- PCM (pulse code modulation) 73
- PDUs (protocol data units) 387
- peers
- IPSec 452–453
  - symmetrical crypto ACLs 468
- performance. *See also* optimization
- compression 320–325
  - queuing 297
- per-interface compression 321. *See also* compression
- permanent virtual connection (PVC) 274
- per-virtual circuit compression 321. *See also* compression
- Phase Alternating Line (PAL) 375
- Physical Layer, DSL 402
- physical interfaces. *See also* interfaces
- configuring 219
  - dial backups 280
- physical layer-async command 91
- ping command, IPSec 454
- PIX (Private Internet Exchange) Firewalls 46. *See also* firewalls; security
- planning NAT 337
- Point-to-Point Protocol. *See PPP*
- point-to-point subinterfaces 247. *See also* subinterfaces
- policies
- IKE
  - creating 457
  - negotiation 459
  - Phase 1 446–449
  - Phase 2 449–452
- ISAKMP 476
- queuing 296
- policy-map command 311
- Port Address Translation (PAT) 333
- port address translation (PAT) 395–396
- port-rate adjustment 84
- ports. *See also* connections
- AUX 90
  - console 90
  - speed 252
- POTS (Plain Old Telephone Service) 384
- power supplies, troubleshooting 402
- PPP (Point-to-Point Protocol) 13
- architecture 113–115
  - authentication 59, 121–128
  - callback 131
  - commands
  - ppp authentication CHAP command 127
  - ppp authentication command 59
  - ppp callback accept command 135
  - ppp callback request command 133
  - ppp command 118
  - ppp multilink interface configuration command 182
  - ppp pap sent-username command 124
- configuring 115
- connections
- compression 321
  - MPPC 323
- debugging 143–145
- enabling 116, 117
  - encapsulation 13
  - frames 115
  - ISDN 181–182
  - called party number 185–186
  - CLID 184–185
  - MLP 182–184
  - rate adaptation 186
- LCP options 121, 128–140
- monitoring 191
  - Multilink PPP 140–143
  - negotiation 404
  - overview of 111–112
  - sessions 117
- PPPoA (PPP over ATM)
- ADSL 392
  - DSL 398–400
- PPPoE (PPP over Ethernet) 365, 394
- ADSL 389

- CPE 392–397
- DSL 394
- VPDN 393
- PPPoE Active Discovery Terminate (PADT) 391
- Predictor 136, 321
- preshared keys, configuring 461
- PRI (Primary Rate Interface) 160–167. *See also* interfaces
- pri-group command 165
- primary lines
  - dial backups
    - activating 276
    - starting 275
  - load backups 282–290
- primary links, dial backups 274
- prioritization 297. *See also* queuing
- priority command 315
- Private Internet Exchange. *See* PIX
- private network dial-in services, spanning remote access servers 393
- profiles (dialer)
  - applications 215
  - commands 214
  - legacy DDR 203, 208–220
  - troubleshooting 221–227
- protections, enabling passwords 58
- protocol data units (PDUs) 387
- protocols
  - AAA 45–46
  - central sites 48
  - clients 48
  - DHCP 119
  - GRE 429
  - IARP 235
  - interfaces 158
  - IPSec 429, 436–445
    - configuring 445–446, 453–454, 463–475
    - IKE Phase 1 policy 446–449
    - IKE Phase 2 policy 449–452
    - peers 452–453
    - troubleshooting 454–456, 475–481
  - ISDN 154–155
  - L2TP 429
  - LAPB 201
  - MNP 83
  - multiplexing 114
  - PPP 12, 111–112
    - callback 131
    - configuring LCP options 128–140
- configuring Multilink PPP 142–143
- debugging 143–145
- encapsulation 13
- LCP options 121
- Multilink PPP 140–142
  - VPN 428
  - WAN 12
- provisioning cable modems 379
- PSTN (public switched telephone network) 7, 73
- public data network (PDN) 232
- public networks 332
- pulse code modulation (PCM) 73
- pulse-time command 129
- PVC (permanent virtual connection) 274
- pvc interface configuration command 399

## Q

- QAM (quadrature amplitude modulation) 377
- QoS (Quality of Service)
  - central site connections 20
  - WAN 16
- QPSK (quadrature phase shifting keying) 377
- queue-limit command 315
- queuing 296–297
  - CBWFQ 305–314
  - comparisons 319
  - LQQ 314–316
  - options 299–301
  - policies 298
  - prioritization 297
  - verifying 316–319
  - WFQ 301–304

## R

- R interfaces 155
- RADIUS (Remote Authentication Dial-In User Service) 421
  - commands
    - radius-server host command 54
    - radius-server key command 54
    - configuring 54
  - Random Early Detection (RED) 308
  - random-detect command 315

- rates
    - adaptation 186
    - enforcement 258
  - reachability, subinterfaces 245
  - RED (Random Early Detection) 308
  - redundancy
    - central site connections 20
    - WAN remote/branch offices 22
  - reference points
    - ISDN BRI 154
    - PRI 161
    - S/T 155
  - regeneration repeaters 74
  - reliability of WAN 16
  - remote access. *See also* access
    - broadband 365
      - ADSL 384–392
      - cable 366
      - DSL 366, 380–383
      - satellite access 367–368
      - wireless access 368–369
    - VPNs 425
    - WAN 26–37
  - Remote Authentication Dial-In User Service. *See also* RADIUS
    - remote destinations, identifying 173
    - remote node connections 111–113
    - remote offices, WAN 21–23
    - remote routers, DLCI 240
    - remote sites, WAN 18
    - repeaters 74
    - requests, IARP 236. *See also* IARP
    - requirements, WAN 18
    - resetting connections 168
    - reverse Telnet terminal sessions 92
    - revisions
      - modemcap databases 101
      - transform sets 465
    - RF channels 374–376
    - RJ-45 wiring 79
    - rotary groups
      - configuring 203–206
      - interfaces 207
      - ISDN 129, 206
      - limitations 207
    - RouterA
      - access lists 179
      - ISDN DDR 175
    - RouterB, ISDN DDR 175
  - routers 47
    - access modes 51
    - ACS 46–47
    - branch offices 23
    - cable modems 379–380
    - callback clients 133
    - DDR
      - configuring 167–181
      - verifying 186–192
    - Frame Relay 235
    - lines 87
    - modems
      - connections 88–91
      - EXEC commands 92
      - NAS 91
      - queuing 316–319
      - remote 240
      - spoke 241
      - WAN central sites 21
    - routes
      - adding 286
      - default static 397
      - floating static 287
    - routing
      - DDR 168
      - GRE 429
      - load backups 282–290
      - Snapshot Routing 169
      - updating 245
- 
- ## S
- SA (Security Association) 421, 466
  - SADB (SA database) 440
  - satellite access 367–368
  - scalability
    - CBWFQ 307
    - central site connections 20
    - DSL 396
    - NAT 331–338
      - configuring 343–354
      - global address 342–343
      - source address 339–342
      - troubleshooting 354–359
  - screening CLID 184. *See also* CLID
  - scripts, chat 104–105
  - SDSL (Symmetric Digital Subscriber Line) 381

- SECAM (Sequential Couleur Avec Memoire) 377
- secret key encryption 432. *See also* encryption
  - Diffie-Helman algorithm 434
  - hashing 435
  - security
    - AAA 43–44
      - commands 53–68
      - configuring 52
      - defining 44–45
      - protocols 45–46
    - CLID 184–185
    - clients 48
    - firewalls 46
    - IPSec 436–445
      - configuring 445–446, 453–454, 463–475
      - IKE Phase 1 policy 446–449
      - IKE Phase 2 policy 449–452
      - peers 452–453
      - troubleshooting 454–456, 475–481
    - PPP authentication 121–128
      - routers 47
      - servers 48
      - VPN 419
    - Security Association (SA) 421, 439
    - selection
      - Cisco product selection tools 36
      - of ISDN switches 158
      - of VPNs 427–430
  - Sequential Couleur Avec Memoire (SECAM) 377
  - serial connections 87, 91. *See also* connections
  - serial lines, dial backups 273–280
  - servers
    - AAA
      - commands 53–68
      - configuring 52
    - access 48
    - ACS 46, 49
      - administrator GUI client 50
      - components 49–50
      - options 48
      - routers 46–47
    - DHCP 397
    - NAS 91
    - PPP callback 134
    - security 48
    - spanning 393
    - TACACS+ 53
  - service profile identifiers (SPIDs) 159, 207
  - services
    - CA 420
    - ISDN 153
    - security 47
    - WAN 3
      - broadband access 11–12
      - central sites 19–21
      - connections 4–6
      - dedicated circuit-switched connections 6–7
      - encapsulation protocols 12–15
      - on-demand circuit-switched connections 7–10
      - packet-switched virtual connections 10–11
      - remote access 26–37
      - remote/branch offices 21–23
      - routers (central sites) 21
      - site requirements 18
      - SOHO 24–25
      - speed comparisons 16–18
      - types 16
  - sessions
    - EXEC
      - commands 92
      - console ports 91
    - PPP 117
  - sharing loads
    - EIGRP 284
    - OSPF 283
  - show commands 454
    - show compress command 139
    - show crypto ipsec transform-set command 476
    - show crypto map command 477
    - show dialer command 143, 144
    - show dialer interface bri number command 221
    - show frame-relay pvc command 264
    - show interface atm0 command 403
    - show interface command 242
    - show interface dialer command 221
    - show interface type number command 286
    - show interfaces bri command 190
    - show ip nat translation command 354
    - show isdn status command 187
    - show line command 85
    - show ppp multilink command 191
    - show privilege command 64
    - show process cpu command 137
    - show queueing command 316
    - show queueing custom command 318
    - show traffic-shape command 264
    - show traffic-shape statistics command 265

- 
- signaling  
     Frame Relay 235–236  
     modems 75–77
- signal-to-noise (S/N) 377
- simple ISDN calls, configuring 175
- site requirements, WAN 18
- site-to-site VPNs, GRE 430
- S/N (signal-to-noise) 377
- Snapshot Routing 169
- SOHO (small office, home office) 365  
     installing 34  
     site requirements 18  
     WAN 24–25
- SONET/SDH (Synchronous Optical NETwork/Synchronous Digital Hierarchy) 6
- source addresses 339–342
- spanning servers 393
- spectrum reuse 377
- speed  
     mismatch 84  
     modems 84  
     WAN 16–18
- SPIDs (service profile identifiers) 159, 207
- split horizons, reachability 246
- spoke routers 241
- STAC compression 321, 324
- Stacker compression scheme 136
- standards  
     compression 83  
     modems 81–83
- standby mode  
     backup interfaces 274  
     dial backups 276
- starting dial backups 275
- statements, dialer map 202
- static address mapping 239–240
- static inside source NAT, configuring 347
- static outside source NAT, configuring 349
- static translation 332
- statistical time division multiplexing (STDM)  
     network 254
- status, Layer 1 188
- STDM (statistical time division multiplexing)  
     network 254
- strings, initialization 95
- stub domains 332
- subinterfaces, Frame Relay 244–250
- subnets, configuring 397
- subscriber drop 373
- suites, configuring 463
- switches  
     Frame Relay 235  
     ISDN types 158  
     Telco ISDN types 163  
     troubleshooting 164
- Symmetric Digital Subscriber Line (SDSL) 381
- symmetric encryption 432
- symmetrical peer crypto ACLs 468
- synchronization, troubleshooting 164
- synchronous connections, EXEC/PPP sessions 118
- synchronous modem connections 8
- Synchronous Optical NETwork/Synchronous Digital Hierarchy (SONET/SDH) 6
- synchronous serial standards 6

## T

---

- T1 controller parameters 164
- tables, adding routes 286
- TACACS+ (Terminal Access Controller Access Control System Plus) 53, 421
- tacacs-server host commands 54
- tail drops, CBWFQ 307
- TCP (Transmission Control Protocol)  
     header compression 136  
     load distribution 345
- TCP/IP (Transmission Control Protocol/Internet Protocol)  
     encryption 421  
     header compression 322
- Telco ISDN switch types 163
- Telnet, reverse terminal sessions 92
- Terminal Access Controller Access Control System Plus (TACACS+) 53, 421
- testing  
     DDR 192  
     IPSec 475–481
- thresholds  
     dialer load-threshold command 170  
     MLP 182
- tools, Cisco product selection 36
- topologies, hub-spoke 241–242
- traffic  
     applications 16  
     compression 320–325  
     crypto ACLs 466

DDR 168  
excessive loads 277  
interesting 171  
queuing 296–297  
    options 299–301  
    policies 298  
    prioritization 297  
traffic shaping  
    configuring 255–266  
    Frame Relay 251–255  
traffic-share commands  
    traffic-share balanced command 286  
    traffic-share min command 286  
transform sets  
    configuring 463  
    editing 465  
    negotiation 465  
transforms  
    commands, 464  
    IPSec 449  
translation  
    NAT 331–338  
        configuring 343–354  
        global addresses 342–343  
        source addresses 339–342  
        troubleshooting 354–359  
    PAT 333, 395  
        configuring 400  
        DSL 396  
transport input protocol command 89  
transport mode, tunneling 438  
transportation networks 373  
troubleshooting 402  
    autoconfiguration 104  
    compression speed 84  
    DDR 187  
    dialer profiles 221  
    disconnections 225  
    DSL 400–405  
    Frame Relay 242–244, 264  
    incoming calls 225  
    IPSec 454–456, 475–481  
    ISDN 187  
    MLP 192  
    modems 83  
    multiplexers 164  
    NAT 354–359  
    negotiation 404  
    nonoccurrence of dialing 222

outbound calls 223  
PPP 143–145  
primary line load backups 282–290  
PVC failures 274  
queuing 296–297  
    options 299–301  
    policies 298  
    prioritization 297  
    verifying 316–319  
reachability 246  
switches 164  
synchronization 164  
tunneling  
    encryption 421  
    GRE 429  
    IKE 442  
    transport mode 438  
    types of 417–430  
    VPN protocols 428  
types  
    of DSL 382–392  
    of lines 87  
    of queuing 297, 319  
    of switches  
        ISDN 158  
        Telco ISDN 163  
    of VPNs 417–427  
    of WAN 16

## U

---

U interfaces 155  
UARTs (Universal Asynchronous Receiver/  
Transmitters) 84  
UNI (User-Network Interface) 232  
updating routing 245  
upstream (US) 376  
US (upstream) 376  
username command 135  
User-Network Interface (UNI) 232

## V

---

V.42bis compression 83  
variance 2 command 285, 286  
variance multiplier command 285

- 
- VCs (virtual circuits) 233  
 verification  
     autoconfiguration 103  
     branch office installation 33  
     called party number 185–186  
     compression 138  
     DDR 186–192  
     dial backups 286  
     dialer profiles 221  
     DSL data 403  
     Frame Relay 242, 264  
     IKE configuration 462  
     IPSec 475–481  
     MLP 191  
     NAT 354–359  
     PPP 143–145, 404  
     queuing 316–319  
     SOHO installation 34  
     WAN installation 31  
 viewing  
     ISAKMP policies 476  
     line commands 85–88  
     working connections 80–81  
 virtual path identifier/virtual channel identifier (VPI/VCI) 394  
 VPDN (virtual private data network) 393  
 vpdn enable command 393  
 vpdn-group name command 393  
 VPI/VCI (virtual channel identifier) 394  
 VPNs (virtual private networks)  
     cryptosystems 430–436  
     IKE 456–462  
     IPSec 436–445  
         configuration 463–475  
         configuring 445–454  
         IKE Phase 1 policy 446–449  
         IKE Phase 2 policy 449–452  
         peers 452–453  
         troubleshooting 454–456, 475–481  
     selecting 427–430  
     types of 417–427  
 VTYs (virtual terminal lines) 55, 87  
 broadband access 11–12  
 dedicated circuit switched 6–7  
 on-demand circuit switched 7–10  
 packet-switched virtual 10–11  
 components 3  
 connections 4–6  
 dial backups  
     configuring 273–280  
     dialer interfaces as 280–282  
 encapsulation protocols 12–15  
 Frame Relay. *See* Frame Relay  
 installing 31  
 ISDN  
     called party number 185–186  
     CLID 184–185  
     DDR 168  
     MLP 182–184  
     PPP 181–182  
     rate adaptation 186  
 PPP 111–112  
     architecture 113–115  
     configuring 115  
     frames 115  
     queuing 296–297  
         options 299–301  
         policies 298  
         prioritization 297  
     remote access 26–37  
     remote/branch office 21–23  
     site requirements 18  
     SOHO 24–25  
     speed comparisons 16–18  
     types 16  
     VPNs. *See* VPNs  
 WFQ (Weighted Fair Queuing) 297–304  
 wireless access 368–369  
 wiring  
     DTE-to-DTE 78  
     RJ-45 79  
 working connections, viewing 80–81  
 WRED (Weighted Random Early Detection) 308–311

## W

- 
- WAN  
     cabling 30  
     central sites 19

## Z

- 
- zones, DMZ 424