

Index

SYMBOLS

- \$ (dollar signs), line scrolling, 133
- ^ (caret symbols), command errors, 133
- ? (question marks), router commands, 133
- 128-bit IP version 6 (IPv6)**, 30

A

access

control lists. *See* ACLs

layers, 9

VPNs, 69

vty, restricting, 143

access-class command, 143

access-list command, 73

ACLs (access control lists), 73

anemd, 74

applying, 73

configuring, 141, 197

creating, 73

extended, 40, 74, 142

filtering options, 142

guidelines, 73

IP address matching, 40

named, 40, 142

number specifications, 141

numbered, 197

overview, 189

packets, 39

placement, 143, 175

standard, 40, 74

traffic, controlling, 73

user protection, 74

verifying, 74, 175

vty access, restricting, 143

VTY lines, 74

wildcard masks, 73

active hubs, 49

AD (administrative distance), 19, 91

adaptability of LANs, 54

adaptive cut-through mode (switches), 17

adding CCNA to resumes, 207

Address Resolution Protocol (ARP), 6, 52

addresses

broadcast, 29

classes (LANs), 52-53

DHCP, 110

IP

allocation, 71

binary-to-decimal conversion, 57

broadcast, 58

classes, 29, 57, 184

finding, 6

hosts, obtaining, 30

Internet, 28

IPv6, 30

matching, 40

name associations, 107

NAT, 61-62

network addresses, determining, 27

obtaining, 53

octets, 29, 57

private, 58

reserved network, 58

subnetting, 58-61

troubleshooting, 167-168

VLSMs, 60

MAC, 15

clearing/viewing, 136

finding, 6

port associations, 51

static configuration, 137

network, 29

determining, 27, 60

private, 30

private, 186

administrative distance (AD), 19, 91

advanced certifications, 208

advertisement requests, 117

allocating IP addresses, 71

American Registry of Internet Numbers (ARIN), 19

analog dial-up WAN service, 79

AND operator, 27, 60

application layer

OSI, 4

protocols, 182

TCP/IP, 5

OSI layers, 6

protocols, 9

applying ACLs, 73

ARIN (American Registry of Internet Numbers), 19

ARP (Address Resolution Protocol), 6, 52

AS (autonomous system) numbers, 19

ATM WAN service, 80

authentication

OSPF, 95

PPP, 145-146

avoiding loops, 184

B

backing up

IOS images, 129

routers, 195

switches, 137-138

bandwidth

EIGRP, 97

interfaces, 94

LANs, 121-122

BECN (Backward ECN), 85

BGP (Border Gateway Protocol), 20, 65

BIA addresses. *See MAC addresses*

BIDs (bridge IDs), 11

binary-to-decimal conversions, 27, 57

bindings (DHCP), 111

bits per second (bps), 121

blocking port state, 12

Boolean logic, 27

Boot ROM, 36

boot system commands, 127

booting routers, 127-128, 195

BOOTP (Bootstrap Protocol), 30, 71

Border Gateway Protocol (BGP), 20, 65

BPUDs, sending, 11

bps (bits per second), 121

bridges

IDs, 11

LANs, 49-51

network functionality, improving, 17

root, 11

broadcasts

addresses, 29, 58

DHCP, 111

LANs, 17

Layer 2, 17

burned-in addresses (BIA). *See MAC addresses*

buses, 15, 35, 49

C

cable modem WAN service, 80

cabling, 50

coaxial, 122

fiber-optic, 122

legacy 10 Mbps Ethernet standards, 124

ScTP, 122

STP, 122

types, 122

UTP, 122-123, 194

WANs, 43

CAM (content addressable memory), 51

career options, 207

caret symbols (^), command errors, 133

Carrier Sense Multiple Access/Collision Detection (CSMA/CD), 17, 39

Catalyst 1900 switch configuration, 136

Catalyst 2950 switch configuration, 136

CCNP (Cisco Certified Network Professional), 208

CCSP (Cisco Certified Security Professional), 208

CDP (Cisco Discovery Protocol), 159

activity, monitoring, 160

device details, 160

enabled devices, viewing, 159

information, clearing, 159

SNAP, 159

starting, 159

turning off, 160

version 2, 159

cdp enable command, 159

cdp run command, 159

CDPv2 (CDP version 2), 159

central office (CO), 43

central processing unit (CPU), 35

certificates, 207

certified score reports, 205

CHAP (Challenge Handshake Authentication Protocol), 82

Cisco

- Certified Network Professional (CCNP), 208
- Certified Security Professional (CCSP), 208
- devices, 159-160
- Discovery Protocol, 159-160
- HDLC encapsulation, 82
- IOS, 36, 196
- routers, 37
- Three-Layer Hierarchical Model, 55

class boundaries, ignoring, 90

Class C Subnet chart, 187

classes

- address, 52-53
- IP addresses, 29, 57, 184

clear cdp counters command, 159

clear isdn bri command, 178

clearing

- MAC addresses, 136
- switches, 135

CLI (command-line interface), 36, 99

client/server models, 51

clock command, 133

clock rate command, 100, 191

CO (central office), 43

coaxial cables, 122

collisions

- domains, 17, 52
- late, 186
- local, 185
- networks, 39, 51
- remote, 185

command-line interface (CLI), 36, 99

commands

- access-class, 143
- access-list, 73
- ACLs, configuring, 197
- boot system, 127
- CDP activity monitoring, 160
- cdp enable, 159
- cdp run, 159
- Cisco IOS editing, 196
- clear cdp counters, 159
- clear isdn bri, 178
- clock, 133
- clock rate, 100, 191
- command history, 134
- configure terminal, 133
- debug
 - DDR, troubleshooting, 178*
 - EIGRP, troubleshooting, 165*
 - IGRP, 163-165*
 - OSPF, troubleshooting, 165*
 - RIP, 164-165*
 - troubleshooting, 172*
- debug frame-relay lmi, 178
- debug ip dhcp server events, 111
- debug ppp interface, 177
- editing, 134
- errors, 133
- extended ping, 168
- history, 134
- ip access-group, 73
- ip classless, 90
- ip default-network, 163
- ip helper-address, 111
- ip route 0.0.0.0/0, 163
- isdn call interface, 178
- LANs, 199-201
- no cdp enable, 160
- no cdp run, 160
- no debug all, 164
- no ip subnet-zero, 60
- passive-interface, 91
- ping
 - ICMP messages, 32*
 - Layer 3 connectivity, 155, 171*
- routers
 - booting, 195*
 - configuration/backup, 195*
 - initial, 196*
 - viewing, 133*
- show, 106-107, 159
 - ACLs, verifying, 175*
 - EIGRP verification, 98, 165*
 - IGRP verification, 163-165*
 - OSPF, troubleshooting, 165*
 - RIP verification, 164-165*
- show access-lists, 175
- show cdp neighbors, 159
- show cdp neighbors detail, 160
- show controllers, 172
- show flash, 130
- show history, 134

show interface, 177
show ip dhcp binding, 111
show ip dhcp server statistics, 111
show ip interface, 175
show ip protocols, 163, 172
show ip rip database, 163
show ip route, 163, 172
show isdn status, 177
show running config, 115, 175
show version, 36
show vlan, 115
switches, 135, 196
telnet, 167
terminal editing, 134
terminal history size, 134
terminal monitor, 172
terminal no editing, 134
tftpndld, 130
traceroute, 171-172
troubleshooting, 172
undebbug all, 164
vlan database, 114-115
VLANs, 199-201
WANs, 197-199
xmodem, 130

communication

CSMA/CD, 39
LANs, 52
networks, 99
nodes, 3
serial WANs, 45, 81
service providers, 43, 78
switches, 51
TCP, 7
WAN data, 44

components

LANs, 15
routers, 35

configuration files

copying, 128
restoring, 127
storing, 126

configuration registers

customizing, 128
values, 195

configure terminal command, 133**configuring**

ACLs, 141
commands, 197
extended, 142
named, 142
DDR, 147-149
DHCP, 110
dynamic NAT, 108
EIGRP, 96-98
Frame Relay, 149-150
IGRP, 92
interfaces
bandwidth, 94
deleting, 101
descriptions, 101
Ethernet, 101-102
IP addressing conventions, 99
loopbacks, 94, 102
serial, 100-102
VLSMs, 93
ISDN, 146-147
load balancing paths, 91
local intranets, 69
login banners, 107
NAT
overload, 109, 192
verifying, 110
OSPF, 93-95
passwords, 105-106
port security, 137
RIP, 90, 93
routers
commands, 195
console, 192
DHCP, 192
Frame Relay PVC, 149
hostnames, 105
initial configuration example, 135
NAT, 192
restoring, 171
vty, 192
routes
default, 90
static, 89
serial interfaces, 191
static MAC addresses, 137
static NAT, 108
static routes, 91
subinterfaces, 150

- switches**
 - Catalyst 1900*, 136
 - Catalyst 2950*, 136
 - clearing*, 135
 - customizing*, 125-126
 - trunk**, 193
 - VLANs**, 113
 - global configuration mode*, 114
 - static commands*, 193
 - subinterfaces*, 117
 - trunking*, 115
 - verifying*, 114-115
 - vlan database command*, 114
 - FTP**, 117, 193
 - WANs**
 - commands*, 197-199
 - PPP encapsulation*, 145
 - connections**
 - Frame Relay networks, 85
 - LANs, 16
 - Frame Relay*, 85
 - switches*, 16
 - Layer 3, 171
 - Layer 4, 157
 - redundant, 11
 - routers, 35-36
 - trunk, 161
 - WANs, 43
 - branch networks*, 81
 - cabling*, 43
 - demarcation points*, 43
 - digital*, 45
 - equipment*, 43
 - HSSI*, 43
 - physical*, 77
 - speeds*, 43
 - switched circuits*, 44, 79
 - types*, 77
 - console**
 - configuring, 192
 - passwords, 105
 - TIA/EIA-232 port connections, 37
 - content addressable memory (CAM)**, 51
 - control messages**, 32
 - controlling**
 - traffic, 73
 - VTY lines with ACLs, 74
 - convergence**
 - networks, 11
 - routers, 19
 - copying configuration files**, 128
 - core layer (three-layer hierarchical model)**, 9
 - CPE (customer premises equipment)**, 43
 - CPU (central processing unit)**, 35
 - CRC (cyclic redundancy check)**, 39
 - crossover cables**, 123
 - crosstalk**, 122-123
 - CSMA/CD (Carrier Sense Multiple Access/Collision Detection)**, 17, 39
 - customer premises equipment (CPE)**, 43
 - customizing**
 - configuration registers, 128
 - routers boot process, 128
 - switch configurations, 125-126
 - VLANs, 116
 - cyclic redundancy check (CRC)**, 39
- D**
- data field (IP packets)**, 31
 - data flow**, 39-40
 - data link layer**
 - OSI, 4
 - WANs, 44, 78
 - data terminal equipment (DTE)**, 43
 - DDR (dial-on-demand routing)**, 45, 178
 - configuring, 147-149
 - troubleshooting, 178
 - dead intervals (OSPF)**, 95
 - debug commands**
 - DDR, troubleshooting, 178
 - EIGRP, troubleshooting, 165
 - IGRP, 163-165
 - OSPF, troubleshooting, 165
 - RIP, 164-165
 - troubleshooting, 172
 - debug frame-relay lmi command**, 178
 - debug ip dhcp server events command**, 111
 - debug ppp command**, 177
 - decimal and binary conversions**, 27
 - default administrative distances**, 164

default routes, 22

configuring, 90
propagating with OSPF, 96
verifying, 90

deleting

interface configurations, 101
static routes, 92
VLANs, 115

demarcation points (WANs), 43**denial-of-service (DoS) attacks, 33****designs**

LANs, 187
networks, 9
WANs, 81

destination address field (IP packets), 31**devices**

Cisco, 159-160
network, 49

DHCP (Dynamic Host Configuration Protocol), 30, 70

addresses, excluding, 110
bindings, 111
broadcasts, 111
configuring, 110, 192
host IP addresses, 53
internetworks, 70
IP address allocation, 71
message counts, 111
processes, 111
starting/stopping, 111

dial-on-demand routing. *See* DDR**dialer profiles, 148-149****diffusing update algorithm (DUAL), 24-25****digital connections (WANs), 45****digital subscribe line (DSL), 77****distance vector protocols, 20, 64, 183****distribution layer (three-layer hierarchical model), 9****DNS (Domain Name System), 6****dollar signs (\$), line scrolling, 133****DoS (denial-of-service) attacks, 33****DSL (digital subscriber line), 77****DSL WAN service, 80****DTE (data terminal equipment), 43****DUAL (diffusing update algorithm), 24-25****Dynamic Host Configuration Protocol.
See DHCP****dynamic NAT, 108****E****editing keys/commands, 134****EIGRP (Enhanced Interior Gateway Routing Protocol), 20, 64**

advanced features, 24, 67
bandwidth, 97
configuring, 96
DUAL algorithm, 25
features, 66
multiprotocol support, 23
packets, 24
route summaries, 97-98
topology tables, 24
troubleshooting, 165
verifying, 98

enabling

PPP, 145
SNMP, 112

encapsulation

PPP, 145-146
WANs, 186

encrypting passwords, 106**Enhanced Interior Gateway Routing Protocol. *See* EIGRP****enterprise servers (LANs), 54****Ethernet**

frames, 16
interfaces, 101-102
LANs, 16, 50
Layer 2 technology, 5
networks, 17

exam day, 205**excluding addresses (DHCP), 110****EXEC mode routers, 133****extending**

ACLs, 40, 74, 142
ping command, 168
stars, 15, 49

exterior routes (IGRP), 22**extranet VPNs, 69**

F

- failing the exam**, 208
- far-end crosstalk (FEXT)**, 123
- FDDI (Fiber Distributed Data Interface)**, 5
 - feasible distance field (EIGRP topology table)**, 24
 - feasible successor routes**, 24
 - FECN (Forward ECN)**, 85
 - FEXT (far-end crosstalk)**, 123
- Fiber Distributed Data Interface (FDDI)**, 5
- fiber-optic cables**, 122
- fields**
 - EIGRP topology table, 24
 - Ethernet frames, 16
 - IP packets, 31
 - ISDN frames, 83
 - Layer 2 frames, 5
 - TCP segments, 8
- files (configuration)**
 - copying, 128
 - restoring, 127
 - storing, 126
- filtering**
 - ACL options, 142
 - traffic, 52
- flags field (IP packets)**, 31
- flash**, 35, 130
- flat WAN topology**, 81
- flow control**, 6-7
- Forward ECN (FECN)**, 85
- forwarding**
 - DHCP broadcasts, 111
 - frames, 11
 - port state, 12
- fragment offset field (IP packets)**, 31
- Frame Relay**, 85, 186
 - configuring, 149-150
 - connections, 85
 - inverse ARP messages, 86
 - LAN connections, 85
 - LMIs, 85
 - switches, 79, 85
 - verifying, 178

virtual circuits, 85
WANs, 44-46, 80

frames

- Ethernet, 16
- forwarding, 11
- HDLC, 78
- ISDN, 83
- Layer 2, 5
- processing, 17
- runt, 39
- WANs, 44

full-duplex bandwidth, 17

G - H

- Gbps (gigabits per second)**, 121
- global configuration mode (VLANs)**, 114
- HCCs (horizontal cross-connects)**, 54
- HDLC frames**, 78
- header checksum field (IP packets)**, 31
- hello intervals**, 95
- hello packets**, 23
- hierarchy**
 - defined, 49
 - networks, 15
- high-bandwidth low latency WANs**, 81
- High-Speed Serial Interface (HSSI)**, 43, 78
- history of commands**, 134
- horizontal cross-connects (HCCs)**, 54
- host-to-network layer**, 6
- hostnames (routers)**
 - configuring, 105
 - testing, 108
- hosts**
 - full-duplex bandwidth, 17
 - interfaces, 99
 - IP addresses, obtaining, 30, 53
 - LANs, 52
 - sessions, 7
 - simultaneous services, 33
 - traffic, 53
- HSSI (High-Speed Serial Interface)**, 43, 78
- hubs**, 49

- I**
- ICMP (Internet Control Message Protocol),** 32
- identification field (IP packets),** 31
- IDF (intermediate distribution facility),** 54
- IEEE (Institute of Electrical and Electronics Engineers),** 113
- IFS (IOS File System),** 128
- IGRP (Interior Gateway Routing Protocol),** 20, 64
 - configuring, 92
 - exterior routes, 22
 - interior routes, 22
 - routing updates, 21
 - system routes, 22
 - troubleshooting, 163-165
 - verifying, 163
- images**
 - IOS, 129-130
 - names, 185
- initial router commands,** 196
- initial router configuration example,** 135
- Institute of Electrical and Electronics Engineers (IEEE),** 113
- Integrated Service Digital Network.** *See ISDN*
- Inter-Switch Link (ISL),** 113
- interfaces**
 - configuration mode (routers), 100
 - configuring
 - bandwidth*, 94
 - deleting*, 101
 - descriptions*, 101
 - Ethernet*, 101-102
 - IP addressing conventions*, 99
 - loopbacks*, 94, 102
 - serial*, 100, 102
 - VLSMs*, 93
 - information field (EIGRP topology table), 24
 - ISDN, 84
 - OSPF costs, 95
 - routing, 35, 91
 - serial, 191
- Interior Gateway Routing Protocol.** *See IGRP*
- interior routes (IGRP),** 22
- intermediate distribution facility (IDF),** 54
- Internet**
 - Control Message Protocol (ICMP), 32
 - IP addresses, 28
 - layer (TCP/IP), 6
- internetworks**
 - DHCP, 70-71
 - dividing switches into VLANs, 70
 - NAT/PAT, 70
 - types, 188
 - VLANs, 70
 - WANs, 71-72, 80
- intranet VPNs,** 69
- inverse ARP messages,** 86
- IOS File System (IFS),** 128
- IOS images,** 129-130
- IOS naming conventions,** 129
- ip access-group command,** 73
- IP addresses**
 - allocating, 71
 - binary-to-decimal conversion, 57
 - broadcast, 58
 - classes, 29, 57, 184
 - finding, 6
 - hosts, obtaining, 30
 - Internet, 28
 - IPv6, 30
 - matching, 40
 - name associations, 107
 - NAT, 61-62
 - network addresses, determining, 27
 - obtaining, 53
 - octets, 29, 57
 - private, 58
 - reserved network, 58
 - subnetting, 58-60
 - troubleshooting, 167-168
 - VLSMs, 60
- ip classless command,** 90
- IP Control Protocol (IPCP),** 82
- ip default-network command,** 163
- IP header length field (IP packets),** 31
- ip helper-address command,** 111
- IP packets,** 31
- ip route 0.0.0.0/0 command,** 163

IPCP (IP Control Protocol), 82
IPv6 (128-bit IP version 6), 30
ISDN (Integrated Service Digital Network), 77
 BRI, 146
 configuring, 147
 frame fields, 83
 interfaces, 84
 out-of-band signaling, 83
 PRI, 146
 PRI E1, 147
 protocols, 83, 190
 reference points, 83-84, 190
 verifying, 177
 WANs, 45, 79
isdn call interface command, 178
ISL (Inter-Switch Link), 113
The IT Career Builder's Toolkit, 207

J - K - L

kbps (kilobits per second), 121
keys, 134

LANs (local area networks)

adaptability, 54
 address classes, 52-53
 ARP, 52
 bandwidth, 121-122
 bridges, 50-51
 broadcasts, 17
 cabling
legacy 10 Mbps Ethernet standards, 124
types, 122
UTP, 123
Cisco Three-Layer Hierarchical Model, 55
client/server models, 51
collisions, 17, 51-52
 communication, 52
 components, 15
 connections, 16
Frame Relay, 85
switches, 16
 data, analyzing, 54
 designs, 187
 enterprise servers, 54
 Ethernet, 16, 50

expectations, 54
 full-duplex bandwidth, 17
 functionality, 54
 gateways to WANs, 78
 hosts, 52
 IP addresses, 53
 latency, 17, 51
 Layer 2 broadcasts, 17
 local intranets, 69
 manageability, 54
 network devices, 49
 NICs, 51-52
 noise, 122-123
 OSI Layer 1 schemes, 54
 OSI Layer 2 schemes, 55
 OSI Layer 3 schemes, 55
 peer-to-peer networks, 51
 performance, 52
 physical layers, 50, 54
 private addresses, 53, 186
 repeaters, 50
 requirements, 54
 routers, 35, 54
 scalability, 54
 segmenting with routers, 63
 signals, 122
 switches
content addressable memory, 51
host traffic, regulating, 53
local machines, identifying, 53
ports, 51
 topologies, 183
 traffic, filtering, 52
 troubleshooting
CDP, 159-161
commands, 199-201
 virtual circuits, 51
 wireless, 50

LAPF (Link Access Procedure for Frame Relay), 85

last mile, 43

late collisions, 39, 186

latency

LANs, 51
 networks, 17

Layer 2 broadcasts, 17

Layer 2 frames, 5

Layer 3 connectivity

testing, 155
troubleshooting, 171

Layer 4 connectivity, 157**layers**

data link, 44
models, 181
OSI, 3-5
physical
 LANs, 50, 54
 WANs, 44
TCP/IP, 28
 application, 5-6, 9
 internet, 6
 network access, 6
 transport, 6-8

three-layer hierarchical model, 9
transport, 32
WANs, 78

LCP (Link Control Protocol), 82**learning port state, 12****leased line WAN service, 80****LED lights (routers), 37****Link Access Procedure for Frame Relay (LAPF), 85****Link Control Protocol (LCP), 82****link management identifiers (LMIs), 85****link-state protocols, 20, 65**

distance vector protocols, compared, 64
updates, 22
vector, 183

Linksys routers, 21**listening port state, 12****LMIs (link management identifiers), 85****load balancing paths/routers, 91****local area networks. *See LANs*****local collisions, 39, 185****local intranets, 69****local loops, 43****local machines (LANs), 53****logical topologies, 15****login banners, 107****loopback interfaces, configuring, 102****loops**

avoiding, 184
redundancy, 182

routers, 21
switching, 12

M**MAC (Media Access Control) addresses, 15**

clearing/viewing, 136
finding, 6
port associations, 51
static configuration, 137

main distribution facility (MDF), 54**management ports, 36****MANs (metropolitan-area networks), 69****masks (VLSMs), 60****Mbps (megabits per second), 121****MDF (main distribution facility), 54****Media Access Control. *See MAC addresses*****megabits per second (Mbps), 121****membership (VLANs), 70****memory**

content addressable, 51
nonvolatile random-access (NVRAM), 35
read-only (ROM), 35
routers, viewing, 36

mesh, 49**mesh networks, 15****messages**

control, 32
counts (DHCP), 111
inverse ARP, 86
VTP, 116

metropolitan-area networks (MANs), 69**microsegmentation, 17****models**

layered, 181
OSI
 Layer 3 connectivity, 155
 Layer 4 connectivity, 157
 networks, 155-157
 overview, 155, 181
 testing, 167
 troubleshooting, 199

TCP/IP, 181

monitoring CDP activity, 160

Moran, Matthew, 207

multicasting (VTP), 116

N

names

ACLs, 40, 74, 142

images, 185

IOS naming conventions, 129

IP address association, 107

NAT (network address translation), 61, 70

configuring, 110, 192

dynamic, 108

internetworks, 70

IP addresses, 61-62

overload, 109

packets, 110

static, 108

NCP (Network Control Protocol), 82

near-end crosstalk (NEXT), 123

network address translation. *See* NAT

Network Control Protocol (NCP), 82

network interface cards (NICs), 49-52

networks

access layer, 6

addresses, 29

determining, 27, 60

private, 30

cabling, 122-124

class boundaries, ignoring, 90

Class C Subnet, 187

collisions, 39, 51-52

communication, 99

convergence, 11

designing, 9

devices (LANs), 49

Ethernet, 17

functionality, improving, 17

latency, 17

layer, 4

OSI management model, 157

paths (routers), 63

peer-to-peer, 51

performance, 52

physical topology, 15

protocols. *See* protocols

PSNs, 79

segments, 70

signals, 122

subnetworks, 30

troubleshooting, 155-156, 171

types, 69, 188

NEXT (near-end crosstalk), 123

NICs (network interface cards), 49-52

no cdp enable command, 160

no cdp run command, 160

no debug all command, 164

no ip subnet-zero command, 60

nodes of communication, 3

noise (LANs), 122-123

number specifications (ACLs), 141

numbered ACLs, 197

NVRAM (nonvolatile random-access memory), 35

O

octets (IP addresses), 29, 57

official certificates, 207

Open Shortest Path First. *See* OSPF

operating environments, 36

options field (IP packets), 31

Organizational Unique Identifiers (OUIs), 15

OSI (Open Source Initiative)

layers

application, 4

data link, 4-5

LAN designs, 187

Layer 1 schemes, 54

Layer 2 schemes, 55

Layer 3 schemes, 55, 63

network, 4

PDUs, 4

physical, 4

presentation, 4

session, 4

transport, 4

model

benefits, 3

Layer 3 connectivity, 155

Layer 4 connectivity, 157

- layers*, 3-4
 - networks*, 155-157
 - overview*, 155, 181
 - TCP/IP*, compared, 28
 - testing*, 167
 - troubleshooting*, 199
 - TCP/IP, compared, 4
 - OSPF (Open Shortest Path First)**, 64, 93, 164
 - authentication, 95
 - configuring, 93
 - databases, 22
 - default routes, propagating, 96
 - features, 65-66
 - hello packets, 23
 - hello/dead intervals, 95
 - interface costs, 95
 - loopback interface, 94
 - priorities, 94
 - testing, 96
 - troubleshooting, 164-165
 - updates, 22-23
 - OUIs (Organizational Unique Identifiers)**, 15
 - out-of-band signaling**, 83
 - overload (NAT)**, 109, 192
- ## P
- packet-switched networks (PSNs)**, 44, 79
 - packets**
 - ACL management, 39
 - EIGRP, 24
 - hello, 23
 - IP, 31
 - NAT, 110
 - paths, 19-20
 - padding field (IP packets)**, 31
 - PAP (Password Authentication Protocol)**, 82
 - PAR (positive acknowledgement and retransmission)**, 33
 - passive-interface command**, 91
 - Password Authentication Protocol (PAP)**, 82
 - passwords**
 - console, 105
 - encrypting, 106
 - privileged EXEC mode, 106
 - virtual terminal, 105
 - PAT (port address translation)**, 70
 - paths**
 - load balancing, 91
 - packets, 19-20
 - PCMCIA (Personal Computer Memory Card International Association)**, 35
 - PDUs (protocol data units)**, 28, 181
 - peer-to-peer networks**, 51
 - per-packet load balancing**, 91
 - permanent virtual circuits (PVCs)**, 79
 - Personal Computer Memory Card International Association (PCMCIA)**, 35
 - phone calls (WANs)**, 44
 - physical layers**
 - LANs, 50, 54
 - OSI, 4
 - WANs, 44, 78
 - physical topology (networks)**, 15
 - physical WAN connections**, 77
 - ping command**
 - extended, 168
 - ICMP messages, 32
 - Layer 3 connectivity, 155, 171
 - plain old telephone service (POTS)**, 77
 - Point-to-Point Protocol**. *See PPP*
 - port address translation (PAT)**, 70
 - ports**
 - demarcation points, 43
 - MAC address associations, 51
 - number assignments, 33
 - number ranges, 33
 - security, 137
 - STP states, 12, 182
 - switches, 51
 - transport layer, 8, 182
 - positive acknowledgement and retransmission (PAR)**, 33
 - POTS (plain old telephone service)**, 77
 - power sum near-end crosstalk (PSNEXT)**, 123
 - power supplies (routers)**, 35

PPP (Point-to-Point Protocol), 82

- authentication, 145-146
- enabling, 145
- encapsulation, 145-146
- LCP, 82
- NCP, 82
- session establishment, 82, 190

presentation layer (OSI), 4**preventing loops, 21****priorities**

- OSPF, 94
- routes, 91

private addresses

- IP addresses, 58
- LANs, 53, 186
- networks, 30

privileged EXEC mode, 106, 133**processes (DHCP), 111****processing frames, 17****professional certifications, 208****protecting users (ACLs), 74****protocol data units (PDUs), 28, 181****protocol field (IP packets), 31****protocols**

- application layer, 9, 182
- ARP, 6, 52
- BOOTP, 30, 71
- CDP, 159-160
- CHAP, 82
- configured, viewing, 92
- defined, 49
- DHCP

- addresses, excluding, 110*
- bindings, 111*
- broadcasts, 111*
- configuring, 110, 192*
- host IP addresses, 53*
- internetworks, 70*
- IP address allocation, 71*
- message counts, 111*
- processes, 111*
- starting/stopping, 111*

- distance vector, 20, 64, 183

- EIGRP, 20, 64

- advanced features, 24, 67*
- bandwidth, 97*
- configuring, 96*
- DUAL algorithm, 25*

- features, 66*

- multiprotocol support, 23*

- packets, 24*

- route summaries, 97-98*

- topology tables, 24*

- troubleshooting, 165*

- verifying, 98*

- ICMP, 32

- IGRP, 20, 64

- configuring, 92*

- exterior routes, 22*

- interior routes, 22*

- routing updates, 21*

- system routes, 22*

- troubleshooting, 163-165*

- verifying, 163*

- ISDN, 77

- BRI, 146*

- configuring, 147*

- frame fields, 83*

- interfaces, 84*

- out-of-band signaling, 83*

- PRI, 146*

- PRI E1, 147*

- protocols, 83, 190*

- reference points, 83-84, 190*

- verifying, 177*

- LCP, 82

- link-state, 20, 65

- distance vector protocols, compared, 64*

- updates, 22*

- vector, 183*

- NCP, 82

- network, 15

- PAP, 82

- PPP, 82

- authentication, 145-146*

- enabling, 145*

- encapsulation, 145-146*

- LCP, 82*

- NCP, 82*

- session establishment, 82, 190*

- RARP, 6, 30

- RIP, 30, 64

- configuring, 90*

- Linksys support, 21*

- load balancing, 91*

- troubleshooting, 164-165*

- verifying, 164*

version 1, 22, 65
version 2, 22, 65, 93
routing, 19, 63
BGP, 20, 65
default administrative distances, 164
distance vector, 20
EIGRP. See *EIGRP*
IGRP, 20-22, 64
link-state, 20, 22
listing of, 64, 188
OSI Layer 3, 63
OSPF, 22-23, 64-66
RIP. See *RIP*
syntax, 190-191
troubleshooting, 201
RSTP, 12
SNAP, 159
STP
 BIDs, 11
 loop redundancy, preventing, 182
 network convergence, 11
 port states, 12, 182
 redundant connections, 11
 switching loops, 12
 troubleshooting, 161
TCP/IP
 DoS attacks, 33
 hosts, 33
 layers, 5-8, 28
 network communication, 99
 OSI, compared, 4, 28
 overview, 181
 PAR, 33
 PDUs, 28
 ports, 33
 sliding windows, 7
 TCP communication, 7
 TCP segments, 8
 transport layer, 32
UDP, 8
VTP, 113
 configuring, 117, 193
 messages, 116
 modes, 193
 multicasting, 116
 switch modes, 116
WANs, 189, 202
PSNEXT (power sum near-end crosstalk), 123

PSNs (packet-switched networks), 44, 79
PVCs (permanent virtual circuits), 79

Q - R

question marks (?), router commands, 133

radio frequency (RF), 50

RAM (random-access memory), 35

Rapid Spanning Tree Protocol (RSTP), 12

RARP (Reverse Address Resolution Protocol), 6, 30

read-only memory (ROM), 35

redundancy

connections, 11

loops, 182

reference points (ISDN), 83-84, 190

remote collisions, 39, 185

repeaters (LANs), 49-50

reported distance field (EIGRP topology table), 24

requirements

exam day, 205

LANs, 54

reserved network IP addresses, 58

restoring

configuration files, 127

IOS images, 129-130

routers, 171

switches, 138

restricting vty access, 143

retaking the exam, 208

Reverse Address Resolution Protocol (RARP), 6, 30

RF (radio frequency), 50

rings, 15, 49

RIP (Routing Information Protocol), 20, 64

configuring, 90

Linksys support, 21

load balancing, 91

troubleshooting, 164-165

verifying, 164

version 1, 22, 65

version 2, 22, 65, 93

-
- RJ-45 connectors, 50**
- rollover cables, 123**
- ROM (read-only memory), 35**
- ROM Monitor (ROMMON), 36**
- ROMMON (ROM Monitor), 36**
- root bridges, 11**
- route source field (EIGRP topology table), 24**
- route status field (EIGRP topology table), 24**
- routers**
- ACL placement, 175
 - available commands, 133
 - backing up, 195
 - boot process, 127-12, 195
 - Cisco, 37
 - CLI modes, 36
 - commands, 196
 - configuration
 - commands, 195*
 - console, 192*
 - DHCP, 192*
 - Frame Relay PVC, 149*
 - modes, 99-100*
 - NAT, 192*
 - registers, customizing, 128*
 - saving, 126*
 - vty, 192*
 - connecting, 35-36
 - console TIA/EIA-232 port connections, 37
 - convergence, 19
 - default routes, 22
 - EXEC mode, 133
 - flash, 130
 - hostnames
 - configuring, 105*
 - testing, 108*
 - initial configuration example, 135
 - interfaces, 99
 - internal components, 35
 - LANs, 49, 54
 - communication, 52*
 - segmenting, 63*
 - LED lights, 37
 - Linksys, 21
 - load balancing, 91
 - loops
 - avoiding, 184*
 - preventing, 21*
- memory, viewing, 36
- networks
- class boundaries, 90*
 - functionality, improving, 17*
 - paths, 63*
- operating environments, 36
- packets, 19-20
- restoring, 171
- route poisoning, 21
- routing metrics, 21
- SNMP, enabling, 112
- software compatibility, 36
- starting, 195
- traffic, filtering, 52
- troubleshooting, 171
- VTY lines, 74
- as WAN devices, 145
- routes**
- default, 22
 - configuring, 90*
 - propagating with OSPF, 96*
 - verifying, 90*
- EIGRP summaries, 97-98
- exterior, 22
- feasible successor, 24
- interior, 22
- poisoning, 21
- priorities, 91
- static
 - configuring, 89-91*
 - deleting, 92*
 - verifying, 90*
- successor, 24
- system, 22
- updates, 91
- routing**
- DDR, 178
 - metrics, 21
 - protocols
 - BGP, 20, 65*
 - default administrative distances, 164*
 - distance vector, 20*
 - EIGRP. See EIGRP*
 - IGRP, 20-22, 64*
 - link-state, 20-22*
 - listing of, 64, 188*
 - OSI Layer 3, 63*
 - OSPF, 22-23, 64-66*
 - RIP. See RIP*
 - routed protocols, compared, 19*

syntax, 190-191
troubleshooting, 201
tables, 19, 163
troubleshooting, 165
Routing Information Protocol. *See RIP*
RSTP (Rapid Spanning Tree Protocol), 12
runts, 39, 186

S

SANs (storage-area networks), 69
saving router configurations, 126
scalability (LANs), 54
ScTP (screened twisted pair), 122
security
 ports, 137
 user protection, 74
 WANs, 81
segments
 LANs, 63
 networks, 70
 TCP, 8
sending BPDUs, 11
serial communication (WANs), 45, 81
serial interfaces, configuring, 100-102, 191
service profile identifiers (SPIDs), 84
session layer (OSI), 4
sessions
 PPP, 190
 starting, 7
shielded twisted pair (STP), 122
show access-lists command, 175
show cdp command, 159
show cdp neighbors command, 159
show cdp neighbors detail command, 160
show commands, 106-107
 ACLs, 175
 EIGRP, 98, 165
 IGRP, 163-165
 OSPF, troubleshooting, 165
 RIP, 164-165
show controllers command, 172
show flash command, 130
show history command, 134
show interface command, 177

show ip dhcp binding command, 111
show ip dhcp server statistics command, 111
show ip interface command, 175
show ip protocols command, 163, 172
show ip rip database command, 163
show ip route command, 16, 172
show isdn status command, 177
show running config command, 115, 175
show version command, 36
show vlan command, 115
signals (network), 122
SIMMs (single inline memory modules), 35
single inline memory modules (SIMMs), 35
sliding windows (TCP/IP), 7
SMTP (Simple Mail Transfer Protocol), 6
SNAP (Subnetwork Access Protocol), 159
SNMP (Simple Network Management Protocol), 6, 112
software compatibility (routers), 36
SONET (Synchronous Optical Network), 77
source address field (IP packets), 31
Spanning Tree Protocol. *See STP*
SPIDs (service profile identifiers), 84
standard ACLs, 40, 74
stars, 15, 49
starting
 CDP, 159
 DHCP, 111
 routers, 195
static MAC address configuration, 137
static NAT, 108
static routes
 administrative distance, 19
 configuring, 89, 91
 deleting, 92
 verifying, 90
static VLANs, 70
stopping DHCP, 111
storage-area networks (SANs), 69
storing configuration files, 126

STP (Spanning Tree Protocol), 11, 182

- BIDs, 11
- loop redundancy, preventing, 182
- network convergence, 11
- port states, 12, 182
- redundant connections, 11
- switching loops, 12
- troubleshooting, 161

STP (shielded twisted pair), 122**straight-through cables, 123****subinterfaces**

- configuring, 150
- VLANs, 117

subnet masks

- VLSMs, 60
- wildcard masks, compared, 40

subnetting

- Class C networks, 187
- IP addresses, 58
 - borrowed bits with corresponding mask, 58*
 - eight borrowed bits, 60*
 - network addresses, determining, 60*
 - seven borrowed bits, 60*
 - two borrowed bits, 59*
- VLSMs, 61

Subnetwork Access Protocol (SNAP), 159**subnetworks, 30****subset advertisements, 117****successor routes, 24****summary advertisements, 117****SVCs (switched virtual circuits), 79****switched circuits (WANs), 44, 79****switches**

- adaptive cut-through mode, 17
- backing up, 137-138
- BIDs, 11
- BPDU, sending, 11
- commands, 196
- communication, 51
- configuring
 - Catalyst 1900, 136*
 - Catalyst 2950, 136*
 - clearing, 135*
 - customizing, 125-126*
- dividing into VLANs, 70

Frame Relay, 85

- virtual circuits, 79*
- WANs, 44-46*

frames

- forwarding, 11*
- processing, 17*

LANs, 49

- connections, 16*
- content addressable memory, 51*
- host traffic, regulating, 53*
- local machines, identifying, 53*
- ports, 51*

MAC addresses, 136-137**microsegmentation, 17****network functionality, improving, 17****port security, 137****restoring, 138****static VLANs, 113****STP, 11, 182****trunks, 115****switching loops, 12****Synchronous Optical Network (SONET), 77****system routes (IGRP), 22****T****tables**

- routing, 19, 163
- topology, 24

Tbps (terabits per second), 121**TCP segments, 8****TCP/IP (Transmission Control Protocol/Internet Protocol)**

- DoS attacks, 33

- hosts, 33

- layers, 28

- application, 5-6, 9*
- internet, 6*
- network access, 6*
- transport, 6-8*

network communication, 99

- OSI, compared, 4, 28

- overview, 181

- PAR, 33

- PDUs, 28

- ports, 33

- sliding windows, 7

- TCP
 - communication*, 7
 - segments*, 8
 - transport layer, 32
- TDM (time division multiplexing), 81**
- telnet command, 167**
- terabits per second (Tbps), 121
- terminal editing command, 134**
- terminal history size command, 134**
- terminal monitor command, 172**
- terminal no editing command, 134**
- testing. See also troubleshooting**
 - Layer 3 connectivity, 155
 - Layer 4 connectivity, 157
 - OSI model, 167
 - OSPF, 96
 - routers, 108
- tftpdnld command, 130**
- three-layer designs (WANs), 81**
- three-layer hierarchical model, 9**
- time division multiplexing (TDM), 81**
- time to live field (IP packets), 31**
- Token Ring Layer 2 technology, 5**
- topologies**
 - LANs, 183
 - logical, 15
 - physical, 15
 - tables, 24
- total length field (IP packets), 31**
- traceroute command, 171-172**
- traffic**
 - controlling, 73
 - filtering, 52
 - hosts, 53
- Transmission Control Protocol/Internet Protocol. See TCP/IP**
- transport layer**
 - OSI, 4
 - ports, 182
 - TCP/IP, 6, 32
 - flow control*, 6-7
 - ports*, 8
 - sessions*, 7
 - TCP communication*, 7
- troubleshooting. See also testing**
 - commands, 172
 - DDR, 178
- DoS attacks, 33
- EIGRP, 165
- extended ping command, 168
- IGRP, 165
- IP addresses, 167-168
- LANs
 - CDP*, 159-161
 - commands*, 199-201
- Layer 3 connectivity, 171
- networks, 155-156, 171
- OSI model, 199
- OSPF, 164-165
- RIP, 165
- routers, 171
- routing, 165
 - protocols*, 163-164, 201
 - tables*, 163
- STP, 161
- trunk connections, 161
- VLANs, 161, 199-201
- WANs
 - Frame Relay*, 178
 - ISDNs*, 177
 - protocols*, 202
 - serial connections*, 177
- trunk**
 - configuring, 193
 - connections, 161
 - switches, 115
 - VLANs, 115
- turning off**
 - CDP, 160
 - EIGRP route summaries, 97
- type of service field (IP packets), 31**

U - V

- UDP (User Datagram Protocol), 8**
- undebug all command, 164**
- unencrypted passwords, 106**
- unshielded twisted pair (UTP), 122-123, 194**
- updates**
 - link-state protocols, 22
 - OSPF, 22-23
 - routes, 91

- User Datagram Protocol (UDP), 8**
- users, protecting, 74**
- UTP (unshielded twisted pair), 122-123, 194**
- variable-length subnet masks. *See* VLSMs**
- VCCs (vertical cross-connects), 54**
- VCs (virtual circuits), 79**
- Frame Relay networks, 85
 - LANs, 51
- verifying**
- ACLs, 74, 175
 - DDR configuration, 149
 - EIGRP, 98
 - Frame Relay, 150, 178
 - ISDNs, 147, 177
 - NAT configurations, 110
 - OSPF priorities, 94
 - routes, 90
 - routing protocols, 163-164
 - VLAN configuration, 114-115
- version field (IP packets), 31**
- vertical cross-connects (VCCs), 54**
- viewing**
- cdp-enabled devices, 159
 - Cisco neighboring devices, 159
 - commands, 133
 - configured protocols, 92
 - DHCP, 111
 - flash, 130
 - MAC addresses, 136
 - memory, 36
 - NAT packets, 110
- virtual circuits. *See* VCs**
- Virtual LANs. *See* VLANs**
- virtual private networks (VPNs), 69, 77**
- virtual terminal passwords, 105**
- vlan database command, 114-115**
- VLAN Trunking Protocol. *See* VTP**
- VLANs (Virtual LANs), 113**
- configuring, 113
 - global configuration mode*, 114
 - static commands*, 193
 - subinterfaces*, 117
 - verifying*, 114-115
 - vlan database command*, 114
 - customizing, 116
 - deleting, 115
 - dividing switches into, 70
 - features, 113
 - membership, 70
 - overview, 193
 - static, 70
 - troubleshooting, 161, 199-201
 - trunking, 115
 - VTP**
 - configuring*, 117
 - messages*, 116
 - modes*, 193
 - multicasting*, 116
 - switch modes*, 116
- VLSMs (variable-length subnet masks), 60, 92**
- interfaces, configuring, 93
 - IP address subnets, 61
- VPNs (virtual private networks), 69, 77**
- VTP (VLAN Trunking Protocol), 113**
- configuring, 117, 193
 - messages, 116
 - modes, 193
 - multicasting, 116
 - switch modes, 116
- vty**
- access, restricting, 143
 - configuring, 192
 - lines, controlling, 74
- W**
- WANs (wide-area networks), 69**
- Cisco HDLC encapsulation, 82
 - communication service providers, 43, 78
 - configuring
 - commands*, 197-199
 - PPP encapsulation*, 145
 - connections, 43
 - branch networks*, 81
 - cabling*, 43
 - demarcation points*, 43
 - digital*, 45
 - equipment*, 43
 - HSSI*, 43
 - provider central office*, 43
 - speeds*, 43
 - switched circuits*, 44, 79
 - types*, 77

data communication, 44
 data link layers, 44, 78
 DDR, 45, 147-149
 defined, 69
 designing, 81
 encapsulation, 186
 flat topology, 81
 Frame Relay, 85
 configuring, 149-150
 connections, 85
 inverse ARP messages, 86
 LAN connections, 85
 LMIs, 85
 switches, 44-46, 85
 virtual circuits, 85
 frames, 44
 gateways to LANs, 78
 high-bandwidth/low latency, 81
 internetworks, 71-72, 80
 ISDN
 BRI, configuring, 146
 configuring, 147
 frame fields, 83
 interfaces, 84
 out-of-band signaling, 83
 PRI, configuring, 146
 PRI E1, configuring, 147
 protocols, 83
 reference points, 83-84
 verifying, 147
 packet-switched networks, 44
 phone calls, 44
 physical connections, 77
 physical layers, 44, 78
 PPP
 authentication, 145-146
 enabling, 145
 encapsulation, 145-146
 LCP, 82
 NCP, 82
 session establishment, 82, 190
 protocols, 189, 202
 routers
 connecting, 36
 as WAN devices, 145
 security, 81
 serial communication, 45, 81
 services, 79-80
 three-layer designs, 81
 troubleshooting, 177-178

websites

certificate online support, 207
 Wikipedia, 3

wide-area networks. *See* WANs

Wikipedia website, 3

wildcard masks

ACLs, 73
 subnet masks, compared, 40
WLANS (wireless LANs), 50

X - Y - Z

X.25 WAN service, 80

xmodem command, 130

YAOMC (Yet Another OSI Model Chart), 3-4