



Symbols

- (*, G) common shared tree structure, 232
- (S, G) shortest path tree structure, 232

Numerics

- 56/64-kbps CSU/DSU back-to-back connections, 444
- 802.1Q
 - GVRP
 - configuring, 164
 - dynamic VLAN creation, 165
 - example configuration, 165–166
 - trunking
 - native VLAN switching, 154
 - voice traffic transport, 418
- 802.1X port authentication, configuring, 322–324

A

- abbreviated commands, typing, 7
- access layer, applying QoS to voice traffic, 425–429
- Access layer functionality, 27
- access ports, 145
- accessing
 - modules, 49
 - switch devices
 - authentication, 316–318
 - permit lists, 319–320
 - SSH, 321–322
- ACEs (access control entries), 372, 386
- ACLs, VLAN ACLs, 309
 - COS configuration, 310–311
 - IOS configuration, 311–314
- activating MISTP instances, 185
- active commands, disabling, 10
- adding entries to switching table, 73
- addresses, well-known IP multicast, 473–485
- adjacency table (CEF), 212–215
- AF (Assured Forwarding) service levels, 369
- aggressive mode (UDLD), 179
- aging time (switching table), setting, 74
- alias commands, 58
- applying QoS policies, 395–397

- assigned ICMP type codes, 458–461
- assigned IP protocol numbers, 447–458
- assigning
 - IP management address, 39
 - static switching table entries, 73
 - traffic to QoS policies, 386–392
 - VLAN ports
 - dynamic, 145–148
 - static, 145
 - verifying, 148
- asynchronous back-to-back connections, 443
- ATM LANE (Asynchronous Transfer Mode LAN Emulation), 99
 - configuring, 100–105
 - displaying information, 107
 - example configuration, 105–106
- authentication, 322–324
 - configuring, 316–317
 - example configuration, 318–319
 - RADIUS, 317–318
 - TACACS, 317
- authorization
 - passwords, recovering, 44
 - privileged passwords, 43
 - user-level passwords, 42
- auto trunking mode (COS), 153
- autoconfig, 39
- automatic IP management address assignment, 38

B

- back-to-back connections
 - 56/64-kbps CSU/DSU, 444
 - asynchronous, 443
 - Ethernet, 443
 - T1/E1 CSU/DSU, 445
- backward compatibility, alias commands, 58
- banners
 - character limitations, 37
 - configuring, 36–37
 - example configuration, 37
- BID (bridge ID), 176
- blocking state (STP), 178
- boot parameters, synchronizing, 61–62
- booting
 - from ROM Monitor, 18
 - images from Flash, 57

- BPDUs (bridge protocol data units), 176
 - BPDU Filtering, 195
 - BPDU Skewing, 192
 - TC bit set, 179
- bridged virtual interfaces, configuring, 129–131
 - subinterfaces, 131–132
 - verifying configuration, 133
- broadcast domains, design principles, 30
- broadcast suppression, 299–300
 - configuring, 300–301
 - time-based, 301
 - verifying configuration, 303
- BUS (Broadcast and Unknown Server), 99

C

- cabling, maximum distances, 440–441
- card modules, Supervisor redundancy, 59
- Catalyst 2900MXL series switches, 21
- Catalyst 2950 series switches, 22
- Catalyst 3500XL switches, 21, 169
- Catalyst 3550 series switches, 22
- Catalyst 4000 series switches, 23
- Catalyst 5000 series switches, 22
- Catalyst 6000 series switches, 23
- CDP (Cisco Discovery Protocol), 154
 - configuring, 63–65
- CEF (Cisco Express Forwarding)
 - configuring, 211–213
 - displaying information, 213–215
 - tables, 211–213
- CGMP (Cisco Group Management Protocol), 237
 - configuring, 238
 - displaying information, 239
 - example, 238
- character limitations of banners, 37
- Cisco IOS, 24
 - trunking modes, 152–153
- class maps, QoS, 391–392
- classification of frames
 - Layer 2, 367–368
 - Layer 3, 368–369
- clearing module configurations, 50–51
- closing Telnet sessions, 7
- collapsed core design, 26
- collecting RMON statistics, 343–344
- command history, 7
- command line (IOS), regular expressions, 12–13
- command set (ROM Monitor), 17–19
- commands
 - editing, 5
 - help, 7
 - output, filtering, 11
 - ping, verifying packet reachability, 357–358
 - recalling, 7
 - session, 49, 112
 - set length, 6
 - show modules, 112
 - switchport trunk encapsulation, 153
 - traceroute, router discovery, 358–360
- community string values, configuring SNMP
 - access, 337
- community VLANs, creating, 168
- compact mode (SFM), 514
- config-sync mode (MSFC), 221–225
- configuration mode (IOS), 9
- configuring
 - broadcast suppression, 300–303
 - CDP, 63–65
 - CEF, 211–213
 - CGMP, 238
 - default gateways, 39
 - DNS services, 40–41
 - FlexWAN module, 516–517
 - GMRP, 240–241
 - GVRP, 164
 - dynamic VLAN creation, 165
 - example, 165–166
 - HSRP, 226–227
 - HTTP services, 41
 - IDSM, 496–504
 - IGMP snooping, 234–236
 - IOS Web browser interface, 15–16
 - IP management address, 38–39
 - Layer 2 interfaces
 - ATM LANE, 99–106
 - EtherChannel, 86–92
 - Ethernet, 79–86
 - port selection, 77–78
 - switching table, 73–76
 - Token Ring, 95–98
 - Layer 3 EtherChannels, 117–119
 - Layer 3 Ethernet interfaces, 113–115
 - Layer 3 routing tables, 134–135
 - Layer 3 switching, 112–113
 - MLS, 205–209
 - MSFC
 - config-sync mode, 222–225
 - SRM, 219–220
 - NAM, 504–513

- NDE, 216–217
- packet tracing, 357–358
- passwords
 - privileged, 43
 - user-level, 42
- permit lists, 319–320
- port authentication, 322–324
- port security, 306–308
- power-supply redundancy, 355
- private VLANs, 167–169
- protocol filtering, 303–304
- QoS
 - Catalyst 2900XL/3500XL, 373–374
 - class maos, 391–392
 - congestion avoidance, 398–399
 - data exports, 406–408
 - example, 400–404
 - ingress port queues, 379–381
 - policers, 382–386
 - policies, 386–397
 - port-based traffic classification, 374–379
- RGMP, 242–243
- SFM, 514–515
- SLB, 247–259
 - DFP, 267–268
 - example, 269–273
 - firewall load balancing, 275–290
 - probes, 291–295
 - sticky connections, 259–266
- SNMP, 336
 - access, 337–340
 - example, 344–345
 - notifications, 341–343
 - RMON support, 343–344
- SPAN, 346–347
 - destination port, 347
 - example, 352–354
 - RSPAN, 349–351
 - source, 348–349
- SSH, 321–322
- STP, 181–186, 192–196
- Supervisor Engine
 - banners, 36–37
 - prompts, 35
- switch authentication, 316–317
 - RADIUS, 317–318
 - TACACS, 317
- system time, 66–69
- terminal screen length, 6
- trunking, 151–152
 - encapsulation method, 153–154
 - example, 155–156
 - identifying trunk link, 155
 - removing VLANs from trunk link, 154–155
- VLAN ACLs, 309
 - COS configuration, 310–311
 - IOS configuration, 311–314
- VLANs
 - bridged virtual interfaces, 129–132
 - dynamic port assignment, 145–148
 - example port assignment, 149–150
 - interfaces, 128–133
 - static port assignment, 145
 - verifying port assignment, 148
- voice, 416–421
 - access layer, 425–429
 - core layer, 430–432
 - distribution layer, 430–431
 - IP phone support, 421
- voice modules
 - on Catalyst 4000/4224, 433
 - on Catalyst 6000, 434
- VTP, 140–141, 157–158
 - changing versions, 161
 - example, 162–163
 - modes, 159
 - pruning, 160
 - setting passwords, 158
 - verifying operation, 162
- WAN interfaces, 121
 - FlexWAN, 122–123
 - Gigabit Ethernet, 124–125
 - POS, 125–126
 - VIP2, 121–122
- congestion avoidance thresholds, 398–399
- connections (back-to-back)
 - 56/64-kbps CSU/DSU, 444
 - asynchronous, 443
 - Ethernet, 443
 - T1/E1 CSU/DSU, 445
- connector pinouts, 442
- context-sensitive help, 7, 10–11
- controlling traffic, protocol filtering, 303–304
- COPS (Common Open Policy Service), 410–412
- copying system files, 55–56
- core layer
 - applying QoS to voice traffic, 430–432
 - functionality, 27

COS-based (Catalyst Operating System) switches, 24–25. *See also* IOS-based switches

ATM LANE

- configuring, 99–105
- displaying information, 107
- example, 105–106

commands

- editing, 5
- history, 7

context-sensitive help, 7

EtherChannel

- configuring, 87–92
- displaying information, 94

Ethernet

- configuring, 79–84
- displaying information, 85–86

GVRP

- configuring, 164
- dynamic VLAN creation, 165
- example configuration, 165–166

Layer 2 port selection, 77–78

modes, 4

refreshing input, 6

session timeout values, configuring, 8

STP, configuring, 181–186

syntax checking, 5–6

Telnet sessions, closing, 7

Token Ring

- configuring, 95–98
- displaying information, 98

trunking modes, 152–153

VLANs, creating, 145

VTP off mode, 159

creating

- community VLANs, 168
- isolated VLANs, 168
- private edge VLANs, 169
- traffic policers, 382–386
- VLANs, 140–141
 - example, 144
 - extended range, 143
 - standard range, 142

D

databases, VTP

- configuring, 140–141
- domain name, specifying, 140
- dynamic VLAN configuration, 146–148

date and time, system calendar configuration, 67

debouncing port state changes, 81

default destination port, defining for switching table, 75

default gateways, configuring, 39

default power allocations (voice ports), 417

default VLANs, 145

defining

- QoS policies, 392–395

- switching table default destination port, 75

deleting files from Flash, 54–55

design principles of switched networks, 25–31

designated port election (STP), 176

desirable trunking mode (COS), 153

deterministic frame distribution, 87

DFP (Dynamic Feedback Protocol), 267–268

DHCP (Dynamic Host Configuration Protocol), PHBs, 369

DiffServ (Differentiated Services), 368

disabled state (STP), 178

disabling

- active commands, 10

- DTP on trunks, 152

- HTTP server, 15

- modules, 50

- system logging, 331

discarding packets, 178

displaying

- ATM LANE information, 107

- CEF information, 213–215

- CGMP information, 239

- EtherChannel information, 94

- file systems devices, 51–54

- GMRP information, 241

- HSRP information, 228

- IDSM information, 504

- IGMP snooping information, 237

- installed modules, 49

- IOS terminal sessions, 14

- Layer 2 information, 85–86

- MLS information, 210–211

- module configurations, 50

- MSFC config-sync mode information, 225

- NAM information, 514

- NDE information, 218

- power management information, 355

- QoS information, 405

- QoS management information, 412

- RGMP information, 243

- SFM information, 516

- SLB firewall load balancing information, 291
- SLB information, 274
- SNMP information, 345
- SPAN information, 354
- SRM information, 220
- STP information, 187
- switching table information, 75
- syslog message information, 334
- Token Ring information, 98
- voice module information, 435
- voice port information, 422
- distribution layer
 - applying QoS to voice traffic, 430–431
 - functionality, 27
- DNS (Domain Name System) services,
 - configuring, 40–41
- domain names, VTP, 157
- domains, QoS, 365
- downloading VMPS database files, 147
- drop precedence categories (AF), 369
- DSCP (Differentiated Services Code Point), 369
 - class selector, 369
 - fields, 370
- DTP (Dynamic Trunking Protocol), 152
- dynamic port assignment (VLANs), 145–148
- dynamic pruning (VTP), 160
- dynamic VLAN creation (GVRP), 165

E

- editing
 - commands, 5
 - IOS command line, 10
- EF (Expedited Forwarding) class, 369
- egress scheduling, tuning, 399
- election processes, STP, 176
- enabling trunking, 152
- encapsulation type, specifying on trunks, 153–154
- ending IOS terminal sessions, 14
- environmental monitoring, 356
- errors, COS syntax, 5–6
- ESI (End-System Identifier), NSAP addresses, 100
- EtherChannel, 86–87
 - configuring, 87–92
 - displaying information, 94
 - example configuration, 92
- Ethernet
 - back-to-back connections, 443
 - configuring, 79–84
 - displaying information, 85–86
 - type codes, 485–492
 - VLANs, configurable parameters, 142
- exporting QoS data, 406–408
- extended VLANs, 141
 - creating, 143
 - extending with IRB, 519–522
 - VLAN number ranges, 140
- external routers, 207–209

F

- facility types (syslog servers), 329
- FIB (Forwarding Information Base) table, 211, 215
- fields of DSCP, 370
- file systems
 - aliases
 - alias command, 58
 - deleting files from Flash, 54–55
 - Flash memory, booting images from, 57
 - navigating, 51–54
 - system files, moving, 55–56
- filtering
 - IOS command output, 11–12
 - traffic with VLAN ACLs, 309
 - COS configuration, 310–311
 - IOS configuration, 311–314
- firewalls, SLB load balancing, 275–286
 - displaying information, 291
 - example, 286–290
- fixed mode (GVRP), 164
- Flash memory
 - booting images from, 57
 - removing files, 54–55
- FlexWAN modules
 - configuring, 516–517
 - extended VLANs, enabling, 143
 - interfaces, configuring, 122–123
- flow-through mode (SFM), 514
- forbidden mode (GVRP), 164
- forgotten passwords, recovering, 44
- Forward Delay timer (STP), 192
- Forward Delay interval, adjusting, 193
- forwarding state (STP), 178
- frames
 - deterministic distribution, 87
 - Layer 2 classification, 367–368
 - Layer 3 classification, 368–369

G

- GARP timers, 240
- gateway address, configuring, 39
- GBIC, types of, 439
- Gigabit Ethernet interfaces, configuring, 124–125
- GMRP (GARP Multicast Router Protocol), 239
 - configuring, 240–241
 - displaying information, 241
- group membership, IGMP join requests, 233–234
- GVRP (GARP VLAN Registration Protocol), 164
 - configuring, 164–166
 - dynamic VLAN creation, 165

H

- hardware clock, configuring, 67
- Hello Timer (STP), 192–193
- help command (IOS), 7, 10–11
- help errors (COS), 5–6
- hierarchy of switched networks, 25–27
- high availability, versioning, 62–63
- HSRP (Hot Standby Routing Protocol), 225
 - configuring, 226–227
 - displaying information, 228
 - example, 227–228
- HTTP services
 - configuring, 41
 - disabling, 15

I

- ICMP (Internet Control Message Protocol)
 - type codes, 458–461
- IDS (Intrusion Detection System Module)
 - configuring, 496–504
 - displaying information, 504
 - performing hardware upgrades, 501–502
 - removing from switch chassis, 497
 - service packs, applying, 503
- IEEE 802.1Q, GVRP
 - configuring, 164–165
 - example configuration, 165–166
- IFS (IOS file system), 58
 - deleting files from Flash, 54–55
 - Flash memory, booting images from, 57

- navigating, 51–54
- system files, moving, 55–56
- IGMP Fast-Leave Processing, 234
- IGMP snooping, 233–234
 - configuring, 234–236
 - displaying information, 237
 - example, 236
- images
 - IOS Supervisor Engine, synchronizing, 60–61
 - versioning, 63
- improving STP stability, 179
- ingress port queues (QoS), tuning, 379–381
- in-profile traffic, 372
- installed modules, viewing, 49
- internal DSCP value
 - applying to QoS theory, 366
 - mapping to egress CoS values, 397–398
- IOS-based switches
 - ATM LANE
 - configuring, 99–105
 - displaying information, 107
 - example, 105–106
 - command line
 - editing, 10
 - regular expressions, 12–13
 - command output, searching, 11–12
 - context-sensitive help, 10–11
 - EtherChannel
 - configuring, 87–92
 - displaying information, 94
 - Ethernet
 - configuring, 79–84
 - displaying information, 85–86
 - file system, 51
 - Layer 2 port selection, 77–78
 - password recovery process, 46–48
 - standby Supervisor, forcing changes in, 60
 - STP, configuring, 181–186
 - terminal sessions, 13
 - configuring timeout values, 15
 - displaying, 14
 - ending, 14
 - resuming, 14
 - screen format, 14
 - Token Ring
 - configuring, 95–98
 - displaying information, 98
 - user interface features, 10
 - user modes, 8–9
 - Web browser interfaces, configuring, 15–16

- IP management address
 - configuring, 38–39
 - DNS service configuration, 40–41
 - gateway address, 39
 - HTTP service configuration, 41
- IP multicast, well-known addresses, 473–485
- IP phones, example configuration, 421
- IP port numbers, well-known, 461–473
- IP precedence fields, 370
- IP protocol numbers, well-known, 447–458
- IRB (integrated routing and bridging), extending VLANs, 519–522
- isolated VLANs, creating, 168

J-K-L

- join requests, IGMP, 233–234
- join timer (GMRP), 241
- Layer 2 classification, 367–368
- Layer 2 interfaces
 - ATM LANE
 - configuring, 99–105
 - displaying information, 107
 - example configuration, 105–106
 - EtherChannel, 86–92
 - configuring, 87–92
 - displaying information, 94
 - example configuration, 92
 - Ethernet
 - configuring, 79–84
 - displaying information, 85–86
 - port selection, 77–78
 - switching table
 - assigning static entries, 74
 - configuring aging time, 74
 - displaying information, 75
 - example, 75–76
 - removing entries, 74
 - Token Ring
 - configuring, 95–98
 - displaying information, 98
 - example configuration, 98
- Layer 3 classification, 368–369
- Layer 3 EtherChannels
 - configuring, 117–119
 - verifying configuration, 119–120

- Layer 3 Ethernet interfaces
 - configuring, 113–115
 - verifying configuration, 116
- Layer 3 routing tables
 - configuring, 134–135
 - route verification, 135
- Layer 3 switching, configuring, 112–113
- learning state (STP), 178
- LECS (LAN Emulation Client), 100
- LECS (LAN Emulation Configuration Server), 99
- LES (LAN Emulation Server), 99
- listening state (STP), 178
- load balancing
 - SLB, 245
 - configuring, 247–259
 - DFP, 267–268
 - displaying information, 274
 - example, 269–273
 - firewall load balancing, 275–291
 - probes, 291–295
 - stick connections, configuring, 259–266
 - STP, example, 189, 191
- logging messages, 327–328
 - to syslog server, 328–332
 - displaying information, 334
 - rate-limiting, 333
 - severity level, 333–334
 - severity levels, 329–330
 - time stamping, 332
- "long mode", default port cost, 177–178
- loop detection, STP
 - configuring, 181–186
 - convergence tuning, 192–196
 - displaying information, 187
 - example, 180
 - example of poor root placement, 187
 - improving stability, 179
 - load balancing example, 189–191
 - topology changes, 178–179
 - topology navigation, 196–200
- loop prevention, STP, 175
 - BID, 176
 - BPDU, 176
 - election processes, 176
 - path costs, 177–178
 - port states, 178
 - tiebreakers, 177
- lost passwords, recovering, 44

M

- manual system time configuration, 66–69
- mapping internal DSCP values to egress CoS values, 397–398
- marking
 - Layer 2 frames, 367–368
 - Layer 3 frames, 368–369
- MaxAge timer (STP), 192–193
- memory buffer, setting for system logging, 331
- messages, logging, 327–328
 - to syslog server, 328–334
 - rate-limiting, 333
 - severity level, 333–334
 - severity levels, 329–330
 - time stamping, 332
- microflow policers, 383
- MISTP instance activation, 185
- MLS (Multilayer Switching), 204–205
 - configuring, 205, 207
 - displaying information, 210–211
 - example, 209–210
 - external routers, 207–209
 - flow mask, 206
- modes of operation
 - COS, 4
 - GVRP, 164
 - VTP, 159
- modules
 - accessing, 49
 - configurations, clearing, 51
 - FlexWAN, configuring, 516–517
 - IDSMD, 495
 - configuring, 496–504
 - displaying information, 504
 - removing from switch chassis, 497
 - upgrading, 501–502
 - NAM
 - configuring, 504–513
 - displaying information, 514
 - removing from switch chassis, 508
 - powering on/off, 50
 - resetting, 50
 - SFM
 - configuring, 514–515
 - displaying information, 516
 - viewing configurations, 49–50
- monitoring environmental conditions, 356
- MOTD (Message of the Day) banners, 36–37

- moving system files, 55–56
- MSFC (Multilayer Switch Feature Card)
 - redundancy, config-sync mode, 221–225
 - SRM, 219
 - configuring, 219–220
 - displaying information, 220
- mtu parameter, Ethernet VLAN configuration, 142
- multicast
 - addressing, tree structures, 232
 - CGMP, 237
 - configuring, 238
 - displaying information, 239
 - example, 238
 - GMRP, 239
 - configuring, 240–241
 - displaying information, 241
 - IGMP snooping, 233–234
 - configuring, 234–236
 - displaying information, 237
 - example, 236
 - packets, flooding suppression, 302
 - RGMP
 - configuring, 242–243
 - displaying information, 243

N

- NAM (Network Analysis Module)
 - configuring, 504–513
 - displaying information, 514
 - removing from switch chassis, 508
- name parameter, Ethernet VLAN configuration, 142
- native VLAN (802.1Q) switching, 154
- navigating
 - IFS, 51–54
 - STP topology, 196–200
- NDE (netflow data export), 215
 - configuring, 216–217
 - displaying information, 218
 - example, 218
- nested Telnet sessions, 13
- NetFlow Collector, 218
- network management, SNMP, 335
 - configuring, 336–340
 - displaying information, 345
 - example, 344–345
 - notifications, 341–343
 - RMON support, 343–344

- saving configuration file to TFTP server, 340
- network media
 - connector pinouts, 442
 - maximum cabling distances, 440–441
- nonegotiate trunking mode (COS), 153
- normal mode (UDLD), 179
- normal range, VLAN numbers, 140
- normal registration mode (GVRP), 164
- normal routing table (CEF), 211
- notifications, SNMP
 - defining recipients, 341
 - traps, 342–343
- NSAP addresses, 100

O

- off mode (VTP), 159
- off trunking mode (COS), 153
- on trunking mode (COS), 152
- operating systems, 23
 - backward compatibility, alias commands, 58
 - Cisco IOS, 24
 - COS, 24–25
- out-of-profile traffic, 372

P

- packets, tracing, 357–358, 361
- passwords
 - privileged, configuring, 43
 - recovering, 44–48
 - setting for VTP, 158
 - user-level, configuring, 42
- path costs, STP, 177–178
- pause frames, 81
- permanently deleting files from Flash, 55
- permit lists
 - configuring, 319–320
 - example, 320
- PHBs (per-hop behaviors), 369
- ping command, verifying packet reachability, 357–358
- pinouts, 442
- policers, creating, 382–386
- policies, QoS, 386–390
 - applying, 395–397
 - COPS, 410–412
 - defining, 392–395

- policing traffic, 372
- port authentication, configuring, 322–324
- port-based traffic classification, 374–379
- port numbers, well-known, 461–473
- port security, 306
 - configuring, 306–307
 - example, 308–309
 - verifying configuration, 308
 - violations, 308
- ports (VLAN)
 - dynamic assignment, 145–148
 - Layer 2, selecting, 77–78
 - static assignment, 145
 - example, 149–150
 - verifying, 148
 - trunking, 151–154
- POS interfaces, configuring, 125–126
- power allocations, voice ports, 415–416
- powering modules on/off, 50
- power-supply redundancy, 355
- Prefix field (NSAP addresses), 100
- primary Supervisor, changing backup Supervisor
 - configuration, 60
- private edge VLANs, creating, 169
- private VLANs
 - configuring, 167–169
 - example configuration, 170–172
 - verifying operation, 169
- privileged EXEC mode (IOS), 9
- privileged mode (COS), 4
- privileged passwords
 - configuring, 43
 - recovering, 44
- probes, traceroute, 359–360
- prompts
 - configuring, 35
 - example configuration, 37
- protected ports, creating private edge VLANs, 169
- protocol filtering, 303
 - example, 305–306
 - verifying configuration, 304
- pruning VTP, 160

Q

- QoS (quality of service)
 - capabilities among Catalyst switch
 - families, 367
 - configuring on Catalyst 2900XL/3500XL, 373–374

- congestion-avoidance thresholds, 398–399
- DHCP, PHBs, 369
- DiffServ, 368
- displaying information, 405
- domains, 365
- DSCP fields, 370
- egress scheduling, tuning, 399
- example, 400–404
- exporting data, 406–408
- ingress port queues, tuning, 379–381
- internal DSCP value, 366, 397–398
- Layer 2 classification and marking, 367–368
- Layer 3 classification and marking, 368–369
- management, 409, 412
- network design principles, 30
- policies, 386–390
 - applying, 395–397
 - class maps, 391–392
 - COPS, 410–412
 - defining, 392–395
- policing, 372
- queuing, 371
- traffic classification, port-based, 374–379
- traffic policing, 382–386
- voice traffic, 422–424
 - access layer configuration, 425–429
 - core layer configuration, 430–432
 - distribution layer configuration, 430–431

queuing, 371

R

- RADIUS (Remote Authentication Dial-In User Service), configuring, 317–318
- rate-limiting syslog messages, 333
- reachability, verifying with ping command, 357–358
- recalling commands, 7
- recipients of SNMP notifications, defining, 341
- recovering lost passwords, 44
- redisplaying command input (COS), 6
- redundancy
 - high availability, enabling, 62–63
 - HSRP, 225
 - configuring, 226–227
 - displaying information, 228
 - example, 227–228
 - MSFC
 - config-sync mode, 221–225

- SRM, 219–220
 - of network building blocks, 28–29
 - Supervisor Engine slots, 59
 - synchronizing boot parameters, 61–62
- redundant power supplies, 355
- regular expressions, 12–13
- removing
 - files from Flash, 54–55
 - IDS module from switch chassis, 497
 - NAM module from switch chassis, 508
 - switching table entries, 74
 - VLANs from trunk links, 154–155
- resetting modules, 50
- restricting traffic with VACLs, example, 314–315
- resuming IOS terminal sessions, 14
- RGMP (Router-port Group Management Protocol)
 - configuring, 242–243
 - displaying information, 243
- RMON history statistics, collecting, 343–344
- rollover cables, 443
- ROM Monitor, 16
 - command set, 17–19
 - saving configuration variables, 18
- root bridge election (STP), 176
- root port election, 176
- router discovery, traceroute command, 358–360
- routing tables, configuring, 134–135
- RPF (Reverse Path Forwarding), 212
- RSPAN (Remote SPAN)
 - configuring, 349–350
 - destination port, configuring, 351
 - source, configuring, 350
- RTP (Real-Time Transport Protocol), 423

S

- saving ROM Monitor configuration variables, 18
- scaling trunks, 30
- SCCP (Skinny Client Control Protocol), 423
- screen format, IOS terminal sessions, 14
- searching IOS command output, 11–12
- security
 - firewalls, SLB load balancing, 275–291
 - IDS module, 495
 - configuring, 496–504
 - displaying information, 504
 - performing hardware upgrades, 501–502

- permit lists
 - configuring, 319–320
 - example configuration, 320
 - port authentication, configuring, 322–324
 - port security
 - configuring, 306–307
 - example, 308–309
 - verifying configuration, 308
 - violations, 308
 - SNMP, defining policies, 339–340
 - SSH, configuring, 321–322
 - switch authentication, 316–317
 - example configuration, 318–319
 - RADIUS, 317–318
 - TACACS+, 317
 - VLAN ACLs, 309
 - COS configuration, 310–311
 - IOS configuration, 311–314
- selecting
 - IDSM service packs, 503
 - Layer 2 ports, 77–78
- Selector field (NSAP addresses), 100
- server farms
 - load balancing, 245
 - configuring, 247–266
 - DFP, 267–268
 - SLB, 269–274
 - SLB probes, 291–295
- server mode (VTP), 157
- service contact ports, 462
- service packs (IDSM), selecting, 503
- session command, 49, 112
- session timeout values, configuring, 8
- set length command, 6
- setting switch buffer size, 331
- severity level of syslog messages, setting, 333–334
- SFM (Switch Fabric Module)
 - configuring, 514–515
 - displaying information, 516
- show commands, syntax, 6
- show modules command, 112
- SLB, 245
 - configuring, 247–259
 - DFP, configuring, 267–268
 - displaying information, 274
 - example, 269–273
 - firewall load balancing, 275–286
 - displaying information, 291
 - example, 286–290
 - probes, configuring, 291–295
 - sticky connections, configuring, 259–266
- SNMP (Simple Network Management Protocol), 335
 - access, configuring, 337–340
 - configuration files, saving, 340
 - configuring, 336
 - displaying information, 345
 - example, 344–345
 - notifications, 341–343
 - RMON support, 343–344
- SPAN (Switched Port Analyzer)
 - configuring, 346–347
 - destination port, configuring, 347
 - displaying information, 354
 - example, 352–354
 - RSPAN, configuring, 349–351
 - source, configuring, 348–349
- Spanning Tree MAC reduction, enabling on
 - extended range VLANs, 143
- SRM (single router mode), 219
 - configuring, 219–220
 - displaying information, 220
- SSH (Secure Shell), configuring, 321–322
- SSRP (Simple Server Redundancy Protocol), 100
- standard VLANs, 141–142
- standby Supervisor, system redundancy, 59
- state parameter, Ethernet VLAN configuration, 142
- static port assignment (VLANs), 145
 - example, 149–150
 - verifying, 148
- static switching table entries, assigning, 73
- statistics (QoS), exporting, 406–408
- sticky connections, 259–266
- STP (Spanning Tree Protocol), 175
 - BID, 176
 - BPDU, 176, 179
 - configuring, 181–186
 - convergence tuning, 192–196
 - displaying information, 187
 - election processes, 176
 - example, 180
 - examples, 187
 - improving stability, 179
 - load balancing, examples, 189–191
 - path costs, 177–178
 - port states, 178
 - tiebreakers, 177

- topology changes, 178–179
- topology navigation, 196–200
- STP Root Guard, enabling, 184
- Supervisor Engine
 - banners, configuring, 36–37
 - boot parameter, synchronizing, 61–62
 - forcing changes in backup Supervisor, 60
 - high availability, versioning, 62–63
 - IOS images, synchronizing, 60–61
 - prompts, configuring, 35
 - system redundancy, 59
- suppressing broadcasts, 299–301
 - time-based, 301
 - verifying configuration, 303
- switch authentication
 - configuring, 316–317
 - example, 318–319
 - RADIUS, configuring, 317–318
 - TACACS+, configuring, 317
- switch operating systems, 23
 - IOS-based, 24
 - COS-based, 24–25
- switch ports
 - path costs, “short mode”, 177–178
 - STP states, 178
- switched networks, design principles, 25–31
- switches, booting in rommon mode, 18
- switching table
 - aging time, configuring, 74
 - configuring, 73
 - default destination port, defining, 75
 - displaying information, 75
 - example configuration, 75–76
 - removing entries, 74
- switching VTP versions, 161
- switchport trunk encapsulation command, 153
- synchronizing
 - boot parameters, 61–62
 - IOS images, 60–61
- synchronous logging, 332
- syntax
 - COS-based commands, 5–6
 - show commands, 6
- syslog server, message logging, 328–331
 - displaying information, 334
 - rate-limiting, 333
 - severity levels, 329–330, 333–334
 - to terminal sessions, 331–332
 - time stamping, 332

- system time
 - example configuration, 69
 - manual configuration, 66–69

T

- T1/E1 CSU/DSU back-to-back connections, 445
- TACACS (Terminal Access Controller Access Control Server), configuring, 317
- TCN BPDUs, 178–179
- Telnet
 - closing sessions, 7
 - SSH, configuring, 321–322
- temperature monitoring, 356
- terminal screen length, configuring, 6
- terminal sessions, IOS, 13
 - configuring timeout values, 15
 - displaying, 14
 - ending, 14
 - resuming, 14
 - screen format, 14
- tiebreakers (STP), 177
- time-based broadcast suppression, 301
- time stamping syslog messages, 332
- time zone, configuring, 66
- timeout values, IOS terminal session configuration, 15
- timers
 - GARP, 240
 - STP convergence tuning, 192–196
- token bucket algorithm, 372
- Token Ring
 - configuring, 95–98
 - displaying information, 98
 - example configuration, 98
- topology changes (STP), 178–179
- ToS (Type of Service) byte, 368
- traceroute command, router discovery, 358–360
- tracing packets, 357–358, 361
- traffic
 - broadcast suppression, 299–300
 - configuring, 300–301
 - time-based, 301
 - verifying configuration, 303
 - controlling with protocol filtering, 303–304
 - load balancing, SLB, 245–274
 - out-of-profile, 372
 - policing, 372, 382–386

- QoS policies, 386–390
 - applying, 395–397
 - class maps, 391–392
 - defining, 392–395
- restricting with VLAN ACLs, 309
 - COS configuration, 310–311
 - IOS configuration, 311–314
- transferring system files, 55–56
- traps (SNMP), 342–343
- truncated mode (SFM), 514
- trunking
 - 802.1Q, voice traffic transport, 418
 - configuring, 151–152
 - DTP, disabling, 152
 - encapsulation method, specifying, 153–154
 - example, 155–156
 - identifying trunk link, 155
 - removing VLANs from trunk links, 154–155
 - scaling, 30
 - verifying VLAN port assignments, 155
- VTP
 - changing modes, 159
 - changing versions, 161
 - configuring, 157–158
 - example, 162–163
 - pruning, 160
 - server mode, 157
 - setting passwords, 158
 - verifying operation, 162
- tuning
 - egress scheduling, 399
 - ingress port queues, 379–381
- type codes, Ethernet, 485–492

U

- UDLD (Unidirectional Link Detection), 179
- unicast packets, flooding suppression, 302
- upgrading IDSM hardware, 501–502
- uplink failover of switched networks, 26
- usage errors (COS), 5–6
- user interface features
 - COS-based switches, 4
 - IOS-based switches, 10
- user mode
 - COS-based switches, 4
 - IOS Software, 8–9
- user-level passwords
 - configuring, 42
 - recovering, 44

V

- VACLs, example, 314–315
- verifying
 - broadcast suppression configuration, 303
 - Layer 3 EtherChannel configuration, 119–120
 - Layer 3 Ethernet interface configuration, 116
 - Layer 3 routing table routes, 135
 - port security, 308
 - private VLAN operation, 169
 - STP operation, 196, 198–200
 - VLAN interface configuration, 133
 - VLAN port assignments, 155
 - VTP operation, 162
 - WAN interface configuration, 126
- versioning Supervisor Engine, 62–63
- versions of VTP, switching, 161
- viewing
 - ATM LANE information, 107
 - CEF information, 213–215
 - CGMP information, 239
 - EtherChannel information, 94
 - file system devices, 51–52, 54
 - GMRP information, 241
 - HSRP information, 228
 - IDSM information, 504
 - IGMP snooping information, 237
 - installed modules, 49
 - Layer 2 information, 85–86
 - MLS information, 210–211
 - module configurations, 50
 - MSFC config-sync mode information, 225
 - NAM information, 514
 - NDE information, 218
 - QoS information, 405
 - QoS management information, 412
 - RGMP information, 243
 - SFM information, 516
 - SLB information, 274
 - SNMP information, 345
 - SPAN information, 354
 - SRM information, 220
 - STP information, 187
 - switching table information, 75
 - Token Ring information, 98
 - voice module information, 435
 - voice port information, 422
- VIP2 WAN interfaces, configuring, 121–122
- VLAN database mode (IOS), 9

VLANs (virtual LANs)

- ACLs, 309
 - COS configuration, 310–311
 - IOS configuration, 311–314
- creating, 140–141
 - example, 144
 - for COS devices, 145
- Ethernet, configurable parameters, 142
- extended range, creating, 143
- extending with IRB, 519–522
- interfaces
 - bridged virtual interfaces, configuring, 129–131
 - configuring, 128–129
 - example configuration, 133
 - subinterface configuration, 131–132
 - verifying configuration, 133
- ports
 - dynamic assignment, 145–148
 - static assignment, 145
 - verifying assignment, 148
- private edge VLANs, creating, 169
- private VLANs
 - configuring, 167–169
 - example configuration, 170–172
 - verifying operation, 169
- standard range, creating, 142
- trunking
 - configuring, 151–152
 - example, 155–156
 - identifying trunk link, 155
 - removing VLANs from trunk link, 154–155
 - specifying encapsulation method, 153–154

VTP

- changing versions, 161
- configuring, 140–141, 157–158
- example configuration, 162–163
- modes, 159
- pruning, 160
- server mode, 157
- setting passwords, 158
- verifying operation, 162

VMPS (VLAN Membership Policy Server)

- client configuration, 147–148
- server configuration, 147

voice

- access layer configuration, 425
- configuring, 416–421
- IP phone support, example, 421

- over 802.1Q trunks, 418
- QoS, 422, 424
 - access layer configuration, 425–429
 - core layer configuration, 430–432
 - distribution layer configuration, 430–431

voice modules

- Catalyst 4000 access gateway, configuring, 433
- Catalyst 6000, configuring, 434
- displaying information, 435

voice ports

- displaying information, 422
- power allocations, 415–416

VTP (VLAN Trunking Protocol)

- configuring, 140–141, 157–158
- domain names, specifying, 140, 157
- example configuration, 162–163
- modes, 159
- off mode (COS), 159
- pruning, 160
- server mode, 157
- setting passwords, 158
- verifying operation, 162
- versions, changing, 161

W

WAN interfaces

- configuring, 121
- example configuration, 126–127
- FlexWAN, configuring, 122–123
- Gigabit Ethernet, configuring, 124–125
- POS, configuring, 125–126
- verifying configuration, 126
- VIP2, configuring, 121–122

Web browser interface, configuring, 15–16

well-known numbers

- Ethernet type codes, 485–492
- ICMP type codes, 458–461
- IP multicast addresses, 473–485
- IP port numbers, 461–473
- IP protocol numbers, 447–458

X

- XOR (exclusive-OR) operation, 87