



# INDEX

## Symbols

- <> (angle brackets), command parameter syntax, 43
- [ ] (square brackets), command parameter syntax, 43
- ? (question mark)
  - BPX CLI help system, 420–422
  - IGX CLI help system, 44–45

## Numerics

- 1-to-N redundancy, 785
- 7/8 embedded coding, 153
- 8/8 inverted coding, 153

## A

- AAL2 multiplexing, 1059
- ABR (Available Bit Rate), 244, 363, 566, 940–941, 1003, 1011. *See also* ABRFST; ABRSTD;  
Foresight
  - characteristics, modifying, 1022–1023
  - configurable parameters, 943–944
  - congestion, 944–945
    - monitoring, 1012
    - potential locations for, 942
  - ForeSight, 1009
  - on UXM cards, 259
  - policing, 580
  - rate adjustments, 942–943
  - RM cells, 941–942
  - standard, 587–588
  - traffic policing, 251, 254
  - VC queuing, 254
- ABRFST
  - characteristics, 1010
  - configurable parameters, 621
  - congestion
    - criteria for, 1008–1010
    - monitoring potential locations, 1009
  - parameters, 266
  - rate adjustments, 260–261, 605–607
  - RM cell, 604–605
  - versus ABR Standard, 604
- AC power supply, IGX switches, 23
- access lines
  - activating, 495–496
  - deactivating, 496
  - statistical alarms, clearing, 704
- accessing
  - BPX CLI
    - with auxiliary port, 412
    - with control port, 411–412
    - with IP Relay, 413
    - with LAN port, 413
  - IGX CLI, 39
    - with auxiliary port, 40
    - with control port, 39
    - with LAN port, 40
  - MGX CLI, 732–733, 767
  - RPM CLI, 1108
- acquisition of Stratacom, Inc., 6
- activating
  - ATM ports, 238, 550–551
  - downed connections, 303
  - Frame Relay ports, 188
  - lines, 490
    - IGX, 87–88
    - on MGX service modules, 811
    - on PXM1, 800
  - logical Frame Relay ports, 192–193
  - physical Frame Relay ports, 192–193
  - ports
    - on AUSM, 983–984
    - on BXM card, 545
    - trunks, 474–476, 486–487
  - active control templates, 192
  - actual trunk loading versus expected, 286
  - adaptive clocking, 882
  - Adaptive Differential Pulse Code Modulation, 103–104
  - Adaptive VAD, 117
    - configuring, 118

addapsln command, 515, 521, 841  
addcdred command, 521  
addcid command, 1085–1086  
addcon command, 106–112, 144–145, 224–225,  
    262–268, 616–617, 866–868, 888–889, 949–950,  
    1016, 1025, 1132  
added trunks, 66  
addendpt command, 1079–1080  
addextlp command, 348, 355  
addimagr command, 984  
adding  
    ATM-Frame Relay connections, 278–279  
    connections  
        BME, 613  
        CBR, 262–264  
        data connections, 144–145  
        Frame Relay, 224–225  
        to AUSM card, 1038–1040  
        to MGX 8850-PXM45, 875–876  
        to PXM1 card, 1025, 1038–1042  
        UBR, 268  
        VBR, 264–267  
    feeder nodes  
        to BPX networks, 830  
        to MGX networks, 831–832  
gain to voice circuits, 121  
lines to MGX service modules, 818–819  
trunks, 474–475  
    between nodes, 481  
    IGX, 67  
users to network, 435  
voice connections, 106–108, 111–112  
    to VISM, 1082  
addjob command, 318–319  
addjobtrig command, 324–325  
addln command, 800, 811, 822  
addloclp command, 346–347, 721  
addport command, 538–539, 769, 885, 919,  
    983–984, 990–991, 1076  
addrd command, 786  
addressing, multicast, 615  
addrmtlp command, 347–348, 354, 721  
addrscprtn command, 1077  
addtrk command, 58, 67, 474–475, 481  
adduser command, 773  
addyred command, 28  
adjusting VC queues, 216  
ADPCM (Adaptive Differential Pulse Code  
    Modulation), 103–104  
alarms, 329, 687  
    ATM port failures, displaying, 552  
    BPX, resolving, 691–699  
    bus alarms, 331, 709  
    card alarms, 330, 708  
    clearing, 314  
    connection alarms, 333, 709  
    displaying counts of, 313  
    event logging, 694–695  
    identifying, 329  
    line alarms, 332  
        resolving, 701  
        summarizing historical statistical errors,  
            702–703  
    local, locating, 705  
    major, 329, 688  
    minor, 329, 689  
    multicast connection, 710–711  
        monitoring, 711  
    port, 332  
    remote, locating, 706–707  
    slots  
        statistical alarm thresholds, 720  
        troubleshooting, 717  
    statistical error counters, clearing, 697  
    status monitor,  
        configuring, 440–441  
        displaying, 439–440  
    summary information, displaying, 684–685  
    trunk alarms, 332, 690  
        displaying configuration, 691–692  
        resolving, 699–700  
        statistical thresholds, 692  
    types of failures reported, 688  
    unreachable nodes, 689  
allocating  
    bandwidth, statistical reserve, 650–652  
    controller resources, 469  
        card-level, 470  
        port-level, 470  
    PVCs for ports, 539  
angle brackets (<>), command parameter syntax, 43

APS (Automatic Protection Switching), 368, 501  
 automatic operation, 505  
 basic operation, 501  
 cards  
   adding line pairs, 521  
   adding redundancy, 521  
   displaying, 520  
   line configuration, 522  
   switching lines, 522  
 configuring, 510  
 directional switching mode, 510  
 implementing on BPX, 506  
 K1K2 protocol, 506  
 manual operation, 505  
 revertive switching, 510  
 verifying operation, 518–520  
 version 1+1, implementing on BPX, 508,  
   511–513  
 versions, 502–504  
 versus Y-cable redundancy, 509  
 APS 1+1 Annex B, implementing on BPX  
   networks, 508  
 arbiter polling, 392–393  
 ARM (Alarm Relay Module) front card, 21  
 ASM (Alarm/Status Monitor) card, 378–379  
   parameters, configuring, 429  
 assigning  
   names  
     to BPX nodes, 441–442  
     to IGX nodes, 55–56  
     port number to AUSM port, 983–984  
 Asynchronous status field (dsport command output), 195  
 asynchronous update mode, 185  
 AT&T, Frame Relay network meltdown, 8–9  
 ATM (Asynchronous Transfer Mode), 27  
   ABR connections, 1011  
     monitoring potential congestion, 1012  
     VC queueing, 254  
 AUSM cards  
   adding connections, 1038–1040  
   configuration example, 1014  
   port configuration, 1000  
   QBins, 975–976  
   traffic flow, 977–978  
   VC queues, 977, 1012

BPX  
   closed-loop congestion avoidance, 402  
   commbus, 391–392  
   connections, 362, 861  
   crosspoint switch, 389–390  
   FBTC, 401  
   functions, 371–372  
   lines, 362  
   network types, 369–370  
   product family, 361–362  
   QoS, 402  
   queuing architectures, 403–404  
   reliability, 368–369  
   service types, 363–366  
   SES, 371  
   system hardware, 372–392  
   system software, 394–399  
   trunks, 362  
   UPC, 400  
 cell relay switching, 366–367  
 cells  
   CLP, 533  
   format, 365  
   payloads for IGX networks, 61  
   transmission over framed trunks, 63  
   transmission over unframed trunks, 63  
 Cisco BPX 8600 switch, 8  
 connections, 243, 563, 1001–1002  
   ABR, 259, 566  
   ABRFST, 604–605  
     rate adjustment, 605–607  
   CBR, 566  
   configurable parameters, 617–618  
   creating on AUSM, 1016  
   displaying channel status, 1028–1029  
   establishing, 628–630  
   feeder, 1002  
   gateways, 274–276  
   local, 1002  
   modifying CBR characteristics, 1021  
   monitoring, 630–635  
   policing, 245–254  
   segments, 256  
   standard ABR, 256–258  
   statistics monitoring, 635–643  
   UBR, 566  
   VBR, 566

- CoS, 1003
  - CBR example, 1007
  - ForeSight, 1008–1010
  - VBR example, 1008
- encapsulation, 276
- endpoints, 856
- Frame Relay interworking, 34, 270–271, 608
  - SIW, 273–275
- ILMI
  - configuration information, displaying, 987–988
  - historical statistics counters, displaying, 998–999
  - enabling, 991
- IMA, 975
  - group characteristics, modifying, 984
  - groups, creating, 984
- IMA trunks, 63
- interworking
  - NIW, 928
  - SIW, 929–930
- lines, configuring, 804
- MGX 8850-PXM45 connection types, 861
- MPLS, 8
- packet flow on IGX switches, 34
- ports, 973
  - activating, 238, 550–551
  - characteristics, displaying, 237
  - configuring, 239–240, 550–551
  - deactivating, 550–551
  - deleting, 550
  - detailed information, displaying, 238
  - device compatibility, configuring, 540–541
  - egress queue thresholds, displaying, 241
  - failures, troubleshooting, 552–558
  - IMA, 974
  - physical versus virtual, 531
  - queue configuration, displaying, 548–549
  - queue depth, modifying, 242
  - statistics, displaying, 553–555, 993–997
  - status, displaying, 980–983
  - summary information, displaying, 979–980
- PXM1 cards
  - adding connections, 1038–1042
  - port configuration, 1000
- services, 568
  - ABR policing, 580
  - CBR policing, 574–575
  - time-based policing, 574
  - UBR policing, 581–582
  - VBR policing, 576–580
- signaling protocols, 239, 535–536
  - ILMI, 537
  - LMI, 536–537
    - statistics, displaying, 555–556
  - timers, modifying, 989
- traffic policing, 1004–1006
- traffic management, 567
  - CAC, 568–569
  - traffic control, 567
  - traffic shaping, 570
  - UPC, 569
- traffic shaping, 534
  - implementing, 534–535
  - port level, 535
  - virtual ports, 530
  - virtual trunks, 465–466
- ATM card group, Cisco IGX switches, 23
- atm pvc command, 1128
- AUI (Attachment Unit Interface), LAN port, accessing IGX CLI, 40
- AUSM cards, 750
  - connections
    - adding, 1016
    - creating, 1038–1040
  - ports
    - activating, 983–984
    - configuring, 1000
- QBins, 975–976
- traffic flow
  - egress ATM traffic, 978
  - ingress ATM traffic, 977–978
- VC queues, 977, 1012
  - characteristics, 1014
  - configuration example, 1014
  - frame-based traffic control, 1012
- automatic fault management, 369
- automatic operation, APS, 505
- Automatic Routing Management, PVC resource partitioning, 491

AutoRoute routing, 7  
 BPX switches, 395  
 determining potential connection routes, 646–647  
 auxiliary ports  
 BPX  
   CLI, accessing, 412  
   configuration, displaying, 450  
   external device window, 452–453  
   print modes, configuring, 451–452  
 data transmission parameters, configuring, 430–431  
 IGX  
   CLI, accessing, 40  
   configuring, 51–52  
   listing functions of, 52–53  
   port functions, configuring, 432–433  
 average utilization rate  
   data channels, configuring, 162  
   voice channels, configuring, 117  
 AXSM card, removing connection endpoints, 869

## B

---

back cards  
 IGX switches, 20  
 RPM, 745  
 summary information, 45–47  
 UFM-U  
   active ports, displaying, 201  
   mode, displaying, 200  
   mode, selecting, 201–202  
 bandwidth  
   allocating on trunks, 650  
   connection load, calculating, 653  
   managing on Cisco IGX switches, 30  
   of NTM trunks, calculating, 64  
   of UXM trunks, calculating, 64  
   statistical reserve, 288, 650–652  
 BCC (Broadband Controller Card), 375–376  
   back cards, 376–377  
   functions, 377–378  
 BdataA queues, 215  
 BdataB queues, 215

BERTs  
   results, reporting, 817–818  
   running on MGX service modules, 815–817  
 BGP (Border Gateway Protocol)  
   APS, verifying operation, 518–520  
 bit conversions  
   receive, configuring, 137–138  
   transmit, configuring, 139  
 bit error correction, ZCS, 152  
 BITS (Building Integrated Timing Supply), 305, 671  
 BME (Broadband Multicast Engine), 384–386  
   adding connections, 613  
 BNI (Broadband Network Interface)  
   arbiter polling, 392–393  
   BPX switches, 386–392  
 boot Flash (RPM), 1107  
 boot images, storing, 1107  
 boot system command, 1115  
 BOP (Bit-Oriented Protocol) frame structure, 217–219  
 BPX switches  
   8600 series switches, 10  
   administrative access, 367  
   alarms, 687  
     locating, 705–707  
     major, 688  
     minor, 689  
     unreachable nodes, 689  
 APS  
   adding card redundancy, 521  
   adding line pairs, 521  
   automatic operation, 505  
   basic operation, 501  
   cards, displaying, 520  
   configuring, 510  
   implementing, 506–508  
   K1K2 protocol, 506  
   line configuration, 522  
   manual operation, 505  
   switching lines, 522  
   versions, 502–504  
   versus Y-cable redundancy, 509  
 ATM  
   ABRFST, 604–605  
   cell-based switching, 366–367  
   cell format, 365  
   connections, 861

- rate adjustment, 605–607
  - standard ABR, 591–592, 595–604
  - auxiliary ports, external device window, 452–453
  - bus architecture, 388–389
  - BXM card module, 380–381
    - ports, activating, 545
  - cards
    - line support, 488
    - trunk support, 464
  - CLI
    - accessing with auxiliary port, 412
    - accessing with control port, 411–412
    - accessing with IP Relay, 413
    - accessing with LAN port, 413
    - command entry modes, 416
    - command privilege levels, 416
    - command structure, 415
    - command syntax, 413–414
    - editing, 423
    - help system, 420–422
    - keyboard shortcuts, 419
    - logging out, 423
    - menu-driven interface, 416
    - repeating commands, 422–423
    - screen information, 418
  - commands
    - addapsln, 515
    - cnfapsln, 516–517
    - delapsln, 518
    - dspapsln, 516
    - dsplog, 518
    - precedence rules, 523–524
    - switchapsln, 517–518
  - commbus, 391–392
  - common core card group, BCC, 375–378
  - concurrent routing, 649
  - connections, 362
    - required load, calculating, 652
  - crosspoint switch, 389–390
  - date/time, configuring, 443–445
  - directed routes, 648
  - environmental measurements,
    - alarm conditions, 690
  - FBTC, 401
  - feeder nodes, adding, 830
- functions, 371–372
  - initial configuration
    - adduser commands, 425
    - cnfasm commands, 429
    - cndate commands, 430
    - cnflan commands, 433
    - cnfname commands, 429
    - cnfnwip commands, 434
    - cnfpwd commands, 426
    - cnfterm commands, 430
    - cnftermfunc commands, 432–433
    - cnftime commands, 430
    - cnftmzn commands, 430
    - commands, 423–424
    - dspcd commands, 428
    - dspcds commands, 427–428
    - dspnds commands, 430
    - dsppwr commands, 428
  - IP addressing schemes
    - configuring, 453–456
    - LAN port, 455–456
  - line alarms, resolving, 701, 704–705
  - lines, 362
  - logging in, requirements, 417
  - network synchronization, 671
    - carrier network timing, 671
    - clock sources, 672
    - example, 674, 677–679
    - guidelines, 680–686
    - selecting clock sources, 673
  - network types, 369–370
  - network-assigned routes, 647
  - nodes
    - assigning names, 441–442
    - displaying, 442–443
    - IP relay addresses, listing, 457
    - names, verifying, 442
  - polling, 392–393
  - ports, 529
    - physical versus virtual, 531
  - preferred routes, 648
  - print modes, configuring, 451–452
  - printer configuration, displaying, 451
  - priority bumping, 649
  - product family, 361–362
  - reliability, 368–369

- serial ports
    - communications parameters, configuring, 446–448
    - functions of, 446–447
  - service types, 363
    - QoS parameters, 364–366
  - SES PNNI Controller, 371
  - slot errors, 690
  - system data, monitoring, 436–439
  - system hardware, 372
    - BNI, 386–392
    - card groups, 374–385
    - chassis, 373
  - system software, 394
    - AutoRoute, 395
    - CAC, 399
    - MPLS, 397–399
    - NOS, 394
    - PNNI, 396
    - VSI, 395
  - terminal port configuration, displaying, 448–449
  - tiered networks, 735
  - time/date, configuring, 443–445
  - traffic management
    - closed-loop congestion avoidance, 402
    - QoS, 402
    - queueing architectures, 403–404
  - traffic shaping, 534
    - implementing, 534–535
    - port level, 535
  - trunks, 362, 464
    - alarms, 690–700
    - physical errors, 690
  - UPC, 400
  - users, adding to network, 435
  - virtual ports, 530
  - virtual trunks, 467
  - VSI controllers, 468–469
  - BRM (backward RM), 1011
  - building data FastPackets, 143
  - bursts
    - handling, 288, 650–652
    - signaling delay, 126
  - bus alarms, 331, 709
  - BXE cards, line support, 488
  - BXM (Broadband Switch Module) card module, 380–381
    - APS 1+1, implementing, 511–513
    - BME, 384–386
    - channels, statistics levels, 633
    - configurable parameters, 478–481
    - enhanced models, 382–383
    - FBTC, implementing, 584–586
    - line support, 488
    - ports
      - activating, 545
      - creating, 538
      - queues, 532
    - standard ABR
      - implementing, 598–601
      - rate adjustments, 601, 604
      - statistics level, verifying, 635–643
    - trunk errors, 697
    - trunk support, 464
    - VI, 532
    - QBins, 466–467
  - bye command, 423, 485
- 
- ## C
- 
- CAC (Connection Admission Control), 568–569
  - BPX switches, 399
  - calculating
    - connection load, 653
      - on BPX connections, 652
    - ER, 596
    - NTM trunk capacity, 64
    - UXM trunk capacity, 64
  - call agents (VISM), VoIP mode, 1065–1067
  - capacity calculations, NTM/UXM trunks, 64
  - CAPC (Congestion Avoidance using Proportional Control), 596
  - card alarms, 330
  - card groups
    - BPX switches, 374–385
    - for routing trunks, 60
  - Card Type field (dspport command output), 197
  - card-level resource partitions (MGX), 776–777
  - cards
    - alarms, 708
    - ASM, configuring parameters, 429

- AXSM, removing endpoints, 869
- BPX**
- trunk support, 464
  - verifying installation, 436–439
- BXM**
- configurable parameters, 478–481
  - FBTC**, 584–586
  - line support, 488
  - port queues, 532
  - resource allocation, 470
  - standard ABR, implementing, 598, 601
  - standard ABR, rate adjustments, 601, 604
  - statistics level, verifying, 635–643
  - trunk support, 464
  - VIIs, 466–467, 532
- CVM**, voice connection types, 107
- data faceplate**, 356
- FRM**, 180
- FRSM-2CT3**, displaying broadband line configuration information, 810
- hardware**, resetting, 723
- IGX**
- state descriptions, 46–47
  - status, displaying, 47–48, 236–237
- MGX**, high-speed, 752
- PXM1 processor card**, 737–738
- back card, 738–740
  - functions, 741
- reserved slots**, 427
- RPM**, 745
- functions, 744
  - memory locations, 1107
  - port numbering, 1107
- slots**
- errors, 690, 717
  - historical statistical errors, summarizing, 718–719
  - statistical alarm thresholds, 720
- SRM card**, 741–743
- functions, 743–744
- statistics**, displaying, 427–428
- UFM**, 180
- leaky bucket policing, 213–214
- UVM**
- Fax Relay, 109
  - line pass-through state, displaying, 111
  - voice connection types, 108
- UXM**
- ABR**, 259
  - supported ATM connections, 244
- VISM**, clocking options, 1070–1073
- carrier network timing**, 671
- clock sources, 672–673
  - IGX**, 305
- CAS (Channel Associated Signaling)**, 125
- Cascade**, 6
- CBR (Constant Bit Rate)**, 566, 1003
- characteristics, modifying, 1021
  - configurable parameters, 618
  - connections, adding, 262–264
  - example, 1007
  - policing, 248, 574–575
  - characteristics, modifying, 1030
- CCS (Common Channel Signaling)**, 125
- CDVT (Cell Delay Variation Tolerance)**, 364, 883, 1005
- time-based model, 1007
- cell delay**, 364
- Cell Delay Variation Tolerance**, 364, 883, 1005
- cell loss**, 364
- cell loss priority (CLP)**, 210
- cell rate**, 364
- Cellbus (Cisco IGX switches)**, 30–31
- cells (ATM)**, 365–367
- AUSM traffic flow**
    - egress traffic, 978
    - ingress traffic, 977–978
- CLP (Cell Loss Priority)**, threshold level, 533
- payloads for IGX networks**, 61
- traffic shaping**, 534
- implementing, 534–535
  - port level, 535
- transmission over unframed trunks**, 63
- CESM (Circuit Emulation Service Module)**, 748–749
- circuit emulation ports, listing, 886
  - circuit emulation services, creating, 897–899
  - egress queues, 882–884
  - historical channel statistics counters, listing, 896–897
  - ingress traffic, 883
  - ports, displaying configuration information, 887
- changing BPX CLI passwords**, 426

- Channel Associated Signaling, 125
- Channel Range field (dsport command output), 197
- Channel Speed field (dsport command output), 197
- channelized narrowband FRSMs, 908
- channels, 564
  - listing on PXM1 UNI ports, 1027–1028
  - statistics levels, 633
  - utilization, 285
- characteristics
  - of ABR, modifying, 1022–1023
  - of CBR, modifying, 1021, 1030
  - of connections, 285–286
    - data connections, 143
  - of ForeSight, modifying, 1020
  - of ingress VCs
    - modifying, 1024
    - queues, 1032
  - of leaky bucket models, 1005
  - of QBins, 975–976
    - modifying, 987
  - of UBR, modifying, 1032
  - of VBR, modifying, 1021–1022, 1031
  - of VC queues, 254, 1014
- chassis, BPX switches, 373
- CIDs
  - adding to connections, 1085–1086
  - displaying for specified LCN, 1086
- circuit emulation connections, 879
  - clocking modes, 882
  - configuring, 893–894
  - deleting, 888–889
  - detailed status, displaying, 891–893
  - signaling, 880
  - testing, 894–896
- circuit emulation ports, 876
  - creating, 885
  - listing on CESM, 886
- Cisco BPX 8600 switch. *See* BPX switches
- Cisco IGX switches, 15
  - 8410 rack-mount chassis, 16–17
    - standalone system, 16
  - 8420 standalone chassis, 17–19
  - 8430 standalone chassis, 19–20
  - ATM card group, 23
  - back card, 20
  - bandwidth management, 30
  - Cellbus, 30
- data card group, 22
- fault management, 29
- Frame Relay card group, 22
- front card, 20
- lanes, 31
- lines, 25
- message formats, 25–27
- NPM card redundancy, 28
- packet flow
  - ATM, 34
  - data packets, 32
  - Frame Relay, 33
  - voice packets, 31
- power supplies, 23
- processor card group, 21
- trunk card group, 21
- trunks, 24
- voice card group, 22
- Y-cable redundancy, 28
- Cisco WAN Manager, 733
- clearing
  - alarms, 314
  - BPX CLI display information, 421
  - clock alarms, 685
  - event log, 695
  - Frame Relay connection statistics, 231–232
  - Frame Relay port statistics, 206–207
  - statistical error counters, 697
- CLI (command-line interface)
  - BPX**
    - accessing with auxiliary port, 412
    - accessing with control port, 411–412
    - accessing with IP Relay, 413
    - accessing with LAN port, 413
    - clearing display information, 421
    - command entry modes, 416
    - command privilege levels, 416
    - command structure, 415
    - command syntax, 413–414
    - editing, 423
    - help system, 420–422
    - keyboard shortcuts, 419
    - logging in, 417
    - logging out, 423
    - menu-driven interface, 416
    - monitoring ATM channel statistics, 630
    - repeating commands, 422–423
    - screen information, 418

- IGX
  - accessing, 39–40
  - CLI shortcuts, 42
  - command syntax, 43
  - direct entry, 43
  - menu-driven interface, 44
  - privilege levels, 43
  - screen display, 41
- MGX, 732–733
  - error messages, 772
  - login process, 775
- RPM
  - accessing, 1108
  - changing configuration file, 1109–1110
  - entering commands, 1109
  - modes, 1108
- CLLM status /x Timer field (dsport command output), 197
- clocking
  - BITS, 305
  - data channels, 171
    - isochronous data clocking, 172–173
    - looped clocking mode, 172
    - normal clocking mode, 172
    - split clock mode, 172
  - network synchronization, 671
    - carrier network timing, 671
    - clock sources, 672
      - example, 674, 677–679
      - guidelines, 680–686
      - selecting clock sources, 673
  - on VISM, 1070–1071
    - configuring, 1072–1073
  - reference selection, 308–309
  - sources, 305–307
    - alarms, clearing, 314
    - listing, 309
    - network-wide, specifying, 311–313
    - stability, 671
  - clocking field (dsport command output), 194
  - closed-loop congestion-avoidance, 402
  - CLP (cell loss priority), 210
    - tagging on UBR connections, 253
    - threshold level, 533
  - clrchstats command, 231, 634
  - clrcblkalm command, 314, 685
  - clrlnalm command, 344, 704
  - clrlnerrs command, 332, 704
  - clrllog command, 329, 336, 695
  - clrportstats command, 206–207, 557
  - clrrtkalm command, 332, 339, 698
  - clrrkerrs command, 332, 697
  - cnfapsln command, 516–517, 522, 841–842
  - cnfasm command, 429, 440–441
  - cnfatmcls command, 627, 628
  - cnfbert command, 815–817
  - cnfbus command, 331
  - cnfcdap command, 510
  - cnfchadv command, 118
  - cnfchanbrparams command, 956
  - cnfchanegressq command, 957
  - cnfchaneir command, 955
  - cnfchanfst command, 956, 1020
  - cnfchaningressq command, 957
  - cnfchanmap command, 957
  - cnfchanpol command, 955
  - cnfchanq command, 1024, 1032
  - cnfchdfm command, 159
  - cnfchdl command, 128
  - cnfchec command, 124
  - cnfchfax command, 119–120
  - cnfchgn command, 121
  - cnfchpri command, 228–229
  - cnfchutl command, 116–117, 285
  - cnfccls command, 311–313, 683–684
  - cnfccls command, 221–224, 269
  - cnfcon command, 225–226, 269, 628, 870, 893–894
  - cnfconbrparams command, 1022–1023
  - cnfcond command, 135–136
  - cnfcos command, 301, 661
  - cnfdate command, 50, 445–446
  - cnfdelk command, 173
  - cnfifastrk command, 807
  - cnfilmi command, 989–991
  - cnfimagr command, 984
  - cnflan command, 433, 455–456
  - cnfln command, 58, 89–90, 493–495, 800–802, 811–812
  - cnflnaln command, 332, 342–343, 693–694
  - cnflnpass command, 109–110
  - cnflnsig command, 1078
  - cnfmode command, 201–202
  - cnfname command, 55–56, 442, 782
  - cnfnwip command, 434, 456

cnfpass command, 774  
 cnfport command, 190–192, 239–240, 536,  
   540–541, 920  
     ILMI parameters, 544  
     LMI parameters, 543–544  
       parameters, 541–543  
 cnfportcllm command, 921  
 cnfportq command, 242, 535  
 cnfportrscprtn command, 806  
 cnfpref command, 297–300, 661–662  
 cnfppt command, 53–54, 451–452  
 cnfpwd command, 49  
 cnfrcvsig command, 137–138  
 cnfrsrc command, 491, 539  
 cnfrtcost command, 300, 663  
 cnfterm command, 51–52, 449  
 cnftermfunc command, 432  
 cnftime command, 50  
 cnftmn command, 51, 443–444  
 cnfrtk command, 58, 69–70, 477  
 cnfrtkalm command, 338, 699  
 cnfupcabr command, 1022  
 cnfupccbr command, 1021, 1030  
 cnfupcrtvbr command, 1022  
 cnfupcubr command, 1022, 1032  
 cnfupcvbr command, 1021–1022, 1031  
 cnfvchtp command, 130–132  
 cnfvismmode command, 1076  
 cnfxmstsig command, 138–139  
 coding data FastPackets, 153  
 commands, 430  
     addapsln, 515, 521, 841  
     addcid, 1085–1086  
     addcon, 106–108, 111–112, 144–145, 224–225,  
       262–268, 616–617, 866–889, 949–950, 1016,  
       1025, 1132  
     addcred, 521  
     addendpt, 1079–1080  
     addextlp, 348, 355  
     addimagr, 984  
     addjob, 318–319  
     addjobtrig, 324–325  
     addln, 800, 811, 822  
     addloclp, 346–347, 721  
     addport, 538–539, 769, 885, 919, 983, 984,  
       990–991, 1076  
     addressed, 786  
     addrmtlp, 347–348, 354, 721  
     addrscprtn, 1077  
     addtrk, 58, 67, 474–475, 481  
     adduser, 773  
     addyred, 28  
     atm pvc, 1128  
     boot system, 1115  
     bye, 423  
     clrchstats, 231, 634  
     clrelkalm, 314, 685  
     clrlnalm, 344, 704  
     clrlnerrs, 332  
     clrlog, 329, 336, 695  
     clrnerrs, 704  
     clrportstats, 206–207, 557  
     clotrkalm, 332, 339, 698  
     clotrkkerrs, 332, 697  
     cnfapsln, 516–517, 522, 841–842  
     cnfasm, 429, 440–441  
     cnfatmcls, 627–628  
     cnfbert, 815–817  
     cnfbus, 331  
     cnfchadv, 118  
     cnfchanabrparams, 956  
     cnfchanegressq, 957  
     cnfchaneir, 955  
     cnfchanfst, 956, 1020  
     cnfchaningressq, 957  
     cnfchanmap, 957  
     cnfchanpol, 955  
     cnfchanq, 1024, 1032  
     cnfchdfm, 159  
     cnfchdl, 128  
     cnfchec, 124  
     cnfchfax, 119–120  
     cnfchgn, 121  
     cnfchpri, 228–229  
     cnfchutl, 116–117, 285  
     cnfclksrc, 311–313  
     cnfcls, 221–224, 269  
     cnfcon, 225–226, 269, 628, 870, 893–894  
     cnfconabrparams, 1022–1023  
     cnfcond, 135–136  
     cnfcos, 301, 661  
     cnfdate, 50, 445–446  
     cnfdclk, 173  
     cnfifastrk, 807

cnfilmi, 989–991  
cnfimagr, 984  
cnflan, 433, 455–456  
cnfln, 58, 89–90, 493–495, 800–802, 811–812  
cnfnalm, 332, 342–343, 693–694  
cnflnpass, 109–110  
cnflnsig, 1078  
cnfmode, 201–202  
cnfname, 55–56, 442, 782  
cnfnwip, 434, 456  
cnfpass, 774  
cnfport, 53–54, 190–192, 239–240, 536, 540–541, 920  
    ILMI parameters, 544  
    LMI parameters, 543–544  
cnfportcllm, 921  
cnfportq, 535  
cnfportseprtn, 806  
cnfpref, 297–300, 661–662  
cnfppt, 451–452  
cnfrsig, 137–138  
cnfrsrc, 491, 539  
cnfrtcost, 663  
cnfrtcost command, 300  
cnfterm, 51–52, 449  
cnftermfunc, 432  
cnftime, 50  
cnftmnz, 51, 443–444  
cnfrtk, 58, 69–70, 477  
cnfrtkalm, 338–699  
cnfupcabr, 1022  
cnfupccbr, 1021, 1030  
cnfupcrtvbr, 1022  
cnfupcubr, 1022, 1032  
cnfupcvbr, 1021–1022, 1031  
cnfvchtp, 130–132  
cnfvismmode, 1076  
cnfwd, 49  
cnfxmtsig, 138–139  
configure terminal, 1115  
copy, 1114  
cpyict, 171  
cspcd, 520  
csprts, 664  
delapsln, 518  
delcon, 115, 155, 229–230, 268, 869  
delcons, 869  
deljob, 323  
deljobtrig, 325  
dellp, 349, 722  
delport, 203, 550  
deltrk, 58, 81–82, 484–485  
dncon, 302–303, 664–665  
dnfportq, 242  
dnln, 58  
dnport, 202–203, 550  
dntrk, 58, 82, 485  
dspalm, 814  
dspalment, 814–815  
dspalms, 313, 329, 334–335, 552, 684–685, 802–804, 813  
dspapsln, 516, 840  
dspasm, 439–440  
dspatmcls, 616  
dspbert, 817–818  
dspbob, 174–175, 332  
dspbuses, 331  
dspcd, 47–48, 236–237, 428, 438, 781–782  
dspcdrscprtn, 783  
dspcds, 45–47, 427–428, 436–437, 778–780  
dspchan, 1028–1029  
dspchancnt, 896–897, 959–961, 1033–1037  
dspchans, 1027–1028  
dspchcnf, 175–176  
dspchdlcnf, 129–130  
dspchec, 123–124  
dspchstats, 219, 230–231, 634  
dspcid, 1086  
dspcids, 1086  
dspelksrcs, 309, 681  
dspcls, 220–221, 269  
dspcon, 114, 154–155, 227–228, 269, 623–625, 872–875, 891–893, 951–954, 1017–1019, 1026–1027, 1083–1084  
dspconcnt, 1088–1089  
dspcond, 134  
dspcons, 112–113, 154, 227, 269, 333, 625, 626–627, 870–871, 889–890, 950–951, 1016–1017, 1025–1026, 1082  
dspconstdab, 1023  
dspcurclk, 310, 682  
dspds3ln, 810  
dspds3lns, 809

**dspendpt**, 1081  
**dspendpts**, 1080  
**dspict**, 167–168  
**dspifip**, 782  
**dspilmi**, 987–988  
**dspilmicnt**, 998–999  
**dspilmis**, 992  
**dspjob**, 320–321  
**dspjobs**, 319–320  
**dsplancnf**, 56–57  
**dsplink**, 824  
**dsplmistats**, 555–556  
**dspln**, 58, 111, 799–800, 822  
**dsplnalmcnf**, 332, 341–342, 691–692  
**dsplncnf**, 58, 88–89, 492–493  
**dsplndsp**, 1079  
**dsplnerrs**, 332, 340–341, 702–703  
**dsplns**, 58, 87, 188, 332, 489, 798,  
 807–809, 821  
**dsupload**, 292–293, 658  
**dsplog**, 329, 335, 518, 694–695  
**dspmngcident**, 1089–1090  
**dspmode**, 200  
**dspmodes**, 201  
**dspnds**, 54–55, 330, 442–443, 706  
**dspnw**, 79–80, 329, 706–707  
**dspnwip**, 57–58, 457  
**dspport**, 193–200, 238, 887, 980–983, 1076  
**dspportcnt**, 922–925, 993–997  
**dspportq**, 241, 548–549, 986  
 parameters, 549  
**dspportrscprtns**, 991  
**dspports**, 198, 237, 332, 545–547, 805, 886,  
 979–980, 990  
**dspportsqs**, 985  
**dspportstats**, 204–206, 332, 553–555  
**dspprtcnf**, 451  
**dsppwd**, 49–50, 427  
**dsppwr**, 48  
**dspred**, 787  
**dsprscprtn**, 1077–1078  
**dsprtk**, 482–483  
**dsprts**, 296–297  
**dpsigqual**, 140  
**dpslotalmcnf**, 720  
**dpslotalms**, 717  
**dpsloterrs**, 718–719  
**dpslotlink**, 825  
**dsptermcnf**, 448–449  
**dsptermfunc**, 52–53, 450  
**dsptrk**, 58, 68–69  
**dsptrkcnf**, 58, 68–69, 483–484  
**dsptrkerrs**, 332, 336–337, 696  
**dsptrks**, 58, 65–66, 314, 332, 686, 806  
**dsprktul**, 294–296, 659–660  
**dsusers**, 774  
**dspvismparam**, 1074–1075  
**dssport**, 916–918  
**dssports**, 915–916  
**editjob**, 321  
**enable**, 1112  
**enable password**, 1116  
**help**, 44  
**help (BPX CLI)**, 420–421  
**hostname**, 1115  
**IGX CLI syntax**, 43  
**interface**, 1120, 1127  
**ip**, 1131  
**ip address**, 1127  
**line**, 1116–1117  
**map-group**, 1130  
**map-list**, 1131  
**password**, 1117  
**reload**, 1114  
**repeating**, 422–423  
**resetcd**, 330, 345, 723  
**rpmrscprtn**, 1117–1118  
**runjob**, 322  
**show atm map**, 1131  
**show atm vc**, 1129–1130  
**show interface**, 1119–1120, 1125–1126  
**show running-config**, 1112–1114  
**show startup-config**, 1112–1114  
**show switch connections**, 1133–1134  
**shutdown**, 1127  
**snfclksrc**, 683–684  
**stopjob**, 323  
**switchapsln**, 517–518, 522, 842  
**switchcc**, 331, 708  
**troubleshooting**, 333  
**tstcon**, 350–354, 894–895, 958, 1037, 1087  
**tstconseg**, 712–714, 1038  
**tstdelay**, 232, 895–896, 959, 1037–1087  
**upcon**, 303, 665

- upln, 58, 87–88, 490
- upport, 192–193, 238, 545
- uptrk, 58, 66, 474–476
- users, 774
- vt, 58, 80–81, 485
- window, 453
- xcnfport, 920–921
- xcnfportq, 987
- commbus, 391–392
- Common Channel Signaling, 125
- common core card group (BPX), BCC, 375–376
  - back cards, 376–377
  - functions, 377–378
- Communicate priority field (dsport command output), 196
- communication failures, 688
  - unreachable nodes, 689
- comparing virtual and physical trunks, 466
- complex gateways, 274–276
- compression schemes, 103
  - ADPCM, 103–104
  - CS-ACELP, 104
  - LD-CELP, 104
  - PCM, 103
- concurrent routing, 649
- conditioning templates, 133
  - configuring, 135–136
  - displaying, 134
- configurable parameters
  - ABRFST, 621
  - ABRSTD, 620
  - ATM connections, 617–618
  - BXM cards, 478–481
  - CBR, 618
  - data channels
    - DFM, 159–160
    - ICS, 160–161
    - utilization, 162
  - IGX lines, 90–92
    - frame scramble, 96
    - HCS masking, 96
    - idle code, 96
    - IMA clock mode, 93
    - IMA group member, 93
    - IMA max. diff. dly, 93
    - IMA protocol option, 93
    - line 56KBS bit pos, 95
- line cable type, 95
- line coding, 94
- line CRC, 94
- line DS-0, 93
- line encoding, 94
- line length, 95
- line pct fast modem, 95
- line recv impedance, 94
- line T1 signaling, 95
- loop clock, 93
- retained links, 93
- IGX trunks, 70–72
  - deroute delay time, 78
  - frame scramble, 78
  - gateway channels, 77
  - HCS masking, 77
  - header type, 75
  - idle code, 75
  - IMA clock code, 78
  - IMA group member, 73
  - IMA max. diff. dly, 78
  - IMA protocol option, 78
  - line cable length impedance, 77
  - line cable type impedance, 76
  - line coding, 76
  - line CRC, 76
  - line DS-0, 73
  - line framing, 76
  - line recv impedance, 76
  - line type, 75
  - loop clock, 74
  - pass sync, 74
  - payload scramble, 77
  - recv trunk rate, 73
  - restrict PCC traffic, 75
  - retained links, 73
  - routing cost, 75
  - statistical reserve, 74
  - subrate data rate, 74
  - subrate interface, 73
  - traffic, 77
  - transit trunk rate, 73
  - VC shaping, 79
  - virtual trunk type, 78
  - virtual trunk VPI, 78
  - VPC conn, 79
  - VPI address, 75

- port queues, 183
- UBR, 622
- VBR, 619
- VC queues, 212
- configuration files, copying, 1114
- configure terminal command, 1115
- configuring
  - access lines, 495–496
  - Adaptive VAD, 118
  - alarm status monitor, 440–441
  - APS, 510, 518–520
  - ATM
    - lines, 804
    - ports, 239–240, 550–551
  - BPX switches
    - adduser command, 425
    - cfnasm command, 429
    - cndate command, 430
    - cndlans command, 433
    - cnnfname command, 429
    - cnnfwip command, 434
    - cnpwd command, 426
    - cncfterm command, 430
    - cncftermfunc command, 432–433
    - cncftime command, 430
    - cncftmzn command, 430
    - commands, 423–424
    - date/time, 443–445
    - dspcd command, 428
    - dspcds command, 427–428
    - dspnds command, 430
    - dspppwr command, 428
    - IP addressing schemes, 453–456
    - print modes, 451–452
    - serial port communications parameters, 446–448
    - terminal ports, 449
  - circuit emulation connections, 893–894
  - data channels, clock mode, 173
  - data connections
    - ICT, 169
    - input control signal transport, 165
    - output control signal transport, 166
  - echo canceller parameters, 124
  - Fax Relay, 119–120
- Frame Relay
  - connections, 220–232
  - ports, 925–926
  - signaling parameters, 190–192
- IGX switches
  - auxiliary port, 51–52
  - control port, 51–52
  - print modes, 53–54
  - trunks, 69–70
- lines, 89–90
  - ATM device compatibility, 493–495
- MGX switches
  - RPM, 1121–1122
- ports
  - on AUSM cards, 1000
  - on PXM1 cards, 1000
- QBins, 976
  - thresholds, 532–533
- routes
  - direct, 290
  - IGX, 290, 304
  - preferred, 290
- RPM, hostname, 1115
- subinterfaces, 1122
- trunks, 486–487
  - alarm reporting, 699
- UVM cards, line pass-through, 109–110
- VISM
  - clocking options, 1072–1073
  - VoATM services, 1067–1070
- voice channels, 130–132
  - conditioning template, 135–136
  - dial types, 127–129
  - gain, 121
  - receive signaling bit conversion, 137–138
  - signaling bit conversion, 136–139
  - transmit signaling bit conversion, 138–139
  - utilization, 116–117
- congestion, 215
  - ABR, 944–945
  - ABRFST rate adjustment, 261
  - ATM
    - EPD, 1012
    - monitoring potential locations, 1012
  - control mechanisms, 570–572
  - EFCI, 533
  - example, 939

- ForeSight, 935, 1009  
 configurable characteristics, 938, 1010  
 criteria for, 937, 1008–1010  
 monitoring potential congestion, 936, 1009  
 rate adjustment, 216  
 VC queue servicing, 216
- Conjugate Structure Algebraic Code Excited Linear Prediction, 104
- connecting to MGX CLI, 767
- connection admission control, 283
- connection alarms, 333
- connection load, estimating, 285
- connection-oriented protocols, encapsulation, 278
- connections
- ABRFST
    - rate adjustment, 605–607
    - RM cell, 604–605
    - activating, 303
    - adding to MGX 8850-PXM45, 875–876
    - alarms, 709
    - ATM, 243, 563, 861, 1001–1002
      - ABR, 259, 566
      - CBR, 566
      - channel status, displaying, 1028–1029
      - configurable parameters, 617–618
      - CoS, 1003
      - creating on AUSM, 1016
      - displaying configuration information, 1017–1019
      - displaying standard ABR characteristics, 1023
      - establishing, 628–630
      - feeder connections, 1002
      - gateways, 274–276
      - local connections, 1002
      - monitoring, 630–635
      - policing, 245–254
      - removing, 268
      - segments, 256
      - single-segment, 564
      - standard ABR, 256–258
      - two-segment, 565
      - UBR, 566
      - VBR, 566
      - VC queuing, 254
    - ATM-Frame Relay, adding, 278–279
- BME Multicast, adding, 613
- BPX, 362
- bursts, handling, 288, 650–652
- CBR, adding, 262–268
- characteristics, 285–286
- CIDs, adding, 1085–1086
- circuit emulation connections, 879  
 clocking modes, 882  
 configuring, 893–894  
 deleting, 888–889  
 detailed status, displaying, 891–893  
 signaling, 880  
 testing, 894–896
- continuity testing, 1037–1087
- creating on RPM, 1134–1135
- data, 142, 153  
 adding, 144–145  
 detailed information, displaying, 154–155
- DFM, 144
- ICT, configuring, 167–170
- removing, 155
- substrate, 151
- summary information, displaying, 154
- super-rate, 151
- transparent, 152
- transporting control signal states, 148–150  
 types of, 146–147
- deactivating, 302–303
- displaying routing information, 296–297
- endpoints  
 managed CID count, displaying, 1089–1090  
 removing, 869
- event logging, 695
- failures, alarms, 687
- feeder nodes on MGX switches, 862–863
- Frame Relay, 207  
 ABR, 940–945  
 adding, 224–225  
 class, specifying, 220–221  
 CLP bit, 210  
 configuring, 220–232  
 creating in MGX network, 962–964  
 customizing, 225–226  
 EFCN bit, 210  
 FR-SSCS, 272  
 global addressing, 208

- parameters, 213
  - removing, 229–230
  - setting channel priority, 228–229
  - UFM leaky bucket policing, 213–214
  - FRSM**, 926–927
    - feeder connections, 927
    - local connections, 928
    - integrity, testing, 714–716
    - load model, statistical reserve, 288
    - load, calculating, 653
    - local loopback
      - removing, 722
      - testing, 712–713
    - maximum route cost, setting, 300
    - multicast services, 613
    - parameters, modifying, 870
  - PNNI**, dynamic partitioning, 473–474
  - potential routes, identifying, 643–647
  - preferred routes, specifying, 297–300
  - remote loopback, testing, 714
  - rerouted, prioritizing, 301
  - routing, 657–658
    - displaying statistics, 664
  - segments, 565
  - standard ABR, 587–588
    - implementing on BXM, 598, 601
    - operation in BPX, 591–592, 595–597
    - rate adjustments, 601–604
    - RM cells, 588–591
    - versus ABRFST, 604
  - statistics monitoring, 635–643
  - testing, 352–353, 632
    - external loopback, 355
    - local loopback, 353–354
    - remote loopback, 354
  - VCs**
    - PVCs, 851–858
    - SPVCs, 853–854, 858
    - SVCs, 855–856, 859
  - voice, 1059
    - AAL2 segmentation, 1062–1063
    - adding to UVM/CVM cards, 106–108, 111–112
    - CIDs, 1059
    - deleting, 115
- detailed parameters, 114
  - displaying, 112–113
  - endpoints, 1059
  - vt, creating, 485
  - continuity of connections, verifying, 1037
  - control port**
    - BPX configuration, displaying, 450
    - CLI, accessing
      - BPX, 411–412
      - IGX, 39
    - data transmission parameters, configuring, 430–431
    - IGX
      - configuring, 51–52
      - listing functions of, 52–53
      - port functions, configuring, 432–433
  - control signal transport (IGX)**, 148–150
    - interleaved, 149–150
    - normal, 149
    - partially interleaved, 150
  - control terminal port**, 430
  - conventions**
    - BPX CLI command structure, 415
    - BPX node names, 441–442
  - converting Frame Relay frames to FastPackets, 209
  - copy command**, 1114
  - copying data channels, 170
  - CoS (class of service)**, 1003
    - ABR, 1011
      - ForeSight, 1008–1010
      - monitoring potential congestion, 1012
    - BPX switch buffers, 403
    - CBR, example, 1007
    - traffic policing, 1005–1006
      - VBR, example, 1008
  - counters**
    - for signaling protocols, 185
    - of summary statistics, 631
  - cpict command**, 171
  - creating**
    - circuit emulation ports, 885
    - connections
      - Frame Relay connections in MGX network, 962–964
      - on AUSM card, 1038–1040
      - on PXM1 card, 1038–1042

- data FastPackets, 143
  - IGX jobs, 318–319
  - IMA groups, 984
  - jobs
    - IGX, 316
    - triggers, 318
  - logical ports
    - Frame Relay ports, 189–190
    - on physical lines, 805, 990–991
  - MGX user IDs, 773
  - service emulation services on MGX, 897–899
  - SPVCs with MGX 8850-PXM45 CLI, 875–876
  - virtual ports, 538
  - vt connections, 485
  - criteria for reporting ATM congestion locations with ForeSight, 1008–1010
  - crosspoint switch, 389–390
  - CS-ACELP (Conjugate Structure Algebraic Code Excited Linear Prediction), 104
  - cspcds command, 436–437
  - customizing Frame Relay connections, 225–226
  - Cutoff RM factor, 595
  - CVM (Channelized Voice Module) cards, 101
    - card group (IGX), 84
    - front card, 22
    - substrate data connections, 151
    - super-rate data connections, 151
    - transparent data connections, 152
    - voice connections, adding, 106–108, 111–112
  - CWM (Cisco WAN Manager), 10
- 
- ## D
- data card group, Cisco IGX switches, 22
  - data channels, 142, 156
    - clocking, 171
      - configuring, 173
      - isochronous data clocking, 172–173
      - looped clocking mode, 172
      - normal clocking mode, 172
      - split clocking mode, 172
    - DFM, 159–160
    - ICS, configuring, 160–161
    - serial, 163
    - utilization, configuring, 162
  - data connections, 142
    - adding, 144–145
    - characteristics, 143
    - control signal states, transporting on IGX, 148–150
  - data channels, 156
    - EIA/TIA-232, 157
    - EIA/TIA-449, 158
    - serial, 163
    - substrate, 158
    - super-rate, 158
    - transparent, 158
    - V.35, 157
    - X.21, 158
  - deleting, 155
  - ICTs
    - configuring, 169
    - copying, 170
    - displaying, 167–168
  - input control signal sampling, configuring, 165
  - output control signals, specifying, 166
  - substrate, 151
  - summary information, displaying, 154
  - super-rate, 151
  - transparent, 152
  - types of, 146–147
  - data faceplate buttons, 356
  - data FastPackets
    - building, 143
    - coding, 153
    - DFM, 144
    - partially filled, 147
  - data networks, private line replacement, 141
  - data packet flow on IGX switches, 32
  - data transmission parameters, configuring control/
    - auxiliary ports, 430–431
  - date/time, setting on IGX nodes, 50
  - DC power supply on IGX switches, 23
  - DCE (Data Communication Equipment), 164
  - DE threshold field (dsport command output), 195
  - deactivating
    - access lines, 496
    - ATM ports, 550–551
    - connections, 302–303
    - Frame Relay ports, 202–203
    - trunks, 485–487
  - delapsln command, 518

delcon command, 115, 155, 229–230, 268, 869  
 delcons command, 869  
 deleting  
     ATM connections, 268  
     circuit emulation connections, 888–889  
     data connections, 155  
     Frame Relay connections, 229–230  
     loopbacks, 722  
     network-wide clock sources, 683–684  
     trunks, 484–485  
         between nodes, 81–82  
         voice connections, 115  
 deljob command, 323  
 deljobtrig command, 325  
 dellp command, 349, 722  
 delport command, 203, 550  
 deltrk command, 58, 81–82, 484–485  
 demand for Frame Relay services, 5  
 deroute delay time parameter (IGX trunks), 78  
 devices  
     CIDs, 1059  
     DCE, 164  
     DTE, 164  
     endpoints, 856, 1059  
         removing, 869  
     FRADs, 180  
     MGX, 729–730, 736  
         features, 730  
         optional features, 732  
         user services, 731  
     modems, 64 kbps upgrade, 119  
 DFM (Data Frame Multiplexing), 7, 30–32, 144  
     configuring, 159–160  
 dial types for voice channels, configuring, 127–129  
 dialing protocols, timing, 126  
 direct command entry mode, 416  
 direct entry of IGX commands, 43  
 Direct NLPID encapsulation, 278  
 directed routes, 290, 648  
 directional switching mode, APS, 510  
 displaying, 545–547  
     alarms, 313  
         ATM port-related, 552  
         status monitor, 439–440  
 ATM ports  
     characteristics, 237  
     queue configuration, 548–549  
     statistics, 553–555  
 auxiliary port functions (IGX), 52–53  
 BPX  
     nodes, 442–443  
     port functions, 450  
     printer configuration, 451  
     terminal port configuration, 448–449  
 card status, 330, 427–428  
 connections  
     configuration information, 1017–1019  
     routing information, 296–297, 664  
 control port functions (IGX), 52–53  
 current network clock sources, 682  
 data connections  
     detailed information, 154–155  
     ICTs, 167–168  
     summary information, 154  
 echo canceller parameters, 123–124  
 egress port queue configuration, 985  
 external device window, 452–453  
 Frame Relay port parameters, 193–197  
 Frame Relay port statistics, 204–206  
 front/back card summary information, 45–47  
 IGX switches  
     card status, 47–48, 236–237  
     environmental measurements, 48  
     job statistics, 319–321  
     line configuration, 88–89  
     line summary information, 87  
     nodes, 54–55  
     tabular network summary, 79–80  
     trunk configuration, 68–69  
     trunk summary information, 65–66  
     user password, 49–50  
 ILMI configuration information, 987–988  
 IP relay address of IGX nodes, 57–58  
 lines  
     detailed configuration information, 492–493  
     pass-through state (UVM cards), 111  
     status information, 489  
 LMI/ILMI statistics per port, 555–556  
 logical ports on MGX PXMI card, 990  
 network users, 435

- node status, 430
- port resource partitions, 991
- potential network clock sources, 681
- power supply status, 428
- QBin statistics, 986
- serial port configurations, 447–448
- signaling protocol configuration on PXMI, 992
- standard ABR characteristics of connections, 1023
- system data, 436–439
- system power status, 439
- trunks
  - alarm state, 314, 686
  - bandwidth, 292–293
  - usage statistics, 294–296
- UFM-U back card mode, 200
- voice channels
  - conditioning template, 134
  - connection state, 132–133
  - signaling bit conversion, 140
  - signaling timing parameters, 129–130
  - summary configuration information, 140–141
- voice connections, detailed parameters, 112–114
- distribution process of T1 lines, 820–825
- DLCIs (data-link connection identifiers), 207, 927
- dncon command, 302–303, 664–665
- dnlm command, 58
- dnport command, 202–203, 550
- dnrk command, 58, 82, 485
- double-height card slots, configuring, 753
- downing
  - Frame Relay ports, 202–203
  - IGX lines, 97
  - trunks, 485
  - IGX, 82
- DRAM (dynamic random-access memory), 1107
- DS0A substrate connections, 151
- DSPs (Digital Signal Processors)
  - echo cancellers, 123
  - PCM, converting voice samples to ATM cells, 1061
  - voice compression, 103
    - ADPCM, 103–104
    - CS-ACELP, 104
- LD-CELP, 104
- PCM, 103
- dspalm command, 814
- dspalmcnt command, 814–815
- dspalms command, 313, 329, 334–335, 552, 684–685, 802–804, 813
- dspapsln command, 516, 840
- dspasm command, 439–440
- dspatmcls command, 616
- dspbert command, 817–818
- dspbob command, 174–175, 332
- dspbuses command, 331
- dspcd command, 47–48, 236–237, 428, 438, 520, 781–782
- dspcdrscprtn command, 783
- dspcds command, 45–47, 427–428, 778–780
- dspchan command, 1028–1029
- dspchancnt command, 896–897, 959–961, 1033–1037
- dspchans command, 1027–1028
- dspchcnf command, 175–176
- dspchdlenf command, 129–130
- dspchec command, 123–124
- dspchstats command, 219, 230–231, 634
- dspcid command, 1086
- dspcids command, 1086
- dspclksrcs command, 309, 681
- dspcls command, 220–221, 269
- dspcon command, 114, 154–155, 227–228, 269, 623–625, 872–875, 891–893, 951–954, 1017–1019, 1026–1027, 1083–1084
- dspconcnt command, 1088–1089
- dspcond command, 134
- dspcons command, 112–113, 154, 227, 269, 333, 625–627, 870–871, 889–890, 950–951, 1016–1017, 1025–1026, 1082
- dspconst command, 132–133
- dspconstdabr command, 1023
- dspcurlk command, 310, 682
- dspd3ln command, 810
- dspd3lns command, 809
- dspendpt command, 1081
- dspendpts command, 1080
- dspict command, 167–168
- dspifip command, 782
- dspilmi command, 987–988
- dspilmicnt command, 998–999

dspilmis command, 992  
 dspjob command, 320–321  
 dspjobs command, 319–320  
 dsplancnf command, 56–57  
 dsplink command, 824  
 dsplmistats command, 555–556  
 dspln command, 58, 111, 799–800, 822  
 dsplnalmcnf command, 332, 341–342, 691–692  
 dsplncnf command, 58, 88–89, 492–493  
 dsplndsp command, 1079  
 dsplnerrs command, 332, 340–341, 702–703  
 dsplns command, 58, 87, 188, 332, 798,  
     807–809, 821  
 dsplns command, 489  
 dsplload command, 292–293, 658  
 dsplog command, 329, 335, 518, 694–695  
 dspmngcident command, 1089–1090  
 dsemode command, 200  
 dsmodes command, 201  
 dsrnds, 430  
 dsrnds command, 54–55, 330, 430, 442–443, 706  
 dsrnw command, 79–80, 329, 706–707  
 dsrnwip command, 57–58, 457  
 dsport command, 193–200, 238, 887, 980–982,  
     983, 1076  
 dsportcnt command, 922–925, 993–997  
 dsportq command, 241, 548–549, 986  
 dsportrscprtns command, 991  
 dsports command, 198, 237, 332, 545–547, 805,  
     886, 979–980, 990  
 dsportsqs command, 985  
 dsportstats command, 204–206, 332, 553–555  
 dspprtcnf command, 451  
 dsppwd command, 49–50, 427  
 dsppwr command, 48  
 dspred command, 787  
 dsprscprtn command, 1077–1078  
 dsprtks command, 482–483  
 dsprts command, 296–297, 664  
 DSPs (Digital Signal Processors), 1070  
 dssigqual command, 140  
 dspslotalmcnf command, 720  
 dspslotalms command, 717  
 dspsloterrs command, 718–719  
 dspslotlink command, 825  
 dsptermcnf command, 448–449  
 dsptermfunc command, 52–53, 450

dsptrk command, 58, 68–69  
 dsptrkcnf command, 58, 68–69, 483–484  
 dsptrkerrs command, 332, 336–337, 696  
 dsptrks command, 58, 65–66, 314, 332, 686, 806  
 dsptrkutl command, 294–296, 659–660  
 dsusers command, 774  
 dsvismparam command, 1074–1075  
 dssport command, 916–918  
 dssports command, 915–916  
 DTE (Data Terminal Equipment), 164  
 dual leaky bucket model, 573, 1004  
     ATM connection policing, 246–247  
     CoS, policing, 1005–1006  
 dynamic partitioning, 473–474  
 dynamic rate control, Frame Relay services, 7

## E

---

E-1, 7  
 E1 format (CAS), 126  
 E1 lines, signaling methods, 1078  
 E3 lines, listing summary configuration information,  
     809  
 echo, 122  
 echo cancellers, 123  
     parameters  
         configuring, 124  
         displaying, 123–124  
 echo perception, 122  
 Echo Return Loss (ERL), 122  
 ECN queue threshold field (dsport command  
     output), 194  
 editing  
     BPX CLI, 423  
     IGX jobs, 317–318  
 editjob command, 321  
 EFCI (Explicit Forward Congestion Indicator), 533,  
     571, 591  
     threshold, 242  
 EFCN (Explicit Forward Congestion  
     Notification), 210  
 egress port queues  
     displaying configuration, 985  
     on CESM, 882–883

- egress traffic
  - AUSM cell flow, 978
  - on CESM, 884
- EIA/TIA-232 data channels, 157
- EIA/TIA-449 data channels, 158
- enable command, 1112
- enable password command, 1116
- enabling
  - Frame Relay ports, 188
  - ILMI, 991
- encapsulation
  - ATM, 276
  - Frame Relay, 277–278
  - simple gateway process, 61
- endpoints, 856, 1059
  - adding to VISM, 1079–1080
  - deleting, 869
  - detailed information, displaying, 1081
  - listing on VISM, 1080
  - managed CID count, displaying, 1089–1090
- end-to-end connections, segments, 863–864
- end-to-end SPVCs, 854
- enhanced BXM cards, 382–383
- Enter User ID prompt (IGX), 40
- entering commands
  - in RPM CLI, 1109
  - partial command entry, IGX help system, 44–45
- entry modes for BPX CLI commands, 416
- environmental measurements (IGX), displaying, 48
- EPD (Early Packet Discard), 585, 1012
- ER (Explicit Rate) control, 571, 596
  - calculating, 596
- ERL (echo return loss), 122
- error counts, dsprkerrs command output, 337–338
- Error threshold field (dspport command output), 195
- errors
  - BERTs
    - reporting results, 817–818
    - running on MGX service modules, 815–817
  - message reporting, MGX CLI, 772
- establishing
  - ATM connections, 628–630
  - vty sessions with remote nodes, 80–81
- estimating connection load, 285
- ETS (errored ten seconds), 697
  - line alarms, 704
- event log
  - alarms, 694–695
  - clearing, 695
- examples
  - of CBR, 1007
  - of VBR, 1008
  - of network synchronization, 674, 677–679
  - of trunk resource partitioning, 471–473
- executing IGX jobs, 317
- expected trunk loading versus actual, 286
- Explicit Forward Congestion Notification (EFCN), 210
- external device window, 452–453
- external loopbacks, IGX, 352

## F

---

- failed connection alarms, 687
- failed trunks, 688
  - rerouting, 648
- failure resets, 723
- FastPackets, 6
  - coding, 153
  - converting from Frame Relay frames, 209
  - creating, 143
  - data, 143
  - DFM, 144
  - last header fields, 211–212
  - message format, 25–27
  - partially filled, 147
  - transmission over framed trunks, 63
  - transmission over unframed trunks, 63
  - voice, 102
- fault management
  - BPX switches, 369
  - IGX switches, 29
- Fax Relay, 109
  - configuring, 119–120
- FBTC (Frame-Based Traffic Control), 253, 401, 583
  - implementing on BXM, 584–586

- features
- of MGX product family, 730
  - of MPLS, 1092, 1104–1105
  - of VISM
    - Release 1.5, 1056–1058
    - Release 2.0, 1058
    - Release 2.1, 1058
- feedback, 364
- feeder connections, 926–927, 1002
  - example, 927
  - MGX, 862–864
- feeder nodes, 828–829
  - adding to BPX networks, 830
  - adding to MGX networks, 831–832
- FGCRA (Frame-Based Generic Cell Rate Algorithm), 586
- fields
  - of Frame Relay header, 182
  - of last FastPacket header, 211–212
- finding MGX command syntax, 771
- first FastPacket header, 209–210
- five nines, 9
- flat networks, 369, 828
- ForeSight, 7, 215, 364, 566, 935, 1003, 1009.
- See also* ABR; ABRFST
  - configurable characteristics, 938, 1010
  - congestion criteria, 937, 1008–1010
  - modifying connection characteristics, 1020
  - monitoring potential congestion, 1009
  - potential congestion locations, 936
  - rate adjustment, 216, 260–261
  - VC queue servicing, 216
- formats
  - of ATM cells, 365
  - of IGX lines, 84
  - of routing trunks, 60
- forwarding packets, MPLS, 1055
- fractional FRSMS, 909
- fractional trunks, 62
- FRAD (Frame Relay access device), 180
- frame discard, 571
- frame forwarding, 217–219, 927
- frame forwarding ports, 908
- Frame Relay
  - AT&T network meltdown, 8–9
  - ATM interworking, 34, 270–271, 608
  - SIW, 273–275
  - cards, 180
  - Cascade, 6
  - channel statistics, 219
  - connections, 207
    - ABR, 940–945
    - adding, 224–225
    - channel priority, setting, 228–229
    - class, specifying, 220–221
    - CLP bit, 210
    - configuring, 220–232
    - creating in MGX network, 962–964
    - customizing, 225–226
    - EFCN bit, 210
    - global addressing, 208
    - parameters, 213
    - removing, 229–230
    - statistics, clearing, 231–232
  - demand for services, 5
  - dynamic rate control, 7
  - encapsulation, 277–278
  - frames, 182
    - converting to FastPackets, 209
    - logical ports, creating, 189–190
    - packet flow on IGX switches, 33
    - port queues, 182
      - configurable parameters, 183
  - ports, 181, 907–908
    - card module information, displaying, 199–200
    - configuring, 925–926
    - displaying detailed information, 198
    - downing, 202–203
    - fractional FRSMS, 909
    - narrowband channelized, 908
    - parameters, displaying, 193–197
    - statistics, clearing, 206–207
    - statistics, displaying, 204–206
  - serial ports, 908
  - signaling protocols
    - counters, 185
    - NNI, 186
    - timers, 185
  - UFM, leaky bucket policing, 213–214

UNI, 184  
VC queue parameters, 212  
Frame Relay card group (Cisco IGX switches), 22  
frame scramble parameter (IGX trunks), 78  
frame-based traffic control (FBTC), 253, 1012  
framed trunks (IGX), 62  
    cell transmission, 63  
    FastPacket transmission, 63  
frames, converting to FastPackets, 209  
framing, 86  
    T1 D4, 125  
    T1 ESF, 125  
FRM (Frame Relay Module), 180  
    back card, 23  
    logical Frame Relay ports  
        creating , 189–190  
        removing, 203  
    front card, 23  
FRM-31 card group (IGX), 84  
front cards  
    IGX switches, 20  
    summary information, displaying, 45– 47  
FRSM (Frame Relay Switch Module), 749–750  
    connection types, 926–927  
    feeder connections, 927  
    high-speed FRSM  
        policing, 934  
        traffic flow, 913–914  
    local connections, 928  
    low-speed  
        policing, 931–932  
        traffic flow, 912  
    NIW, 928  
    port queues, 910  
        high-speed, 911–912  
        low-speed, 910  
    ports, configuring, 925–926  
    SIW, 929–930  
    VC queues, 946–947  
FRSM-2CT3 card modules, displaying broadband line configuration information, 810  
FR-SSCS (Frame Relay Service-Specific Convergence Sublayer), 272  
full status poll, 185  
Full Status Polling Cycle field (dspport command output), 197

full-mesh networks, resolving persistent loops with MPLS, 1094–1095  
functions  
    of BPX serial ports, 446–447  
    of BPX switches, 371–372  
    of voice channel conditioning template, 133  
    of VSI controllers, 468–469  
FUNI (Frame-based user-network interface)  
    ports, 908, 927  
future of WAN technologies, 9  
    MPLS VPN over ATM, 10

## G

---

gain, configuring on voice channels, 120–121  
Gang of Four, 5  
gateway channels parameter (IGX trunks), 77  
generating  
    loopback test patterns  
        local loopback, 712–713  
        remote loopback, 714  
    RM cells, 590–591  
global addressing, 208

## H

---

handling bursts, 288  
hardware  
    BPX, 372  
        BNI, 386–392  
        card groups, 374–385  
        chassis, 373  
        failures, 688  
        MGX, selecting, 755–758  
        resetting for cards, 330, 723  
    HCS masking parameter (IGX trunks), 77  
    HDM (High-Speed Data Module) front card, 22  
    header type parameter (IGX trunks), 75  
    HEC framing, 63  
    help command, 44, 420–421, 770–771  
    help system  
        BPX CLI, 420–422  
        IGX CLI, 44–45  
    high availability services, necessity of, 9  
    high-speed card modules, MGX, 752

high-speed FRSMs  
 ingress traffic flow, 913–914  
 policing, 934  
 port queues, 911–912  
 hop count, 211  
 hostname command, 1115

IBGP distribution of VPN routing information, 1106  
 IBS (initial burst size), 947  
 ICS (Idle Code Suppression), configuring, 160–161  
 ICT (Interface Control Template), 166  
 configuring, 169  
 copying, 170  
 displaying, 167–168  
 IDE to DE Mapping field (dsport command output), 197  
 identifying  
   alarms, 329  
   connection routes, 643  
     AutoRoute routing, 646–647  
     BPX routing, 644–646  
 idle code parameter (IGX trunks), 75  
 IGX switches  
   8410 rack-mount chassis, 16–17  
   8420 standalone chassis, 17–19  
   8430 standalone chassis, 19–20  
   Adaptive VAD, 117–118  
   alarms  
     bus alarms, 331  
     card alarms, 330  
     connection alarms, 333  
     identifying, 329  
     line alarms, 332  
     port alarms, 332  
     trunk alarms, 332  
   ATM card group, 23  
   ATM connections  
     cell payloads, 61  
     congestion control segments, 256  
     removing, 268  
   auxiliary port  
     configuring, 51–52  
     listing functions of, 52–53

back cards, displaying summary information, 45–47  
 bandwidth management, 30  
 card states, displaying, 46–47, 236–237  
 Cellbus, 30–31  
 CLI  
   accessing, 39–40  
   direct entry, 43  
   menu-driven command interface, 44  
   privilege levels, 43  
 connections  
   ATM, 243  
   testing, 352–355  
 control port  
   configuring, 51–52  
   listing functions of, 52–53  
 control signal states, transporting, 148–150  
 CVM cards, voice connection types, 107  
 data card group, 22  
 data channels, clocking, 171–172  
 data connections, 142  
   adding, 144–145  
   characteristics, 143  
   removing, 155  
   substrate, 151  
   super-rate, 151  
   transparent, 152  
   types of, 146, 147  
 displaying network in tabular form, 79–80  
 environmental measurements, displaying, 48  
 fault management, 29  
 Frame Relay card group, 22  
 front cards, displaying summary information, 45–47  
 help system, 44–45  
 jobs  
   creating, 316  
   deleting, 323  
   editing, 317–318  
   executing, 317  
   managing, 316  
   planning, 317  
   statistics, displaying, 319–321  
   stopping, 318, 323  
 LAN interfaces, displaying screen information, 56–57  
 LEDs, 330

- lines, 83
    - card group hardware, 84
    - configurable parameters, 90–96
    - configuring, 89–90
    - displaying configuration, 88–89
    - displaying summary information, 87
    - downing, 97
    - formats, 84
    - multiplexed, 85
    - notation, 86
    - technologies, 84
    - unmultiplexed, 85
    - upping, 87–88
  - login procedures, 40
    - CLI screen, 41
    - CLI shortcuts, 42
    - command syntax, 43
  - message formats, 25
    - FastPacket, 25–27
  - network synchronization
    - carrier network timing, 305
    - clock reference selection, 308–309
    - clocking sources, 305–307
    - commands, 304
  - NPM cards, redundancy, 28
  - nodes
    - displaying, 54–55
    - IP relay address, 57–58
    - naming, 55–56
  - packet flow
    - ATM, 34
    - data packets, 32
    - Frame Relay, 33
    - voice packets, 31
  - passwords, changing, 49
  - power supplies, 23
  - print modes, configuring, 53–54
  - processor card group, 21
  - route configuration, 290–304
    - direct routes, 290
    - network-assigned routes, 290
    - preferred routes, 290
  - routing trunks, 59
    - card groups, 60
    - formats, 60
    - technologies, 60
  - transmission facilities, 60–61
- serial ports, DCE/DTE selection, 164
  - simple gateway process, 61
  - T1/12 trunks, 62
  - time zone, modifying, 51
  - troubleshooting commands
    - addextlp, 348
    - addloclp, 346–347
    - addrmtlp, 347–348
    - clrlnalm, 344
    - clrlog, 336
    - clrtrkalm, 339
    - cnflnalm, 342–343
    - cnntrkalm, 338
    - dellp, 349
    - dspalms, 334–335
    - dsplnlmcnf, 341–342
    - dsplnerrs, 340–341
    - dspllog, 335
    - dsptkerrs, 336–337
    - resetcd, 345
    - tstcon, 350–351
  - trunk card group, 21
  - trunks
    - adding, 67
    - configurable parameters, 70–79
    - configuring, 69–70
    - displaying configuration, 68–69
    - downing, 82
    - framed versus unframed, 62
    - notation, 63–64
    - removing between nodes, 81–82
    - upping, 66
  - UVM cards
    - Fax Relay, 119–120
    - line pass-through configuration, 109–110
    - voice connection types, 108
  - UXM cards
    - ABR, 259
    - supported ATM connections, 244
  - voice card group, 22
  - voice channels
    - conditioning templates, 133
    - configuring, 130–132
    - connection state, displaying, 132–133
    - signaling bit conversion, 136–140
    - signaling bit interpretation, 126, 130

- voice connections, 101
- Y-cable redundancy, 28
- ILMI (Integrated Local Management Interface), 537
  - enabling, 991
  - field descriptions, 240–241
  - historical statistics counters, displaying, 998–999
- IMA (Inverse Multiplexing over ATM), 975
  - groups
    - characteristics, modifying, 984
    - creating, 984
  - ports, 973–974
    - displaying status information, 982–983
  - trunks, 63
- IMA clock code parameter (IGX trunks), 78
- IMA group member parameter (IGX trunks), 73
- IMA max. diff. dly parameter (IGX trunks), 78
- IMA protocol option parameter (IGX trunks), 78
- implementing
  - APS on BPX networks, 506
    - version 1+1, 508, 511–513
  - FBTC on BXM cards, 584–586
  - level loss plans, 121
- MGX switches on MPLS networks
  - as ELSRs, 1098–1100
  - IP MPLS core, 1101
  - MGX 8850-PXM45 ATM MPLS core, 1100
- standard ABR on BXM card, 598–601
- traffic shaping, 534–535
  - port level, 535
- in-band dialing, 126
- index number, command history function (BPX CLI), 423
- indicator LEDs, IGX, 330
- ingress ATM traffic, AUSM cell flow, 977–978
- ingress port queues, Frame Relay, 910
- ingress traffic
  - high-speed FRSMS, 913–914
  - low-speed FRSMS, 912
  - on CESM, 883
  - policing, 1004
    - CoS-based, 1005–1006
    - dual leaky bucket model, 1004
    - leaky bucket model, 1004
- ingress VC queues, modifying characteristics, 1032
- initial BPX configuration
  - adduser command, 425
  - cfnasm command, 429
  - cnfdate command, 430
  - cnflan command, 433
  - cnfname command, 429
  - cnfnwip command, 434
  - cnfpwd command, 426
  - cnfterm command, 430
  - cnftermfunc command, 432–433
  - cnftime command, 430
  - cnftmzn command, 430
  - commands, 423–424
  - dspsc command, 428
  - dspcds command, 427–428
  - dsppnd command, 430
  - dsppwr command, 428
- input control signal transport, configuring, 165
- integrity of connections, testing, 714–716
- interface command, 1120, 1127
- interleaved control signal transport, 149–150
- interpreting voice channel signaling bit on IGX, 130
- interpretive DS0A data connections, 151
- interval statistics, monitoring, 631
- interworking
  - ATM and Frame Relay, 270–271
  - NIW, 928
    - FR-SSCS, 272
    - SIW, 273–275, 929–930
      - translational, 273
      - transparent, 273
- IOS images, loading on startup, 1115
- ip address command, 1127
- IP addressing schemes (BPX)
  - configuring, 453–456
  - LAN port, 455–456
- ip command, 1131
- IP Relay, 40
  - accessing BPX CLI, 413
  - displaying address for IGX nodes, 57–58
- IPX
  - DFM, 7
  - E-1, 7
  - FastPacket, 6
  - Frame Relay service integration, 7
  - voice/data integration, 7
- isochronous data clocking, 172–173

ISPs, PoPs, 1055

IWF (Interworking Function)

BPX connection types, 608

BPX interworking connection types, 608

NIW, 608–611

SIW, 608–612

## J

---

J1 format, CAS signaling, 126

jobs (IGX)

creating, 318–319

deleting, 323

editing, 317–318

executing, 317

managing, 316

planning, 317

privilege levels, 316

statistics, displaying, 319–321

stopping, 318, 323

triggers, creating, 318

## K

---

K1K2 protocol (APS), 506

keepalive procedure, ILMI, 537

keyboard shortcuts

  BPX CLI, 419

  IGX CLI, 42

## L

---

label switching, MPLS, 1091

  configuring on MGX switch, 1101–1103

  features, 1092

  resolving persistent loops in full-mesh  
    networks, 1094–1095

  versus IP over ATM, 1092–1093

  VPNs, 1103–1106

LAN interfaces (IGX), displaying screen  
information, 56–57

LAN port

BPX

  CLI, accessing , 413

  configuring, 455–456

  IGX CLI, accessing, 40

last FastPacket header, 211–212

LD-CELP (Low-Delay Code Excited Linear  
Prediction), 104

LDI (Low-Speed Data Interface) back card, 22

LDM (Low-Speed Data Module) front card, 22

leaky bucket model, 572–573, 1004

  ATM connection policing, 245–246

  high-speed FRSM policing, 934

  low-speed FRSM policing, 931–932

  time-based, 1007

  UFM policing, 213–214

leaves, 613

LED indicators, IGX, 330

Level 1 channel statistics, 636–638

Level 2 channel statistics, 639–640

Level 3 channel statistics, 641–643

level loss plans, implementing, 121

line alarms, 332

line cable length parameter (IGX trunks), 77

line cable type parameter (IGX trunks), 76

line coding parameter (IGX trunks), 76

line command, 1116, 1117

line CRC parameter (IGX trunks), 76

line DS-0 parameter (IGX trunks), 73

line framing, 86

line framing parameter (IGX trunks), 76

line pass-through

  configuring on UVM card, 109–110

  displaying on UVM card, 111

line recv impedance parameter (IGX trunks), 76

line type parameter (IGX trunks), 75

lines, 487

  activating on PXM1, 800

  adding to MGX service modules, 818–819

  alarms

    on PXM1 (MGX), displaying, 802–804

    resolving, 701–705

    statistical thresholds, 692

    summarizing historical statistical errors,  
      702–703

- ATM
  - configuring, 804
  - device compatibility, 493–495
- BPX, 362
  - configuring, 89–90
  - detailed configuration information, displaying, 492–493
  - DSP configuration, displaying, 1079
  - errors, displaying, 689
  - IGX, 25, 83
    - card group hardware, 84
    - configurable parameters, 90–96
    - configuring, 89–90
    - displaying configuration, 88–89
    - displaying summary information, 87
    - downing, 97
    - formats, 84
    - multiplexed, 85
    - notation, 86
    - technologies, 84
    - unmultiplexed, 85
    - upping, 87–88
  - LOS, 688
  - MGX, 795–796
    - FRSM-8T1, 797
    - PXM1 OC-3c, 796
  - narrowband, modifying characteristics, 811–812
  - OOF (out of frame), 688
  - physical, creating logical ports, 805
  - PXM1, displaying summary information, 798
  - serial, modifying characteristics, 811–812
  - status, displaying, 489
  - upping, 490
  - voice lines, 101
- link integrity timer, 185
- Link Integrity Timer field (dspport command output), 197
- listing
  - BPX nodes, IP relay addresses, 457
  - clock sources, 309
  - connections on PXM1, 1025–1026
  - current network clock sources, 682
  - network users, 435
  - potential network clock sources, 681
- Littlewood, Morgan, 5
- LLC/ISO (Logical Link Control/International Standards Organization), 277
- LLC/SNAP (Logical Link Control/Subnetwork Access Protocol), 277
- LMI (Local Management Interface), 536–537
- load model, 653
  - bursts, handling, 288
  - expected versus actual trunk loading, 286
  - statistical reserve, 288
  - versus actual usage, 284
- local alarms, locating, 705
- local connections, 864, 926–928, 1002
- local loopback
  - IGX, 352
  - performing, 353–354
- locating alarms, 329
  - local, 705
  - remote, 706–707
- logging in
  - to BPX switch, requirements, 417
  - to IGX switch, 40
    - CLI screen, 41
    - CLI shortcuts, 42
    - command syntax, 43
  - to MGX switch, 775
- logging out of BPX CLI, 423
- logical Frame Relay ports, 181
  - activating, 192–193
- logical ports, 532
  - creating on physical lines, 805, 990–991
  - displaying on MGX PXMI cards, 990
  - on MGX PXM1, listing, 805
  - removing from FRM/UFM-C cards, 203
  - resource partitions, displaying, 806
- loop clock parameter (IGX trunks), 74
- loopback testing
  - local loopback, 712–713
  - remote loopback, 714
- looped clocking mode, 172
- LOS (Loss of Signal), 688
- Low-Delay Code Excited Linear Prediction, (LD-CELP), 104
- low-speed card modules, MGX, 752
- low-speed data connections, partially filled FastPackets, 147

low-speed FRSMs  
  ingress traffic flow, 912  
  policing, 931–932  
  port queues, 910  
LSRs (label switch routers), 1091

## M

---

major alarms, 329, 687–688  
managing traffic on CESM, 882–884  
mandatory framing structure, IGX transmission facilities, 62  
manual operation of APS, 505  
map-group command, 1130  
map-list command, 1131  
master connections, MGX, 864  
maximum route cost  
  configuring, 663  
  setting for connections, 300  
MBS (Maximum Burst Size), 1005  
measuring echo perception, 123  
memory, DRAM, 1107  
menu-driven command interface, 416  
  IGX, 44  
message formats, IGX switches, 25  
  FastPacket, 25–27  
MGX switches, 729–730  
  8800 series switches, 10  
  8850-PXM45/8230 tiered network, 734  
  ATM connections, 1001–1002  
    feeder, 1002  
    local, 1002  
  ATM lines, configuring, 804  
  card modules, high-speed, 752  
  card-level resource partitions, 776–777  
  circuit emulation services, creating, 897–899  
  CLI, 732–733  
    accessing, 767  
    error messages, 772  
    login process, 775  
  commands  
    Help, 770–771  
    syntax, 768–770  
  connections  
    network connections, 863–864  
    slave/master connections, 864  
    testing network continuity, 1037, 1087

double-height card slots, configuring, 753  
features, 730  
feeder connections, 862–863  
feeder nodes, 828–829  
  adding, 831–832  
Frame Relay connections, creating, 962–964  
hardware, selecting, 755–758  
implementing on MPLS networks  
  as ELSRs, 1098–1100  
  IP MPLS core, 1101  
  MGX 8850-PXM45 ATM MPLS core, 1100  
  lines, 795, 796  
    FRSM-8T1, 797  
    PXM1 OC-3c, 796  
  MGX 8550-PXM45  
    adding connections, 875–876  
    ATM connection types, 861  
    standalone switches, configuring, 833  
  MPLS support, 1096  
    configuring, 1101–1103  
    QoS, 1097  
    RPM as ELSR, 1096  
    VPNs, 1097  
  network management, 733–734  
  optional features, 732  
  PXM1 processor cards, 737–738  
    back card, 738–740  
    characteristics, modifying, 800–802  
    functions, 741  
    lines, activating, 800  
    logical ports, displaying, 990  
    logical ports, listing, 805  
    SONET APS, 834–836, 839  
  required features, 754  
  RPM card, 745–745, 1055  
    configuring, 1121–1122  
    connections, creating, 1134–1135  
    PVCs, 1124  
  service modules, 745–746  
    adding lines, 818–819  
    AUSM, 750  
    BERTs, running, 815–817  
    CESM, 748–749  
    E1 lines, testing, 825–828  
    FRSM, 749–750

- lines, activating, 811
- redundancy, 783–785
- reserved card slots, 751
- SRM-3T3 T1 line distribution, 819
- T1 line distribution process, 820–825
- T1 lines, testing, 825–828
- VISM, 750
- SRM card, 741–744
- standalone devices, 736
- supported VCs
  - PVCs, 851–858
  - SPVCs, 853–858
  - SVCs, 855–859
- trunks, displaying, 806
- user IDs, 773
  - user services, 731
- middle FastPacket header, 209–210
- Min. flags/frame field (dspport command output), 196
- minimum wink, 128–129
- minor alarms, 687–689
- modems, 64 kbps upgrade, 119
- modes of RPM CLI, 1108
- modifying
  - ABR connection characteristics, 1022–1023
  - ATM
    - port queue depth, 242
    - signaling protocols, 989
    - timers, 989
  - BPX CLI passwords, 426
  - CBR characteristics, 1021, 1030
  - ForeSight connection characteristics, 1020
  - ingress VC characteristics, 1024
  - IGX trunk parameters, 69–70
  - IMA group characteristics, 984
  - ingress VC queue characteristics, 1032
  - QBin characteristics, 987
  - serial port configurations, 447–448
  - UBR policing characteristics, 1032
  - VBR policing characteristics, 1031
  - VGR policing characteristics, 1021–1022
- Monitored events count field (dspport command output), 196
- monitoring
  - alarms, multicast connection, 711
- ATM
  - connections, 630–635
  - port failures, 552–558
  - traffic, potential congestion locations, 1009
- BPX
  - line alarms, 704–705
  - trunk alarms, 691–699
  - system data, 436–439
  - voice channel signaling bit on IGX, 130
- MPLS (Multiprotocol Label Switching), 8, 1055, 1091
  - BPX switches, 397–399
  - configuring on MGX switch, 1101–1103
  - features, 1092
- MGX switches
  - as ELSRs, 1098–1100
  - IP MPLS core, 1101
  - MGX 8850-PXM45 ATM MPLS core, 1100
- resolving persistent loops in full-mesh networks, 1094–1095
- support on MGX switches, 1096
  - QoS, 1097
  - RPM as ELSR, 1096
  - VPNs, 1097
- versus IP over ATM, 1092–1093
- VPNs, 1103, 1104
  - features, 1104–1105
  - IBGP distribution of routing information, 1106
  - label forwarding, 1106
  - operation, 1105
  - over ATM, 10
  - route-target communities, 1105
- multicast connection alarms, 710–711
- multicast services, 613
  - addressing, 615
  - BME connections, adding, 613
- Multilevel Channel Statistics, 632–633
- multiplexing, 85
  - AAL2, 1059
  - DFM, 144
  - line framing, 86
  - TDM, 85
  - voice FastPackets, 102

**N**

N392 Error Threshold field (dspport command output), 197  
 N393 Monitored Events Count field (dspport command output), 197  
 naming  
   IGX nodes, 55–56  
   network nodes, 429, 441–442  
   trunk nodes, 475  
 NAPs (network access points), 1055  
 narrowband IMA, 975  
 narrowband channelized Frame Relay ports, 908  
 narrowband lines  
   modifying characteristics, 811–812  
   summary configuration information, listing, 807–809  
 network management  
   BPX, 367  
   MGX switches  
     Cisco WAN Manager, 733  
     CLI, 732–733  
     connections, 863–864  
     SNMP management tools, 734  
 network synchronization, 671  
   carrier network timing, 671  
   clock alarms, clearing, 685  
   clock sources, 672  
     listing, 682  
     removing, 683–684  
     selecting, 673  
   example, 674, 677–679  
   guidelines, 680–686  
   IGX  
     clock reference selection, 308–309  
     commands, 304  
 network topologies  
   BPX/MGX tiered networks, 735  
   MGX 8850-PXM45/8230 tiered networks, 734  
   PNNI networks, 736  
 network types, BPX, 369–370  
 network-assigned routes, 290, 647  
 network-wide clock source, specifying, 311–313  
 network-wide BPX configuration, date & time, 445–446

NIW (network interworking), 270–271, 608, 928.

*See also* SIW

FR-SSCS, 272  
 operation, 610–611  
 NNI (Network-Node Interface) cell headers, 366  
 NNI (Network-to-Network Interface), 186  
 nodes  
   BPX  
     date/time configuration, 443–445  
     displaying, 442–443  
     naming, 429, 441–442  
     status, displaying, 430  
   normal clocking mode, 172  
   normal control signal transport, 149  
   NOS (Network Operating System), BPX  
     switches, 394  
   NPM (Nodal Processor Module) front card, 21  
     redundancy, 28  
     toggling between active and standby, 331  
   nrt-VBR (nonreal-time VBR), 363, 1003  
     configurable parameters, 622–623  
   NTM (Network Trunk Module) front card, 21, 60  
     capacity, calculating, 64  
   NTS (non-time-stamped) data FastPackets, 143  
     DFM, 144

**O**


---

OAM FastPacket Threshold field (dspport command output), 196  
 OAM segment loopback, testing connection integrity, 714–716  
 ones density, ZCS, 152  
 OOF (out of frame), 688  
 operating modes (VISM), 1053–1054  
 optional features of MGX switches, 732  
 optional framing structures of IGX transmission facilities, 62  
 optional parameters of BPX CLI command syntax, 414  
 output control signal transport, configuring, 166

# P

---

Packet Technologies, 6

packets

  Cisco IGX switches

    ATM, 34

    data packets, 32

    Frame Relay, 33

    voice packets, 31

encapsulation, simple gateway process, 61

forwarding, MPLS, 1055

parameters

  addcon command, 106–107, 111–112

  addjob command, 319

  addjobtrig command, 325

  BPX CLI command syntax, 414

  BPX serial ports, configuring, 446–448

  clrlnalm command, 344

  cnfasm command, 429

  cnfcndl command, 129

  cnfcchn command, 122

  cnfccls command, 311–312

  cnfccls command, 221–224

  cnfcond command, 136

  cnfcos command, 302

  cnflan command, 434

  cnflnalm command, 343

  cnfnwip command, 434

  cnfpport command, 541–544

  cnfpref command, 298

  cnfrtcost command, 301

  cnfterm command, 52, 431

  cnftermfnc command, 432–433

  cnftmzn command, 444

  cnfxmtsig command, 139

  command syntax, 770

  dncon command, 303

  dspcons command, 112–113

  dspnds command, 55

  dspportq command, 549

  dsprk command, 69

  dsprkutl command, 295

  for ABR, 943, 944

  for ABRFST, 266, 621

  for ABRSTD, 260, 267, 620

  for CBR, 618

  for echo cancellers

configuring, 124

displaying, 123–124

for Frame Relay

  connections, 213

  ports, displaying, 193–197

for IGX lines, 90–92

  frame scramble, 96

  HCS masking, 96

  idle code, 96

  IMA clock mode, 93

  IMA group member, 93

  IMA max. diff. dly, 93

  IMA protocol option, 93

  line 56 KBS bit pos, 95

  line cable type, 95

  line coding, 94

  line CRC, 94

  line DS-0, 93

  line encoding, 94

  line length, 95

  line PCT fast modem, 95

  line recv impedance, 94

  line T1 signaling, 95

  loop clock, 93

  retained links, 93

for IGX trunks

  configuring, 70–72

  deroute delay time, 78

  frame scramble, 78

  gateway channels, 77

  HCS masking, 77

  header type, 75

  idle code, 75

  IMA clock code, 78

  IMA group member, 73

  IMA max. diff. dly, 78

  IMA protocol option, 78

  line cable length, 77

  line cable type, 76

  line coding, 76

  line CRC, 76

  line DS-0 map, 73

  line framing, 76

  line recv impedance, 76

  line type, 75

  loop clock, 74

  pass sync, 74

- payload scramble, 77
- rcv trunk rate, 73
- restrict PCC traffic, 75
- retained links, 73
- routing cost, 75
- statistical reserve, 74
- substrate data rate, 74
- substrate interface, 73
- traffic, 77
- transit trunk rate, 73
- VC shaping, 79
- virtual trunk type, 78
- virtual trunk VPI, 78
- VPC conns, 79
- VPI address, 75
- for ports, displaying summary, 545–547
- for UBR, 622
- for VBR, 619
- for VC queues, 212
- resetcd command, 345
- tstcon command, 351
- tstdelay command, 232
- partial command entry, IGX help system, 44–45
- partially interleaved control signal transport, 150
- partially filled FastPackets, 147
- pass sync parameter (IGX trunks), 74
- passing sync, 673
- pass-through mode, UVM card configuration, 109–110
- password command, 1117
- passwords
  - BPX CLI, changing, 426
  - entering for BPX login, 417
  - IGX
    - changing, 49
    - displaying, 49–50
- payload (ATM cells)
  - for IGX networks, 61
  - partially filled FastPackets, 147
- payload scramble parameter (IGX trunks), 77
- PCM (Pulse Code Modulation) algorithm, 102–103
  - voice samples, conversion to ATM cells, 1061
- PCR (Peak Cell Rate), 364, 1005
  - time-based model, 1007
- performance, traffic shaping, 534
  - implementing, 534–535
  - port level, 535
- physical errors
  - on BPX lines, 701
  - on trunks, 690
- physical lines, creating logical ports, 805
- physical ports, 529
  - creating, 538
  - Frame Relay, 181
    - activating, 192–193
  - port queues, 532
    - QBins, 532–533
    - versus virtual ports, 531
- physical trunks
  - displaying statistics, 482–483
  - parameters, configuring, 477
  - resource partitions, 468
    - example, 471–473
    - resource allocation, 469–470
  - statistical alarms, clearing, 698
  - versus physical trunks, 466
- planning IGX jobs, 317
- playout delay, 128–129
- PNNI (Private Network to Network Interface), 10, 371, 736
  - BPX switches, 396
  - dynamic partitioning, 473–474
- policing
  - ABR, 580
  - ATM connections, 245–247, 1004
    - ABR traffic policing, 251, 254
    - CBR traffic policing, 248
    - CoS-based, 1005–1006
      - dual leaky bucket model, 246–247, 1004
      - leaky bucket model, 246, 1004
      - time-based leaky bucket models, 1007
      - UBR traffic policing, 252–253
      - VBR traffic policing, 248–250
    - CBR traffic, 574–575
    - dual leaky bucket model, 573
    - high-speed FRSM policing, 934
    - leaky bucket model, 572–573
    - low-speed FRSM policing, 931–932
    - time-based, 574
  - UBR, 581–582
  - VBR, 576–580
- polling, 392–393

polling timer,  
     ILMI, 537  
     verification timer, 185

Polling verify timer field (dspport command output), 195

PoPs (points of presence), 1055

port alarms, 332

Port ID field (dspport command output), 194

port level traffic shaping, 535

Port queue depth field (dspport command output), 194

port queues, 182, 532

- configurable parameters, 183
- Frame Relay
  - high-speed, 911–912
  - low-speed, 910
- QBins
  - configurable thresholds, 532–533
  - displaying statistics, 986

port summary information, 545–547

Port type field (dspport command output), 194

port-level resource partitions, MGX, 776–777

ports, 529

- activating on BXM cards, 545
- ATM, 973
  - activating, 238, 550–551
  - characteristics, displaying, 237
  - configuring, 239–240, 550–551
  - deactivating, 550–551
  - deleting, 550
  - detailed information, displaying, 238
  - device compatibility, configuring, 540–541
  - displaying queue configuration, 548–549
  - displaying statistics, 993–997
  - displaying status, 980–983
  - displaying summary information, 979–980
  - egress queue thresholds, displaying, 241
  - failures, troubleshooting, 552–558
  - QBins, 975–976
  - queue depth, modifying, 242
  - signaling protocol statistics, displaying, 555–556
  - statistics, displaying, 553–555
- AUSM, activating, 983–984

circuit emulation ports, 876

- creating, 885
- listing on CESM, 886

configuring on PXM1 cards, 1000

Frame Relay, 181, 907–908

- activating, 188, 192–193
- card module information, displaying, 199–200
- configuring, 925–926
- displaying detailed information, 198
- downing, 202–203
- narrowband fractional Frame Relay
  - ports, 909
- serial, 908
- signaling parameters, configuring, 190–192
- statistics, clearing, 206–207
- statistics, displaying, 204–206

IMA, 974

logical, creating, 189–190, 805, 990–991

multicast, monitoring alarms, 711

physical, 529

- creating, 538
- versus virtual, 531

PVCs, allocating, 539

resource partitions, displaying, 991

serial, DCE, 164

signaling failure, 689

summary information, displaying, 545–547

virtual ports, 529–530

- creating, 538
- versus physical, 531

VI, 532

potential congestion locations, ABR, 942

potential connection routes, identifying, 643

- AutoRoute routing, 646–647
- on BPX switches, 644–646

power supplies

- IGX switches, 23
- status, displaying, 428

precedence rules for BPX switching commands, 523–524

preferred routes, 290, 648

- configuring, 662
- specifying, 298–300

previous commands, listing, 422–423

print modes (IGX), configuring, 53–54

prioritizing rerouted connections, 301  
priority bumping, 649  
private line replacement, 141  
privilege levels  
    BPX CLI, 416  
    IGX CLI, 43  
    IGX jobs, 316  
    MGX CLI, 773  
processor cards  
    IGX switches, 21  
    PXM1, 737–738  
        back cards, 738–740  
        functions, 741  
    switching between active and standby, 331  
Proctor, Don, 5  
prompts, BPX CLI, 416  
protection (P) line, APS, 502  
protocol-independent data connections, 143  
provisioning  
    PVCs, 852  
    SPVCs, 866–868  
Pulse Code Modulation. *See* PCM  
pulse dialing, 126  
PVCs (permanent virtual circuits), 207, 563, 851–853  
    circuit emulation connections, 879–880  
    data connections, 142  
    example, 856–858  
    on RPM, 1124  
    port allocation, 539  
    provisioning, 852  
    signaling protocols, 535–536  
        ILMI, 537  
        LMI, 536–537  
    Status Inquiry messages, 536  
    UNI signaling, asynchronous update mode, 185  
Update Status messages, 537  
voice connections, 101, 1059  
    AAL2 segmentation, 1062–1063  
    CIDs, 1059  
    endpoints, 1059  
PXM1 processor card, 737–738, 741  
    back cards, 738–740  
    connections  
        adding, 1025  
        creating, 1038–1042  
        listing, 1025–1026

ports  
    configuring, 1000  
    displaying signaling protocol configuration, 992  
on MGX switch  
    displaying configuration information, 799–800  
    displaying summary line information, 798  
    displaying line alarm conditions, 802–804  
    logical ports, listing, 805  
    SONET APS, 834–839  
    UNI ports, listing channels, 1027–1028

## Q

---

Q.2931 code points, 277  
QBins, 467, 532, 975–976  
    characteristics, modifying, 987  
    configurable thresholds, 532–533  
    displaying statistics, 986  
QoS (quality of service), 402  
    BPX service type parameters, 364–366  
    queuing architectures, 403–404  
question mark (?), IGX help system, 44–45  
queuing architectures  
    BPX switches, 403–404  
    congestion, 215

## R

---

RA (Rate Adjustment) bits, 210  
rate adjustments  
    ABR, 942–943  
    ABR ForeSight, 260–261  
rcv trunk rate parameter (IGX trunks), 73  
rebooting RPM processor card, 1114  
receive signaling bit conversion, configuring, 137–138  
redundancy  
    MGX service module, 783–784  
        1-to-N redundancy, 785  
    NPM cards, 28

- SONET APS, 834
  - 1+1 setup, 836, 839
  - versions, 834–835
- Y-cable, 28
- Relative Rate EFCI, 571
- reliability
  - BPX, 368–369
  - five nines, 9
- reload command, 1114
- remote alarms, locating, 706–707
- remote loopback
  - IGX, 352
  - performing, 354–355
- remote nodes, establishing vty sessions, 80–81
- removing
  - ATM connections, 268
  - circuit emulation connections, 888–889
  - connection endpoints from AXSM card, 869
  - data connections, 155
  - downed ATM ports, 550
  - Frame Relay connections, 229–230
  - logical ports from FRM/UFM-C cards, 203
  - loopback connections, 722
  - network-wide clock sources, 683–684
  - trunks, 484–485
    - between nodes, 81–82
    - voice connections, 115
- repeating commands, 422–423
- reporting
  - BERT test results, 817–818
  - trunk alarms, 699
- required features of MGX switches, 754
- required parameters, BPX CLI command
  - syntax, 414
- rerouting
  - failed trunk connection routes, 648
  - prioritizing connections, 301
  - rules, 291
- reserved card slots, 427, 751
- resetcd command, 330, 345, 723
- resolving
  - alarms
    - bus, 709
    - card, 708
    - connection, 709
- line, 701, 704–705
- multicast connection, 710–711
- trunk, 691–700
  - ATM port failures, 557–558
- resource partitions, 468, 491
  - displaying, 991
  - example, 471–473
  - on logical ports, displaying, 806
- resource allocation, 469
  - card-level, 470
  - port-level, 470
- restrict PCC traffic parameter (IGX trunks), 75
- retained links parameter (IGX trunks), 73
- revertive option, APS configuration, 501, 510
- RM (resource management), 1011
  - cells, 588–591, 941–942
  - Cutoff RM factor, 595
- roots, 613
- route-target communities, 1105
- routing connections, 657–658
- routing cost parameter (IGX trunks), 75
- routing trunks, 59
  - card groups, 60
  - formats, 60
  - technologies, 60
  - transmission facilities, 60–61
- RPM (Route Processing Module), 745, 1055
  - access lines, configuring, 1116–1117
  - ATM switch interface, configuring, 1119–1120
  - CLI
    - accessing, 1108
    - changing configuration file, 1109–1110
    - entering commands, 1109
    - modes, 1108
  - configuring, 1121–1122
  - connections, creating, 1134–1135
  - functions, 744
  - hostname, setting, 1115
  - memory locations, 1107
  - MPLS support, 1096–1097
  - port numbering, 1107
  - PVCs, 1124
  - rebooting, 1114
- rpmrscprtn command, 1117–1118
- RPS (Repetitive Pattern Suppression) algorithms, DFM (Data Frame Multiplexing), 144
- RR (Relative Rate) control, 592

**S**

- rt-VBR (real-time VBR), 363, 1003
- rules for rerouting traffic, 291
- runjob command, 322
  
- S**
- sample WAN network, 370
- SCM (System Clock Module) back card, 21
- SCR (Sustainable Cell Rate), 364, 1005
- screen information, BPX CLI, 418
- SDH (Synchronous Digital Hierarchy), 501
- SDI (Synchronous Data Interface) back card, 22
- security, IGX switches
  - user privilege levels, 43
  - changing passwords, 49
- segments, 256, 565, 863–864
- selecting
  - clock reference, 308–309, 673
  - commands from menu-driven interface, 416
  - control signals for data connections, 150
  - MGX hardware, 755–758
  - UFM-U card mode, 201–202
  - VISM clocking option, 1070–1071
  - voice channel type, 131–132
- selective cell discard, 571
- serial data channels, 163
- serial interfaces, active control templates, 192
- serial lines
  - characteristics, modifying, 811–812
  - summary configuration information, listing, 807–809
- serial ports
  - communications parameters, configuring, 446–448
  - DCE, 164
  - Frame Relay, 908
- service interworking, FR-SSCS, 272
- service modules
  - CESM
    - egress queues, 882–883
    - egress traffic, 884
    - ingress traffic, 883
  - E1 lines, testing, 825–828
  - MGX, 745–746
    - adding lines, 818–819
  - AUSM, 750
- CESM, 748–749
- FRSM, 749–750
- high-speed card modules, 752
- redundancy, 783–785
- reserved card slots, 751
- T1 line distribution process, 820–825
- VISM, 750
- T1 lines, testing, 825–828
- VISM, 1053–1054
  - AAL2 coding schemes, 1063
  - adding endpoints, 1079–1080
  - adding voice connections, 1082
  - clocking options, 1070–1073
  - DSPs, 1070
  - listing historical connection statistics
    - counters, 1088–1089
  - port status, displaying, 1076
  - Release 1.5 features, 1056–1058
  - Release 2.0 features, 1058
  - Release 2.1 features, 1058
  - resource partitions, creating, 1077
  - VoATM services, creating, 1067–1070
  - voice mode configuration, displaying, 1074–1075
  - voice mode, changing, 1076
  - VoIP mode, 1065–1067
- service types, BPX, 363–366
- SES (Service Expansion Shelf), 371
- setting date/time on IGX nodes, 50
- shelf units
  - cards
    - alarms, 330
    - statistics, displaying, 427–428
  - spacer brackets, 17
- shortcuts
  - BPX CLI cursor movement, 419
  - IGX CLI keyboard sequences, 42
- show atm map command, 1131
- show atm vc command, 1129–1130
- show interface command, 1119–1120, 1125–1126
- show running-config command, 1112–1114
- show startup-config command, 1112–1114
- show switch connections command, 1133–1134
- shutdown command, 1127

- signaling
  - bit conversion, 136–139
  - displaying, 140
  - bit interpretation on IGX, 130
  - bit timing, 126
    - dial type configuration, 127–129
  - bit transport, 126
  - CAS, 125
  - delay, 126
  - on circuit emulation connections, 880
  - UNI, 184
- signaling protocol field (dspport command output), 195
- signaling protocols, 184, 535–536
  - asynchronous update mode, 185
  - ATM, 239
  - counters, 185
  - ILMI, 537
    - field descriptions, 240–241
  - LMI, 536–537
    - field descriptions, 240–241
  - NNI, 186
  - port signaling failures, 689
  - timers, 185
- silence suppression
  - Adaptive VAD, 117–118
  - VAD, 116
- simple gateway process, 61, 274–276
- single-segment connections, 564
- SIW (service interworking), 270–275, 608, 929–930
  - adding ATM-Frame Relay connections, 278–279
  - operation, 611–612
  - translational, 273
  - transparent, 273
- SLAs (Service-Level Agreements), 1092
- slave/master connections, MGX, 864
- slot errors, 690
- slot.port field (dspport command output), 194
- slot.port.line field (dspport command output), 194
- slots
  - alarms
    - statistical thresholds, 720
    - troubleshooting, 717
  - historical statistical errors, summarizing, 718–719
- SNAP encapsulation, 278
- SNMP (Simple Network Management Protocol)
  - management tools, 734
- software
  - BPX, 394
    - AutoRoute, 395
    - CAC, 399
    - MPLS, 397–399
    - NOS, 394
    - PNNI, 396
    - VSI, 395
    - resetting for cards, 723
  - SONET APS (Automatic Protection Switching), 834
    - 1+1 setup, 836, 839
    - versions, 834–835
  - sources of BPX network clocks, 672–673
  - spacer brackets, 17
  - specifying
    - BPX network node names, 442
    - network-wide clock sources, 311–313
    - preferred routes for connections, 297–300
  - Speed field (dspport command output), 194
  - split clocking mode, 172
  - SPVCs (Soft Permanent Virtual Circuits), 853–854
    - example, 858
    - provisioning, 866–868
    - status information, displaying, 872–875
  - SRAM (static random-access memory), 1107
  - SRM processor card, 741–744
  - SRM-3T3, T1 line distribution, 819
  - SRTS clocking, 882
  - stability of clocking mechanisms, 671
  - stages of ATM cell egress traffic, 978
  - standalone chassis
    - IGX 8410 rack-mount chassis, 16
    - IGX 8420 switch, 17–19
    - IGX 8430 switch, 19–20
    - MGX switches, 736, 833
  - standalone feeders, 829
  - standard ABR, 256–258, 566, 587–588, 1003, 1011
    - displaying characteristics per connection, 1023
    - implementing on BXM, 598, 601
    - rate adjustments, 601–604
  - RM cells, 588–590
    - generation, 590–591
    - operation in BPX, 591–592, 595–597
  - versus ABRFST, 604

- standby NPM processor card, switching to active, 331
- static PVC connections, 851, 853, 856–858
- statistical alarm thresholds for lines/trunks, 692
- statistical errors
- counters, clearing, 697
  - on BPX lines, 701
- statistical reserve, 288, 650–653
- statistical reserve parameter (IGX trunks), 74
- Status Inquiry messages, 536
- status LEDs, Cisco IGX 8420 standalone system, 18
- STI (StrataCom Trunk Interface) cells, 366
- stopjob command, 323
- stopping IGX jobs, 318
- StrataCom
- acquisition by Cisco, 6
  - development of Frame Relay services, 6
  - MPLS, 8
- Stratum 1 clocks, 672
- Stratum 2 clocks, 672
- BITS, 305
- structure of BOP frames, 217–219
- structured ports, card module support, 876
- subinterfaces, configuring, 1122
- substrate data channels, 158
- substrate data connections, 151
- substrate data rate parameter (IGX trunks), 74
- substrate interface parameter (IGX trunks), 73
- summary statistics
- counters, 631
  - extending, 632–633
- super-rate data channels, 158
- super-rate data connections, 151
- suppressing data FastPackets, 144
- SVCs (Switched Virtual Circuits), 855–856
- example, 859
- switchapsln command, 517–518, 522, 842
- switchcc command, 331, 708
- switches
- BPX. *See* BPX switches
  - IGX. *See* IGX switches
  - MGX. *See* MGX switches
  - VT, 25
- switching, cell-based, 366–367
- synchronization
- carrier network timing, 305
  - clock sources, 305–307
- synchronous clocking, 882
- synchronous data connections, 143
- syntax
- addexp command, 348
  - addloclp command, 347
  - addport command, 538–539
  - addrmtlp command, 348
  - BPX CLI commands, 413–414
  - clrlnalm command, 344
  - clrtrkalm command, 339
  - cnflnalm command, 343
  - cnftrkalm command, 338
  - dsplnerrs command, 341
  - dsprkerrs command, 337
  - IGX CLI commands, 43
  - MGX commands, 768–771
  - reseted command, 345
  - tstcon command, 351
- system data, monitoring, 436–439
- system hardware, BPX, 372
- BNI, 386–392
  - card groups, 374–385
  - chassis, 373
- system power, displaying status, 439
- system software, BPX, 394
- AutoRoute, 395
  - CAC, 399
  - MPLS, 397–399
  - NOS, 394
  - PNNI, 396
  - VSI, 395
- system time, configuring on BPX nodes, 443–445
- 
- T**
- 
- T1 D4 framing, 125
- T1 ESF framing, 125
- T1 lines
- CAS, 126
  - distribution, 820–825
  - signaling method, configuring, 1078
  - SRM-3T3 distribution, 819
- T1/12 trunk, 62
- T3 lines, listing summary configuration information, 809

- Tag Switching, 8
- TDM (time-division multiplexing), 85
- technologies for routing trunks, 60
- terminating virtual terminal sessions, 485
- testing
  - circuit emulation connections, 894–896
  - connections, 352–353, 632
    - external loopback, 355
    - integrity, 714–716
    - local loopback, 353–354, 712–713
    - remote loopback, 354, 714
  - E1 lines on MGX service modules, 825–828
  - MGX network continuity, 1087
  - T1 lines on MGX service modules, 825–828
- thresholds
  - for EPD (early packet discard), 1013
  - for QBins, configuring, 532–533
  - for VC queues, 583
- tiered networks, 370, 828
  - BPX/MGX tiered network, 735
  - MGX 8850-PXM45/8230 tiered network, 734
- time zones
  - setting for BPX nodes, 444
  - setting for IGX nodes, 50–51
- time-based policing, 574
- timers
  - ATM, modifying, 989
  - for signaling protocols, 185
- timing
  - tone dialing, 126
  - voice channel signaling, displaying parameters, 129–130
- toggling NPM processor card between active and standby, 331
- tone detection, 123
- topologies
  - BPX/MGX tiered network, 735
  - MGX 8850-PXM45/8230 tiered network, 734
  - PNNI networks, 736
- traffic
  - ABRFST, 935
    - configurable parameters, 621, 938
    - congestion criteria, 937
    - potential congestion locations, 936
  - ABRSTD
    - configurable parameters, 620
    - rate adjustment, 260–261
- ATM
  - ABR, 1011–1012
  - ABR policing, 580
  - CAC, 568–569
  - CBR policing, 574–575
  - CoS, 1003
  - ForeSight, 1008–1010
  - management, 567
  - policing, 245–254, 1004–1006
  - shaping, 570
  - time-based policing, 574
  - UBR policing, 581–582
  - UPC, 569
  - VBR policing, 576–580
  - VC queuing, 254
- AUSM cell flow
  - egress traffic, 978
  - ingress traffic, 977–978
- CBR, configurable parameters, 618
- congestion, 215, 570–572
  - EFCI, 533
  - example, 939
  - ForeSight rate adjustment, 216
  - ForeSight VC queue servicing, 216
- controlling, FBTC, 583–586
  - FBTC, 583–586
    - flow through FRSRM, 912–914
    - high-speed FRSRM policing, 934
    - ingress, VC queues, 946–947
    - low-speed FRSRM policing, 931–932
  - management on BPX switches
    - closed-loop congestion avoidance, 402
    - FBTC, 401
    - QoS, 402
    - queuing architectures, 403–404
    - UPC, 400
- policing
  - dual leaky bucket model, 573
  - leaky bucket model, 572–573
- rerouting, 291
- UBR, configurable parameters, 622
- VBR, configurable parameters, 619
- traffic contracts, 567
- traffic descriptors, BPX service types, 364–366
- traffic parameter (IGX trunks), 77

traffic shaping, 534  
    implementing, 534–535  
    port level, 535  
    VC queues, 1012  
        configuration example, 1014  
        frame-based traffic control, 1012

transit trunk rate parameter (IGX trunks), 73

translational SIW, 273, 612

transmission facilities  
    IGX framing structures, 62  
    of routing trunks, 60–61

transmit signaling bit conversion, configuring, 138–139

transparent data channels, 158

transparent data connections, 143, 152

transparent SIW, 273, 611

TransPath, 11

transporting control signal states on IGX, 148–150

triggers for IGX jobs  
    creating, 318  
    deleting, 325

troubleshooting  
    ATM port failures, 552–558  
    BPX  
        line alarms, 701, 704–705  
        trunk alarms, 691–700

commands  
    addextlp, 348  
    addloclp, 346–347  
    addrmtlp, 347–348  
    clrlnalm, 344  
    clrlog, 336  
    clrtrkalm, 339  
    cnflnalm, 342–343  
    cnfrkalm, 338  
    dellp, 349  
    dspalms, 334–335  
    dsplnalmcnf, 341–342  
    dsplnerrs, 340–341  
    dsplog, 335  
    dsprkerrs, 336–337  
    resetcd, 345  
    tstcon, 350–351

slot alarms, 717  
    with real-time statistics, 632

trunk card group (Cisco IGX switch), 21

trunk loading, expected versus actual, 286

trunks, 463, 464  
    activating, 486–487  
    adding, 474–475  
    adding between nodes, 481  
    alarms, 332, 690  
        displaying, 314  
        displaying configuration, 691–692  
        reporting, 699  
        statistical thresholds, 692  
        status, displaying, 686  
    as clock sources, 673  
    bandwidth, displaying, 292–293  
    bandwidth allocation, 650  
    BPX, 362  
    cell routing restriction, 34  
    communication failures, 688  
    configuring, 486–487  
    deactivating, 487  
    deleting, 81–82, 484–485  
    detailed information, displaying, 483–484  
    downing, 485  
    errors, displaying, 689  
    failures, 688  
        line error counts, displaying, 696  
        rerouting, 648

fractional, 62

framed  
    cell transmission, 63  
    FastPacket transmission, 63

IGX  
    adding, 67  
    configurable parameters, 70–79  
    configuring, 69–70  
    displaying configuration, 68–69  
    downing, 82  
    framed versus unframed, 62  
    notation, 63–64  
    summary information, displaying, 65–66

IGX switches, 24

IMA, 63

load model versus actual usage, 284

MGX, displaying, 806

NTM capacity, calculating, 64

parameters, configuring, 477

passing sync, 673

physical versus virtual, 466

physical errors, 690

- resource partitions, 468
  - card-level resource allocation, 470
  - example, 471–473
  - port-level resource allocation, 470
  - resource allocation, 469
- routing trunks, 59
  - card groups, 60
  - formats, 60
  - technologies, 60
  - transmission facilities, 60–61
- T1/12, 62
- unframed
  - cell transmission, 63
  - FastPacket transmission, 63
- upping, 66, 474–476
- usage statistics, displaying, 294–296
- utilization, expected versus actual trunk
  - loading, 653, 656
- UXM capacity, calculating, 64
- VI, 466–467
- virtual, 465–467
- TS (time-stamped) data FastPackets, 143–144
- tstcon command, 350–354, 894–895, 958, 1037, 1087
- tstconseg command, 712–714, 1038
- tstdelay command, 232, 895–896, 959, 1037, 1087
- two-segment ATM interworking connections, 565
  
- U**
- UAI (Universal ATM Interface) back card, 21–23
- UBR (unspecified bit rate), 244, 363, 566
  - characteristics
    - modifying, 1032
  - configurable parameters, 622
  - connections, adding, 268
  - traffic policing, 252–253, 581–582
- UFI (Universal Frame Relay Interface)
  - back card, 22
- UFM (Universal Frame Relay Module) front card, 22, 180
  - creating logical Frame Relay ports, 189–190
  - leaky bucket policing, 213–214
- UFM-C card group (IGX), 84
  - logical ports, removing, 203
- UFM-U back card
- active ports, displaying, 201
- mode, displaying, 200
- uncongested networks, example, 940
- unframed trunks, 62–63
- UNI (User-Network Interface) cell headers, 184–185, 366
- unmultiplexed lines, 85
- unstructured ports, card module support, 876
- UPC (Usage Parameter Control), 400, 569
- upcon command, 303, 665
- Update Status messages, 537
- upgrading modems to 64 kbps, 119
- upln command, 58, 87–88, 490
- Upper/lower RNR field (dspport command output), 196
- upping
  - IGX lines, 87–88
  - lines, 490
  - trunks, 66, 474
- upport command, 192–193, 238, 545
- uptrk command, 58, 66, 474–476
- user services, MGX switches, 731
- user IDs
  - BPX, adding to network, 425–426, 435
  - IGX
    - command syntax, 43
    - login procedures, 40–42
    - privilege levels, 43
  - MGX, 773
  - passwords, displaying, 49–50
- users command, 774
- utilization
  - data channels, configuring, 162
  - of voice channels, configuring, 117
  - trunks, 653, 656
- UVI (Universal Voice Interface) back card, 22
- UVM (Universal Voice Module) front card, 22
- UVM card group (IGX), 84
  - Fax Relay, 109, 119–120
  - line pass-through
    - configuring, 109–110
    - displaying, 111
  - super-rate connections, 151
  - transparent data connections, 152
  - voice connections, adding, 106–108, 111–112
- UXM (Universal Switching Module) card group, 21–23, 60, 84, 101

ABR, 259  
IMA trunks, 63  
supported ATM connections, 244  
trunk capacity, calculating, 64

## V

---

V.35 data channels, 157  
VAD (Voice Activity Detection), 30, 104, 116  
VBR (Variable Bit Rate), 244, 566, 1003  
configurable parameters, 619  
connections, adding, 264–267  
example, 1008  
modifying characteristics, 1021–1022  
policing characteristics, modifying, 576–580, 1031  
traffic policing, 248–250  
VC (virtual circuit) queues, 402, 532, 946–947, 977  
adjusting, 216  
characteristics, 1014  
congestion control, ABRFST rate  
adjustment, 261  
IBS, 947  
on ABR connections, 254  
on AUSM, 1012  
configuration example, 1014  
frame-based traffic control, 1012  
parameters, 212  
thresholds, 583  
VC shaping parameter (IGX trunks), 79  
VCs (virtual circuits)  
CoS, 1003  
CBR example, 1007  
VBR example, 1008  
PVCs, 851, 853  
circuit emulation connections, 879, 880  
example, 856–858  
on RPM, 1124  
provisioning, 852  
SPVCs, 853–854  
example, 858  
provisioning, 866–868  
status information, displaying, 872–875  
SVCs, 855–856  
example, 859  
VD (virtual destination), 256

verifying  
APS operation, 518–520  
BPX card installation, 436–439  
BPX node names, 442  
BXM card statistics level, 635  
Level 1, 636–638  
Level 2, 639–640  
Level 3, 641–643  
continuity of connections, 1037  
Frame Relay line configuration, 188  
versions of APS, 502–504  
VIs (Virtual Interfaces), 466–467, 529, 532  
virtual ports, 529–530  
creating, 538  
port queues, 532–533  
PVCs, signaling protocols, 535–537  
versus physical ports, 531  
virtual trunk type parameter (IGX trunks), 78  
virtual trunk VPI parameter (IGX trunks), 78  
virtual trunks, 465, 466  
BPX support, 467  
displaying statistics, 482–483  
parameters, configuring, 477  
resource partitions, 468  
example, 471–473  
resource allocation, 469–470  
statistical alarms, clearing, 698  
versus physical trunks, 466  
VISM (Voice Interworking Service Module), 750  
AAL2 coding schemes, 1063  
AAL2 trunking mode, 1064  
clocking options, 1070–1073  
connections, listing summary status  
information, 1082  
DSPs, 1070  
endpoints  
adding, 1079, 1080  
displaying detailed information, 1081  
listing, 1080  
historical connection statistics counters, listing, 1088–1089  
PCM, converting voice samples to ATM cells, 1061  
port status, displaying, 1076  
Release 1.5 features, 1056–1058  
Release 2.0 features, 1058  
Release 2.1 features, 1058

- resource partitions, creating, 1077
- VoATM services, creating, 1067–1070
- voice connections, adding, 1082
- voice mode, changing, 1076
- voice mode configuration, displaying, 1074–1075
- VoIP mode, 1065, 1067
- VoAAL2 (Voice over AAL2) trunking mode, 1064
- VoATM services, creating on VISM, 1067–1070
- voice card group, Cisco IGX switches, 22
- voice channels, 101, 115
  - conditioning templates, 133
    - configuring, 135–136
    - displaying, 134
  - configuring, 130–132
  - connection state, displaying, 132–133
  - echo, 122
  - Fax Relay, configuring, 119–120
  - gain, 120–121
  - PCM voice sample processing, 116
  - signaling, 126
    - bit conversion, 136–140
    - bit interpretation, 130
    - bit timing, 126
    - bit transport, 126
    - timing parameters, displaying, 129–130
  - summary configuration information, displaying, 140–141
  - utilization, configuring, 116–117
  - VAD, 116
- voice compression schemes
  - ADPCM, 103–104
  - CS-ACELP, 104
  - LD-CELP, 104
- voice connections, 101, 1059
  - AAL2 segmentation, 1062–1063
  - adding, 106–108, 111–112
  - CIDs, 1059
    - adding, 1085–1086
    - listing for specified LCN, 1086
  - deleting, 115
  - displaying, 112–113
  - displaying detailed parameters, 114
  - endpoints, 1059
- voice channels
  - connection state, displaying, 132–133
  - echo, 122
  - gain, 120–121
  - level loss plan, 121
- voice FastPackets, 102
- voice lines, 101
- VPC conns parameter (IGX trunks), 79
- VPCs (Virtual Permanent Circuits), virtual trunks, 465–466
- VPI address parameter (IGX trunks), 75
- VPNs, MPLS, 1103–1105
  - distribution of routing information, 1106
  - label forwarding, 1106
  - route-target communities, 1105
- VS (virtual source), 256
- VS/VD (Virtual Source/Virtual Destination), 571
- VSI (Virtual Switch Interface) controllers, 395, 468–469
- VSI-MPLS, resource partitioning, 491
- VSI-PNNI, resource partitioning, 491
- VT (virtual terminal), 25
- vt command, 58, 80–81, 485

## W—Z

- 
- window command, 453
  - working (W) line, APS, 502

- X.21 data channels, 158
- X.25 packets, encapsulation, 278
- xcnfport command, 920–921
- xcnfportq command, 987

- Y-cable redundancy, 28
- BPX switches, 368
- versus APS, 509

- ZCS (Zero Code Suppression) algorithm, 152