

INDEX

Numerics

- 3-way handshaking, 555
- 90-second timer (IGRP), 254

A

- A class IP addresses, 18–19**
 - address masks, 20
 - subnetting, 24
- ABRs (Area Border Routers), 369, 516**
- access-class command, 794**
- access-list compiled command, 789**
- Aceves, J.J. Garcia Luna, 137**
- Acknowledgment Number field (TCP), 43**
- acknowledgments, 364**
 - delayed, 365
 - direct, 365
- ACLs (access control lists)**
 - calling, 792–793
 - access-class command, 794*
 - categories of, 775
 - comments, adding, 783–784
 - dynamic, 786
 - editing, 780
 - effect on switching, 800
 - effect on system performance, 799
 - extended IP, 785, 789
 - effect on system performance, 788*
 - example of, 787–788*
 - features, 786–787*
 - sequence numbers, 786*
 - filter layers, numbering, 778, 780
 - fragments, handling, 787
 - ICMP, 791–792
 - implicit deny any filter, 777
 - keywords, 796–797
 - named, 780, 797
 - placement of, 799
 - reflexive, 794
 - example, 795–796*
 - parameters, 794*
- sequence number, 781
- sequentiality, 778
- standard IP, 782–784
 - Boolean AND/OR functions, 784*
 - inverse masks, 785*
- TCP, 790
- Turbo ACLs, 789
- UDP, 791
- acquiring hands-on experience, 805**
- active state, 273**
 - SIA, 274
- adding comments to ACLs, 783–784**
- address aggregation, 293–296**
 - CIDR, 296–297
- Address Family Identifier field (RIP), 173**
- Address Family Identifier field (RIPv2), 202**
- address masks, 20–21. *See also* subnet masks**
- Address Resolution Protocol. *See* ARP**
- address spaces, designing lollipop-shaped, 152**
- address summarization**
 - EIGRP, configuring, 315–316
 - OSPF
 - configuring, 435–440*
 - troubleshooting, 464–466*
- addresses, IP, 16**
 - internetworks, 18
 - masks, 20–21
 - reverse ARP, 36
 - RIP, 173
 - subnet mask, 24
 - subnets, 24
 - secondary RIP, 187
- adjacencies, 147, 267, 336–337**
 - building process, 358–362
 - formation of, 351
 - IS-IS, 517, 522–523
 - troubleshooting, 607–610*
 - troubleshooting, 456–458*
- adjusting RIPng metrics, 233–235**
- administrative distance, 98, 175**
 - effect on redistribution, 633–639
 - setting route preferences, 722–723
- advertising default networks, 690**
- aging process (LSAs), 153–154**

alternative routes, creating for static routes, 96–97
always keyword (default-information originate command), 694
AND operator, 21
 Boolean AND function, 784–785
anycast addresses, 55–56
application layer (TCP/IP), 6
Area ID, 368
areas, 160, 367
 Area ID, 368
 autonomous systems, 160–162
 backbone, 369
 IS-IS, 516–517
 L1 routers, 517
 maximum size of, 369
 multiple L1 areas, IS-IS configuration, 604–606
 NSSAs, 387–389
 configuring, 428–434
 partitioned areas, 371
 path types, 391
 stub areas, 386
 configuring, 423–426
 totally stubby areas, 387
 configuring, 426–428
 traffic types, 369
 troubleshooting, 460–463
ARP (Address Resolution Protocol), 32–34, 40
 gratuitous ARP, 36
 packets
 Hardware Address Length field, 33
 Hardware Type field, 33
 Operation field, 33–34
 Protocol Address Length field, 33
 proxy ARP, 35–36
 reverse ARP, 36
arp command, 45, 123
arp timeout command, 45
ASBR Summary LSAs, 382
ASBRs (Autonomous System Border Routers), 370
AS-External LSAs, 488–489
assigning metrics to redistributed routes, 644
asynchronous updates, 145–146
ATT (Attached bit), 518
Attempt state (OSPF neighbors), 354

authentication
 OSPF, 393
 configuring, 441–444
 IS-IS, configuring, 587–591
 RIPng, 213
 RIPv2, 210–212
 configuring, 222–224
Authentication Information TLV, 544
auto-cost reference-bandwidth command, 345
automatic summarization, disabling on EIGRP, 307–309
Autonomous System External LSAs, 383, 408–409
autonomous systems, 160–162

B

B class IP addresses, 18–19
 address masks, 20
 subnetting, 24
backbone, 369
 virtual links, 373–374
backbone routers, 370
bandwidth, 134–135, 255–256
 IGRP metric, modifying, 257
 reference bandwidth, 345
BDRs (Backup Designated Routers), election process, 342–344
best path determination, convergence, 135–137
binary numbering system, 769–770
 converting to hex, 772–773
 converting to decimal, 771
bitcount format, 24
bits, IP packet flags, 11
Boolean operators
 AND, 784–785
 OR, 784
boundaries, 174
boundary routers, 177–178
bounded updates, 262
broadcast networks, 339
 IPv6 static routes, configuring, 94
broadcast updates, 138
building process for OSPF adjacencies, 358–362
bytes, 770

C

C class IP addresses, 18–19

- address masks, 20
- octet boundaries, 26
- subnetting, 24–25

calculating

- host addresses for subnets, 27–28
- hosts per subnet requirements, 25
- IGRP default metric, 260–261
- place values, 769

calling ACLs, 792–793

- access-class command, 794

case studies

- IPv6 redistribution with route maps, 759–760
- policy routing, 737–740
 - and QoS, 744–747*
 - and redistribution, 747–751*
 - router configuration, 743*
 - standard IP access lists, 740–742*
- protocol migration, 711, 714–716
 - routing loops, 712–714*
- RIP configuration, 178–180
- route filtering, 708–709
 - filtering by routing process, 710*
- route tagging, 752–758

categories of ACLs, 775

CCIE exam, preparing for, 803–804

- certification path, 805
- exam day, 807
- hands-on experience, 805
- study materials, 805–807
- training classes, 804

CDP (Cisco Discovery Protocol), 90, 680–681

- enabling, 697

cdp enable command, 698

cdp run command, 698

CEF (Cisco Express Forwarding), 104

- per destination load sharing, 103

Cerf, Vint, 5, 49

certification path for CCIE exam, 805

characteristics of distance vector protocols, 138

- broadcast updates, 138
- full routing table updates, 139
- neighbors, 138

Checksum field

- LSAs, 366

- TCP, 44

CIDR (Classless Interdomain Routing), 296–297

circular sequence number space, 150–151

Cisco IOS Software, switching method

- determination, 106

classes of IP addresses, 18

classful routing, 23

- RIP, 169, 175–178

- replies, 170*

- requests, 170*

- subnetting, 176*

- summarization, 177*

classless route lookups, 205–206, 682

classless routing, 24, 206

- redistribution into classful domains, 639–640

- unmatching masks, 641–642*

clear arp-cache command, 34, 45

clear ip accounting command, 801

CLNP (Connectionless Network Protocol), 513

columns in route tables, 82

command field (RIPv2), 202

commands, 46, 123

- access class, 794

- access-list compiled, 789

- arp, 45, 123

- arp timeout, 45

- auto-cost reference-bandwidth, 345

- cdp enable, 698

- cdp run, 698

- clear arp-cache, 34, 45

- clear ip accounting, 801

- config-router, 179

- debug arp, 32

- debug igrp neighbors, 321

- debug ip icmp, 45

- debug ip packet, 123

- debug ip policy, 739

- debug ip rip, 180, 193

- debug ipv6 packet, 123

- default metric, 644

- default-information originate, 691–693

- always keyword, 694*

- for IPv6 addresses, 695–697*

- distance, 711–712, 715, 719–722

- distribute-list, 703, 706, 717–718

eigrp stub, 310
ip access-group, 792–793
ip accounting access-violations, 801
ip address, 45, 193
ip cef, 123
ip classless, 682, 698
ip default network, 687–690
ip default-network, 698
ip load-sharing per packet, 104
ip netmask-format, 24, 46
ip ospf cost, 389
ip ospf dead-interval, 338
ip ospf priority, 346
ip ospf transmit-delay, 346
ip policy route-map, 743
ip policy-route map, 737
ip proxy-arp, 46, 123
ip rip triggered, 190
ip route, 123
ip route cache, 123
ip router isis, 574
ipv6 cef, 123
ipv6 nd prefix, 71
ipv6 route command, 123
ipv6 unicast-routing, 123
isis isp-interval, 572
lsp-gen-interval, 572
maximum-paths, 393
metric weights, 268
metric-style wide, 560
neighbor, 193
network, 178, 194
network area, 412–413
no ip proxy-arp, 36
no ip redirects, 40
offset-list, 187, 194
output-delay, 193–194
passive-interface, 182, 194
redistribute connected, 665
redistribute eigrp, 754
router, 179
router odr, 697–698
router rip, 178, 194
set ip next-hop verify-availability, 738
show arp, 34
show cdp, 90
show cdp neighbor detail, 123
show clns is-neighbors, 608
show clns is-neighbors detail, 597
show interface, 256
show ip access list, 800
show ip accounting access-violations, 801
show ip cef, 123
show ip eigrp topology, 268
show ip ospf database, 374
show ip ospf database nssa-external, 409
show ip ospf interface, 344
show ip ospf neighbor, 351–352
show ip route, 83, 123
show ipv6 cef, 123
show ipv6 detail, 123
show ipv6 interface, 123
show ipv6 rip, 228
show ipv6 route, 123
show isis database, 529
summary address, 652
timers active time, 275
timers basic, 194
trace, 12
variance, 300
which route, 534

comparing
OSPFv2 and OSPFv3, 478–479
RIPng and RIPv2, 213

compatibility of RIPv2 and RIPv1, 205

compatibility switches, 205, 215–217

config-router command, 179

configuring, 187–190
ACLs, keywords, 796–797
default routes, 681–682

- in IPv6, 695–697*
- ip default-network command, 687–690*

dual-protocol routing, 711–716
EIGRP, 297–299

- address summarization, 315–316*
- authentication, 316–317*
- maximum paths for load sharing, 302–304*
- multiple processes, 305–306*
- stub routing, 309–315*
- unequal-cost load balancing, 299–302*

extended IP ACLs, 785–789

- sequence number, 786*

floating static routes, 97–100
ICMP ACLs, 791–792

-
- IPv6 floating static routes, 100–101
IS-IS
authentication, 587–591
IPv4, 574–579
IPv6, 591–595
multiple area addresses, 581–584
multiple L1 areas, 604–606
multiple topology mode, 596–598
route leaking, 598–603
route summarization, 585, 587
routers, 579–581
load sharing, 102
CEF, 103–104
named ACLs, 797
ODR, 697
OSPF, 411–413
address summarization, 435–440
authentication, 441–444
Domain Name Service lookups, 417–418
LSA filtering, 441
network area command, 412–413
NSSAs, 428–434
on NBMA networks, 446–454
over demand circuits, 454–455
Router IDs, 415–417
secondary addresses, 418–422
stub areas, 423–426
totally stubby areas, 426–428
virtual links, 444–445
OSPFv3, 494–497
multiple instances on a link, 499
on NBMA networks, 500–505
stub area, 497–498
policy routing, 737–740
and QoS, 744–747
and redistribution, 747–751
global router configuration, 743
standard IP access lists, 740–742
redistribution, 642
EIGRP into OSPF, 646–651
IGRP into RIP, 645–646
metrics, 643–644
reflexive ACLs, 794
example, 795–796
parameters, 794
RIP, 178–180
discontiguous subnets, 184–187
metrics, 187–190
passive interfaces, 181–182
unicast updates, 182–184
RIPng, 224–232
global parameters, 232–233
RIPv2, 214
authentication, 222–224
route maps, 734–736
route tagging, 754–758
standard IP ACLs, 782–784
Boolean AND/OR functions, 784
inverse masks, 785
static routes, 84
IPv4, 85–89
IPv6, 90–94
TCP ACLs, 790
UDP ACLs, 791
virtual links, 374
connection-oriented services, TCP, 41–42
control protocols, ICMPv6 header format, 63–64
convergence, 135–137
after router reboot in redistributed protocol environment, 635–637
converting
binary to hex, 772–773
decimal to binary, 771
routing protocols, 711–716
CoS (Class of Service), 9
cost metric, 135, 155, 345, 389
counting to infinity, 142–144
cryptographic checksum, MD5, 211
CSNPs (Complete SNPs), 527, 552

D

data links

- address masks, 21
IP addresses
masks, 20–21
subnets, 24
TCP/IP, 6

data structure of OSPF neighbors

- components, 345–348, 352–353

- Database Description packets (OSPF),** 399–400
data-link identifiers, ARP, 30
DC-bit, 395
DD (Database Description) packets, 358
debug arp command, 32
debug eigrp neighbors command, 321
debug ip icmp command, 45
debug ip packet command, 123
debug ip policy command, 739
debug ip rip command, 180, 193
debug ipv6 packet command, 123
debugging route table entries, 96
decimal numbering system, 769
 converting to binary, 771
 converting to hexadecimal, 772–773
 IP addresses, 17
decision points for OSPF adjacency formation, 357
decision process (IS-IS), 531–534
default metrics, IGRP
 calculating, 260–261
 modifying, 257
default networks, 253
 advertising, 690
default routes, 677–679, 683
 classless route lookups, 682
 configuring, 681–682
 IPv4, 695–697
 in IPv6, 695
 ip default-network command, 687–690
 filtering, 706
 flapping, 694
 gateway of last resort, 683
 in hub-and-spoke topologies, 678
 large-scale use of, 678
 redistribution, 693
 risk of suboptimal routing, 679
 static, 682
 “*don’t care*” bits, 683
 redistribution, 684–686
default IGRP timers, modifying, 255
default-information originate command, 691–693
 always keyword, 694
 for IPv6 addresses, 695–697
default-metric command, 644
delay metric, 135, 255–257
 modifying, 257
delayed acknowledgments, 365
demand circuits, 393
 OSPF, configuring, 454–455
 presumption of reachability, 394
depletion of IPv4 addresses, 49
designated routers (IS-IS), 523–526
designing
 lollipop-shaped address spaces, 152
 subnets, 24–25
Destination Address field (IPv6 packets), 60
destination ports, TCP, 43
devices, boundary routers, 177–178
DF bit, 10
DiffServ (Differentiated Services framework), 9
diffusing computations, 262
 feasible successor selection process, 273–287
digits, 769
Dijkstra, E.W., 266
Dijkstra’s algorithm, 156–159
direct acknowledgments, 366
directly connected subnets, 176
disabling
 automatic summarization on EIGRP, 307–309
 split horizon, 722
 summarization on RIPv2, 221
discontiguous subnets, 85, 178
 configuring, 184–187
 RI, 185
 summarizing RIPv2 routes across, 220–222
displaying
 IGRP delay, 256
 IPv6 addresses, 90
 IS-IS link state database, 529–530
 IS-IS neighbor table, 523
 RIPng processes, 228
distance command, 711–712, 715, 719–722
distance vector routing protocols, 137, 261
 asynchronous updates, 145–146
 characteristics of, 138
 broadcast updates, 138
 full routing table updates, 139
 neighbors, 138
 periodic updates, 138

counting to infinity, 143–144
 holdown timers, 144–145
RIP
configuring, 178–180
metrics, configuring, 187–190
 route filtering, 702
 route invalidation timers, 140–141
 routing by rumor, 139–140
 split horizon, 141
 triggered updates, 144
distributed database protocols. *See link-state protocols*
distribute-list command, 703, 706, 717–718
domain authentication, IS-IS configuration, 590–591
Domain Name Service lookups, OSPF
configuration, 417–418
domains
 OSPF, areas, 368
 IS-IS, domain-wide prefix distribution extension, 556–557
Don’t Fragment (DF) bit, 10
dotted-decimal format, 17, 24
Down state (OSPF neighbors), 353
DRs (Designated Routers), 341
 DRothers, 344
 election process, 342–344
DSCP (Differentiated Services Code Point), 9
DUAL (Diffusing Update Algorithm), 266–267
 feasible successors, selection process, 270–287
 input events, 273
dual-protocol routing, configuring, 711–716
Duplicate Address Detection, 73–74
dynamic ACLs, 786
Dynamic Hostname Exchange, 562
dynamic routing protocols, RIP. *See RIP (Routing Information Protocol)*

E

echo packets, tracing, 112
Echo Request/Reply messages (ICMP), 39–40
ECN (Explicit Congestion Notification), 10
editing
 ACLs, 780
 route maps, 735
EGPs (Exterior Gateway Protocols), 162

EIGRP (Enhanced Interior Gateway Routing Protocol), 263

address aggregation, 293–296
CIDR, 296–297
 address summarization, configuring, 315–316
 adjacencies, 267
 authentication, configuring, 316–317
 automatic summarization, disabling, 307–309
 configuring, 297–299
 diffusing computations, 262
DUAL, 266–267
 feasible successors, selection process, 270–284, 287
 input events, 273
 load sharing, configuring maximum paths, 302–304
 metrics, 270
delay, 268
FC, 267
FD, 267
feasible successors, 267
variance, 300
 missing neighbors, troubleshooting, 318–323
 multiple processes, configuring, 305–306
 neighbor discovery/recovery, 265–266
 neighbor table, 266
 packets, 264
header format, 288–289
Hello, 265
sequence numbers, 264
TLVs, 289–293
 protocol-dependent modules, 264
Q Count, 266
 redistribution into OSPF, 656
configuring, 646–651
RTO, 265–266
RTP, 264
SRTT, 265
 stub routing, configuring, 309–315
 stuck-in-active neighbors, troubleshooting, 323, 325–327
 summarization, 654–655
 timers, multicast flow timer, 265
 topological table, contents of, 268
 troubleshooting, 317
 unequal-cost load balancing, configuring, 299–302
 updates, 262
eigrp stub command, 310

election process for DRs/BDRs, 342–344
electrical protocols, 6
embedded IPv4 addresses, 58
enabling
 CDP, 697
 classless route lookups, 206
 per packet load sharing, 104
 process switching, 105
encapsulation (SNAP), ARP, 34
environments, 24
EPHOS (European Procurement Handbook for Open Systems), 513
equal-cost load balancing, 102, 175
error correction in IP packets, 13
ES (End System), 515
establishing adjacencies
 decision points, 357
 OSPF, 351
Ethernet, 184
examples
 of diffusing computations, 276–284, 287
 of extended IP ACLs, 787–788
 of reflexive ACLs, 795–796
exams, CCIE
 certification path, 805
 preparing for, 803–807
 training classes, 804
Exchange state (OSPF neighbors), 354
expiration timer, RIP, 171
explicit acknowledgments, 359, 364
ExStart state (OSPF neighbors), 354
extended IP ACLs, 785, 789
 effect on system performance, 788
 example of, 787–788
 features, 786–787
 placement of, 799
 sequence numbers, 786
extended metrics, 596
Extended Ping utility, 10
extension headers, 61–63
 functions performed, 62
extensions to IS-IS
 3-way handshaking, 555
 domain-wide prefix distribution, 556–557
 Dynamic Hostname Exchange, 562
 IPv6 routing, 560
 mesh groups, 566–571

 Multi Topology routing, 562–564
 wide metrics, 558
exterior routes, 253
External Attributes LSAs, 383–385
external routes, 532
 summarization, 435
external traffic, 369

F

failed routes, tracing, 109–112
 IPv6, 120–122
fast switching, per destination load sharing, 105
FC (feasible condition), 267
FD (feasible distance), 267, 270
feasible successors, 267
 diffusing computations, 273–284, 287
 selection process, 270–276
features
 of extended IP ACLs, 786–787
 of OSPF, 335
 of TCP ACLs, 790
fields
 of IS-IS Hello PDUs, 541
 of IS-IS LSPs, 546–547
 of RIPng messages, 214
 of TCP header, 42–44
filter layers, numbering, 778, 780
filtering
 implicit deny any, 777
 IPv6 routes, 704–705
 prefix lists, 798
 sequentiality, 778
first octet rule, 18–20
Flags field (TCP), 43
flapping routes, 694
flash updates. *See triggered updates*
Fletcher algorithm, 366
floating static routes, 97–100
 IPv6, 100–101
flooding, 147
 LSAs, 363
 acknowledgments, 364–366
 checksum, 366

sequence numbers, 148–149, 366
circular sequence number space, 150–151
linear sequence number space, 149–150
lollipop-shaped sequence number space, 152–153
flooding delays (IS-IS), 571–573
Flow Label field (IPv6 packets), 59
Floyd, Sally, 145
flush timer (RIP), 171
format
 of IPv6 multicast addresses, 57
 of OSPFv3 LSAs, 484
 AS-External LSAs, 488–489
 Inter-Area Prefix LSAs, 486–487
 Inter-Area Router LSAs, 487
 Intra-Area Prefix LSAs, 491–493
 Link LSAs, 489–491
 Network LSAs, 486
 Router LSAs, 484–486
 of RA messages, 66
 of Redirect messages, 69
 of RIPng messages, 213–214
 of RIPv2 messages, 201–204
formation of OSPF adjacencies, 351
 decision points, 357
Fragment Offset field (IP packets), 11
fragmenting IP packets, 10
fragments, processing through ACLs, 787
Frame-Relay mapping, OSPFv3, 506–509
full routing table updates, 139
Full state (OSPF neighbors), 354
functional protocols (TCP/IP), 6

G

garbage collection (RIP), 171
gateway of last resort, 683
general TLV fields, 289
global parameters for RIPng configuration, 232–233
global unicast addresses, 53
GOSIP (Government Open Systems Interconnection Profile), 513

gratuitous ARP, 36
Group Membership LSAs, 385
group pacing, 377

H

Hardware Address Length field (ARP packets), 33
Hardware Type field (ARP packets), 33
Header Checksum field (IP packets), 13
Header Length field
 IP packets, 8
 TCP packets, 43
headers
 EIGRP packet format, 288–289
 IP packets, 7–8
 flags, 10
 Fragment Offset field, 11
 Header Checksum field, 13
 identifiers, 10
 Options field, 14–16
 options field, 14
 size, 8
 TOS, 8
 total length, 10
 TTL field, 12–13
 IS-IS PDU fields, 535–536
 TCP, 42–43
 UDP, 44–45
Hedrick, Charles, 169
Hello packets
 EIGRP, 264
 hold time, 265
 OSPF, 338–339, 398–399
Hello PDUs, 539
 Area Addresses TLV, 542–543
 Authentication Information TLV, 544
 fields, 541
 Intermediate System Neighbors TLV, 543
 IP Interface Address TLV, 545
 Padding TLV, 543
 Protocols Supported TLV, 545
Hello protocol, 147, 338
HelloInterval, 338

- hexadecimal numbering system, 769–772**
converting to decimal, 772–773
IP address format, 24
hexadecimal IPv6 representation, 51
- hippit bit, 528**
- holddown**
RIP, 172
IGRP, 255
- holddown timers, 144–145**
- hop count metric, 134, 170–173**
- Hop Limit field (IPv6 packets), 60**
- host addresses, subnet mask octet boundaries, 26**
- hosts**
IP addresses, 16–17
quantity per subnet requirement, calculating, 25
- host-to-host layer (TCP/IP)**
TCP, 41–44
UDP, 44–45
- Host-to-Host Layer Protocol, 13**
- “hot potato” routing, 392**
- hub-and-spoke topologies**
ODR, 680
stub routers, 678
- Huitema, Christian, 514**
- ICMP (Internet Control Message Protocol), 37–38**
ACLs, 791–792
echo packets, tracing, 112
Echo Request/Reply messages, 39–40
redirect packets, 40
Router Advertisement packets, 40
Router Selection packets, 40
- ICMPv6 header format, 63–64**
- identifying IPv6 address types, 54**
- IGPs (Interior Gateway Protocols), 161**
- IGRP (Interior Gateway Routing Protocol), 253**
default timers, modifying, 255
delay, 256–257
holddown, 255
load, 259
metrics, 255
modifying, 256–257
- process domains, 252**
redistribution into RIP, configuring, 645–646
reliability, 258–259
similarities to RIP, 251
timers
90-second, 254
sleeptime, 255
- Implicit Acknowledgments, 359**
- implicit acknowledgments, 364**
- implicit deny any filter, 777**
- improving SPF efficiency on IS-IS networks, 573–574**
- InfTransDelay, 366**
- Init state (OSPF neighbors), 354**
- input events, 273**
for OSPF interface state machine, 350
for OSPF neighbors, 356–357
- inter-area paths, 391**
- Inter-Area Prefix LSAs, 486–487**
- Inter-Area Router LSAs, 487**
- inter-area summarization, 435**
- inter-area traffic, 369**
- Inter-Domain Routing Protocol**
Information TLV, 551
- Interface ID, 53**
- interface state machine (OSPF), 348–349**
input events, 350
- interfaces, OSPF, 344**
data structure, 344–348
input events, 350
states, 348–349
- interface-specific summarization, 653**
- interior routes, 252**
- Intermediate System Neighbors TLV, 549**
- internal routers, 369**
- internal routes, 532**
- Internet layer (TCP/IP), 6**
- internetwork IP addresses, 17–18**
- intra-area paths, 391**
- Intra-Area Prefix LSAs, 491–493**
- intra-area traffic, 369**
- Intradomain Routing Protocol Discriminator, 535**
- invalid timers**
IGRP, 254
RIP, 171
- invalid updates, sources of, 210**

- inverse masks, 784–785
- ip access-group command, 792–793**
- ip accounting access-violations command, 801**
- ip address command, 45, 193**
- IP Address field**
 - RIP, 173
 - RIPv2, 203
- IP addresses, 16–17**
 - bitcount format, 24
 - dotted decimal format, 24
 - dotted-decimal format, 17
 - first octet rule, 18–20
 - hexadecimal format, 24
 - internetworks, 17
 - masks, 20–21
 - prefix lists, 798
 - reverse ARP, 36
 - RIP, 173
 - subnet masks, troubleshooting, 29
 - subnets, 22–24, 27–28
 - designing, 24–26*
 - summary routes, 94
- IP packets, 7**
 - flags, 10
 - Fragment Offset field, 11
 - Header Checksum field, 13
 - header length, 8
 - identifiers, 10
 - Options field, 14–16
 - Protocol field, 13
 - TOS (Type of Service), 8
 - total length, 10
 - TTL (Time to Live) field, 12
 - versions of, 8
- ip cef command, 123**
- ip classless command, 682, 698**
- ip default-network command, 687–690, 698**
- IP External Reachability TLV, 551**
 - U/D bit, 556
- IP External Routes TLV, 291–293**
- IP Interface Address TLV, 545**
- IP Internal Reachability TLV, 550–551**
 - U/D bit, 556
- IP Internal Routes TLV, 290–291**
- ip load-sharing, 123**
- ip load-sharing command, 123**
- ip load-sharing per-packet command, 104**
- ip netmask-format, 24**
- ip netmask-format command, 24, 46**
- ip ospf cost command, 389**
- ip ospf dead-interval command, 338**
- ip ospf priority command, 346**
- ip ospf transmit-delay command, 346**
- ip policy route-map command, 737, 743**
- ip proxy-arp command, 46, 123**
- ip redirects command, 46**
- ip rip triggered command, 190**
- ip route command, 123**
- ip route-cache command, 123**
- ip router isis command, 574**
- IP-specific TLV fields, 290**
- IPv4, 8**
 - configuring on IS-IS, 574–579
 - depletion of, 49
 - static routes, configuring, 85–89
- IPv6, 8**
 - address representation, 50–51
 - anycast addresses, 55–56
 - configuring on IS-IS, 591–595
 - default-information originate command, default route configuration, 695–697
 - double colon representation, 51
 - embedded IPv4 addresses, 58
 - extension headers, 61–63
 - failed routes, tracing, 120–122
 - floating static routes, 100–101
 - global unicast addresses, 53
 - identifying address types, 54
 - local unicast addresses, 55
 - modifying static entries on replaced routers, 116–120
 - multicast addresses, 56–57
 - NDP, 64–65
 - address autoconfiguration, 71–73*
 - Duplicate Address Detection, 73–74*
 - messages, 65*
 - Neighbor Address Resolution, 74–75*
 - Neighbor Unreachability Detection, 76–77*
 - privacy addresses, 75–76*
 - router discovery, 70–71*
 - need for, 50
 - packet header format, 58–60

- prefixes, 52
 redistribution with route tags, 759–760
RIPng, 212
 - configuring*, 224–232
 - next-hop route entries*, 214
 - route summarization*, 235
 route filtering, 704–705
 routing with IS-IS, 560
 static routes, configuring, 90–94
 unspecified addresses, 52
- ipv6 cef command**, 123
- ipv6 nd prefix command**, 71
- IPv6 Prefix field (RIPng messages)**, 214
- ipv6 route command**, 123
- ipv6 unicast-routing command**, 123
- IS (intermediate system)**, 515
- IS-IS (intermediate System-to-Intermediate System)**, 513
 - adjacencies, 517
 - troubleshooting*, 607–610
 - areas, 516
 - authentication, configuring, 587–591
 - extensions
 - 3-way handshaking*, 555
 - domain-wide prefix distribution*, 556–557
 - Dynamic Hostname Exchange*, 562
 - IPv6 routing*, 560
 - mesh groups*, 566–571
 - Multi Topology routing*, 562–564
 - wide metrics*, 558
 - flooding delay, 571–572
 - controlling*, 572–573
 - IPv4, configuring, 574–579
 - IPv6, configuring, 591–595
 - layered network architecture, 521
 - subnetwork dependent functions*, 521–526
 - subnetwork independent functions*, 526–534
 - link-state database
 - displaying*, 529–530
 - troubleshooting*, 607, 610–614
 - LSPs, 546
 - fields*, 546–547
 - Inter-Domain Routing Protocol Information TLV*, 551
- Intermediate System Neighbors TLV*, 549
- IP External Reachability TLV*, 551
- IP Internal Reachability TLV*, 550–551
- TLVs*, 547–548
- multiple area addresses, configuring, 581–584
 multiple L1 areas, configuring, 604–606
 multiple topology mode, configuring, 596–598
 neighbor table, displaying, 523
NETs, 519
 - format*, 519–520
 - selecting*, 520
- on NBMA networks, troubleshooting, 615–619
- PDUs**
 - format*, 534
 - header fields*, 535–536
 - Hello PDU format*, 539
 - Hello PDUs*, 541–545
 - IS-IS LSPs*, 546–551
 - IS-IS Sequence Number PDU format*, 552–553
 - TLV fields*, 536–539
- redistribution into RIP/RIPng, 663–669
 route leaking, configuring, 598–603
 route summarization, configuring, 585–587
 router types, configuring, 579–581
 similarities with OSPF, 514
 SNPs, 527
 SPF efficiency, improving, 573–574
 System ID, 519
 troubleshooting, 606
 virtual link support, 518
- isis lsp-interval command**, 572
- IS-IS Sequence Number PDUs**, 552
 - LSP Entries TLV, 553

J–K

Jacobson, Van, 145

- Kahn, Bob**, 5, 49
- key chains**, configuring for RIPv2
 - authentication**, 223
- keywords for ACL configuration**, 796–797

L

- L1 LSPs, TLVs**, 547
- L1 routers**, 517
- L1/L2 routers**, 517
- L2 LSPs, TLVs**, 548
- L2 routers**, 517
- LAN Hellos**, 540
- layered network architecture, IS-IS**, 521–534
- Level 3 Routing**, 162
- linear sequence number space**, 149–150
- link costs**, 155
- Link LSAs**, 489, 491
- Link State Acknowledgment packets (OSPF)**, 402
- link state refresh process**, 376
- Link State Request packets (OSPF)**, 400
- Link State Update packets (OSPF)**, 401
- link-local unicast addresses**, 55
- links, OSPF**, 344
- link-state advertisements**, see **LSAs**
- link-state database**, 147, 154–156, 336, 363, 374
 - IS-IS**
 - displaying*, 529–530
 - troubleshooting*, 607, 610–614
 - LSA group pacing**, 377
- link-state routing protocols**, 146, 262
 - areas**, 160–162
 - Dijkstra's algorithm, 156–157
 - router adaptation*, 157–159
 - flooding, 147
 - sequence numbers*, 148–153
 - IS-IS**. *See* **IS-IS**
 - LSAs**, 146–147
 - aging process*, 153–154
 - OSPF**. *See* **OSPF**
 - neighbor discovery, 147
 - route filtering, 702
- LIRs (Local Internet Registries)**, 54
- load (IGRP)**, 259
- load balancing**, 137, 175
 - unequal-cost, EIGRP configuration, 299–302
- load sharing**
 - CEF, 103–104
 - configuring, 102
 - maximum paths, EIGRP configuration, 302–304
 - per destination, 103–105, 301
- per packet**
 - enabling*, 104
 - process switching*, 105–106
- Loading state (OSPF neighbors)**, 354
- local computations**, 273
- local unicast addresses**, 55
- lollipop-shaped sequence number space**, 152–153
- lookups**
 - classless, 682
 - recursive, 107–109
- loopback interfaces**, 337, 340
- LSAs (link-state advertisements)**, 146–147, 336, 402, 702
 - acknowledgments**, 359
 - during flooding process*, 364–366
 - aging process**, 153–154
 - ASBR Summary LSAs**, 382
 - Autonomous System External LSAs**, 408–409
 - External Attributes LSAs**, 385
 - filtering, OSPF configuration**, 441
 - flooding**, 147, 363, 366
 - checksum*, 366
 - sequence numbers*, 148–150, 152–153
 - Group Membership LSAs**, 385
 - group pacing**, 377
 - header format**, 403
 - Network LSAs**, 379–381, 406
 - Network Summary LSAs**, 381–382, 407–408
 - NSSA External LSAs**, 385, 409
 - Opaque LSAs**, 385
 - Options field**, 410
 - OSPFv3**, 481–483
 - format**, 484
 - Inter-Area AS-External LSAs**, 488–489
 - Inter-Area Prefix LSAs**, 486–487
 - Inter-Area Router LSAs**, 487
 - Intra-Area Prefix LSAs**, 491–493
 - Link LSAs**, 489–491
 - Network LSAs**, 486
 - Router LSAs**, 484–486
 - Router LSAs**, 378–379, 403–406
 - sequence numbers**, 367
 - types of**, 377
- LSP Entries TLV**, 553
- lsp-gen-interval command**, 572
- LSPs**
 - ATT**, 518
 - flooding delays, 571–573
 - controlling, 572–573

M

MAC addresses, ARP, 31
MAC-to-EUI64 conversion, 72–73
masks, 176. *See also subnet masks*
 octet boundaries, 25–27

MaxAge timer, link state refresh, 376
maximum-paths command, 393
MD5, 211
mechanical protocols (TCP/IP), 6
medium internetworks, 18
medium networks, 18
mesh groups, 566–571
messages
 ICMP, Echo Request/Reply, 39–40
 NDP, 65
 OSPFv3, 479–480
 RIP, 172–175
 RIPng, 213–214
 RIPv2, 201–204

Metric field
 RIP, 173
 RIPng, 214

metric weights command, 268

metrics, 84, 133. *See also administrative distance*
 and redistribution, 633
 bandwidth, 134–135
 cost, 135, 155, 345, 389
 delay, 135
 EIGRP, 270
delay, 268
FC, 267
FD, 267, 270
feasible successors, 267
variance, 300

hop-count, 134
IGRP, 255
default metric, calculating, 260–261
load, 259
modifying, 256
reliability, 259
 redistribution, configuring, 643–644
 reliability, 135
RIP, 170, 187–190
 RIPng, adjusting, 233–235
 triggered updates, 144

metric-style wide command, 560
MF bit (More Fragments), 11
microflows, 59
 migrating to new routing protocols, 711–716
 minimizing impact of updates on RIP, 190–193
minimumLSPTransmissionInterval, 528
 misconfigured OSPF summarization,
 troubleshooting, 463–466
 missing EIGRP neighbors, troubleshooting,
 318–323
 missing route table entries, 83
modifying
 cost metric, 345
 IGRP default metrics, 256–257
 IGRP default timers, 255
 RouterDeadInterval, 338
More Fragments (MF) bit, 11
MOSPF (Multicast OSPF), 385
MT (Multi Topology) routing, 562–564
MTU (Maximum Transmission Unit), 10
 IP packets, 10
multiaccess, 446
multicast addresses, 56–57
multicast flow timer, 265
multiple area addresses, configuring on IS-IS,
 581–584
multiple EIGRP processes, configuring, 305–306
multiple L1 areas, IS-IS configuration, 604–606
multiple topology mode, IS-IS configuration,
 596–598
mutual redistribution, 657, 701
 at multiple redistribution points, 716–722

N

NA (Neighbor Advertisement) messages, 65
 format, 68
named ACLs, 780, 797
NAT (Network Address Translation), 49
NBMA networks, 340
 IS-IS, troubleshooting, 615–619
 OSPF, configuring, 446–454, 500–505
NDP (Neighbor Discovery Protocol), 64–65
 address autoconfiguration, MAC-to-EUI64
 conversion, 71–73
 Duplicate Address Detection, 73–74
 messages, 65–66

Neighbor Address Resolution, 74–75
 neighbor discovery, 70–71
 Neighbor Unreachability Detection, 76–77
 privacy addresses, 75–76
Neighbor Address Resolution, 74–75
neighbor command, 193

neighbor state machine (OSPF), 353–357
neighbor table, 337
 EIGRP, 266
Neighbor Unreachability Detection, 76–77
neighbors, 138
 adjacencies
formation of, 351
troubleshooting, 456–458
 discovery/recovery
adjacencies, 147
EIGRP, 265–266
 EIGRP, adjacencies, 267
 IS-IS, 522–523
 OSPF, 350
adjacency building process, 358–362
data structure, 351–353
input events, 356–357
NETs (Network Entity Titles)
 format, 519
 selecting, 520
network area command, 412–413
network command, 178, 194
Network LSAs, 379, 406, 486
Network Summary LSAs, 382, 407–408
Next Header field (IPv6 packets), 60
Next Hop field (RIPv2), 203
next-hop addresses on replaced routers,
troubleshooting, 116–120
next-hop route entries (RIPng), 214
NLA (Next-Level Aggregator), 53
no ip proxy-arp command, 36
no ip redirects command, 40
nonperiodic updates, 262
not-so-stubby areas, 387–389
NPDUs (Network Protocol Data Units), 515
NS (Neighbor Solicitation) messages, 65
NS messages, format, 67
NSSA External LSAs, 385, 409
NSSAs (not-so-stubby areas), 388–389
configuring, 428–434
null interface, 656

numbering ACL filter layers, 778–780

numbering systems
 binary, 769–770
 hexadecimal, 769–773
 place values, 769

O

octets, 770–773
 binary, 770
 boundary subnet masks, 25–27
 hexadecimal, 771–772
 subnetting, 26
ODR (On-Demand Routing)
 CDP, 680–681
 configuring, 697
 redistribution, 697
offset lists, RIP, 189
offset-list command, 187, 194
OL (Overload) bit, 528
opaque LSAs, 385
operation of OSPFv3, 477
Operation field (ARP packets), 33–34
operators
 Boolean AND function, 21, 784–785
 Boolean OR function, 784
optical protocols, 6
Options field
 IP packets, 14–16
 LSAs, 410
 TCP, 44
OSPF (Open Shortest Path First). See also OSPFv3
 ABRs, 369
 address summarization, configuring, 435–440
 adjacencies, 336–337
formation of, decision points, 357
troubleshooting, 456–458
 areas, 367
Area ID, 368
backbone, 369
maximum size of, 369
not-so-stubby areas, 387–389
partitioned areas, 371
path types, 391
stub areas, 386
totally stubby areas, 387
traffic types, 369

- area-wide problems, troubleshooting, 459
- ASBRs, 370
- authentication, 393
 - configuring*, 441–444
- backbone routers, 370
- BDRs, 342
 - election process*, 342–344
- broadcast networks, 339
- configuring, 411–413
 - on NBMA networks*, 446–454
 - over demand circuits*, 454–455
- cost metric, modifying, 345
- DD packets, 358
- Domain Name Service lookups, configuring, 417–418
- DRs, 341
 - election process*, 342–344
- features of, 335
- Hello packets, 338–339
- Hello protocol, 338
- interface state machine, 348–349
 - input events*, 350
- interfaces, data structure, 344–348
- internal routers, 369
- isolated areas, troubleshooting, 460–463
- link state database, 374
 - LSA group pacing*, 377
- link state refresh process, 376
- link-state database, 336, 363
- links, 344
- loopback interfaces, 337
- LSAs, 402
 - ASBR Summary LSAs*, 382
 - Autonomous System External LSAs*, 408–409
 - External Attributes LSAs*, 385
 - filtering*, 441
 - flooding process*, 363
 - Group Membership LSAs*, 385
 - group pacing*, 377
 - header format*, 403
 - Network LSAs*, 379–381, 406
 - Network Summary LSAs*, 381–382, 407–408
 - NSSA External LSAs*, 385, 409
 - Opaque LSAs*, 385
 - Options field*, 410
- Router LSAs, 378–379, 403–406
 - sequence numbers*, 367
 - types of*, 377
- metrics, cost, 345, 389
- misconfigured summarization, troubleshooting, 463–466
- MOSPF, 385
- NBMA networks, 340
- neighbor table, 337
- neighbors, 350
 - data structure*, 351–353
 - input events*, 356–357
 - state machine*, 353–357
- NSSAs, 388–389
 - configuring*, 428–434
- over demand circuits, 393
- oversubscription, 394
- packets, 395–396
 - Database Description packets*, 399–400
 - header format*, 396–398
 - Hello packets*, 398–399
 - Link State Acknowledgment packets*, 402
 - Link State Request packets*, 400
 - Link State Update packets*, 401
- point-to-multipoint networks, 340
- point-to-point networks, 339
- PollInterval, 351
- presumption of reachability, 394
- pseudonodes, 341
- redistribution into EIGRP, configuring, 646–651
- reference bandwidth, 345
- refresh process versus IS-IS Update process, 526
- route table entries, lookups, 393
- Router IDs, 337
 - configuring*, 415–417
- RouterDeadInterval, 338
- routing table entries
 - destination types*, 390–391
 - path types*, 391–392
- secondary addresses, configuring, 418–422
- similarities with IS-IS, 514
- stub areas, configuring, 423–426
- stub networks, 340
- totally stubby areas, configuring, 426, 428
- transit networks, 340

- troubleshooting, 455–456
- virtual links, 340, 373
 - configuring*, 374, 444–445
- OSPFv3, 477**
 - configuring*, 494–497
 - Frame-Relay mapping, 506–509
 - LSAs, 481–483
 - AS-External LSAs*, 488–489
 - format*, 484
 - Inter-Area Prefix LSAs*, 486–487
 - Inter-Area Router LSAs*, 487
 - Intra-Area Prefix LSAs*, 491–493
 - Link LSAs*, 489–491
 - Network LSAs*, 486
 - Router LSAs*, 484, 486
 - messages, 479–480
 - multiple instances on a link, configuring, 499
 - on NBMA networks, configuring, 500–505
 - operation, 477
 - redistribution into RIPng, 657–663
 - stub areas configuring, 497–498
 - troubleshooting, 506
 - versus OSPFv2, 478–479
- out keyword, 706**
- output-delay command, 193–194**
- oversubscription, 394**

- P**
- packet filtering routers, 800**
- packets, 34**
 - ARP, 30–34
 - Hardware Address Length field*, 33
 - Hardware Type field*, 33
 - Operation field*, 33–34
 - Protocol Address Length field*, 33
 - EIGRP
 - header format*, 288–289
 - Hello*, 265
 - sequence numbers*, 264
 - TLVs*, 289–293
 - fragments, processing through ACLs, 787
 - Hello (OSPF), 338–339
 - ICMP, 37–39
 - Echo Reply*, 39
 - Echo Request*, 39
 - IP, 7
 - flags*, 10
 - Fragment Offset field*, 11
 - Header Checksum field*, 13
 - header length*, 8
 - identifiers*, 10
 - Options field*, 14–16
 - Protocol field*, 13
 - TOS (Type of Service)*, 8
 - total length*, 10
 - TTL field*, 12
 - IPv6, 58
 - Destination Address field*, 60
 - Flow Label field*, 59
 - Hop Limit field*, 60
 - Next Header field*, 60
 - Payload Length field*, 60
 - Source Address field*, 60
 - Traffic Class field*, 59
 - LSAs, 402
 - acknowledgment during flooding process*, 364–366
 - ASBR Summary LSAs*, 382
 - AS-External LSAs*, 488–489
 - Autonomous System External LSAs*, 408–409
 - External Attributes LSAs*, 385
 - Group Membership LSAs*, 385
 - header format*, 403
 - Inter-Area Prefix LSAs*, 486–487
 - Inter-Area Router LSAs*, 487
 - Intra-Area Prefix LSAs*, 491–493
 - Link LSAs*, 489–491
 - Network LSAs*, 379–381, 406, 486
 - Network Summary LSAs*, 381–382, 407–408
 - NSSA External LSAs*, 385, 409
 - Opaque LSAs*, 385
 - Options field*, 410
 - OSPFv3*, 481–484
 - Router LSAs*, 378–379, 403–406, 484–486
 - sequence numbers*, 367
 - types of*, 377

- OSPF, 395–396
 - Database Description*, 358
 - Database Description packets*, 399–400
 - header format*, 396–398
 - Hello packets*, 398–399
 - Link State Acknowledgment packets*, 402
 - Link State Request packets*, 400
 - Link State Update packets*, 401
- PDUs. *See* PDUs (Protocol Data Units)
- Padding TLV**, 543
- parameters**
 - of extended IP ACLs, 786–787
 - of reflexive ACLs, 794
- Partial Route Calculation**, 573
- partial updates**, 262
- partitioned areas**, 371
- passive interfaces**, configuring, 181–182
- passive state**, 273
- passive-interface command**, 182, 194
- path types (OSPF)**, 391–392
- Payload Length field (IPv6 packets)**, 60
- P-bit**, 388
- PDUs (Protocol Data Units)**, 515
 - format, 534
 - header fields, 535–536
 - Hello PDUs
 - Area Addresses TLV*, 542–543
 - Authentication Information TLV*, 544
 - fields*, 541
 - format*, 539
 - Intermediate System Neighbors TLV*, 543
 - IP Interface Address TLV*, 545
 - Padding TLV*, 543
 - Protocols Supported TLV*, 545
 - IS-IS LSPs, 546
 - fields*, 546–547
 - Inter-Domain Routing Protocol Information TLV*, 551
 - Intermediate System Neighbors TLV*, 549
 - IP External Reachability TLV*, 551
 - IP Internal Reachability TLV*, 550–551
 - TLVs*, 547–548
 - IS-IS Sequence Number PDU format, 552
 - LSP Entries TLV*, 553
 - TLV fields, 536–539
- per destination load sharing**, 105, 301
 - CEF, 103–104
- per packet load sharing**
 - enabling, 104
 - process switching, 105–106
- periodic updates**, 138
- Perlman, Radia**, 152, 514
- PHB (Per-Hop Behavior)**, 9
- physical layer (TCP/IP)**, 6
- place values of numbering systems**, 769
- placement of ACLs**, 799
- point-to-multipoint networks**, 340
- point-to-point connections**, TCP, 41
- point-to-point Hellos**, 540
- point-to-point networks**, 339
- policy routing**, 731
 - and QoS, 744–747
 - and redistribution, 747–751
 - case study, 737–40
 - match commands, 733
 - set commands, 734
 - standard IP access lists, case study, 740–743
- PollInterval**, 351
- port numbers**, 42
- ports**
 - sockets, 43
 - TCP, 43
- Prefix Length field (RIPng messages)**, 214
- prefix lists**, 798
- preparing for CCIE exam**, 803–804
 - certification path, 805
 - exam day, 807
 - hands-on experience, 805
 - study materials, 805–807
 - training classes, 804
- presumption of reachability**, 394
- privacy addresses**, 75–76
- procedural protocols**, 6
- process domains**, 252
- process switching**, 105–106
- promiscuous ARP**, 35–36
- Protocol Address Length field (ARP packets)**, 33
- protocol conflicts**, troubleshooting, 112, 115–116
- Protocol field**, 13
- protocol migration**, case study, 711–716
- protocol-dependent modules**, 264
- Protocols Supported TLV**, 545
- proxy ARP**, 35–36
 - resolving protocol conflicts, 115

pseudonodes, 341
PSNPs (Partial SNPs), 527 552

Q-R

Q Count, 266
QoS and policy routing, 744–747
queries, EIGRP, 264
query origin flags, 275

RA (Router Advertisement) messages, 65–66
RARP (Reverse ARP), 36
recursive table lookups, 107–109
Redirect messages, 65
 format, 69
redirects (ICMP), 40
redistribute connected command, 665
redistribute eigrp command, 754
redistribution
 administrative distances, 633–639
 and policy routing, 747–751
 and summarization, 652–657
 case study, 708–710
 classless to classful protocols, 639–640
 unmatching masks, 641–642
 configuring, 642
 conflicting metrics, 633
 convergence after router reboot, 635–637
 EIGRP into OSPF, 656
 configuring, 646–651
 IGRP into RIP, configuring, 645–646
 IPv6 addresses with route maps, 759–760
 IS-IS into RIP/RIPng, 663–669
 match commands, 733
 metrics, configuring, 643–644
 mutual redistribution, 701
 at multiple redistribution points, 716–722
 of default routes, 693
 of default static routes, 684–686
 of ODR-discovered routes, 697
 of static routes, 669–671
 into dynamic routing protocols, 632
 of static routes into OSPF, 631
 OSPFv3 into RIPng, 657–663

route feedback, 701
route tagging, 752–758
 tagged routes, filtering, 757
routing loops, 636–639
set commands, 733
SIN routing, 632
reference bandwidth, 345
reflexive ACLs, 794
 example, 795–796
 parameters, 794
reliability as IGRP metric, 135, 258–259
reliable multicast, 264
remarks, adding to ACLs, 783–784
replaced routers, troubleshooting next-hop addresses, 116–120
replies
 EIGRP, 264
 gratuitous ARP, 36
 ICMP, 39
 RIP, 170
representation of IPv6 addresses, 50
 double colon, 51
 prefixes, 52
Request messages (RIP), 170, 174–175
requests
 ARP, 30
 EIGRP, 264
 gratuitous ARP, 36
 ICMP, 39
 RIP, 170
Reserved field, TCP, 43
Response messages, RIP, 170
reverse ARP, 36
reverse routes, 141
RFCs, ICMP-related, 37
RIB (routing information base). *See route tables*
RIP (Routing Information Protocol), 169, 172.
 See also RIPng; RIPv1; RIPv2
 classful routing, 175–178
 subnetting, 176
 summarization, 177
 configuring, 178–180
 discontiguous subnets, 184–187
 metrics, 187
 equal-cost load balancing, 175

- hop counts, 170
- messages, 172–173
- metrics, configuring, 187–190
- offset lists, 189
- passive interfaces, configuring, 181–182
- redistribution into IGRP, configuring, 645–646
- redistribution into IS-IS, 663–669
- replies, 170
- Request messages, 174–175
- requests, 170
- silent hosts, 172
- similarities to IGRP, 251
- timers, 170–172
- triggered updates, 172
- troubleshooting, 193
- updates
 - minimizing impact of*, 190–193
 - unicast, configuring*, 182–184
- RIP_JITTER variable**, 170
- RIPng (Routing Information Protocol next generation)**, 212
 - authentication, 213
 - configuring, 224–232
 - global parameters, configuring, 232–233
 - message format, 213–214
 - metrics, adjusting, 233–235
 - misconfigured VLSM, troubleshooting, 236–242
 - next-hop route entries, 214
 - processes, displaying, 228
 - redistribution
 - into IS-IS*, 663–669
 - into OSPFv3*, 657–663
 - route summarization, 235
- RIPv1, compatibility with RIPv2**, 205
- RIPv2**, 201
 - authentication, 210–212
 - configuring*, 222–224
 - compatibility switches, 215–217
 - compatibility with RIPv1, 205
 - configuring, 214
 - messages, 202–204
 - misconfigured VLSM, troubleshooting, 236–242
 - similarity to RIPng, 213
 - summarization, 220–222
 - VLSM, 218–220
- RIRs (Regional Internet Registries)**, 54
- route feedback**, 701
- route filtering**, 701
 - case study, 708–709
 - filtering by routing process, case study, 710
 - specific routes, filtering, 703–708
 - tagged routes, filtering, 757
- route flapping**, 135
- route invalidation timers**, 140–141
- route leaking**, 556, 601
 - IS-IS configuration, 598–603
- route lookups, classless**, 205–206
- route maps**, 731
 - configuring, 734, 736
 - editing, 735
 - redistribution of IPv6 addresses, 759–760
 - sequence number, configuring, 734–735
- route redistribution**. *See* **redistribution**
- route summarization**. *See* **summarization**
- route tables**, 81
 - administrative distance, 98
 - columns, 82
 - entries
 - debugging*, 96
 - of static routes*, 89
 - floating static routes, IPv6, 100–101
 - metrics, 84
 - missing entries, 83
 - static routes
 - configuring*, 84–94
 - creating alternative routes*, 96–97
 - floating static routes*, 97–100
 - load sharing, configuring*, 102–104
 - recursive table lookups*, 107–109
 - summarizing*, 95
 - troubleshooting*, 109–112
- Route Tag field (RIPng messages)**, 214
- Route Tag field (RIPv2)**, 202
- route tagging**, 722, 752–758
- Router Advertisement packets (ICMP)**, 40
- router command**, 179
- Router IDs**, 337
 - configuring, 415–417
- Router LSAs**, 378, 403–406, 484–486
- router odr command**, 697–698
- router preferences, setting with administrative distance**, 722–723

router rip command, 178, 194

Router Selection packets (ICMP), 40

RouterDeadInterval, 338

routers

 boundary routers, 177–178

 configuring on IS-IS, 579–581

 IS-IS

designated routers, 523–524, 526

hold time, 522

System ID, 519

“**routing by rumor**,” 137–140

routing domains versus process domains, 252

Routing Information Protocol. *See RIP*

routing loops

 counting to infinity, 143–144

 in redistributed protocol environments, 636–639

 troubleshooting, 114

routing policies, 701

routing protocols

 classless, 206

redistribution into classful domains, 639–642

distance vector, 137

asynchronous updates, 145–146

characteristics of, 138–139

counting to infinity, 143–144

holddown timers, 144–145

route invalidation timers, 140–141

routing by rumor, 139–140

split horizon, 141

triggered updates, 144

link state, 146

areas, 160

autonomous systems, 160–162

Dijkstra’s algorithm, 156–159

flooding, 147–153

LSAs, 146–147

neighbor discovery, 147

metrics, 133

bandwidth, 134–135

cost, 135

delay, 135

hop count, 134

reliability, 135

selecting, 162–164

routing table entries (OSPF)

destination types, 390–391

lookups, 393

path types, 391–392

RS (Router Solicitation) messages, 65–67

RTO (retransmission timeout), 265–266

RTP (Reliable Transport Protocol), 264

S

Scholten, C.S., 266

secondary addresses

OSPF configuration, 418–422

RIP, 187

security, authentication

configuring on EIGRP, 316–317

configuring on IS-IS, 587–591

OSPF configuration, 393, 441–444

RIPv2, 210–212, 222–224

selecting

NETs, 520

routing protocols, 162–164

Sequence Number field (TCP), 43

sequence numbers, 148–149, 366–367, 734–735,

781, 786

circular sequence number space, 150

EIGRP, 264

linear sequence number space, 149–150

lollipop-shaped sequence number space, 152–153

TCP, 43

sequentiality of access list filters, importance of

778

set ip next-hop verify-availability command, 738

shortest path first protocols. *See link-state*

routing protocols

show arp command, 34

show cdp command, 90

show cdp neighbor detail command, 123

show clns is-neighbors command, 608

show clns is-neighbors detail command, 597

show interface command, 256

show ip access-list command, 800

show ip accounting access-violations

command, 801

show ip cef command, 123

show ip eigrp topology command, 268

show ip osfp interface command, 344
show ip ospf database command, 374
show ip ospf database nssa-external command, 409
show ip ospf neighbor command, 351–352
show ip route command, 83, 123
show ipv6 cef command, 123
show ipv6 cef detail command, 123
show ipv6 interface command, 123
show ipv6 rip command, 228
show ipv6 route command, 123
show isis database command, 529
SIA (stuck-in-active), 274
 troubleshooting, 324–327
silent hosts, 172
Simple Internet Protocol (SIP), 8
SIN (ships in the night) routing, 632
SIP (Simple Internet Protocol), 8
site-local unicast addresses, 55
sizing IP packet headers, 8
sleeptime, IGRP, 255
small internetworks, 18
SNAP (subnetwork access protocol), 681
 ARP encapsulation, 34
SNPA (Subnetwork Point of Attachment), 515
sockets, 43
solicited-node multicast addresses, 73
Source Address field (IPv6 packets), 60
source ports, TCP, 43
sources of invalid updates, 210
SPF efficiency, improving on IS-IS networks, 573–574
split horizon, 141
 disabling, 722
 resolving routing loops in redistributed environments, 637–639
 with poisoned reverse, 142, 172
spoofing attacks, 799
SRTT (smooth round-trip time), 265
standard IP ACLs, 782–784
 Boolean AND/OR functions, 784
 inverse masks, 785
 placement of, 799
 policy routing configuration, 740–742
static default routes, 682
 “don’t care” bits, 683
static routes
 administrative distance, 98
 configuring, 84
 failed routes, tracing, 109–112
 floating static routes, creating, 97–100
 IPv4, configuring, 85–89
 IPv6
 configuring, 90–94
 floating static routes, 100–101
 troubleshooting on replaced routers, 116–120
 load sharing
 CEF, 103–104
 configuring, 102
 per destination, 103
 per packet, 105–106
 policy routes, 731
 policy routing
 match commands, 733
 set commands, 734
 protocol conflicts, resolving, 112, 115–116
 recursive table lookups, 107–109
 redistribution, 669–671
 redistribution into dynamic routing
 protocols, 632
 redistribution into OSPF, 631
 summarizing, 95
 troubleshooting, 109
static routing
 creating alternative routes, 96–97
 per destination load sharing, 105
stub areas, 386, 497–498
 configuring, 423–426
stub networks, 340
stub routers, 678
 configuring on EIGRP, 309–315
 ODR, 680
 unreachable destinations, 678
stuck-in-active EIGRP neighbors, 323–327
study materials for CCIE exam, 805–807
subinterfaces, 208
subnet, 177
subnet hiding, 177
Subnet ID field, 53
Subnet Mask field (RIPv2), 203
subnet masks, 22–24
 octect boundaries, 25–27
 troubleshooting, 29
 unmatching, advertising, 641–642
 VLSM, 206–209

subnets, 22–24, 27–28, 180
 bitcount format, 24
 classful routing protocols, 23
 designing, 24–25
 discontiguous, 85, 178
summarizing RIPv2 routes across, 220–222
 dotted decimal format, 24
 hexadecimal format, 24
 IP addresses, 24
 number of required hosts, calculating, 25
 RIP, classful routing, 176
subnetting, VLSM
 and RIPv2 routing, 218–220
 troubleshooting, 236–242
subnetwork dependent functions of IS-IS layered network architecture, 521
 Decision process, 531–534
 designated routers, 523–524, 526
 neighbors, 522–523
 Update process, 526–530
Subnetwork Independent sublayer (IS-IS), 521
sub-subnetting, 208
summarization, 677
 address aggregation, 293–296
CIDR, 296–297
 EIGRP, 655
 in redistributed environments, 652–657
 interface-specific, 653
 null interfaces, 657
 of RIPv2 routes, disabling, 221
 OSPF
configuring, 435–440
troubleshooting, 463–466
 RIP, 177
 RIPng, 235
summary addresses, 677
summary routes, 94
summary-address command, 652
supernetting, 95
System ID (IS-IS), 519
system routes, 252

T

TCP (Transmission Control Protocol), 41–44
 ACLs, 790
 header information, 42
TCP/IP (Transmission Control Protocol/Internet Protocol), 5
 application layer, 6
 ARP, 33–34
proxy ARP, 36
 data link layer, 6
 host-to-host layer, 6, 41
TCP, 41–42, 44
UDP, 44–45
 ICMP Echo Requests/Replies, 39
 Internet layer, 6
 physical layer, 6
three-way handshaking, 555
timers
 EIGRP, multicast flow timer, 265
 holddown timers, 144–145
 IGRP, 254–255
 OSPF, group pacing timer, 377
 RIP, 170–172
expiration timer, 171
 route invalidation, 140–141
timers active time command, 275
timers basic command, 194
timing jitter, 145
TLA (Top Level Aggregator), 53
TLV (Type/Length/Value) fields, 70
 general fields, 289
 IP External Routes TLV, 291–293
 IP Internal Reachability, U/D bit, 556
 IP Internal Routes TLV, 290–291
 IP-specific fields, 290
 of IS-IS PDUs, 536–539
Area Addresses TLVs, 542–543
Authentication Information TLV, 544
Intermediate System Neighbors TLVs, 543
IP Interface Address TLV, 545
Padding TLV, 543
Protocols Supported TLV, 545

of IS-IS LSPs, 547–548
Inter-Domain Routing Protocol Information, 551
Intermediate System Neighbors, 549
IP External Reachability, 551
IP Internal Reachability, 550–551
topological table, contents of, 268
totally stubby areas, 387
 configuring, 426, 428
trace command, 12
tracing failed routes, 109–112
 IPv6, 120–122
 traffic, load balancing, 137
Traffic Class field (IPv6 packets), 59
training classes for CCIE exam, 804
transit networks, 340
transition technologies, 58
triggered updates, 144
 RIP, 172
troubleshooting
 EIGRP, 317
 missing neighbors, 318–323
 stuck-in-active neighbors, 323–327
 IS-IS, 606
 adjacencies, 607–610
 link-state database, 607, 610–614
 on NBMA networks, 615–619
 OSPF, 455–456
 adjacencies, 456–458
 area-wide problems, 459
 isolated areas, 460–463
 misconfigured summarization, 463–466
 OSPFv3, Frame-Relay mapping, 506–509
 RIP, 193
 RIPng, misconfigured VLSM, 236–242
 RIPv2, misconfigured VLSM, 236–242
 static routes, 109
 failed routes, 109–112
 protocol conflicts, 112, 115–116
 subnet masks, 29
TTL (Time to Live) field, 12
Type 1 external paths, 392
Type 2 external paths, 392
types of LSAs, 377
 ASBR Summary LSAs, 382
 External Attributes LSAs, 385
 Group Membership LSAs, 385
 Network LSAs, 379–381

 Network Summary LSAs, 381–382
 NSSA External LSAs, 385
 Opaque LSAs, 385
 Router LSAs, 378–379
types of traffic in OSPF areas, 369

U

U/D (Up/Down) bit, 556
UDP (User Datagram Protocol)
 ACLs, 791
 header information, 44–45
unequal-cost load balancing, EIGRP configuration, 299–302
unequal-cost load sharing, 102
unicast addresses, 174
 global addresses, 53
 updates, configuring, 182–184
unreachable networks, 144
unspecified addresses, 52
Update process (IS-IS), 526–530
update timers, RIP, 172
updates
 EIGRP, 264
 invalid, sources of, 210
 minimizing impact of, 190–193
 nonperiodic, 262
 RIP, 172
uptime, 266
Urgent Pointer field, TCP, 44
User Datagram Protocol. *See UDP*

V

variables, RIP_JITTER, 170
variance command, 300
verifying EIGRP stub router configuration, 311
Version field
 RIP, 173
 RIPv2, 202
versions of IP, 8
viewing
 IS-IS link-state database, 529–530
 IS-IS neighbor table, 523
virtual links, 340, 373

- configuring, 374
 - IS-IS support, 518
 - OSPF, configuring, 444–445
- VLSM (variable-length subnet masking),**
206–209
- and RIPv2 routing, 218–220
 - troubleshooting, 236–242

W-X-Y-Z

- which-route command, 534**
- wide metrics, 558**
- Window Size field, TCP header, 43**
- windowing, TCP, 42**