



INDEX

Numerics

50-ms resiliency, 15–16

A

access control lists (ACLs), 206, 337
access layer, 143, 292–298
accounting, management of, 334–335
accumulated outage time (AOT), 356
achieving high-availability, 16–25
ACLs (access control lists), 206, 337
Address Resolution Protocol (ARP), 49, 312
addresses
 Internet module, 194–199
 multihoming, 202
 net-hop address tracking (BGP), 214
 vMAC, 296
adjacency tables, 50–51
adjusted availability, 18
Adv Rtr (advertising router), 87
aggregation
 layer design, 298–300
 switches, 298
aggressive mode, UDLD configuration, 155
alerts, PSIRT, 350
ALG (Application Level Gateway), 226
algorithms
 fairness (SRP), 255
 universal load-sharing, 131
alternate ports, 146
analysis
 baselines. *See* baselines
 thresholds, 344
Anomaly Detection and Mitigation Modules, 328
ANS (authoritative name server), 321
anti-spoofing, 206
AOT (accumulated outage time), 356
Application Level Gateway (ALG), 226
applications, 5
 classifying, 78
 effect of NAT on, 232

failures, 21
QoS, 69–77
that use UDP, 33
application-specific gateways, 233
application-specific integrated circuit (ASIC), 3
applying GSS, 323
APS (Automatic Protection Switching), 249
architecture
 DPT, 252–258
 flow-based, 187
 MPLS-VPN, 269
 networks (Data Center module), 291–301
 next-generation IOS, 362
 scaling, 301–302
 servers, 288–289, 301
 switch forwarding, 314
 three-tier, 142
 two-tier, 142
ARP (Address Resolution Protocol), 49, 312
ASIC (application-specific integrated circuit), 3
assignment of addresses, 194
attacks
 DoS, 195, 204
 failures, 21
authoritative name server (ANS), 321
auto route injection, 231
Automatic Protection Switching (APS), 249
autonegotiation, turning off, 178
availability
 calculating, 10
 defects-per-million method, 367
 devices, 369
 high-availability networks, 9
 50-ms resiliency, 15–16
 achieving, 16–25
 five-nines, 9–12
 Telcordia GR-512-Core document, 12–15
 HSA, 39
 measuring, 17
 of parallel devices, 369
 percentage method, 367
 simple network topologies, 370
 simple systems, 370
 theoretical availability of devices, 368–369
avoidance, congestion, 75

B

BackboneFast, 152–154
backbones, Gigabit Ethernets, 3
backups
 dial backups (WAN), 258–261
 simple hardware, 38
baselines, establishing, 337–345
BCPs (Best Current Practices), 194
best practices
 Layer 2, 173–178
 Layer 3, 187, 189–190
BFD (Bidirectional Forwarding Detection), 103,
 EIGRP, 124–126
BGP (Border Gateway Protocol), 7, 193
 convergence, 213
 fast peering session deactivation, 214
 Internet modules, 222
 next-hop address tracking, 214
 route dampening, 215
 updates, 221
BID (bridge ID), 147
Bidirectional Forwarding Detection. *See* **BFD**
bidirectional line switch ring (BLSR), 249
binding, delayed, 319
blade server connectivity, 288
blocks
 private addresses, 195
 states, 148
BLSR (bidirectional line switch ring), 249
boot codes, 334
Border Gateway Protocol. *See* **BGP**
BPDU (Bridge Protocol Data Unit), 153
BPDUGuard, 157–158
bridge ID (BID), 147
Bridge Protocol Data Unit. *See* **BPDU**
bridges, 146
 root, 148
 selecting, 176
building blocks (access module), 144

C**cabling**

 Data Center module, 282–283
 options, 286

caches, 326
calculations
 availability, 10
 defects-per-million method, 367
 percentage method, 367
 simple network topologies, 370
 simple systems, 370
 theoretical availability of devices,
 368–369
 downtime, 12
 MTBF using COOL, 357
capacity failures, 21
Catalyst switch support, PVLANS, 310
causes of network failures, 20
CE (customer edge) routers, 270, 276–278
CEF (Cisco Express Forwarding), 46, 129
 central mode, 53
 configuring, 53
 dCEF, 54
 switching, 50
channeling, 171–173
CIDR (classless interdomain routing), 194
circuits
 half, 239
 WAN leased lines, 237–244
Cisco Component Outage Online (COOL), 355
Cisco Express Forwarding. *See* **CEF**
Cisco IOS deployment, 345–351
Cisco Networking Services (CNS) events, 360
CISCO-OUTAGE-MONITOR MIB, 355
CISCO-PROCESS-MIB, OIDs within, 341
Class-Based QoS MIB, 82
classes of service, DPT/SPR, 254
classification
 applications, 78
 DiffServ model, 75
 IP Precedence, 66
classless interdomain routing (CIDR), 194
client name server (CNS), 321
clustering, 297
CNS (Cisco Networking Services) events, 360
CNS (client name server), 321
cold restart feature, 37
coloring, 75
commands
 backbonefast, 154
 debug dampening interface, 128

debug ip ospf database-timer rate-limit, 99
 debug ip ospf flood, 99
 debug ip ospf spf, 95, 99
 debug isis adj, 121
 debug isis adj-packets, 115
 debug isis nsf, 121
 debug isis.snp, 121
 execute-on <lot>, 125
 flood packet pacing timer, 104
 glbp priority, 184
 ip accounting, 335
 ip cef load-sharing algorithm original, 132
 ip ospf network point-to-point, 87
 ip tcp path-mtu-discovery, 213
 ip-ospf flood-reduction, 101
 mpls traffic-eng backup path tunnel, 135
 peer, 229
 pim query-interval, 138
 ping, 353
 portfast, 150
 primary, 229
 redistribute connected, 276
 redistribute ospf 10, 278
 router ospf 10 vrf RED, 278
 show, 337
 show bfd neigh detail, 125
 show ip bgp neighbors, 211
 show ip cef, 131
 show ip cef exact-route, 132
 show ip ospf, 96, 98
 show ip ospf neighbor detail, 110
 show ip pim neighbor, 138
 show ip route, 129
 show ip rpf events, 139
 show isis nsf, 120
 show running-config, 36
 spf-interval, 112
 timer lsa arrival, 100
 times spf spf-holdtime, 97
 tunnel mode gre, 264
 tunnel mode ipip, 264
 tunnel mpls traffic-eng fast-reroute, 135
 tunnel path-mtu-discovery, 264
 uplinkfast, 152
Common Spanning Tree (CST), 161
community ports, 305
community VLANs, 306

Complete Sequence Number Packet (CSNP), 117
components
 availability, 10
 COOL, 355
 network management, 331–337
 PBX systems, 12
conditioning, traffic, 76
configuration
 BackboneFast, 154
 BGP
NSF/SSO, 217–218
route dampening, 215
soft reconfiguration, 210
 BPDUGuard, 158
 CE routers, 276–278
 CEF, 53
 DHCP, 315
 DPR/SPR rings, 256
 dynamic ARP inspection, 313
 EEM, 362
 EtherChannel, 177
 file management, 333
 GLBP, 186
 HSA, 38
 HSRP, 181
 IEEE 802.1s, 170
IP
event dampening, 127
tunnels, 263
IS-IS
Fast Hello, 115
incremental SPF, 117
LSA Flooding Reduction, 114
LSP generation interval timers, 113
partial route computation timers, 113
SPF throttling, 112
update packet-pacing timers, 116
 ISL trunking, 159
 L2TP, 266
 LoopGuard, 157
 management, 333
 MPLS-VPN, 273
 PPP, 243
NAT
HSRP, 225
maximum number of entries, 230
multihoming, 223
stateful NAT on HSRP, 227

networks, 86
NSF, 46
OSPF
 BFD, 125
 Fast Hello, 102
 incremental SPF, 106
 LSA flood-reduction, 101
 LSA throttling, 98
 NSF/SSO, 109
 update packet-pacing timers, 104
P routers, 273
PE routers, 274
per-packet load balancing, 130
PortFast, 150
port security, 311
PVLANs, 307
RACL, 68
Rapid-PVST+, 168
reverse proxy caching, 327
RootGuard, 156
RPR, 40
RPR+, 42
single line card reload, 36
SONET/SDH, 250
SPF throttling, 96
SSO, 44
static routes, 259
UDLD, 155
WCCP, 326
congestion
 avoidance, 75
 management, 76
 QoS (uncongested links), 73
 transient, 73
connections
 blade servers, 288
 cabling, 283. *See also* cabling
 Layer 2, 175
 leased circuit encapsulation, 239
 NIC teaming, 296
 three-way handshakes (TCP), 31
conserving peering resources, 189
content switching. *See* SLB
Content Switching Module (CSM), 328
continuous fault detection, 23
control packets, tagging, 65
control planes
 MIB, 342
 policing, 314
 protecting, 55–56
 QoS, 63–69
 traffic, 76–77
controller cards, 13
convergence
 BGP, 213
 IP event dampening, 126
 MPLS-TE, 132
 multicast subsecond, 137–139
 network in the core, 85–86
 networks, 90
 OSPF, 86–95
COOL (Cisco Component Outage Online), 355
core layer, 144
counter-rotating rings (DPT), 252
CRS-1 router, 3
CSM (Content Switching Module), 328
CSNP (Complete Sequence Number Packet), 117
CST (Common Spanning Tree), 161
customer edge (CE) routers, 270, 276–278
customization. *See also* configuration
 EIGRP, 123
 BFD, 124–126
 graceful shutdown, 123
 stub router, 123
 IS-IS, 111
 Fast Hellos, 114–115
 graceful restart, 117–122
 incremental SPF, 116
 LSA flooding reduction, 114
 LSP generation, 113
 SPF throttling, 112–113
 update packet-pacing timer, 115–116
 OSPF, 86–95
 Fast Hello, 102–103
 graceful restart, 106–111
 incremental SPF, 105
 LSA flooding reduction, 100–101
 LSA throttling, 98–100
 SPF, 97
 update packet-pacing timer, 104–105
cycles, STP, 148

D

dampening (routes), 215
DARPA (Defense Advanced Research Projects Agency), 4
Data Center module, 281
 environmental considerations, 282
 cabling, 282–283
 power supply, 287
 rack space, 283
 server architecture, 288–289
 server size, 284–287
 networks, 289–291
 architecture, 291–301
 security, 289, 302–315
 server performance, 290
 service optimization, 315–328
data planes
 MIBs, 342
 protecting, 55–56
datagrams, 27. *See also UDP*
dCEF (Distributed CEF), 54
debug commands
 debug dampening interface, 128
 debug ip ospf database-timer rate-limit, 99
 debug ip ospf flood, 99
 debug ip ospf spf, 95, 99
 debug isis adj, 121
 debug isis adj-packets, 115
 debug isis nsf, 121
 debug isis.snp, 121
default path costs for STP, 147
defects-per-million method, 367
Defense Advanced Research Projects Agency (DARPA), 4
defining
 metrics, 19
 policies, 81
delayed binding, 319
demilitarized zone (DMZ) servers, 196
denial-of-service (DoS) attacks, 195, 204
deployment
 Cisco IOS, 345–351
 EtherChannel, 177
 IP tunnels, 263
 L2TPv3, 265
 QoS, 72, 77–82

design

access layer, 292–298
 aggregation layer, 298–300
 ASIC, 3
 Data Center module, 281
 cabling, 282–283
 environmental considerations, 282
 network architecture, 291–301
 network security, 289, 302–315
 network server performance, 290
 networks, 289–291
 power supply, 287
 rack space, 283
 servers, 284–289
 service optimization, 315–328
 high availability, 21
 Internet module, 193
 BGP, 222
 filtering, 206
 NAT, 235
 redundancy, 199–204
 security, 204–209
 Internet modules, 194–199
 life cycle management (IOS), 349
 multilayer campus, 141–143
 access layer, 143
 building blocks, 144
 core layer, 144
 distribution layer, 143
 Layer 2 domains, 145–178
 Layer 3 domains, 178–190
 resiliency, 59–61
 security, 60
designated IS (DIS), 114
designated ports, 146
detection, 332
 continuous fault, 23
 EEM, 361
device-level redundancy, 201
device-level resiliency, 34, 57
 HSA, 39
 NSF, 45–48
 OIR, 34–36
 RPR, 40–41
 RPR+, 41–43
 single line card reload, 36–37
 SSO, 43–45

devices

- configuration file management, 333
- parallel, 369
- theoretical availability of, 368–369
- DHCP (Dynamic Host Control Protocol)**
 - servers, 314
 - snooping, 315
- diagrams, cabling**, 283
- dial backup (WAN)**, 258–261
- diameter keyword**, 176
- DiffServ model (QoS)**, 74–76
- direct connections (Layer 2)**, 175
- directed mode (SLB)**, 318
- DIS (designated IS)**, 114
- disabled ports**, 146
- disabled states**, 148
- disasters (failures)**, 21
- discipline, cabling**, 283
- dispatch mode (SLB)**, 318
- Distributed CEF (dCEF)**, 54
- distribution layer**, 143
- DLC (domestic leased circuit)**, 238
- DMZ (demilitarized zone) servers**, 196
- DNS (Domain Name System)**, 321
- DNSR (DNS resolver)**, 321
- documentation, cabling**, 283
- Domain Name System (DNS)**, 321
- domains**
 - Layer 2, 145–178
 - Layer 3, 178–190
- domestic leased circuit (DLC)**, 238
- DoNotAge link-state advertisements**, 114
- DoS (denial-of-service) attacks**, 195, 204
- downtime**
 - calculating, 12
 - fault management, 332
 - scheduling, 23
- DPT (Dynamic Packet Transport)**, 7, 251
 - architecture, 252–258
 - classes of service, 254
- duplicate acknowledgment (DUPACK)**, 130
- dynamic ARP inspection**, 312
- Dynamic Host Control Protocol.** *See* **DHCP**
- Dynamic Packet Transport.** *See* **DPT**
- dynamic soft reset**, 211

E

-
- Early Deployment (ED) release**, 346
 - echo (ICMP)**, 353
 - ECMP (equal-cost multipath)**, 129, 188
 - ED (Early Deployment) release**, 346
 - EEM (Embedded Event Manager)**, 359–362
 - effect of Internet growth, 4
 - EIGRP (Enhanced Interior Gateway Routing Protocol)**, 123
 - BFD, 124–126
 - graceful shutdown, 123
 - stub routers, 123
 - Embedded Event Manager (EEM)**, 359–362
 - enabling**
 - BGP fast peering session deactivation, 214
 - COOL, 357
 - encapsulation**
 - ISL, 159
 - leased circuit, 239
 - end nodes (L2TP)**, 268
 - End of Engineering (EOE)**, 346
 - End of Life (EOL)**, 346
 - End of Sales (EOS)**, 346
 - End-of-Table (EOT) signal**, 123
 - Enhanced Interior Gateway Routing Protocol.**
 - See* **EIGRP**
 - entries**
 - in adjacency tables, 51
 - MIB, 340
 - entry limitation (NAT)**, 230
 - environmental considerations (Data Center module)**, 282
 - cabling, 282–283
 - power supply, 287
 - rack space, 283
 - servers
 - architecture, 288–289
 - size, 284–287
 - EOE (End of Engineering)**, 346
 - EOL (End of Life)**, 346
 - EOS (End of Sales)**, 346
 - EOT (End-of-Table) signal**, 123
 - equal-cost load balancing**, 241
 - equal-cost multipath (ECMP)**, 129, 188
 - errors, software protection**, 38
 - establishing baselines**, 337–345

-
- EtherChannel**, 172
 configuring, 177
 deploying, 177
 Later 2, 177
 load balancing, 177
- event dampening (IP)**, 126
- Event Publisher**, 360
- Event Subscriber**, 360
- events**
 CNS, 360
 EEM, 359–362
 internal trouble-ticket, 24
- execute-on**, 125
- exponential back-off behavior, SPF**, 97
- extensions, graceful restart**, 46
- external users, routing**, 198
- extranet servers, reachability**, 196
- F**
-
- failure**, 3. *See also* troubleshooting
 causes of, 20
 MTBF, 10, 368
- fairness algorithms (SRP)**, 255
- farms (servers)**, 292, 301
- Fast EtherChannel (FEC)**, 171
- Fast Hellos**
 IS-IS, 114–115
 OSPF, 102
- fast peering session deactivation**, 214
- Fast Reroute (FRR)**, 6
- fast reroute link protection**, 133
- fast reroute node protection**, 136
- fault detection**, 23
- fault management**, 332
- fault-tolerant servers**, 290
- FCIP (Fibre Channel over IP)**, 5
- FEC (FastEtherChannel)**, 171
- FEC (forwarding equivalence class)**, 6, 270
- Fibre Channel over IP (FCIP)**, 5
- Field Programmable Gate Array (FPGA) codes**, 334
- files, configuration management**, 333
- filtering (Internet module)**, 206
- Firewall Service Module (FWSM)**, 328
- five-nines availability**, 9–12
- flags, pak_priority**, 66
- flaps (routing)**, 45
- flash crowds**, 316
- floating static routes**, 258
- flood packet pacing timer command**, 104
- flooding**
 IS-IS, 114
 LSAs, 100–101
- flow-based architecture**, 187
- formatting UDP**, 33. *See also* configuration
- forward delay timers**, 149
- forwarding**
 architecture (switches), 314
 CEF, 46, 129
 central mode, 53
 configuring, 53
 dCEF, 54
 switching, 50
 NSF, 45–48
 packets, 134
 states, 148
- forwarding equivalence class (FEC)**, 6, 270
- FPGA (Field Programmable Gate Array) codes**, 334
- framing (SONET/SDH)**, 245
- FRR (Fast Reroute)**, 6
- functional entities**, 57
- FWSM (Firewall Service Module)**, 328
- G**
-
- gateways, application-specific**, 233
- GD (General Deployment) release**, 346
- GEC (Gigabit EtherChannel)**, 171
- General Deployment (GD) release**, 346
- generation**
 LSP, 113
 of updates, 211
- Gigabit EtherChannel (GEC)**, 171
- Gigabit Ethernet backbones**, 3
- Gigabit Switch Router (GSR)**, 106
- GLBP (Global Load Balancing Protocol)**, 183–186
- glbp priority command**, 184
- Global Load Balancing Protocol (GLBP)**, 183–186

global server load balancing (GSLB), 320
Global Site Selector (GSS), 320–323
global synchronization, 75
graceful restart
 extensions, 46
 IS-IS, 117–122
 OSPF, 106–111
graceful shutdown (EIGRP), 123
graphs, MRTG, 343
groups, availability of, 369
growth of Internet, effect of, 4
GSLB (global server load balancing), 320
GSR (Gigabit Switch Router), 106
GSS (Global Site Selector), 320–323

H

half circuits, 239
hardware
 baselines. *See* baselines
 failures, 21
 simple backups, 38
headers, ISL, 158
heartbeat mechanisms, 297
Hello packets, 86
Hello protocol, 102, 114–115
hello timers, 149
hierarchical IP addressing schemes, 190
high system availability (HSA), 39
high-availability networks, 9
 50-ms resiliency, 15–16
 achieving, 16–25
 five-nines, 9–12
 Telcordia GR-512-Core document, 12–15
high-density server farms, scaling, 301
high-priority services, 254
hops, next-hop address tracking (BGP), 214
Hot Standby Routing Protocol (HSRP), 179, 181
 stateful NAT, 227
 static mapping, 224
hot swap capability, 35
HSA (high system availability), 39
HSRP (Hot Standby Routing Protocol), 179, 181
 stateful NAT, 227
 static mapping, 224
human error (failures), 21

I

IANA (Internet Assigned Numbers Authority), 195
ICMP (Internet Control Message Protocol)
 echo, 353
 NAT, 232
 SLAs, 353
IEEE 802.17, 255
IEEE 802.1d, 146
IEEE 802.1q, 158
IEEE 802.1s, 168–171
IEEE 802.1w, 165–168
IETF (Internet Engineering Task Force), 6, 118
IGESM (Intelligent Gigabit Ethernet Switch Module), 288
impact of different switching paths, 48–55
implementation. *See also* configuration
 life cycle management (IOS), 350
 QoS, 82
inbound ACLs, 206
inbound soft reset, 211
incident response, 205
incremental SPF, 116
inferior BPDU, 153
INS (intermediate name server), 321
in-service software upgrade (ISSU), 364
Integrated Service Digital Network. *See* ISDN
integrated service modules, 328–329
Intelligent Gigabit Ethernet Switch Module (IGESM), 288
interfaces
 IP event dampening, 126
 iSCSI, 5
 POS, 28
intermediate name server (INS), 321
Intermediate System-to-Intermediate System (IS-IS), 7
Internal trouble-ticket events, 24
internal users, routing, 197
international private leased circuit (IPLC), 238
International Telecommunication Union-Telecommunication Standardization Sector (ITU-T), 15
Internet Assigned Numbers Authority (IANA), 195
Internet Control Message Protocol. *See* ICMP

Internet Engineering Task Force (IETF), 6, 118

Internet module, 193

- addressing/routing, 194–199
- BGP, 222
- filtering, 206
- NAT, 235
- redundancy, 199–204
- security, 204–209

Internet Protocol. *See IP*

Internet Small Computer System Interface (iSCSI), 5

Inter-Switch Link (ISL), 158

intervals, 86

inventory

- management, 334
- snapshots, 340
- tracking, 333

IOS deployment, 345–351

IP (Internet Protocol), 27–29

- event dampening, 126
- next-generation transport systems, 6
- next-generation applications, 5
 - IP Storage, 5*
 - VoIP, 5*
- Precedence, 65
- SLA, 354
- VPNs, 261

ip accounting command, 335

ip cef load-sharing algorithm original command, 132

ip ospf flood-reduction command, 101

ip ospf network point-to-point command, 87

IP SLA (IP Service Level Agreement), 82, 352

ip tcp path-mtu-discovery command, 213

IPLC (international private leased circuit), 238

iSCSI (Internet Small Computer System Interface), 5

ISDN (Integrated Service Digital Network)

- as dial backups, 258

IS-IS (Intermediate System-to-Intermediate System), 7, 111

- Fast Hellos, 114–115
- graceful restart, 117–122
- incremental SPF, 116
- LSA flooding reduction, 114
- LSP generation, 113
- SPF throttling, 112–113
- update packet-pacing timer, 115–116

ISL (Inter-Switch Link), 158

isolated ports, 305

isolated VLANs, 306

ISP-level redundancy (multihoming), 202

ISSU (in-service software upgrade), 364

ITU-T (International Telecommunication Union-Telecommunication Standardization Sector), 15

J–K

jitter, 71

keywords, diameter, 176

L

L2TP (Layer 2 Tunnel Protocol), 265

Label Distribution Protocol (LDP), 270

label edge router (LER), 269

label switch router (LSR), 269

label switched path (LSP), 113, 269

labels

- MPLS, 6
- stacking, 134

LAN Management Solution (LMS), 334

LATA (Local Access and Transport Area) switching systems, 12

latency, 70

Layer 2

- best practices, 173–178
- control packets, 65
- domains, 145–178
- EtherChannel, 177
- security, 303–313

Layer 2 Tunnel Protocol (L2TP), 265

Layer 3

- best practices, 187, 189–190
- domains, 178–190
- security, 313–315

layers

- access design, 292–298
- aggregation design, 298–300
- multilayer campus design, 141–143
 - access, 143*

- building blocks*, 144
- core*, 144
- distribution*, 143
- Layer 2 domains*, 145–178
- Layer 3 domains*, 178–190
- LD (limited deployment) release**, 346
- LDP (Label Distribution Protocol)**, 270
- leaf nodes**, 150
- learning states, 148
- leased lines (WAN), 237–244
- LER (label edge router)**, 269
- levels of security breaches, 205
- life cycle management (IOS), 348
- limitation of entries (NAT), 230
- Limited Deployment (LD) release**, 346
- limiting spans of VLANs, 174
- lines cards, 13
- link local signaling (LLS)**, 108
- link-level redundancy, 58, 200
- Link-Local Opaque link-state advertisements**, 107
- links**
 - fast reroute link protection, 133
 - sham, 278
 - uncongested, 72
- link-state advertisements**. *See LSAs*
- link-state ID (LSID)**, 87
- link-state type (LS-Type)**, 87
- listening states, 148
- LLS (link local signaling)**, 108
- LMS (LAN Management Solution)**, 334
- load balancing**
 - equal-cost, 241
 - EtherChannel, 177
 - GLBP, 183–184, 186
 - multipath routing, 128
 - per-destination, 130
 - per-packet, 129
- Local Access and Transport Area (LATA)**
 - switching systems, 12
- local protection**, 133
- logging**, 332
- logical redundancy**, 57
- LoopGuard**, 157
- loops**, 146–154
 - BPDUGuard, 157–158
 - channeling, 171–173
- IEEE 802.1s, 168–171
- IEEE 802.1w, 165–168
- LoopGuard**, 157
- PortFast**, 150
- RootGuard**, 155–157
- UDLD**, 154–155
- UplinkFast**, 151
- VLANs, 158–165
- loss**, 72
- lower-bound thresholds**, 344
- low-priority services**, 254
- LSAs (link-state advertisements)**
 - DoNotAge, 114
 - flooding reduction, 100–101, 114
 - Link-Local Opaque, 107
 - neighbor propagation, 88
 - OSPF, 87
 - throttling, 98–100
- LSID (link-state ID)**, 87
- LSP (label switched path)**, 113, 269
- LSR (label switch router)**, 269
- LS-Type (link-state type)**, 87

M

-
- Major (IOS) release**, 346
 - management**
 - accounting, 334–335
 - configuration, 333
 - congestion, 76
 - EEM, 359–362
 - fault, 332
 - inventory, 334
 - life cycles (IOS), 348
 - LMS, 334
 - networks
 - Cisco IOS deployment*, 345–351
 - components, 331–337
 - establishing baselines, 337–345
 - operations, 24
 - proactive, 351–364
 - performance, 335–336
 - security, 336–337
 - software, 334
 - Management Information Base**. *See MIB*

- maps**
 - routes (NAT with), 223
 - static mapping with HSRP, 224
- marking (DiffServ model), 75**
- maximum age timers, 149**
- maximum segment size (MSS), 213**
- maximum transmission unit (MTU), 29**
- MBGP (Multiprotocol BGP), 271**
- mean time before failure (MTBF), 368**
- mean time between failure (MTBF), 10, 355**
- mean time to repair (MTTR), 368**
- mean time to restore (MTTR), 355**
- measurements.** *See also* calculations
 - availability, 17
 - COOL, 356
 - high availability, 23
- merge point (MP), 134**
- messages**
 - fault management, 332
 - SRM, 118
- metrics**
 - COOL measurements, 356
 - defining, 19
- MHSRP (Multigroup HSRP), 181**
- MIB (Management Information Base), 82**
 - CISCO-OUTAGE-MONITOR, 355
 - entries, 340
- microcodes, 334**
- models, network management, 331–337**
- modularity of network design, 59**
- modules**
 - Data Center, 281
 - architecture, 291–301*
 - cabling, 282–283*
 - environmental considerations, 282*
 - networks, 289–291*
 - power supply, 287*
 - rack space, 283*
 - security, 289, 302–315*
 - server architecture, 288–289*
 - server size, 284–287*
 - service optimization, 315–328*
 - IGESM, 288
 - integrated service, 328–329
 - Internet, 193
 - addressing/routing, 194–199*
 - BGP, 222
- filtering, 206**
- NAT, 235**
- redundancy, 199–204**
- security, 204–209**
- pass-through, 288**
- Traffic Anomaly Detector service, 335
- monitoring**
 - QoS, 82
 - RMON, 332
- MP (merge point), 134**
- MPLS (Multiprotocol Label Switching), 6**
- mpls traffic-eng backup path tunnel command, 135**
- MPLS-TE (MPLS Traffic Engineering), 6, 132**
- MPLS-VPN, 269**
- MPPP (Multilink Point-to-Point Protocol), 243**
- MRTG (Multi-Router Traffic Grapher), 340, 343**
- MSS (maximum segment size), 213**
- MTBF (mean time between failure), 10, 355, 368**
- MTTR (mean time to repair), 355, 368**
- MTU (maximum transmission unit), 29**
- multicast subsecond convergence, 137–139**
- multifaceted servers, 291**
- Multigroup HSRP (MHSRP), 181**
- multihoming, 202, 223, 230**
- multilayer campus design, 141–143**
 - access layer, 143
 - building blocks, 144
 - core layer, 144
 - distribution layer, 143
 - Layer 2 domains, 145–178
 - Layer 3 domains, 178–190
- Multilink Point-to-Point Protocol (MPPP), 243**
- multipath routing, 128**
- multiplexing SONET, 247**
- Multiprotocol BGP (MBGP), 271**
- Multiprotocol Label Switching (MPLS), 6**
- Multi-Router Traffic Grapher (MRTG), 340, 343**

N

-
- NAF (number of accumulated failures), 356**
 - NAM (Network Analysis Module), 328, 332**
 - naming conventions (IOS), 346**

- NAT (Network Address Translation), 49, 194**
- effect on applications, 232
 - entry limitation, 230
 - ICMP, 232
 - Internet modules, 235
 - multihoming, 223, 230
 - performance, 235
 - security, 235
 - stateful, 226
 - TCP, 232
 - VoIP, 234
- NEBS (Network Equipment Building System), 57**
- need for application QoS, 69–72**
- neighbors**
- BFD, 125
 - LSA neighbors, propagating, 88
- NetFlow, 335**
- Network Address Translation. *See* NAT**
- Network Analysis Module (NAM), 328, 332**
- Network Equipment Building System (NEBS), 57**
- network interface card (NIC), 288, 295**
- network layer reachability information (NLRI), 213**
- networks**
- configuring, 86
 - convergence, 90
 - core, 85–86
 - Data Center module, 289–291
 - architecture, 291–301
 - security, 289, 302–315
 - server performance, 290
 - high-availability, 9
 - 50-ms resiliency, 15–16
 - achieving, 16–25
 - five-nines, 9–12
 - Telcordia GR-512-Core document*, 12–15
 - Layer 2 best practices, 173–178
 - management
 - Cisco IOS deployment*, 345–351
 - components, 331–337
 - establishing baselines, 337–345
 - proactive, 351–364
 - multilayer campus design, 141–143
 - access layer, 143
 - building blocks, 144
 - core layer, 144
 - distribution layer, 143
- Layer 2 domains, 145–178**
- Layer 3 domains, 178–190**
- WAN**
- dial backup*, 258–261
 - leased lines*, 237–244
 - RPR*, 251–258
 - SONET/SDH*, 244–251
 - VPN*, 261–279
- next-generation IOS architecture, 362**
- next-generation IP applications, 5**
- IP Storage, 5
 - VoIP, 5
- next-hop address tracking (BGP), 214**
- next-hop routers, 134**
- NIC (network interface card), 288, 295**
- NLRI (network layer reachability information), 213**
- nodes**
- fast reroute node protection, 136
 - leaf, 150
- Non Stop Forwarding with Stateful Switchover (NSF/SSO), 106, 216**
- non-responder-based IP SLA operations, 354**
- nonstop forwarding (NSF), 45–48**
- normal mode, UDLD configuration, 155**
- notification, 332**
- NSF (nonstop forwarding), 45–48**
- NSF/SSO (Non Stop Forwarding with Stateful Switchover), 106, 216**
- number of accumulated failures (NAF), 356**
-
- O**
-
- object identifier (OID), 340**
- objects, COOL measurements of, 356**
- OID (object identifier), 340**
- OIR (online insertion and removal), 34–36**
- Open Shortest Path First. *See* OSPF**
- Open Systems Interconnection (OSI), 27**
- operations**
- IP SLAs, 354
 - life cycle management (IOS), 350
 - non-responder-base IP SLA, 354
 - responder-based IP SLA, 353
- optimization. *See also* customization**
- BGP convergence, 213

EIGRP, 123
BFD, 124–126
graceful shutdown, 123
stub routers, 123
enhanced NAT resiliency, 222
IS-IS, 111
Fast Hellos, 114–115
graceful restart, 117–122
incremental SPF, 116
LSA flooding reduction, 114
LSP generation, 113
SPF throttling, 112–113
update packet-pacing timer, 115–116
OSPF, 86–95
Fast Hello, 102–103
graceful restart, 106–111
incremental SPF, 105
LSA flooding reduction, 100–101
LSA throttling, 98–100
SPF throttling, 97
update packet-pacing timer, 104–105
protocols, 7
security, 7
services, 315–328

options

cabling, 286
EIGRP, 123
BFD, 124–126
graceful shutdown, 123
stub router, 123
IS-IS, 111
Fast Hellos, 114–115
graceful restart, 117–122
incremental SPF, 116
LSA flooding reduction, 114
LSP generation, 113
SPF throttling, 112–113
update packet-pacing timer, 115–116
OSPF, 86–95
Fast Hello, 102–103
graceful restart, 106–111
incremental SPF, 105
LSA flooding reduction, 100–101
LSA throttling, 98–100
SPF, 97
update packet-pacing timer, 104–105

OSI (Open Systems Interconnection), 27
OSPF (Open Shortest Path First), 7
enhancements, 86–95
Fast Hello, 102–103
graceful restart, 106–111
incremental SPF, 105
LSA
flooding reduction, 100–101
throttling, 98–100
network convergence in the core, 85
NSF, 46
SPF throttling, 97
update packet-pacing timer, 104–105
outbound soft reset, 211

P

P (provider) routers, 270, 273
Packet over SONET (POS) interface, 28
packets

- CSNP, 117
- DPT, 251–258
- forwarding, 134
- Hello intervals, 86
- loss, 72
- PSNP, 118
- RPR, 251–258
- tagging, 65

pak_priority flags, 66

parallel components, 10

parallel devices, availability of, 369

Partial Sequence Number Packet (PSNP), 118

partial SPF, 106

pass-through modules, 288

passwords, 337

PAT (Protocol Address Translation), 222

paths

- default costs for STP, 147
- LSP, 269
- multipath routing, 128
- network convergence in the core, 85–86
- protection, 133
- switching, 48–55

PBX (private branch exchange) systems, 12

PE (provider edge) routers, 270, 274

peer command, 229

- peering resources, conserving**, 189
- penultimate hop popping**, 134
- percentage method, calculating availability**, 367
- per-destination load balancing**, 130
- performance**
 - baselines. *See* baselines
 - management, 335–336
 - NAT, 235
- per-packet load balancing**, 129
- Per-VLAN Spanning Tree (PVST)**, 162
- Per-VLAN Spanning Tree Plus (PVST+)**, 164
- physical redundancy**, 57
- pim query-interval command**, 138
- ping command**, 353
- planning life cycle management (IOS)**, 349
- PLR (point of local repair)**, 134
- point of local repair (PLR)**, 134
- policies**
 - defining, 81
 - security, 204–205
 - SLB, 317
 - testing, 81
- polling data (baselines)**, 340–343
- PortFast**, 150
- portfast command**, 150
- ports**
 - alternate, 146
 - designated, 146
 - disabled, 146
 - EtherChannel, 177
 - IEEE 802.1w, 166
 - PVLANS, 305
 - root, 146
 - routed (aggregation switches), 299
 - security, 311
 - trunks (aggregation switches), 298
- POS (Packet over SONET) interface**, 28
- power supplies**, 13
 - Data Center module, 287
 - UPS, 287
- PPP over SONET/SDH**, 247
- primary command**, 229
- primary power equipment**, 287
- primary VLANs**, 306
- primary/secondary method (static NAT)**, 228
- principles of security policies**, 205
- prioritization**
 - syslog messages, 360
 - thresholds, 345
- private addresses**, 194
 - blocks, 195
 - DoS attacks, 195
 - filtering, 206
- private branch exchange (PBX) systems**, 12
- private VLANs (PVLANS)**, 304
 - Catalyst switch support, 310
 - configuring, 307
 - ports, 305
- proactive network management**, 351–364
- process switching**, 49
- processors**
 - RPR, 40–41
 - RPR+, 41–43
- Product Security Incident Response Team (PSIRT)**, 23, 350
- promiscuous ports**, 305
- properties, applications**, 78
- protection**
 - applications with QoS, 69–74
 - control planes, 55–56, 63–69
 - data planes, 55–56
 - switching (SONET/SDH), 248
- Protocol Address Translation (PAT)**, 222
- protocols**
 - ARP, 49, 312
 - BGP, 193–222
 - convergence*, 213
 - fast peering session deactivation*, 214
 - next-hop address tracking*, 214
 - route dampening*, 215
 - updates*, 221
 - EIGRP, 123
 - BFD*, 124–126
 - graceful shutdown*, 123
 - GLBP, 183–186
 - Hello, 102, 114–115
 - HSRP, 179, 181
 - stateful NAT*, 227
 - static mapping*, 224
 - ICMP, 232
 - IP, 27–29

IS-IS, 111
Fast Hellos, 114–115
graceful restart, 117–122
incremental SPF, 116
LSA flooding reduction, 114
LSP generation, 113
SPF throttling, 112–113
update packet-pacing timer, 115–116

L2TP, 265
LDP, 270
MPPP, 243
NAT, 235
optimizing, 7
OSPF
enhancements, 86–95
Fast Hello, 102–103
graceful restart, 106–111
incremental SPF, 105
LSA flooding reduction, 100–101
LSA throttling, 98–100
update packet-pacing timer, 104–105

routing, 65
RSTP, 165
SNMP, 332
Spatial Reuse Protocol, 251
STP, 146–150
BackboneFast, 152–154
BPDUGuard, 157–158
channeling, 171–173
cycles, 148
IEEE 802.1s, 168–171
IEEE 802.1w, 165–168
Layer 2 domains, 145
LoopGuard, 157
PortFast, 150
RootGuard, 155–157
UDLD, 154–155
UplinkFast, 151
VLANs, 158–165

TCP, 29–33
delayed binding, 320
MSS, 213
NAT, 232
three-way handshakes, 31

UDP, 33–34
VRRP, 183
WCCP, 324–328

provider (P) routers, 270, 273
provider edge (PE) routers, 270, 274
PSIRT (Product Security Incident Response Team), 23, 350
PSNP (Partial Sequence Number Packet), 118
public addresses, 194–195, 202
punting, 49
PVLANs (private VLANs), 304
Catalyst switch support, 310
configuring, 307
ports, 305
PVST (Per-Vlan Spanning Tree), 162
PVST+ (Per-Vlan Spanning Tree Plus), 164

Q

QoS (quality of service), 29, 63
applications, 69–74
control plane traffic, 76–77
control planes, 63–69
deploying, 77–82
DiffServ model, 74–76
implementing, 82
monitoring, 82
queues (SRP), 254

R

rack space, Data Center module, 283
RACL (receive access control list), 67
RANCID (Really Awesome New Cisco Config Differ), 333
random early detect (RED), 75
Rapid Spanning Tree Protocol (RSTP), 165
Rapid-PVST+, 168
raw availability, 18
reachability, 196
Really Awesome New Cisco Config Differ (RANCID), 333
receive access control list (RACL), 67
RED (random early detect), 75
redistribute connected command, 276
redistribute ospf 10 command, 278

- redundancy**, 13
 - device-level, 201
 - Internet modules, 199–204
 - ISP-level, 202
 - link-level, 58, 200
 - logical, 57
 - NIC teaming, 297
 - physical, 57
 - router status, 217
 - RPR, 40–41, 107
 - RPR+, 41–43, 216
 - site-level, 203
 - strategies, 56
 - VRRP, 183
- release, Cisco IOS**, 346
- reliability**, 9, 34
 - HSA, 39
 - IP networks, 3
 - NSF, 45–48
 - OIR, 34–36
 - RPR, 40–41
 - RPR+, 41–43
 - single line card reload, 36–37
 - SSO, 43–45
- remote monitoring (RMON)**, 332, 336
- Request For Proposals (RFPs)**, 12
- rerouting** 85–86
- resiliency**
 - 50-ms, 15–16
 - design, 59–61
 - device-level, 34, 57
 - HSA*, 39
 - NSF*, 45–48
 - OIR*, 34–36
 - RPR*, 40–41
 - RPR+*, 41–43
 - single line card reload*, 36–37
 - SSO*, 43–45
 - IP, 28
 - strategies, 59
- Resilient Packet Ring (RPR)**, 7, 85, 251–258
- resolution, DNS**, 321
- resources, peering**, 189
- responder-based IP SLA operations**, 353
- restarting (graceful restart)**
 - IS-IS, 117–122
 - OSPF, 106–111
- reverse proxy caching**, 326
- RFC 3623**, 107
- RFPs (Request For Proposals)**, 12
- rings, configuring DPR/SPR**, 256
- RMON (remote monitoring)**, 332, 336
- RNS (root name server)**, 321
- root bridges**, 148, 176
- root name server (RNS)**, 321
- root ports**, 146
- RootGuard**, 155–157
- route processor redundancy (RPR)**, 40–41, 107
- route processor redundancy plus (RPR+)**, 41–43, 216
- routed ports, aggregation switches**, 299
- router ospf 10 vrf RED command**, 278
- routers**
 - Adv Rtr, 87
 - CE, 276–278
 - CRS-1, 3
 - DPT, 252
 - equal-cost load balancing, 241
 - GSR, 106
 - ISDN, 258
 - leased line connections, 241
 - LER, 269
 - LSR, 269
 - MPPP, 243
 - NAT performance, 235
 - next hop, 134
 - P, 270, 273
 - PE, 270, 274
 - redundancy status, 217
 - stub (EIGRP), 123
- routes**
 - CE, 270
 - dampening, 215
 - floating static, 258
 - maps (NAT), 223
- routing**
 - CIDR, 194
 - external users, 198
 - flaps, 45
 - internal users, 197
 - Internet module, 194–199
 - multipath, 128
 - tagging, 65

RPR (Resilient Packet Ring), 7, 85, 251–258
RPR (route processor redundancy), 40–41, 107
RPR+ (route processor redundancy plus), 41–43,
 216
RSTP (Rapid Spanning Tree Protocol), 165

S

SAA (Service Assurance Agent), 82
SAFE (Security Blueprint for Enterprise Networks), 289
scaling
 architecture, 301–302
 strategies, 58
scheduling downtime, 23
scripting (TCL), 360
SDH (Synchronous Digital Hierarchy), 15
security
 Data Center networks, 289
 design, 60
 DHCP servers, 314
 Internet modules, 204–209
 Layer 2, 303–313
 Layer 3, 313–315
 management, 336–337
 NAT, 235
 networks (Data Center module), 302–315
 optimizing, 7
 policies, 204–205
 ports, 311
Security Blueprint for Enterprise Networks (SAFE), 289
selecting root bridges, 176
send routing message (SRM), 118
serial devices, availability of, 369
series components, 10
server load balancing (SLB), 316–320
servers
 blade connectivity, 288
 clustering, 297
 Data Center module, 284–289
 Data Center network performance, 290
 DHCP, 314
 DMZ, 196
 extranet reachability, 196
 failures, 21

farms, 292, 301
 fault-tolerant, 290
Service Assurance Agent (SAA), 82
service level agreement. *See SLA*
services
 classes of, 254
 integrated service modules, 328–329
 optimization, 315–328
 QoS. *See QoS*
sessions, fast peering deactivation, 214
sham links, 278
shortest path first. *See SPF*
shortest-path tree. *See SPT*
show bfd neigh detail command, 125
show commands, 337
 show ip bgp neighbors, 211
 show ip cef, 131
 show ip cef exact-route, 132
 show ip ospf, 96, 98
 show ip ospf neighbor detail, 110
 show ip pim neighbor, 138
 show ip route, 129
 show ip rpf events, 139
 show isis nsf, 120
 show running-config, 36
SIA (stuck-in-active) state, 123
signals, EOT, 123
simple hardware backups, 38
Simple Network Management Protocol (SNMP),
 332
simple network topology availability, 370
simple system availability, 370
simplicity
 Layer 2, 173
 of network design, 59
single line card reload, 36–37
site-level redundancy, 203
sizing windows, 32
SLA (service level agreement), 16, 335
 ICMP, 353
 IP SLAs, 352
SLB (server load balancing), 316–320
sliding windows (TCP), 32
snapshots, taking of inventory, 340
SNMP (Simple Network Management Protocol),
 332
snooping (DHCP), 315

- soft reconfiguration (BGP),** 210
- soft reset refresh,** 211
- software error protection,** 38
- software management,** 334
- SONET (Synchronous Optical Network)/SDH (Synchronous Digital Hierarchy),** 244–251
- Spanning Tree Protocol.** *See* STP
- spans of VLANs, limiting,** 174
- Spatial Reuse Protocol,** 251
- special-use address measures,** 206
- speeds, SONET/SDH,** 244
- SPF (shortest path first)**
 - incremental, 105, 116
 - partial, 106
 - throttling (IS-IS), 112–113
- spf-interval command,** 112
- spoofing, anti-spoofing measures,** 206
- SPT (shortest-path tree),** 105
- SRM (send routing message),** 118
- SSO (stateful switchover),** 43–45
 - stacking labels, 134
 - standards, RPR, 255
 - standby power equipment, 287
 - stateful NAT, 226
 - stateful switchover (SSO), 43–45
- states**
 - blocking, 148
 - disabled, 148
 - forwarding, 148
 - learning, 148
 - listening, 148
 - steady (STP), 149
- static mapping with HSRP,** 224
- static routes, configuring,** 259
- status**
 - router switching, 53
 - RPR, 40
 - RPR+, 42
 - SSO, 44
- steady state (STP),** 149
- STM (Synchronous Transport Module),** 244
- storage, IP,** 5
- stored routing update information,** 211
- STP (Spanning Tree Protocol),** 7, 146–150
 - BackboneFast, 152–154
 - BPDUGuard, 157–158
 - channeling, 171–173
- cycles,** 148
- IEEE 802.1s,** 168–171
- IEEE 802.1w,** 165–168
- Layer 2 domains,** 145
- LoopGuard,** 157
- PortFast,** 150
- RootGuard,** 155–157
- UDLD,** 154–155
- UplinkFast,** 151
- VLANs,** 158–165
- strategies**
 - high availability, 21
 - QoS deployment, 77–82
 - redundancy, 56
 - resiliency, 59
 - scaling, 58
- stream data transfers,** 30
- STS (Synchronous Transport Signal),** 244
- stub routers,** 123
- stuck-in-active (SIA) state,** 123
- switches,** 146
 - aggregation, 298
 - forwarding architecture, 314
 - L2TPv3, 268
 - PVLANs, 310
- switching**
 - CEF, 50
 - LATA, 12
 - MPLS, 6
 - paths, 48–55
 - process, 49
 - protection (SONET/SDH), 248
 - topology-based, 186
- synchronization, global,** 75
- Synchronous Optical Network (SONET)/Synchronous Digital Hierarchy (SDH).** *See* SONET/SDH
- Synchronous Transport Module (STM),** 244
- Synchronous Transport Signal (STS),** 244
- syslog messages**
 - fault management, 332
 - prioritizing, 360

T

tables

adjacency, 50
entries in, 51

TACACS, 337

tagging

cables, 282
routing protocols, 65

TCL (Tool Command Language), 360

TCP (Transmission Control Protocol), 29–33

delayed binding, 320

MSS, 213

NAT, 232

sliding windows, 32

three-way handshakes, 31

TDM (time-division multiplexing), 13

teaming (NIC), 295

Telcordia GR-512-Core document, 12–15

testing

life cycle management (IOS), 350
policies, 81

theoretical availability of devices, 368–369

three-tier architecture, 142

three-way handshakes (TCP), 31

thresholds

analyzing, 344
baselines. *See* baselines
prioritizing, 345
troubleshooting, 345

throttling

LSAs, 98–100
SPF (IS-IS), 112–113

time-division multiplexing (TDM), 13

timers

forward delay, 149
hello, 149
maximum age, 149

timers lsa arrival command, 100

timers spf spf-holdtime command, 97

Tool Command Language (TCL), 360

tools

COOL, 355
MRTG, 343

topologies 171–174

topology-based switching, 186

ToS (type-of-service), 29

tracking

inventory, 333
next-hop address tracking (BGP), 214

traffic

conditioning, 76
control planes, 76–77
network convergence in the core, 85–86
types that affect control planes, 64
VoIP, 234

Traffic Anomaly Detector service module, 335

transferring stream data, 30

transient congestion, 73

Transmission Control Protocol. *See* TCP

traps, SNMP, 332

trees, SPT, 105

triangle topologies, 174

troubleshooting

congestion, 73
DoS attacks, 195
failures, 3, 20
fault management, 332
MTTR, 368
thresholds, 345

trunking

cards, 13
ports, 298
STP, 158–165

tunnel mode gre command, 264

tunnel mode ipip command, 264

tunnel mpls traffic-eng fast-reroute command, 135

tunnel path-mtu-discovery command, 264

tunneling

IP, 261
L2TP, 265

turning off autonegotiation, 178

two-tier architecture, 142

type-of-service (TOS), 29

types

of ISDN, 258
of traffic that affect control planes, 64
of VLANs, 306

U

UDLD (Unidirectional Link Detection), 154–155
UDP (User Datagram Protocol), 33–34
 uncongested links, 72
 Unicast Reverse Path Forwarding (uRPF), 335
Unidirectional Link Detection (UDLD), 154–155
 unidirectional self-healing ring (USHR), 248
 uninterruptible power supply (UPS), 287
 universal load-sharing algorithm, 131
 update packet-pacing timer, 104–105, 115–116
 updates
 BGP, 221
 generating, 211
upgrading ISSU, 364
UplinkFast, 151
uplinkfast command, 152
 upper-bound thresholds, 344
UPS (uninterruptible power supply), 287
 upstream failures, 21
uRPF (Unicast Reverse Path Forwarding), 335
User Datagram Protocol. *See UDP*
User IDs, 337
USHR (undirectional self-healing ring), 248

vMAC (virtual MAC) addresses, 4, 296
VoIP (Voice over IP), 5, 234
VPN (Virtual Private Network), 6, 261–279
VRID (virtual router identifier), 183
VRRP (Virtual Router Redundancy Protocol),
 183

W–Z

WAN (wide area network)
 dial backup, 258–261
 leased lines, 237–244
 RPR, 251–258
 SONET/SDH, 244–251
 VPN, 261–279
warm standby mode, 40
WCCP (Web Cache Communication Protocol),
 324–328
weighed random early detection (WRED), 30
what-if analysis, 344
windows, sliding (TCP), 32
worms, 204, 304
WRED (weighted random early detection), 30

V

VACL (VLAN access control list), 310
verification
 OSPF in NSF mode, 47
 router switching status, 53
 RPR+ status, 42
 SSO status, 44
virtual LANs. *See VLANs*
virtual MAC (vMAC) addresses, 4, 296
Virtual Private Network. *See VPN*
virtual router identifier (VRID), 183
Virtual Router Redundancy Protocol (VRRP),
 183
viruses, 204
VLAN access control list. *See VACL*
VLANs (virtual LANs)
 spans, 174
 types of, 306
 STP, 158–165